{EPITECH}

MINISHELL2_

< BOOTSTRAP />

MINISHELL2

binary name: my_pipe
language: C
groupe size: 1
compilation: via Makefile, including re, clean and fclean rules
authorized functions: malloc, free, exit, opendir, readdir, closedir, getcwd, chdir, fork, stat, lstat, fstat, open, close, getline, strtok, strtok_r, read, write, execve, access, isatty, wait, waitpid, wait3, wait4, signal, kill, getpid, strerror, perror, strsignal, pipe, dup, dup2

- ✓ The totality of your source files, except all useless files (binary, temp files, objfiles,...), must be included in your delivery.
- ✓ All the bonus files (including a potential specific Makefile) should be in a directory named bonus.
- ✓ Error messages have to be written on the error output, and the program should then exit with the 84 error code (0 if there is no error).

{EPITECH}

Objectives

Now you will learn how to make a redirection from a FD to another.

Write a program that takes two character strings *s1* and *s2* as parameters, each containing a binary name with its path and list of arguments.

Your program should execute the command *s1*/*s2* .

For example:

```
Terminal
$> ./my_pipe "/bin/ls -l /dev" "/bin/grep tty"
```

should give the same result as:

```
Terminal
$> /bin/ls -l /dev | /bin/grep tty
```


{EPITECH}

v 1

{EPITECH}