LINKWARE™ PC
CABLE TEST MANAGEMENT SOFTWARE

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
1TRA-277	PASS	TIA Cat 5e Channel	60 ft	16.9 dB (NEXT)	10/21/2022 12:35 PM

Total Length:	60 ft
Number of Reports:	1
Number of Passing Reports:	1
Number of Failing Reports:	0
Number of Warning Reports:	0
Documentation Only:	0

Cable ID: 1TRA-277

Test Limit: TIA Cat 5e Channel
Limits Version: V7.6
Date / Time: 10/21/2022 12:35:43 PM
Operator: BILLY MOORE
Headroom 16.9 dB (NEXT 3,6-4,5)
Cable Type: Cat 5e U/UTP
NVP: 69.0%

Main: Versiv
S/N: 19140167
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000 (DSX-CHA004)
S/N: 4592537

Test Summary: PASS

Remote: Versiv
S/N: 19140163
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000R (DSX-PLA004)
S/N: 4537098

Length (ft), Limit 328	[Pair 1,2]	60
Prop. Delay (ns), Limit 555	[Pair 7,8]	89
Delay Skew (ns), Limit 50	[Pair 7,8]	1
Resistance (ohms)	[Pair 3,6]	3.78
Insertion Loss Margin (dB)	[Pair 1,2]	19.8
Frequency (MHz)	[Pair 1,2]	100.0
Limit (dB)	[Pair 1,2]	24.0

	Worst Case Margin		Worst Case Value	
PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
NEXT (dB)	17.6	16.9	17.6	16.9
Freq. (MHz)	73.8	73.8	73.8	73.8
Limit (dB)	32.4	32.4	32.4	32.4
Worst Pair	3,6	3,6	3,6	3,6
PS NEXT (dB)	17.7	18.2	17.7	18.3
Freq. (MHz)	73.8	73.8	73.8	74.3
Limit (dB)	29.4	29.4	29.4	29.3

PASS	MAIN	SR	MAIN	SR
Worst Pair	1,2-4,5	4,5-1,2	4,5-1,2	1,2-4,5
ACR-F (dB)	29.2	29.2	30.1	30.2
Freq. (MHz)	81.8	81.8	100.0	100.0
Limit (dB)	19.2	19.2	17.4	17.4
Worst Pair	1,2	1,2	1,2	1,2
PS ACR-F (dB)	30.6	30.6	31.2	32.1
Freq. (MHz)	77.0	44.8	100.0	100.0
Limit (dB)	16.7	21.4	14.4	14.4

N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-4,5	3,6-4,5	3,6-4,5	3,6-4,5
ACR-N (dB)	22.8	23.5	34.5	33.8
Freq. (MHz)	6.5	7.6	73.8	73.8
Limit (dB)	44.4	42.8	12.0	12.0
Worst Pair	4,5	3,6	3,6	4,5
PS ACR-N (dB)	24.7	23.6	34.6	40.9
Freq. (MHz)	6.5	1.6	73.8	100.0
Limit (dB)	41.4	53.9	9.0	3.1

PASS	MAIN	SR	MAIN	SR
Worst Pair	1,2	1,2	1,2	3,6
RL (dB)	9.5	13.3	9.5	13.6
Freq. (MHz)	80.5	55.3	80.5	91.0
Limit (dB)	11.0	12.6	11.0	10.4

Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	ATM-25
ATM-51	ATM-155	100VG-AnyLan
TR-4	TR-16 Active	TR-16 Passive