

Cable ID	Summary	Test Limit	Length	Headroom	Date / Time
2D.R02.04:25	PASS	TIA Cat 6A Perm. Link	103 ft	6.4 dB (NEXT)	08/19/2022 09:50 AM
2D.R02.04:26	PASS	TIA Cat 6A Perm. Link	103 ft	7.1 dB (NEXT)	08/19/2022 09:50 AM

Total Length:	206 ft
Number of Reports:	2
Number of Passing Reports:	2
Number of Failing Reports:	0
Number of Warning Reports:	0
Documentation Only:	0



Cable ID: 2D.R02.04:25


Test Limit: TIA Cat 6A Perm. Link
Limits Version: V7.6
Date / Time: 08/19/2022 09:50:37 AM
Operator: ZEKE GOMEZ
Headroom 6.4 dB (NEXT 4,5-7,8)
Cable Type: GenSpeed 10 MTP CMP
NVP: 67.0%

Main: Versiv
S/N: 19140167
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000 (DSX-PLA004)
S/N: 4537098

Test Summary: PASS

Remote: Versiv
S/N: 19140163
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000R (DSX-PLA004)
S/N: 4537097

Length (ft), Limit 295	[Pair 1,2]	103
Prop. Delay (ns), Limit 498	[Pair 4,5]	169
Delay Skew (ns), Limit 44	[Pair 4,5]	13
Resistance (ohms)	[Pair 4,5]	5.37
Insertion Loss Margin (dB)	[Pair 4,5]	24.9
Frequency (MHz)	[Pair 4,5]	500.0
Limit (dB)	[Pair 4,5]	43.8




Wire Map (T568B)

PASS





Insertion Loss (dB)





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	4,5-7,8	4,5-7,8	3,6-4,5	3,6-7,8
NEXT (dB)	6.4	6.6	10.8	9.8
Freq. (MHz)	99.3	99.3	465.0	447.0
Limit (dB)	41.9	41.9	27.7	28.3
Worst Pair	7,8	7,8	3,6	3,6
PS NEXT (dB)	8.0	7.7	11.7	11.8
Freq. (MHz)	99.3	99.3	479.0	500.0
Limit (dB)	39.4	39.4	24.4	23.8





PASS	MAIN	SR	MAIN	SR
Worst Pair	7,8-4,5	4,5-7,8	7,8-4,5	4,5-7,8
ACR-F (dB)	16.0	16.7	16.0	16.7
Freq. (MHz)	383.0	383.0	383.0	383.0
Limit (dB)	12.5	12.5	12.5	12.5
Worst Pair	4,5	7,8	4,5	7,8
PS ACR-F (dB)	18.1	17.7	18.1	17.7
Freq. (MHz)	383.0	383.0	383.0	383.0
Limit (dB)	9.5	9.5	9.5	9.5



N/A	MAIN	SR	MAIN	SR
Worst Pair	1,2-7,8	1,2-7,8	3,6-4,5	3,6-4,5
ACR-N (dB)	13.4	13.8	34.9	37.6
Freq. (MHz)	13.1	9.0	465.0	500.0
Limit (dB)	49.6	53.3	-14.2	-17.1
Worst Pair	1,2	7,8	3,6	3,6
PS ACR-N (dB)	14.2	14.1	36.3	36.8
Freq. (MHz)	13.0	8.9	479.0	500.0
Limit (dB)	47.4	51.1	-18.3	-20.0



PASS	MAIN	SR	MAIN	SR
Worst Pair	3,6	3,6	1,2	1,2
RL (dB)	7.7	8.9	10.8	10.7
Freq. (MHz)	22.4	22.4	358.0	461.0
Limit (dB)	19.3	19.3	8.5	8.0



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
10GBASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	



Cable ID: 2D.R02.04:26

Test Limit: TIA Cat 6A Perm. Link
Limits Version: V7.6
Date / Time: 08/19/2022 09:50:56 AM
Operator: ZEKE GOMEZ
Headroom 7.1 dB (NEXT 1,2-7,8)
Cable Type: GenSpeed 10 MTP CMP
NVP: 67.0%

Main: Versiv
S/N: 19140167
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000 (DSX-PLA004)
S/N: 4537098

Test Summary: PASS

Remote: Versiv
S/N: 19140163
Software Version: V6.7 Build 1
Calibration Date: 07/01/2022
Adapter: DSX-5000R (DSX-PLA004)
S/N: 4537097

Length (ft), Limit 295	[Pair 1,2]	103
Prop. Delay (ns), Limit 498	[Pair 4,5]	170
Delay Skew (ns), Limit 44	[Pair 4,5]	13
Resistance (ohms)	[Pair 4,5]	5.37
Insertion Loss Margin (dB)	[Pair 4,5]	25.1
Frequency (MHz)	[Pair 4,5]	500.0
Limit (dB)	[Pair 4,5]	43.8




103 ft




Wire Map (T568B)

PASS





Insertion Loss (dB)





Worst Case Margin Worst Case Value



PASS	MAIN	SR	MAIN	SR
Worst Pair	1,2-7,8	1,2-7,8	3,6-4,5	3,6-4,5
NEXT (dB)	7.6	7.1	10.5	11.0
Freq. (MHz)	226.5	196.5	500.0	485.0
Limit (dB)	36.0	37.1	26.7	27.1
Worst Pair	7,8	3,6	3,6	3,6
PS NEXT (dB)	9.4	7.5	11.2	12.3
Freq. (MHz)	227.0	306.0	500.0	487.0
Limit (dB)	33.4	31.1	23.8	24.2





PASS	MAIN	SR	MAIN	SR
Worst Pair	7,8-4,5	4,5-7,8	7,8-4,5	7,8-4,5
ACR-F (dB)	14.0	14.8	14.1	14.9
Freq. (MHz)	386.0	386.0	390.0	396.0
Limit (dB)	12.5	12.5	12.4	12.2
Worst Pair	4,5	7,8	4,5	7,8
PS ACR-F (dB)	15.8	16.6	17.1	16.7
Freq. (MHz)	386.0	386.0	465.0	387.0
Limit (dB)	9.5	9.5	7.8	9.4



N/A	MAIN	SR	MAIN	SR
Worst Pair	3,6-7,8	3,6-7,8	3,6-4,5	3,6-4,5
ACR-N (dB)	11.8	12.6	35.6	35.8
Freq. (MHz)	5.6	5.8	500.0	485.0
Limit (dB)	57.6	57.4	-17.1	-15.9
Worst Pair	3,6	3,6	3,6	3,6
PS ACR-N (dB)	13.4	14.5	36.5	37.8
Freq. (MHz)	6.1	5.8	500.0	494.0
Limit (dB)	54.5	55.1	-20.0	-19.5



PASS	MAIN	SR	MAIN	SR
Worst Pair	4,5	1,2	4,5	1,2
RL (dB)	8.8	9.3	8.8	10.0
Freq. (MHz)	440.0	145.5	440.0	238.0
Limit (dB)	8.0	12.4	8.0	10.2



Compliant Network Standards:

10BASE-T	100BASE-TX	100BASE-T4
1000BASE-T	2.5GBASE-T	5GBASE-T
10GBASE-T	ATM-25	ATM-51
ATM-155	100VG-AnyLan	TR-4
TR-16 Active	TR-16 Passive	