

JDBC Performance from the Inside

March, 2017



Introduction

- Dave Cramer
- Work for Pivotal on the Greenplum database project <https://github.com/greenplum-db/gpdb>
- Maintainer for the JDBC driver since 1999
- Overheard conversation about how poorly the driver performed because of how it was built.
- Allegedly was very CPU intensive because of all the inheritance
- Things have changed a lot since then so I thought this would be a good idea for a talk, gather some statistics and show all the performance gains as a result of simplifying the code



Overview

- History of the driver
- Previous source layout
- Under utilized features
- Performance tips
- Latest Release major features



History

- Originally written by Peter Mount in 1997
- Supported JDBC 1.2
- 1997 JDBC 1.2 Java 1.1
- 1999 JDBC 2.1 Java 1.2
- 2001 JDBC 3.0 Java 1.4
- 2006 JDBC 4.0 Java 6
- 2011 JDBC 4.1 Java 7
- 2014 JDBC 4.2 Java 8
- 2017 JDBC 4.3 Java 9 (Maybe ?)
- Each one of these were incremental additions to the interface
- Requiring additional concrete implementations of the spec to be implemented

Source code layout




Before Maven (the ant years)

- jdbc2->jdbc3->jdbc3g->jdbc4->jdbc42
- Each one of these had abstract implementations, and concrete implementations
- Which one was built was determined by filters using ant
- Lions share of code was in jdbc2 package
- This meant that a concrete jdbc42 implementation public class Jdbc42Connection extended AbstractJdbc42Connection which extends **AbstractJdbc4Connection** which extends **AbstractJdbc3gConnection** which extends **AbstractJdbc3Connection** which extended **AbstractJdbc2Connection**



Before Maven (the ant years)





What we should have done (the ant years)

- Why didn't you just use `-target` and compile previous versions with the latest compiler
- In theory since older versions of the spec will never attempt to access more recent functions in an interface this should "just work"
- Well embarrassingly we didn't think of it.
- Up until Java 8 this was possible.. The JDBC spec was never supposed to introduce a backward incompatibility.
- In Java 8 they added `java.time.*` the problem is: attempting to load a driver using an earlier JDK with `java.time` in it will cause a `ClassNotFoundException`. The spec required to be able to pass a `java.time.*` object into `setObject`, so when the driver is loaded it will look for this class, and not find it in older JDK's



Mavenizing the driver

- Why ? I was pretty hesitant to essentially rewrite the driver
- Easier to just include in your project

```
<dependency>  
  <groupid>org.postgresql</groupid>  
  <artifactid>postgresql</postgresql>  
  <version>42.0.0</version>  
</dependency>
```


- Still have the same problems they are just solved differently
- Ant had filters to filter out which files are compiled for each build
- Maven uses pre-processing to add or remove code, avoids the multiple class extension
- *//#if mvn.project.property.postgresql.jdbc.spec >= "JDBC4.2"*



Mavenizing the driver

- Code re-organized release 1207 Dec 2015
- All of the abstract class machinations have been removed
- Far fewer source files for all versions of JDBC
- Reduces CPU load*
- Real advantage to mavenizing the project. The code is much simpler.
- Easier to debug, can be easily loaded into an IDE
- More people have provided Pull Requests

After Maven





Time to test the hypothesis

- Borrowed some code from <https://github.com/8kdata/javapgperf>
- Plug for ToroDB <https://github.com/torodb/torodb>
- **CREATE TABLE IF NOT EXISTS** number **AS SELECT** i, 'Hello there ' || i **AS** t, '{"i": ' || i || ', "t": "' || 'Hello there ' || i || '" }' **AS** j **FROM** *generate_series*(1,10 * 1000 * 1000) **AS** i;
- | Column | Type | Modifiers |
|--------|---------|-----------|
| i | integer | |
| t | text | |
| j | text | |



What do the tests do ?

- 1_int select i from number
- 2_String select t from number
- 3_IntString select i,t from number
- 4_IntStringJson select i, t, j from number
- 5_IntStringColumnNumber select i,t and use column number instead of column name
- 6_StringNoAutocommit select t from number
- Ran the test suite for a number of different JDBC versions 1204, 1208, 1210, 1212, 42.0.0



What do the tests do ?


```
public class _4_IntStringJson {
    public static final String QUERY = "SELECT i, t, j FROM number";

    private class JsonElements {
        private int i;
        private String t;
    }

    @Benchmark
    public void test(Blackhole blackhole, PgStatStatements pgStatStatements) throws SQLException {
        pgStatStatements.setTestName(QueryBenchmarks.JMHTestNameFromClass(_4_IntStringJson.class));

        Gson gson = new Gson();

        QueryUtil.executeProcessQuery(QUERY, resultSet -> {
            while (resultSet.next()) {
                blackhole.consume(resultSet.getInt("i"));
                blackhole.consume(resultSet.getString("t"));
                blackhole.consume(gson.fromJson(resultSet.getString("j"), JsonElements.class));
            }
        });
    }
}
```





Something good came out of Maven

- Well it didn't really improve performance but:
- It is Easier to understand
- More people are working on it
- Easier to work with simply import the maven pom.xml into IntelliJ
- Easier to push to maven





Some things that really did improve performance

- Set Fetch Size
- Fixed deadlocks
- Insert rewrite
- Fixing bugs



Set FetchSize performance

- Fetch a large amount of data with different fetch sizes

```
public static final String QUERY = "SELECT t FROM number";
```

```
@Benchmark
```


```
public void test(Blackhole blackhole, PgStatStatements pgStatStatements) throws SQLException {  
    pgStatStatements.setTestName(QueryBenchmarks.JMHTestNameFromClass(_6_String_NoAutocommit.class));  
    QueryUtil.executeProcessQueryNoAutocommit(QUERY, resultSet -> {  
        while (resultSet.next()) {  
            blackhole.consume(resultSet.getString(1));  
        }  
    });  
}
```

```
// Used to fetch rows in batches from the db. Will only work if the connection does not use  
AutoCommit
```

```
PGProperty.DEFAULT_ROW_FETCH_SIZE.set(properties, FETCH_SIZE);
```



Time it takes to fetch 1M rows





Inserting batch Deadlock issue

- Ideally we would like to:
- Insert N rows where N is some arbitrarily large number
- PARSE S_1
- BIND/EXEC N TIMES
- DEALLOCATE



Unfortunately this doesn't work

- Driver is busy sending data, so it hasn't retrieved any responses
- BIND/EXEC only sends data it does not read it
- Server is busy sending responses, so it can't fetch any more insert queries
- So we have a situation where the driver is continually sending, and the server is continually sending. Neither one is reading the responses.



Every so often we have to sync

- Parse S_1
- BIND/EXEC
- BIND/EXEC
- SYNC ... flush and wait for response
- The more sync's the slower it performs
- Current code sync's every 64k of data

What are the options for inserting lots of data



- For each row insertExecute this is the slowest
- For each row insertBatch this would be ideal
- Insert into foo (i,j) values (1,'one'), (2,'two') (n,'n') hand rolled code
- Copy into foo from stdin...



JDBC micro benchmark suite

- Java 1.8_60
- Core i7 2.8GHz
- PostgreSQL 9.6
- <https://github.com/pgjdbc/pgjdbc/tree/master/ubenchmark>
- create table batch_perf_test(a int4, b varchar(100), c int4)

Table "public.batch_perf_test"

Column	Type
a	integer
b	character varying(100)
c	integer



INSERT Batch 1 row at a time

- For each row Insert into perf (a,b,c) values (?, ?, ?)
- After N rows executeBatch
- Normal mode this executes N inserts, not any faster than
- Looping over N inserts without batch mode



INSERT Batch N rows_at_a_time

- For each row Insert into perf (a,b,c) values (?, ?, ?), (?, ?, ?), (?, ?, ?), (?, ?, ?)
- After N/ rows_at_a_time rows executeBatch
- Given 1000 (N) rows if we insert them 100(rows_at_a_time) , end up inserting 10 rows 100 wide
- More data inserted per statement, less statements



INSERT Batch with insertRewrite

- For each row Insert into perf (a,b,c) values (?, ?, ?)
- After N rows executeBatch
- Same as last slide except we set the connection parameter insertRewrite=true
- As of version 1209 this has been enabled
- Same as insert into foo (i,j) values (1,'one'), (2,'two') (n,'n') except the driver does it for you.



Copy

- Loop over the rows creating the input string in memory
- Build a string in memory which looks like `0\t0\t0\n1\t1\t1\n....`
- The string will end up being `nrows / rows_at_a_time` long
- Use the copy API to copy this into the table



Hand rolled insert struct N structs at a time


- Insert into batch_perf_test select * from unnest (?:batch_perf_test[])
- For N rows setString to '{“(1,s1,1)”,“(2,s2,2)”,“(3,s3,3)”}'
- Add Batch
- executeBatch
- The query that gets executes look like:

```
Insert into batch_perf_test select *  
      from unnest ('{(1,s1,1)”,“(2,s2,2)”,“(3,s3,3)”}'::batch_perf_test[])
```

Results



Batch size of 128






Conclusion

- Compared to batch inserts, plain inserts are very slow for large amounts of data

Results



1024 rows different batch sizes





Bug fixes

- <https://github.com/pgjdbc/pgjdbc/pull/380>
- `QUERY_FORCE_DESCRIBE_PORTAL` shared the same value as `QUERY_DISABLE_BATCHING` effectively disabling batch inserts
- 10x increase in throughput



How not to use JDBC (unfortunately typical)

- Open connection
- Prepare statement 'select * from foo where id=?'
- `preparedStatment.executeQuery()`
- `preparedStatement.close()`
- Close Connection
- Without a pool connection creation is a heavyweight operation. PostgreSQL uses processes so each connection is a process
- Does not take advantage of caching



Better solution

- Open connection
- Prepare statement 'select * from foo where id=?'
- By default after 5 executions will create a named statement PARSE S_1 as 'select * from foo where id=?'
- Multiple preparedStatment.executeQuery() BIND/EXEC instead of PARSE/BIND/EXEC
- Never close the statement if possible



Query cache best practices

- Client side query cache only works in 9.4.1203 and up
- Do not use generated queries, as they generate new server side prepared statement
- Things like `executeUpdate('insert into foo (i,l,f,d) values (1,2,3,4)')` will never use a named statement
- Do not change the type of a parameter as this leads to DEALLOCATE/PREPARE
- `Pstmt.setInt(1,1)`
- `Pstmt.setNull(1,Types.VARCHAR)` this will cause the prepared statement to be deallocated



Less obvious issues

- Server Prepare activated after 5 executions
- There is a configuration parameter called `prepareThreshold` (default 5)
- `PGStatement.isUseServerPrepare()` can be used to check
- After 5 executions of the same prepared statement we change from unnamed statements to named
- Named statements will use binary mode where possible;
- binary mode is faster when we have to parse things like timestamps
- Named statements are only parsed once on the server then bind/execute operations on the server



setFetchSize

- If we don't use a fetch size we will read the entire response into memory then process
- Optimizing the data sent at one time reduces memory usage and GC
- Only works with in a transaction
- Make sure fetch size is above 100
- If you have a lot of data this is really the only way to read it in without an Out Of Memory Exception



Adaptive FetchSize

- <https://github.com/pgjdbc/pgjdbc/pull/675>
- Attempt to avoid Out of Memory errors
- Adapt the fetch size based on the width of the row
- The server protocol does not allow the fetch size to be specified in bytes so we will examine the row size and optimize



Performance enhancements review

- Cache parsed statements across PreparedStatement calls now don't have to parse the statement in java each time
- Execute Batch changed to not execute statement by statement bug in code disabled batching
- Rewrite Batched inserts rewrites inserts from multiple insert into foo (a,b,c) values (1,2,3) to insert into foo (a,b,c) values (1,2,3), (4,5,6) this provides 2x-3x speed up
- Avoid Calendar cloning provides 4x speed increase for setTimestamp pr 376



Conclusions

- Using insert rewrite gives us a 2-3x performance increase for batch inserts
- Makes sense as it is one trip
- Use `setFetchSize(100)` or greater and use transactions
- Don't close prepared statements.



New Release 42.0.0

- Wanted to divorce ourselves from the server release schedule
- Wanted to reduce confusion as to which version to use. Previously the numbers 9.x were in the version number.
- Introduce semantic versioning
- 42 more or less at random, but also the answer to the question.



Notable changes

- Support dropped for versions before 8.2
- Replace hand written logger with `java.util.logging`
- Replication protocol API was added.



Logging

- Setting using url, or properties file
- Root logger is org.postgresql
- Properties via URL are loggerLevel and loggerFile
- loggerLevel can be one of: OFF, DEBUG, TRACE
- Corresponds to OFF, FINE, FINEST
- Also possible to use logging.properties file as per normal



Logical Replication Overview

- Reads the WAL logs and outputs them in any format you want
- Read changes
- Send confirmation of changes read
- GOTO read more changes



Logical Replication High level Steps

- Create a replication connection
- Create a logical replication slot
- Read changes
- Send confirmation of changes read
- GOTO read more changes



Create a Replication Connection

```
String url = "jdbc:postgresql://localhost:5432/postgres";
Properties props = new Properties();
PGProperty.USER.set(props, "postgres");
PGProperty.PASSWORD.set(props, "postgres");
PGProperty.ASSUME_MIN_SERVER_VERSION.set(props, "9.4");
PGProperty.REPLICATION.set(props, "database");
PGProperty.PREFER_QUERY_MODE.set(props, "simple");
Connection con = DriverManager.getConnection(url, props);
PGConnection replConnection = con.unwrap(PGConnection.class);
```

- PGProperty.REPLICATION set to “database” instructs the walsender to connect to the database in the url and allow the connection to be used for logical replication.
- PREFER_QUERY_MODE needs to be set to simple as replication does not allow the use of the extended query mode



Create a Logical Replication Slot

```
String outputPlugin = 'test_decode';
try (PreparedStatement preparedStatement =
    connection.prepareStatement("SELECT * FROM
pg_create_logical_replication_slot(?, ?)")
{
    preparedStatement.setString(1, slotName);
    preparedStatement.setString(2, outputPlugin);
    preparedStatement.executeQuery()

}
```

- Slots require a name and an output plugin
- Any unique name will work
- The output plugin is a previously compiled C library which formats the logical WAL



Create a replication stream

```
PGReplicationStream stream =  
    pgConnection  
        .getReplicationAPI()  
        .replicationStream()  
        .logical()  
        .withSlotName(SLOT_NAME)  
        .withStartPosition(lsn)  
        .withSlotOption("include-xids", true)  
        .start();
```

- Open a PGReplicationStream with the same slot name
- Start position can be an existing LSN or InvalidLSN
- SlotOptions are sent to the logical decoder and are decoder specific



Read Changes from database

```
while (true) {  
    //non blocking receive message  
    ByteBuffer msg = stream.readPending();  
    if (msg == null) {  
        TimeUnit.MILLISECONDS.sleep(10L);  
        continue;  
    }  
    int offset = msg.arrayOffset();  
    byte[] source = msg.array();  
    int length = source.length - offset;  
    System.out.println(new String(source, offset, length));  
    //feedback  
    stream.setAppliedLSN(stream.getLastReceiveLSN());  
    stream.setFlushedLSN(stream.getLastReceiveLSN());  
}
```

- Read from the stream, data will be in a ByteBuffer
- After reading the data send confirmation messages
- github.com:davecramer/LogicalDecode.git

Live Demo





<https://github.com/pgjdbc/pgjdbc>

- Credit where credit is due:
- Much of the optimization work on the driver was done by Vladimir Sitnikov
- Much (if not all) of the work to convert the build to Maven was done by Stephen Nelson
- Rewriting batch statements thanks to Jeremy Whiting
- Replication support was provided by Vladimir Gordiychuk
- Questions ?