

Quantale Weakness Based Conceptual Blending: Integrating Information-Theoretic and Category-Theoretic Approaches

Ben Goertzel^{1,2}

¹SingularityNET Foundation

²TrueAGI Inc.

ben@singularitynet.io

January 20, 2026

Abstract

We present a unified mathematical framework for conceptual blending that integrates information-theoretic and category-theoretic approaches through the lens of *quantale weakness*. Conceptual blending, as introduced by Fauconnier and Turner, is a fundamental cognitive operation underlying creative thought. Prior computational approaches have treated information-theoretic measures (emergence, coherence) and category-theoretic constructions (algebraic specifications, colimits) as separate paradigms. We demonstrate that commutative quantales provide the natural algebraic structure to unify these approaches: concepts become V -predicates, vital relations become V -profunctors, blending becomes colimit construction in **V-Cat**, and quality measures arise from quantale weakness. We extend this framework with four novel contributions: (1) vital relations formalized as V -enriched profunctors, (2) Fauconnier-Turner optimality constraints as V -colimit conditions, (3) Peircean habit-weighted priors for culturally grounded blending, and (4) McBride derivatives for local gradient-based blend optimization. Three detailed examples—from commonsense reasoning, scientific discovery, and creative arts—illustrate how this integrated framework captures phenomena inaccessible to either approach alone.

Contents

1	Introduction	3
1.1	Contribution: Quantale Weakness as Unifying Framework	4
1.2	Paper Organization	4
2	Background	4
2.1	Conceptual Blending	4
2.2	Information-Theoretic Approach to Blending	5
2.2.1	Concepts as Fuzzy Property Vectors	5
2.2.2	Blend Membership	5
2.2.3	Emergence	5
2.2.4	Coherence	6
2.3	Category-Theoretic Approach to Blending	6
2.3.1	Concepts as Algebraic Specifications	6
2.3.2	Blending via Colimits	6
2.3.3	Quality Metrics	6
2.4	Quantale Weakness	6
2.4.1	Commutative Quantales	6

2.4.2	Quantale-Enriched Categories	7
2.4.3	Weakness on Enriched Categories	7
2.4.4	Connection to Occam’s Razor	7
3	Unified Framework: Quantale-Based Blending	7
3.1	The Product Quantale for Blending	7
3.2	Concepts as V -Predicates	7
3.3	Weakness-Based Quality Measures	8
3.4	Why the Integration is Natural	8
4	Vital Relations as V-Enriched Structure	9
4.1	Vital Relations as V -Profunctors	9
4.2	Profunctor Composition	9
4.3	Vital Relation Preservation	9
5	Optimality Constraints as Colimit Conditions	10
5.1	V -Enriched Colimits	10
5.2	The Six Constraints	10
5.2.1	Integration	10
5.2.2	Unpacking	10
5.2.3	Metonymic Tightening	11
5.3	Unified Optimality Score	11
6	Peircean Habits for Blending	11
6.1	Peirce’s Tendency to Take Habits	11
6.2	Habit-Weighted Weakness	11
6.3	Fluency vs. Creativity	12
6.4	Habit Dynamics	12
7	McBride Derivatives for Blend Optimization	12
7.1	One-Hole Context Derivatives	12
7.1.1	Weakness Derivative	12
7.1.2	Pattern Intensity Derivative	12
7.1.3	Emergence Derivative	12
7.2	Descent Dynamics in Quantales	12
7.2.1	Ordered Descent Rule	12
7.2.2	Product Quantale Updates	13
7.2.3	Natural Gradient	13
7.3	Hybrid Evolutionary-Local Search	13
8	Detailed Examples	13
8.1	Example 1: Commonsense—“Time is Money”	13
8.1.1	Source Concepts	14
8.1.2	Habit Strengths (Peircean Analysis)	14
8.1.3	Vital Relations as V -Profunctors	14
8.1.4	Blend Construction	14
8.1.5	Emergence	15
8.1.6	Peircean Quality Analysis	15
8.2	Example 2: Science—“Natural Selection as Optimization”	15
8.2.1	Source Concepts	15
8.2.2	Habit Strengths (Pre-Darwin, c. 1850)	15
8.2.3	Generic Space (for Colimit Construction)	16

8.2.4	Colimit Construction and Optimality Constraints	16
8.2.5	McBride Derivative Optimization	16
8.2.6	Emergence Analysis	16
8.2.7	Habit Evolution	17
8.3	Example 3: Creative Arts—“Jazz Fusion as Musical Blending”	17
8.3.1	Source Concepts	17
8.3.2	Vital Relations as V -Profunctors	17
8.3.3	Peircean Habit Analysis	18
8.3.4	Colimit Construction	18
8.3.5	McBride Derivative Refinement	18
8.3.6	Emergent Properties	18
8.3.7	Synthesis: All Extensions	19
9	Implementation Considerations	19
9.1	Data Structures	19
9.2	Core Algorithms	19
9.3	Complexity	19
10	Related Work	20
11	Conclusion	20
A	Quantale Operations: Detailed Definitions	21
A.1	Residuation	21
A.2	Total Correlation in Quantale Form	22
B	Proof Sketches	22
B.1	Proposition: Emergence Criterion	22
B.2	Proposition: Colimit Integration Minimality	22

1 Introduction

Conceptual blending, introduced by Fauconnier and Turner [4], is a cognitive operation that combines elements from distinct mental spaces to produce novel conceptual structures exhibiting *emergent* properties not present in either source. The theory has profound implications for understanding creativity, metaphor, scientific discovery, and everyday reasoning.

Computational approaches to blending have developed along two largely separate trajectories:

Information-Theoretic Approaches. These represent concepts as property vectors with fuzzy membership degrees and measure blend quality through information-theoretic quantities: emergence (properties in the blend exceeding source maxima), coherence (statistical interdependence among properties), and compression (efficient encoding of the blend).

Category-Theoretic Approaches. These represent concepts as algebraic specifications (in languages like CASL) and construct blends via categorical colimits (pushouts, amalgams). Quality is assessed through structural measures: generalization depth, morphism balance, and specification consistency.

Both approaches have merit, yet neither alone captures the full richness of blending. Information-theoretic methods excel at quantifying emergence but lack principled structural composition. Category-theoretic methods provide rigorous compositional structure but struggle to capture graded, fuzzy phenomena.

1.1 Contribution: Quantale Weakness as Unifying Framework

We propose that *commutative quantales* provide the natural mathematical structure to unify these approaches. A quantale $(V, \otimes, \oplus, e, \leq)$ generalizes both:

- Information-theoretic structures: probability spaces, entropy, mutual information
- Category-theoretic structures: enriched categories, profunctors, weighted colimits

The key insight is that *quantale weakness*—measuring how many distinctions a hypothesis fails to make—provides a unified Occam-like bias that:

1. Recovers information-theoretic emergence and coherence as special cases
2. Characterizes categorical colimits via universal properties in **V-Cat**
3. Enables principled composition across heterogeneous representations

We extend this framework with four contributions:

1. **Vital Relations as V-Profunctors** (Section 4): Fauconnier-Turner’s vital relations (Identity, Analogy, Cause-Effect, etc.) are formalized as V -profunctors, enabling compositional reasoning about relational structure in blends.
2. **Optimality Constraints as Colimit Conditions** (Section 5): The six optimality constraints (Integration, Topology, Unpacking, Good Reason, Metonymic Tightening, Relevance) translate to precise conditions on V -enriched colimits.
3. **Peircean Habits for Blending** (Section 6): Peirce’s “tendency to take habits” provides a principled prior over blends, balancing fluency (habit-conforming) with creativity (habit-breaking emergence).
4. **McBride Derivatives for Optimization** (Section 7): One-hole context derivatives enable local gradient-based refinement of blends, complementing global evolutionary search.


1.2 Paper Organization

Section 2 reviews conceptual blending, the information-theoretic and category-theoretic approaches, and quantale weakness. Section 3 presents the unified framework. Section 4–Section 7 develop the four extensions. Section 8 provides three detailed examples. Section 9 sketches implementation. Section 11 concludes.

2 Background

2.1 Conceptual Blending

Fauconnier and Turner’s theory posits that blending operates over a network of *mental spaces*: partial cognitive structures representing scenarios, concepts, or situations. A blend integrates elements from two *input spaces* A and B via a shared *generic space* G , producing a *blended space* C .



Vital Relations. Elements across spaces are connected by *vital relations*: Identity, Analogy, Cause-Effect, Part-Whole, Role-Value, Time, Space, Representation, Property, Similarity, Category, Change, and Intentionality.

Optimality Constraints. High-quality blends satisfy six *optimality constraints*:

1. **Integration:** The blend forms a tightly integrated unit.
2. **Topology (Web):** Appropriate connections are maintained from inputs.
3. **Unpacking:** The blend can be unpacked to recover the inputs.
4. **Good Reason:** Every element has motivation from the inputs.
5. **Metonymic Tightening:** Relations compress in the blend.
6. **Relevance:** Elements serve the blend's purpose.

2.2 Information-Theoretic Approach to Blending

2.2.1 Concepts as Fuzzy Property Vectors

A concept A is represented as a function $m_A : \text{Props} \rightarrow [0, 1]$ assigning to each property p a degree $\deg(p, A) = m_A(p)$ indicating how characteristic p is of A .

2.2.2 Blend Membership

An entity C is a *blend* of A and B if its properties derive from the sources:

$$\mu_{\text{blend}}(C; A, B) = \min \left(\frac{1}{|\text{Props}(C)|} \sum_{p \in \text{Props}(C)} \max\{\deg(p, A), \deg(p, B)\}, 1 \right) \quad (1)$$

2.2.3 Emergence

A property p is *emergent* in blend C if it exceeds both sources:

$$\mu_{\text{emergence}}(p; A, B, C) = \deg(p, C) - \max\{\deg(p, A), \deg(p, B)\} \quad (2)$$

The *high-quality blend membership* weights emergence by shared properties:

$$\mu_{\text{hq}}(C; A, B) = \min \left(\frac{1}{|\text{Props}(C)|} \sum_{p \in \text{Props}(C)} \min\{\deg(p, A), \deg(p, B)\} \cdot \mu_{\text{emergence}}(p; A, B, C), 1 \right) \quad (3)$$

2.2.4 Coherence

Coherence measures the interdependence of blend properties via *total correlation*:

$$TC(C) = \sum_{p \in \text{Props}(C)} H(p) - H(\text{Props}(C)) \quad (4)$$

where $H(\cdot)$ denotes entropy. The normalized coherence is:

$$\mu_{\text{coh}}(C) = \frac{TC(C)}{\sum_p H(p)} \quad (5)$$

2.3 Category-Theoretic Approach to Blending

2.3.1 Concepts as Algebraic Specifications

A concept is represented as an algebraic specification in CASL (Common Algebraic Specification Language) or its prioritized extension PCASL:

$$\text{Spec} = (\Sigma, \Gamma, \pi) \quad (6)$$

where Σ is a signature (sorts, operations), Γ is a set of axioms, and π assigns priorities to elements.

2.3.2 Blending via Colimits

Given specifications A and B with a common generalization G and morphisms $\sigma_A : G \rightarrow A$, $\sigma_B : G \rightarrow B$, the blend is the *colimit* (pushout):

$$C = A \amalg_G B = \text{colim}(A \xleftarrow{\sigma_A} G \xrightarrow{\sigma_B} B) \quad (7)$$

The colimit identifies elements mapped from G and freely combines the rest, subject to consistency.

2.3.3 Quality Metrics

Category-theoretic blending uses metrics including:

- **infoValue**: Information content of the blend specification
- **compression**: Reduction in specification size relative to inputs
- **imbalance**: Asymmetry in contributions from A and B

2.4 Quantale Weakness

2.4.1 Commutative Quantales

Definition 2.1. A commutative quantale $(V, \otimes, \oplus, e, \leq)$ is a complete lattice $(V, \leq)$ equipped with:

- A commutative, associative monoidal product $\otimes : V \times V \rightarrow V$ with unit e
- The lattice join $\oplus$ (supremum) as aggregation
- Distributivity: $a \otimes \bigoplus_i b_i = \bigoplus_i (a \otimes b_i)$

Example 2.2 (Key Quantales). The following are commutative quantales:

1. **Probability**: $([0, 1], \times, +, 1, \leq)$ —product for conjunction, bounded sum for disjunction
2. **Description length**: $(\mathbb{N} \cup \{\infty\}, +, \max, 0, \leq)$ —addition for composition, max for alternatives
3. **Possible worlds**: $(\mathcal{P}(W), \cap, \cup, W, \subseteq)$ —intersection for conjunction, union for disjunction

2.4.2 Quantale-Enriched Categories

A category $\mathcal{C}$ is *enriched over* a quantale V if:

- For each pair of objects X, Y , there is a hom-object $\mathcal{C}(X, Y) \in V$
- Composition: $\mathcal{C}(Y, Z) \otimes \mathcal{C}(X, Y) \leq \mathcal{C}(X, Z)$
- Identity: $e \leq \mathcal{C}(X, X)$

2.4.3 Weakness on Enriched Categories

Definition 2.3 (Quantale Weakness). *Let $\mathcal{C}$ be enriched over $(V, \otimes, \oplus, e, \leq)$ with objects U and valuation $\mu : U \rightarrow V$. For a relation $H \subseteq U \times U$, define the weakness:*

$$w(H) = \bigoplus_{(u,v) \in H} \mu(u) \otimes \mu(v) \quad (8)$$

Interpretation. Weakness measures the aggregate importance of pairs that the relation fails to distinguish. Higher weakness means more indistinction among high-value elements—a “weaker” (more general) hypothesis.

2.4.4 Connection to Occam’s Razor

Quantale weakness unifies classical simplicity measures:

- **MDL (Minimum Description Length):** Using $V = (\mathbb{N} \cup \{\infty\}, +, \max, 0, \leq)$ with $\mu(c) = 1$ per symbol, $w(H)$ equals description length.
- **Bennett’s Weakness:** Using $V = (\mathcal{P}(W), \cap, \cup, W, \subseteq)$ with $\mu(c) = \{w \in W : w \models c\}$, $w(H)$ is the set of worlds consistent with all constraints.
- **Probabilistic:** Using $V = ([0, 1], \times, +, 1, \leq)$ with $\mu(u) = p(u)$, weakness relates to Ellerman’s logical entropy.

3 Unified Framework: Quantale-Based Blending

3.1 The Product Quantale for Blending

We work over the *product quantale*:

$$Q = Q_{\text{logic}} \times Q_{\text{tv}} \quad (9)$$

where:

$$Q_{\text{logic}} = (\mathcal{P}(W), \cap, \cup, W, \subseteq) \quad (\text{denotational/possible-worlds}) \quad (10)$$

$$Q_{\text{tv}} = ([0, 1], \times, +, 1, \leq) \quad (\text{fuzzy truth values}) \quad (11)$$

Operations on Q are component-wise:

$$(A_1, x_1) \otimes (A_2, x_2) = (A_1 \cap A_2, x_1 \cdot x_2) \quad (12)$$

$$(A_1, x_1) \oplus (A_2, x_2) = (A_1 \cup A_2, \min(x_1 + x_2, 1)) \quad (13)$$

3.2 Concepts as V -Predicates

Definition 3.1. A concept A is a V -predicate $m_A : \text{Props} \rightarrow Q$:

$$m_A(p) = (\llbracket p \rrbracket_A, \deg(p, A)) \quad (14)$$

where $\llbracket p \rrbracket_A \subseteq W$ is the set of worlds where A has property p , and $\deg(p, A) \in [0, 1]$ is the fuzzy degree.

This representation captures both:

- **Crisp algebraic structure:** The logic component $\llbracket \cdot \rrbracket_A$ corresponds to the denotational semantics of CASL specifications.
- **Fuzzy degrees:** The tv component $\deg(\cdot, A)$ matches the information-theoretic property vectors.

3.3 Weakness-Based Quality Measures

Definition 3.2 (Concept Weakness). *The weakness of concept A given valuation $\varphi : \text{Props} \rightarrow Q$:*

$$w(A) = \bigoplus_{p \in \text{Props}} \varphi(p) \otimes m_A(p) \quad (15)$$

Definition 3.3 (Pattern Intensity). *The intensity of pattern A in concept C :*

$$I_A(C) = w(A) \Rightarrow w(C) \quad (16)$$

where $\Rightarrow$ is the quantale residuation: $a \otimes b \leq c \iff b \leq a \Rightarrow c$.

Definition 3.4 (Joint Pattern Intensity). *For source concepts A, B and blend C :*

$$I_{A,B}(C) = (w(A) \otimes w(B)) \Rightarrow w(C) \quad (17)$$

Definition 3.5 (Emergence (Synergy)). *The emergence of blend C from sources A, B :*

$$\sigma_{A,B}(C) = (I_A(C) \otimes I_B(C)) \Rightarrow I_{A,B}(C) \quad (18)$$

C exhibits emergence iff $\sigma_{A,B}(C) \geq e$.

Proposition 3.6. *The quantale synergy criterion $\sigma_{A,B}(C) \geq e$ holds iff:*

$$I_{A,B}(C) \not\leq I_A(C) \otimes I_B(C) \quad (19)$$

That is, the joint contribution exceeds the product of individual contributions.

Definition 3.7 (Coherence). *Let $H_C \subseteq \text{Props} \times \text{Props}$ be the set of property pairs that should cohere in C . The internal weakness is:*

$$w_{\text{int}}(C) = \bigoplus_{(p,q) \in H_C} m_C(p) \otimes m_C(q) \quad (20)$$

The coherence measure is:

$$\mu_{\text{coh}}(C) = \frac{w_{\text{int}}(C)}{w(C) \otimes w(C)} \quad (21)$$

3.4 Why the Integration is Natural

The quantale framework unifies information-theoretic and category-theoretic approaches because:

1. **Shared Algebraic Structure:** Both approaches rely on monoidal operations ($\wedge/\otimes$ for conjunction, $\vee/\oplus$ for disjunction) and residuation ($\Rightarrow$ for implication/abstraction). Quantales make this structure explicit and compositional.
2. **Graded and Crisp in One Framework:** The product quantale $Q_{\text{logic}} \times Q_{\text{tv}}$ carries both crisp set-theoretic semantics and graded fuzzy degrees. Operations respect both components simultaneously.

3. **Weakness as Universal Quality Measure:** The weakness function $w(H)$ generalizes both MDL (syntactic simplicity) and Bennett’s weakness (semantic generality). Applied to blends, it captures emergence, coherence, and structural properties.
4. **Enriched Categories Bridge Representations:** V -enriched categories allow concepts to have “graded” relationships. Colimits in **V-Cat** preserve this grading, enabling fuzzy categorical constructions.
5. **Compositionality:** Quantale operations compose correctly. A blend-of-blends, nested generalization, or chained vital relations all work through the same algebraic machinery.

4 Vital Relations as V -Enriched Structure

4.1 Vital Relations as V -Profunctors

Definition 4.1. Let $\mathcal{C}_{\text{Conc}}$ be the V -enriched category of concepts. A vital relation R is a V -profunctor (distributor, bimodule):

$$R : \mathcal{C}_{\text{Conc}}^{\text{op}} \otimes \mathcal{C}_{\text{Conc}} \rightarrow V \quad (22)$$

assigning to each pair (A, B) a value $R(A, B) \in Q$ representing the degree/manner to which A and B stand in relation R .

For the product quantale:

$$R(A, B) = (\llbracket A \ R \ B \rrbracket, \deg(R; A, B)) \quad (23)$$

where $\llbracket A \ R \ B \rrbracket$ is the set of worlds where A and B are R -related, and $\deg(R; A, B)$ is the fuzzy strength.

4.2 Profunctor Composition

V -profunctors compose via the coend formula:

$$(S \circ R)(A, C) = \bigoplus_{B \in \mathcal{C}_{\text{Conc}}} R(A, B) \otimes S(B, C) \quad (24)$$

Example 4.2. Composing CAUSE-EFFECT with PART-WHOLE:

$$(\text{PART-WHOLE} \circ \text{CAUSE-EFFECT})(A, C) = \bigoplus_B \text{CAUSE-EFFECT}(A, B) \otimes \text{PART-WHOLE}(B, C) \quad (25)$$

captures “part of a cause relates to part of an effect.”

4.3 Vital Relation Preservation

Definition 4.3. A blend C preserves vital relation R from source A if for all $a, a' \in A$ with images $\iota_A(a), \iota_A(a')$ in C :

$$R_A(a, a') \leq R_C(\iota_A(a), \iota_A(a')) \quad (26)$$

In quantale terms, the pullback of blend relations dominates source relations:

$$\iota_A^*(R_C) \geq R_A \quad (27)$$

Definition 4.4 (Vital Relation Coherence). For blend C with vital relations $\mathcal{R}$:

$$\text{VR-coh}(C) = \bigwedge_{R \in \mathcal{R}} \bigwedge_{p, q \in \text{Props}(C)} (R_A(p_A, q_A) \otimes R_B(p_B, q_B)) \Rightarrow R_C(p, q) \quad (28)$$

5 Optimality Constraints as Colimit Conditions

We now translate Fauconnier-Turner's optimality constraints to conditions on V -enriched colimits.

5.1 V -Enriched Colimits

In a V -enriched category, the colimit of diagram $D : J \rightarrow \mathcal{C}$ is an object C with cocone $(\iota_j : D(j) \rightarrow C)_{j \in J}$ satisfying:

$$\mathcal{C}(C, X) \cong \lim_{j \in J^{\text{op}}} \mathcal{C}(D(j), X) \quad (29)$$

For the blend diagram $A \xleftarrow{\sigma_A} G \xrightarrow{\sigma_B} B$, this becomes a pushout in **V-Cat**:

$$\mathcal{C}(C, X) \cong \mathcal{C}(A, X) \otimes_{\mathcal{C}(G, X)} \mathcal{C}(B, X) \quad (30)$$

5.2 The Six Constraints

Constraint	V -Colimit Condition	Quantale Measure
Integration	C is the colimit (not just cocone)	$\text{Int}(C) = \mathcal{C}(A, C) \otimes \mathcal{C}(B, C)$ minimal
Topology	Vital relations preserved	$\text{VR-coh}(C)$ from §4
Unpacking	Cocone morphisms V -split	$\text{Unpack}(C) = \mathcal{C}(C, A) \otimes \mathcal{C}(A, C) \geq \theta$
Good Reason	Blend generated by cocone images	$m_C(p) \leq \bigoplus (\text{input contributions})$
Met. Tightening	Relations strengthen via G	$\text{Tighten}(C; R) = R_C - (R_A \otimes_G R_B) \geq 0$
Relevance	Weighted/filtered colimit	Weights w_A, w_B or filter J_{rel}

Table 1: Optimality constraints as V -colimit conditions.

5.2.1 Integration

Definition 5.1. C is tightly integrated iff C is the actual colimit (satisfying the universal property), not merely a cocone. The integration measure:

$$\text{Int}(C) = \mathcal{C}(A, C) \otimes \mathcal{C}(B, C) \quad (31)$$

is minimal for the true colimit among all valid cocones.

5.2.2 Unpacking

Definition 5.2. The cocone morphism $\iota_A : A \rightarrow C$ is V -split if there exists $\pi_A : C \rightarrow A$ such that:

$$\mathcal{C}(A, C) \otimes \mathcal{C}(C, A) \geq e_A \quad (32)$$

The unpacking measure:

$$\text{Unpack}(C) = (\mathcal{C}(C, A) \otimes \mathcal{C}(A, C)) \oplus (\mathcal{C}(C, B) \otimes \mathcal{C}(B, C)) \quad (33)$$

5.2.3 Metonymic Tightening

Definition 5.3. *Blend C exhibits metonymic tightening for vital relation R if:*

$$R_C(\iota_A(a), \iota_B(b)) \geq R_A(a, g) \otimes R_B(g, b) \quad (34)$$

for elements $a \in A$, $b \in B$ with common preimage $g \in G$.

The tightening measure:

$$\text{Tighten}(C; R) = \bigwedge_{a,b,g} R_C(\iota_A(a), \iota_B(b)) \ominus (R_A(a, g) \otimes R_B(g, b)) \quad (35)$$

5.3 Unified Optimality Score

$$\text{Opt}(C) = \text{Int}(C) \otimes \text{VR-coh}(C) \otimes \text{Unpack}(C) \otimes \text{GoodReason}(C) \otimes \text{Tighten}(C) \otimes \text{Relevance}(C) \quad (36)$$

Alternatively, for multi-objective optimization:

$$\text{Opt}(C) = \langle \text{Int}, \text{VR-coh}, \text{Unpack}, \text{GoodReason}, \text{Tighten}, \text{Relevance} \rangle \quad (37)$$

6 Peircean Habits for Blending

6.1 Peirce's Tendency to Take Habits

Charles Sanders Peirce proposed that the universe exhibits a fundamental *tendency to take habits*: regularities emerge and entrench through repetition. For blending, this suggests:

- **Habit-weighted priors:** Blends involving frequently co-occurring concepts are easier to construct and comprehend.
- **Habit-breaking as creativity:** Genuine novelty requires overcoming entrenched habits.
- **Habit-formation:** Successful blends become new habits.

6.2 Habit-Weighted Weakness

Definition 6.1 (Peircean Habit Strength). *The habit strength $M_P : U \times U \rightarrow \mathbb{R}_{\geq 0}$ encodes associative entrenchment. Operationalizations include:*

$$M_P^{\text{freq}}(u, v) = \frac{\text{count}(u, v)}{\text{count}(u) + \text{count}(v) - \text{count}(u, v)} \quad (\text{Jaccard co-occurrence}) \quad (38)$$

$$M_P^{\text{PMI}}(u, v) = \log \frac{P(u, v)}{P(u) \cdot P(v)} \quad (\text{Pointwise Mutual Information}) \quad (39)$$

$$M_P^{\text{emb}}(u, v) = \text{sim}(\vec{e}_u, \vec{e}_v) \quad (\text{Embedding similarity}) \quad (40)$$

Definition 6.2 (Habit-Weighted Joint Measure). *The Peircean joint valuation:*

$$\mu_P(u, v) = \mu(u) \cdot \mu(v) + \lambda_P \cdot M_P(u, v) \quad (41)$$

where $\lambda_P \geq 0$ controls habit influence.

Definition 6.3 (Habit-Weighted Weakness).

$$w_P(H) = \sum_{(u,v) \in H} \mu_P(u, v) \quad (42)$$

6.3 Fluency vs. Creativity

Definition 6.4 (Habit Bonus). *Reward for combining habitually associated properties:*

$$\text{HabitBonus}(C; A, B) = \bigoplus_{p \in \text{Props}(C)} M_P(p_A, p_B) \otimes m_C(p) \quad (43)$$

Definition 6.5 (Habit Break). *Reward for emergent properties from weakly associated sources:*

$$\text{HabitBreak}(C; A, B) = \bigoplus_{p \in \text{Props}(C)} (e \ominus M_P(p_A, p_B)) \otimes m_C(p) \otimes \mu_{\text{emergence}}(p) \quad (44)$$

Definition 6.6 (Peircean Blend Quality).

$$Q_P(C) = \alpha \cdot \text{HabitBonus}(C) + (1 - \alpha) \cdot \text{HabitBreak}(C) \cdot \sigma_{A,B}(C) \quad (45)$$

where $\alpha \in [0, 1]$ balances fluency (high α) vs. creativity (low α).

6.4 Habit Dynamics

The framework supports dynamic habit evolution:

- **Accumulation:** Successful blends strengthen M_P for their mappings.
- **Decay:** Unused associations weaken: $M_P(u, v) \leftarrow \gamma \cdot M_P(u, v)$.
- **Transfer:** Habits in one domain bootstrap blending in related domains.

7 McBride Derivatives for Blend Optimization

7.1 One-Hole Context Derivatives

McBride derivatives compute the sensitivity of a structure to changes at a single point—the “one-hole context.” For quantale-valued objectives, this enables local gradient-like optimization.

7.1.1 Weakness Derivative

Proposition 7.1. *The McBride derivative of weakness at property p :*

$$\partial_p w(C) = \varphi(p) \quad (46)$$

7.1.2 Pattern Intensity Derivative

Proposition 7.2.

$$\partial_p I_A(C) = w(A) \Rightarrow \varphi(p) \quad (47)$$

$$\partial_p I_{A,B}(C) = (w(A) \otimes w(B)) \Rightarrow \varphi(p) \quad (48)$$

7.1.3 Emergence Derivative

Proposition 7.3.

$$\partial_p \sigma_{A,B}(C) = (I_A(C) \otimes I_B(C)) \Rightarrow ((w(A) \otimes w(B)) \Rightarrow \varphi(p)) \quad (49)$$

7.2 Descent Dynamics in Quantales

7.2.1 Ordered Descent Rule

For maximization (emergence, coherence):

$$m_C^{(t+1)}(p) = m_C^{(t)}(p) \oplus (\eta \otimes \partial_p \sigma_{A,B}(C)) \quad (50)$$

where $\eta \in V$ is the quantale-valued step size.

7.2.2 Product Quantale Updates

For $Q = Q_{\text{logic}} \times Q_{\text{tv}}$:

$$\llbracket p \rrbracket_C^{(t+1)} = \llbracket p \rrbracket_C^{(t)} \cup (\eta_{\text{logic}} \cap \partial_p^{\text{logic}} \sigma) \quad (51)$$

$$\deg^{(t+1)}(p, C) = \deg^{(t)}(p, C) + \eta_{\text{tv}} \cdot \partial_p^{\text{tv}} \sigma_{A,B}(C) \quad (52)$$

7.2.3 Natural Gradient

Using Fisher-like metric $g_{pp}(C) = \deg(p, C)(1 - \deg(p, C))$:

$$\deg^{(t+1)}(p, C) = \deg^{(t)}(p, C) + \eta \cdot \deg(p, C) \cdot (1 - \deg(p, C)) \cdot \partial_p^{\text{tv}} \sigma_{A,B}(C) \quad (53)$$

This automatically prevents convergence to boundary values (the “trivial solution” problem).

7.3 Hybrid Evolutionary-Local Search

Algorithm 1 Memetic Quantale Blending

Require: Sources A, B , generic space G , vital relations $\mathcal{R}$, habit memory M_P

Ensure: Pareto front of high-quality blends

- 1: Initialize population $\mathcal{P}$ with habit-biased sampling
 - 2: **for** generation = 1 to max_gen **do**
 - 3: **for** each $C \in \mathcal{P}$ **do**
 - 4: Evaluate multi-objective fitness: $(\sigma, \mu_{\text{coh}}, Q_P, \text{Opt})$
 - 5: **end for**
 - 6: **for** each $C \in \mathcal{P}$ with probability p_{local} **do**
 - 7: $C \leftarrow \text{MCBRIDEREFINE}(C, A, B, \text{steps})$
 - 8: **end for**
 - 9: $\mathcal{P}_{\text{parents}} \leftarrow \text{Pareto tournament selection}$
 - 10: $\mathcal{P}_{\text{offspring}} \leftarrow \text{Crossover and mutation}$
 - 11: $\mathcal{P} \leftarrow \text{Environmental selection from } \mathcal{P} \cup \mathcal{P}_{\text{offspring}}$
 - 12: Update M_P with successful blends (habit formation)
 - 13: Apply habit decay: $M_P \leftarrow \gamma \cdot M_P$
 - 14: **end for**
 - 15: **return** Pareto front of $\mathcal{P}$
-

8 Detailed Examples

We now present three detailed examples illustrating how the integrated framework captures phenomena inaccessible to either approach alone.

8.1 Example 1: Commonsense—“Time is Money”

This example highlights **Peircean habits** and **vital relations**.

8.1.1 Source Concepts

TIME (as V -predicate):

$$\begin{aligned} m_{\text{TIME}}(\text{duration}) &= (W_{\text{temporal}}, 0.95) \\ m_{\text{TIME}}(\text{passage}) &= (W_{\text{flow}}, 0.90) \\ m_{\text{TIME}}(\text{finite}) &= (W_{\text{bounded}}, 0.85) \\ m_{\text{TIME}}(\text{valuable}) &= (W_{\text{worth}}, 0.70) \\ m_{\text{TIME}}(\text{spent}) &= (W_{\text{expenditure}}, 0.80) \end{aligned}$$

MONEY (as V -predicate):

$$\begin{aligned} m_{\text{MONEY}}(\text{currency}) &= (W_{\text{economic}}, 0.95) \\ m_{\text{MONEY}}(\text{exchange}) &= (W_{\text{transaction}}, 0.90) \\ m_{\text{MONEY}}(\text{finite}) &= (W_{\text{bounded}}, 0.80) \\ m_{\text{MONEY}}(\text{valuable}) &= (W_{\text{worth}}, 0.95) \\ m_{\text{MONEY}}(\text{spent}) &= (W_{\text{expenditure}}, 0.90) \end{aligned}$$

8.1.2 Habit Strengths (Peircean Analysis)

Property Pair	M_P
$(\text{finite}_T, \text{finite}_M)$	0.30
$(\text{valuable}_T, \text{valuable}_M)$	0.70
$(\text{spent}_T, \text{spent}_M)$	0.80
$(\text{duration}_T, \text{currency}_M)$	0.05
$(\text{passage}_T, \text{exchange}_M)$	0.15

The high-habit pairs (spent, valuable, finite) form the blend's foundation.

8.1.3 Vital Relations as V -Profunctors

The blend exploits the ANALOGY vital relation:

$$\text{ANALOGY}(\text{TIME}, \text{MONEY}) = (W_{\text{resource}}, 0.75) \quad (54)$$

This decomposes into property-level analogies:

$$\begin{aligned} \text{ANALOGY}(\text{spent}_T, \text{spent}_M) &= (W_{\text{expenditure}}, 0.85) \\ \text{ANALOGY}(\text{valuable}_T, \text{valuable}_M) &= (W_{\text{worth}}, 0.80) \end{aligned}$$

Vital relation preservation requires:

$$\text{ANALOGY}_{\text{BLEND}}(\iota(\text{spent}_T), \iota(\text{spent}_M)) \geq (W_{\text{expenditure}}, 0.85) \quad (55)$$

8.1.4 Blend Construction

The blend “TIME-IS-MONEY” inherits:

$$\begin{aligned} m_C(\text{spending_time}) &= (W_{\text{expenditure}} \cap W_{\text{temporal}}, 0.85) \\ m_C(\text{time_value}) &= (W_{\text{worth}} \cap W_{\text{temporal}}, 0.80) \\ m_C(\text{time_budget}) &= (W_{\text{allocation}}, 0.75) \end{aligned}$$

8.1.5 Emergence

Emergent properties not in either source:

- **“Wasting” time:** Stronger negative valence than wasting money
- **“Investing” time:** Future returns on time expenditure
- **Time inflation:** Busy periods “cost” more per unit

Computing emergence:

$$\mu_{\text{emergence}}(\text{investing_time}) = 0.70 - \max(0.20, 0.60) = 0.10 > 0 \quad (56)$$

8.1.6 Peircean Quality Analysis

$$\text{HabitBonus} = 0.80 \cdot 0.85 + 0.70 \cdot 0.80 + 0.30 \cdot 0.75 = 1.465$$

$$\text{HabitBreak} = (1 - 0.05) \cdot 0.10 \cdot 0.70 = 0.067$$

$$\sigma_{A,B}(C) = 0.65 \quad (\text{moderate emergence})$$

$$Q_P(C; \alpha = 0.6) = 0.6 \cdot 1.465 + 0.4 \cdot 0.067 \cdot 0.65 = 0.896$$

The blend scores high on fluency (habit-conforming core) with moderate creativity (emergent investment/inflation concepts).

8.2 Example 2: Science—“Natural Selection as Optimization”

This example highlights **optimality constraints as colimit conditions** and **McBride derivatives**.

8.2.1 Source Concepts

BIOLOGICAL EVOLUTION :

$$m_E(\text{variation}) = (W_{\text{genetic}}, 0.90)$$

$$m_E(\text{inheritance}) = (W_{\text{heredity}}, 0.95)$$

$$m_E(\text{differential_reproduction}) = (W_{\text{selection}}, 0.85)$$

$$m_E(\text{adaptation}) = (W_{\text{fitness}}, 0.80)$$

$$m_E(\text{population}) = (W_{\text{species}}, 0.90)$$

MATHEMATICAL OPTIMIZATION :

$$m_O(\text{search_space}) = (W_{\text{solutions}}, 0.95)$$

$$m_O(\text{iteration}) = (W_{\text{algorithm}}, 0.90)$$

$$m_O(\text{objective_function}) = (W_{\text{fitness}}, 0.95)$$

$$m_O(\text{convergence}) = (W_{\text{optimum}}, 0.85)$$

$$m_O(\text{solution_population}) = (W_{\text{candidates}}, 0.85)$$

8.2.2 Habit Strengths (Pre-Darwin, c. 1850)

Property Pair	M_P (1850)
(variation _E , search_space _O)	0.05
(adaptation _E , convergence _O)	0.10
(differential_reproduction _E , objective_function _O)	0.02
(population _E , solution_population _O)	0.08

All habit strengths are very low—this was a *revolutionary* blend.

8.2.3 Generic Space (for Colimit Construction)

The generic space G captures shared abstract structure:

$$\begin{aligned} m_G(\text{variation_source}) &= (W_{\text{diversity}}, 0.70) \\ m_G(\text{selection_pressure}) &= (W_{\text{filtering}}, 0.65) \\ m_G(\text{improvement_over_time}) &= (W_{\text{progress}}, 0.60) \end{aligned}$$

8.2.4 Colimit Construction and Optimality Constraints

Integration. The blend forms a tightly integrated unit:

$$\text{Int}(C) = \mathcal{C}(E, C) \otimes \mathcal{C}(O, C) = (W_{\text{evolutionary_optimization}}, 0.75) \quad (57)$$

Topology (Web). Vital relations preserved:

$$\text{VR-coh}(C) = \text{ANALOGY}(E, O)_C \geq \text{ANALOGY}(E, O)_G = (W_{\text{abstract}}, 0.70) \quad (58)$$

Unpacking. The blend can be unpacked:

$$\begin{aligned} \text{Unpack}(C) &= \mathcal{C}(C, E) \otimes \mathcal{C}(E, C) + \mathcal{C}(C, O) \otimes \mathcal{C}(O, C) \\ &\geq (W, 0.80) \quad \checkmark \end{aligned}$$

Good Reason. Every blend element traces to inputs:

- “Fitness landscape” $\leftarrow$ adaptation + objective function
- “Selection pressure” $\leftarrow$ differential reproduction + optimization gradient

Metonymic Tightening. Relations compress:

$$\text{Tighten}(C; \text{CAUSE-EFFECT}) = R_C(\text{variation, adaptation}) - R_E \otimes_G R_O = 0.15 > 0 \quad (59)$$

8.2.5 McBride Derivative Optimization

To refine the blend, compute gradients for emergence:

$$\begin{aligned} \partial_{\text{fitness_landscape}} \sigma_{E,O}(C) &= (I_E \otimes I_O) \Rightarrow ((w_E \otimes w_O) \Rightarrow \varphi(\text{fitness_landscape})) \\ &= 0.65 \Rightarrow (0.72 \Rightarrow 0.80) = 0.68 \end{aligned}$$

Gradient ascent step:

$$\text{deg}^{(t+1)}(\text{fitness_landscape}) = 0.75 + 0.1 \cdot 0.75 \cdot 0.25 \cdot 0.68 = 0.763 \quad (60)$$

Natural gradient scaling prevents runaway: step size $\propto \text{deg}(1 - \text{deg})$.

8.2.6 Emergence Analysis

Emergent properties (not in either source alone):

- **Fitness landscape:** Geometric visualization of evolution
- **Local optima traps:** Evolutionary dead-ends as suboptimal convergence
- **Genetic algorithms:** Reverse engineering evolution for optimization
- **Neutral networks:** Flat regions in fitness space

$$\sigma_{E,O}(C) = 0.82 \quad (\text{very high emergence}) \quad (61)$$

8.2.7 Habit Evolution

By 2025, the blend has become entrenched:

Property Pair	M_P (1850)	M_P (2025)
(variation _E , search_space _O)	0.05	0.75
(adaptation _E , convergence _O)	0.10	0.80
(fitness _E , fitness _O)	0.00	0.90

The revolutionary blend became a conceptual habit.

8.3 Example 3: Creative Arts—“Jazz Fusion as Musical Blending”

This example highlights **all four extensions** working together.

8.3.1 Source Concepts

TRADITIONAL JAZZ :

$$\begin{aligned}
m_J(\text{swing_rhythm}) &= (W_{\text{groove}}, 0.90) \\
m_J(\text{blues_harmony}) &= (W_{\text{tonal}}, 0.85) \\
m_J(\text{improvisation}) &= (W_{\text{spontaneous}}, 0.95) \\
m_J(\text{acoustic_instruments}) &= (W_{\text{organic}}, 0.90) \\
m_J(\text{call_response}) &= (W_{\text{dialogue}}, 0.80)
\end{aligned}$$

ELECTRONIC MUSIC :

$$\begin{aligned}
m_E(\text{synthesized_timbre}) &= (W_{\text{digital}}, 0.95) \\
m_E(\text{sequenced_rhythm}) &= (W_{\text{precise}}, 0.90) \\
m_E(\text{layered_production}) &= (W_{\text{studio}}, 0.85) \\
m_E(\text{electronic_instruments}) &= (W_{\text{technology}}, 0.95) \\
m_E(\text{loop_structure}) &= (W_{\text{repetition}}, 0.85)
\end{aligned}$$

8.3.2 Vital Relations as V -Profunctors

Analogy relations:

$$\begin{aligned}
\text{ANALOGY}(\text{improvisation}_J, \text{live_manipulation}_E) &= (W_{\text{real-time}}, 0.70) \\
\text{ANALOGY}(\text{call_response}_J, \text{sequencer_interaction}_E) &= (W_{\text{dialogue}}, 0.50)
\end{aligned}$$

Disanalogy relations (creative tension):

$$\begin{aligned}
\text{DISANALOGY}(\text{swing_rhythm}_J, \text{sequenced_rhythm}_E) &= (W_{\text{contrast}}, 0.80) \\
\text{DISANALOGY}(\text{acoustic}_J, \text{electronic}_E) &= (W_{\text{contrast}}, 0.90)
\end{aligned}$$

Vital relation preservation in the blend:

$$\text{VR-coh}(C) = \bigwedge_R (R_J \otimes R_E) \Rightarrow R_C = (W_{\text{fusion}}, 0.72) \quad (62)$$

8.3.3 Peircean Habit Analysis

Property Pair	M_P (1970)	M_P (2025)
(improvisation _J , live_manipulation _E)	0.10	0.70
(swing _J , sequenced _E)	0.05	0.45
(acoustic _J , synthesized _E)	0.02	0.55
(blues_harmony _J , layered_production _E)	0.08	0.50

In 1970 (Miles Davis’s *Bitches Brew*), this was a **habit-breaking** blend:

$$\text{HabitBreak}(C; 1970) = 0.88, \quad \sigma_{J,E}(C) = 0.75 \quad (63)$$

By 2025, jazz-electronic fusion is established:

$$\text{HabitBonus}(C; 2025) = 0.72, \quad \text{HabitBreak}(C; 2025) = 0.35 \quad (64)$$

8.3.4 Colimit Construction

The generic space G captures shared musical structure:

$$\begin{aligned} m_G(\text{rhythm}) &= (W_{\text{temporal}}, 0.80) \\ m_G(\text{harmony}) &= (W_{\text{pitch}}, 0.75) \\ m_G(\text{performance}) &= (W_{\text{execution}}, 0.70) \end{aligned}$$

The blend $C = J \amalg_G E$ satisfies optimality constraints:

Integration: The fusion forms a coherent style, not mere juxtaposition.

$$\text{Int}(C) = (W_{\text{fusion}}, 0.78) \quad (65)$$

Metonymic Tightening: Distant relations become direct:

- “Human-machine dialogue” tightens call-response + sequencer interaction
- “Organic electronics” tightens acoustic warmth + digital precision

8.3.5 McBride Derivative Refinement

Starting from an initial blend, refine toward higher emergence:

$$\begin{aligned} \partial_{\text{human-machine}} \sigma &= 0.72 \\ \text{deg}^{(t+1)}(\text{human-machine}) &= 0.65 + 0.1 \cdot 0.65 \cdot 0.35 \cdot 0.72 = 0.666 \end{aligned}$$

After 10 iterations of natural gradient ascent:

$$\sigma_{J,E}^{(10)}(C) = 0.81 \quad (\text{improved from } 0.75) \quad (66)$$

8.3.6 Emergent Properties

The blend exhibits properties absent from both sources:

- “**Controlled chaos**”: Improvisation within electronic constraints
- “**Groove quantization**”: Swing feel with digital precision
- “**Timbral morphing**”: Acoustic-to-synthetic transformation in real-time
- “**Algorithmic call-response**”: AI as improvisation partner

8.3.7 Synthesis: All Extensions

1. **Vital relations:** ANALOGY and DISANALOGY profunctors structure the blend’s creative tensions.
2. **Optimality constraints:** Integration ensures coherent style; metonymic tightening creates “human-machine dialogue.”
3. **Peircean habits:** 1970’s revolutionary blend (low M_P , high HabitBreak) became 2025’s established genre (high M_P , high HabitBonus).
4. **McBride derivatives:** Local refinement increased emergence from 0.75 to 0.81.

9 Implementation Considerations

9.1 Data Structures

Definition 9.1 (Quantale Value). *A value in the product quantale:*

`QuantaleValue = (logic: Set[World], tv: float)`

with operations:

$$\begin{aligned} (A_1, x_1) \otimes (A_2, x_2) &= (A_1 \cap A_2, x_1 \cdot x_2) \\ (A_1, x_1) \oplus (A_2, x_2) &= (A_1 \cup A_2, \min(x_1 + x_2, 1)) \\ (A_1, x_1) \Rightarrow (A_2, x_2) &= (A_2 \cup \overline{A_1}, x_2/x_1) \end{aligned}$$

Definition 9.2 (Concept). `Concept = {property: str -> QuantaleValue}`

Definition 9.3 (Habit Memory). `HabitMemory = {`

`pair_counts: (str, str) -> int,`
`embeddings: str -> Vector,`
`causal_links: (str, str) -> float`

`}`

9.2 Core Algorithms

The hybrid memetic algorithm (Algorithm 1) combines:

- **Global search:** Evolutionary operators (crossover, mutation) explore the blend space
- **Local refinement:** McBride derivative ascent exploits promising regions
- **Peircean priors:** Habit-weighted initialization and fitness
- **Constraint satisfaction:** Colimit conditions filter valid blends

9.3 Complexity

Let $n = |\text{Props}|$, $m = |\text{vital relations}|$, $k = |W|$ (worlds).

- Weakness computation: $O(n \cdot k)$
- Emergence evaluation: $O(n)$
- Vital relation coherence: $O(n^2 \cdot m)$
- McBride gradient: $O(n)$ per property
- Colimit construction: Depends on specification complexity

For practical applications, k (worlds) can be approximated via sampling or symbolic representation.

10 Related Work

Conceptual Blending. Fauconnier and Turner [4] introduced the theory. Computational implementations include [8] (algebraic semiotics), [10] (CASL-based), and [3] (ontology blending).

Quantales and Enriched Categories. Quantale theory originates with Mulvey [12]. Lawvere’s enriched categories [11] provide the categorical foundation. Applications to logic appear in [2].

Weakness and Simplicity. Bennett [1] develops weakness as a foundational concept. MDL foundations are in [9]. Quantale weakness for AGI appears in [7].

Peircean Semiotics. Peirce’s philosophical works [13] introduce habit-taking. Applications to AI include [5].

11 Conclusion

We have presented a unified framework for conceptual blending that integrates information-theoretic and category-theoretic approaches through quantale weakness. The key contributions are:

1. **Unification:** The product quantale $Q_{\text{logic}} \times Q_{\text{tv}}$ carries both crisp algebraic structure and graded fuzzy degrees, enabling seamless integration.
2. **Vital Relations as V -Profunctors:** Fauconnier-Turner’s vital relations become compositional, gradable structures supporting rich relational reasoning.
3. **Optimality as Colimit Conditions:** The six optimality constraints translate precisely to conditions on V -enriched colimits, providing mathematical rigor to qualitative intuitions.
4. **Peircean Habit Priors:** Habit-weighted weakness captures the balance between fluency and creativity, with dynamic habit evolution modeling cultural entrenchment.
5. **McBride Derivatives:** One-hole context derivatives enable local gradient-based optimization, complementing global evolutionary search.

The three detailed examples demonstrate that this integrated framework captures phenomena—cultural entrenchment of metaphors, revolutionary scientific blends, dynamic artistic fusion—that are inaccessible to either approach alone.

Future Work. Directions include:

- Quantum quantales for blending under uncertainty
- Integration with large language models for property extraction
- Application to scientific hypothesis generation
- Implementation in the Hyperon/PRIMUS cognitive architecture

References

- [1] C. H. Bennett. Weak and strong conceptions of simplicity. Manuscript, 2019.
- [2] B. Coecke, M. Sadrzadeh, and S. Clark. Mathematical foundations for a compositional distributional model of meaning. *Linguistic Analysis*, 36(1-4):345–384, 2013.
- [3] R. Confalonieri, M. Schorlemmer, O. Kutz, R. Peñaloza, E. Plaza, and M. Eppe. Conceptual blending in EL++. In *Proc. KR*, 2018.
- [4] G. Fauconnier and M. Turner. *The Way We Think: Conceptual Blending and the Mind’s Hidden Complexities*. Basic Books, 2002.
- [5] J. H. Fetzer. *Computers and Cognition: Why Minds Are Not Machines*. Kluwer, 2001.
- [6] B. Goertzel. A formalization of concept blending: An information-theoretic approach. In *Proc. AGI-25*, 2025.
- [7] B. Goertzel. Quantale weakness: A unifying Occam-like bias for AGI. Keynote, AGI-25, 2025.
- [8] J. Goguen. What is a concept? In *Conceptual Structures: Common Semantics for Sharing Knowledge*, pages 52–77. Springer, 2005.
- [9] P. D. Grünwald. *The Minimum Description Length Principle*. MIT Press, 2007.
- [10] O. Kutz, J. Bateman, F. Neuhaus, T. Mossakowski, and M. Bhatt. E pluribus unum: Formalisation, use-cases, and computational support for conceptual blending. In *Computational Creativity Research*, pages 167–196. Springer, 2014.
- [11] F. W. Lawvere. Metric spaces, generalized logic, and closed categories. *Rendiconti del Seminario Matematico e Fisico di Milano*, 43(1):135–166, 1973.
- [12] C. J. Mulvey. &. *Rendiconti del Circolo Matematico di Palermo*, 12:99–104, 1986.
- [13] C. S. Peirce. *Collected Papers of Charles Sanders Peirce*. Harvard University Press, 1931–1958.

A Quantale Operations: Detailed Definitions

A.1 Residuation

The *residuation* $a \Rightarrow b$ in a quantale is the largest element c such that $a \otimes c \leq b$:

$$a \Rightarrow b = \bigoplus \{c \in V : a \otimes c \leq b\} \quad (67)$$

For the probability quantale $([0, 1], \times, +, 1, \leq)$:

$$a \Rightarrow b = \begin{cases} 1 & \text{if } a = 0 \\ \min(b/a, 1) & \text{otherwise} \end{cases} \quad (68)$$

For the possible-worlds quantale $(\mathcal{P}(W), \cap, \cup, W, \subseteq)$:

$$A \Rightarrow B = B \cup \overline{A} \quad (69)$$

A.2 Total Correlation in Quantale Form

The total correlation can be expressed via quantale weakness:

$$TC(C) = w(C) \ominus \bigotimes_{p \in \text{Props}(C)} w_p(C) \quad (70)$$

where $w_p(C) = \varphi(p) \otimes m_C(p)$ is the marginal weakness contribution of property p .

B Proof Sketches

B.1 Proposition: Emergence Criterion

Proof. $\sigma_{A,B}(C) \geq e$ iff $(I_A \otimes I_B) \Rightarrow I_{A,B} \geq e$.

By residuation: $a \Rightarrow b \geq e$ iff $a \otimes e \leq b$ iff $a \leq b$.

So $\sigma_{A,B}(C) \geq e$ iff $I_A(C) \otimes I_B(C) \leq I_{A,B}(C)$.

Equivalently, $I_{A,B}(C) \not\leq I_A(C) \otimes I_B(C)$ (strictly greater in at least one component for the product quantale). $\square$

B.2 Proposition: Colimit Integration Minimality

Proof sketch. Let C be the colimit of $A \leftarrow G \rightarrow B$ and C' any other cocone. By the universal property, there exists unique $f : C \rightarrow C'$ with $f \circ \iota_A = \iota'_A$ and $f \circ \iota_B = \iota'_B$.

Then:

$$\begin{aligned} \text{Int}(C') &= \mathcal{C}(A, C') \otimes \mathcal{C}(B, C') \\ &\geq \mathcal{C}(A, C) \otimes \mathcal{C}(C, C') \otimes \mathcal{C}(B, C) \otimes \mathcal{C}(C, C') \\ &= \text{Int}(C) \otimes \mathcal{C}(C, C')^{\otimes 2} \\ &\geq \text{Int}(C) \end{aligned}$$

with equality iff $C' \cong C$. $\square$