Rippling Removal for Windows

rippling_removal_windows.ps1 · v1.4.1 · Iru, Inc.

Removes leftover Rippling components from Windows devices after they migrate to Iru.

Safe by default. The script ships in dry-run mode: it scans and reports, and changes nothing until you edit one line.

Quick start

STEP	WHAT TO DO
1. Dry run	Add the script to Iru as a Custom Script and push it as-is to one test device. It runs elevated (SYSTEM).
2. Read the result	Open the script output in the Iru console and read the SUMMARY block at the bottom.
3. Restart first, if suggested	If the Rippling app is **not** installed and a restart is pending, restart and run the dry run again. Queued deletions often clear on their own. If the app **is** still installed, a restart won't help — go to step 4.
4. Go live	Decide on the two optional settings below, change `$DryRun = $true` to `$false`, and push again.
5. Roll out	When the result says CLEANED, push live mode to your remaining devices. The script is safe to re-run.

The two modes

One setting at the top of the script, under **Editable defaults**, controls everything:

```
$DryRun = $true    # DRY RUN (default) — scan and report only. Changes nothing.
$DryRun = $false   # LIVE — same scan, then removes what it finds.
```

Both modes run the same scan, so a dry run shows exactly what a live run will do — including whether the optional admin-account removal would be allowed or blocked.

What it does

Phase 1 · Assessment (read-only, both modes)

Checks whether the migration completed on this device:

- Is the Iru agent installed? (checks for the Iru agent service)
- Is any Rippling MDM enrollment left? (reported only — never modified)
- Is the Rippling app still installed? (`C:\Program Files\Rippling\App\Rippling.exe`)
- Is a restart pending? (Uninstalls often queue locked files for deletion at the next restart.)

Phase 2 · Sweep (follows the mode setting)

Runs in this order, so nothing can restore itself mid-cleanup:

1. **Scheduled tasks** — removed first, including Rippling's repair task, which could otherwise restore the service or processes
2. **Service** — the Rippling agent service is stopped and deleted
3. **Processes** — any Rippling process still running, such as the tray app
4. **Official uninstaller** — run silently, if still present
5. **Startup entries** — Rippling entries that launch at sign-in, for the device and for signed-in users
6. **Folders** — `C:\Program Files\Rippling`, `C:\Program Files (x86)\Rippling`, `C:\ProgramData\Rippling`, and Rippling folders in each user's AppData
7. **Uninstall registry entries** — Rippling's entries in the installed-programs list
8. **Chocolatey** — only if you turn on the optional setting below
9. **Local admin account** — only if you turn on the optional setting below

Phase 3 · Summary

Counts of items found, removed, and not removed, whether a restart is pending, and a one-line RESULT. Read the output from the bottom up.

Reading the result

RESULT	MEANING	NEXT STEP
CLEAN	Nothing left to remove.	None. If a restart is pending, restart.
DRY RUN complete	Report only. The FOUND lines are what a live run would remove.	Review, then set `$DryRun = $false`. Follow any NOTE line — it tells you whether to restart first or go straight to a live run.
CLEANED	Everything found was removed.	Restart to clear any queued deletions.

PARTIAL	Some items couldn't be removed. Each one is named in a FAILED line.	For files, restart and re-run — they're usually locked. If the admin account was **NOT removed**, fix the reason it gives first — a restart won't change it.

Output goes to the Iru console and to a log file at `C:\ProgramData\Iru\MDMMigration\Logs\`.

Exit codes: `0` = clean, dry run complete, or cleaned · `1` = a live run couldn't remove something, including a blocked admin-account removal.

Optional settings (both off by default)

SETTING	DEFAULT	WHEN TURNED ON	BEFORE YOU TURN IT ON
`$RemoveRipplingAdmin`	`$false`	Removes the RipplingAdmin local account and its profile, if the safety checks below pass.	Run a dry run with it on. The output says **passed preflight** or **would be BLOCKED**, with the reason. When off, the script only logs a warning.
`$RemoveChocolatey`	`$false`	Removes Chocolatey, which Rippling used to install apps.	Confirm nothing else depends on it. Apps it installed are no longer managed by Chocolatey, and portable tools stored inside the Chocolatey folder are removed with it.

Admin account safety checks (both modes). The script won't remove the account if:

- the account is signed in;
- no other enabled **local** admin account exists on the device (Entra ID or domain admins don't count toward this); or
- the script can't read the local Administrators group — it blocks rather than guess.

When the checks pass, the account is deleted first and confirmed gone. Only then is its profile removed. A blocked removal changes nothing.

> **If RipplingAdmin is the only local admin on the device,** the checks will block removal. Create another local admin account first, then re-run.

The account name is set by `$UserToRemove = "RipplingAdmin"`. Change it only if your Rippling setup used a different name. You can leave this setting off and handle the account later.

Built-in safeguards

- **Dry run by default.** The first run on any device only reports.

- **Enrollment is never touched.** Iru's own MDM enrollment lives in the same place Windows stores all enrollments, so the script only reads it. A leftover Rippling enrollment is reported, not removed.
- **Repair task removed first.** Rippling's repair task is removed before anything else, so it can't restore what the script removes.
- **Every removal is verified.** The script re-checks each item and reports FAILED if it's still there, so the summary is accurate.
- **Admin removal checks first.** It won't leave a device without another local admin.
- **Safe to re-run.** Any mode, any number of times.
- **Out of scope, on purpose:** SentinelOne, even if Rippling delivered it. Removing a security agent is a separate decision.

FAQ

The dry run found several items. Is that a problem? No. It means the migration didn't remove every Rippling component on that device — which is what this script is for. Switch to live mode.

The dry run says a restart is pending. Should I restart first? If the Rippling app is no longer installed, yes — restart and run the dry run again. Leftover files often clear on their own. If the app is still installed, a restart won't remove it; run the script live.

The result is PARTIAL and the admin account was "NOT removed." What now? A safety check blocked it, and nothing was changed. Fix the reason in the FAILED line — usually by creating another local admin — then re-run.

The dry run reported a leftover Rippling MDM enrollment. The script doesn't remove enrollments. Restart the device; if it's still reported, contact Iru support.

Should I turn on Chocolatey removal? Only if nothing else on your devices uses Chocolatey. Some teams use it independently of Rippling.

Can I run it more than once? Yes, in any mode, as many times as you need.