

Final Presentation — A DSA-Compliant Tourism RS

David Gallob

Technische Universität München

School of Computation, Information and Technology

Chair of Connected Mobility

Munich, July 6, 2026



TUM Uhrenturm

Introduction & Motivation

- **The Recommender "Black Box":**
 - Most modern recommender systems (RS) hide their inner workings (e.g. neural network rankings) [1, 2].
 - Causes user distrust, especially in high-stake domains like tourism (travel planning, hotel bookings) [3, 4].
- **Regulatory Requirements: EU Digital Services Act (DSA) [5]:**
 - **Article 27:** Mandates that platforms explain the main parameters of their RS in plain, understandable language.
 - **Article 38:** Mandates that Very Large Online Platforms (VLOPs) offer at least one profiling-free recommendation alternative.
- **Project Goal:** Design and build an interactive, transparent, and DSA-compliant tourism recommender system prototype.

Background: Recommender Systems in Tourism

- **Unique Domain Characteristics [3, 2]:**

- High financial risk and emotional investment.
- Infrequent purchasing decisions (trips are planned only once or twice a year).
- Multi-attribute search spaces (price, location, stars, transport, amenities).

- **Decision Complexity [3, 2]:**

- Unlike low-cost retail products (e.g. movies, books), users do not buy travel packages on impulse.
- Users require active comparison tools and want to express precise trade-offs.
- Trust and perceived control over the algorithm are essential for user acceptance [4].

Solution

Multiple Algorithms including explanations

Two Algorithms with user defined weights/limits

- **5 Attributes for Hotels:**

- price per night, distance to center, stars, public transport access, user rating

- **Two Algorithms:**

- **Weighted MAUT:** compensatory approach with user defined weights.
- **Constraint-Guided:** Focused on hard limit rules and non-compensatory filtering.




Abbildung: Dashboard

System Architecture & Technical Stack

- **Technology Stack:**

- React¹ for component-based reactive state rendering.
- Vite² as a fast bundler and build system.
- Vanilla CSS for a custom, glassmorphic design language.
- Client-side KaTeX³ rendering for mathematical formulas.

- **Real-Time Computation Flow:**

- Eliminates the latency of database queries. Real-time updates occur client-side as users drag the sliders.
- Caches the hotel calculations, avoiding unnecessary re-renders.
- Normalization boundaries recalculate dynamically upon city changes.

- **Quality Assurance & Verification:**

- Standalone recommender engine (`src/recommenderEngine.js`).
- 60 automated unit tests (`run-tests.js`) verifying edge cases, boundary conditions, and preventing division-by-zero errors.

¹<https://react.dev/>

²<https://vite.dev/>

³<https://katex.org/>

Interactive Landing Page for Algorithm Selection

- **Algorithmic State Initialization:**
 - Recommendations, transparency boards, and controls are hidden initially to prevent cognitive overload.
- **Two Strategy Selection Cards:**
 - **Weighted MAUT Card:** Focused on relative importance weighting and compensatory trade-offs.
 - **Constraint-Guided Card:** Focused on hard limit rules and non-compensatory filtering.
- **Strategy Switching:**
 - Simple back button ("Switch Algorithm") to return to the landing page.
 - Fast toggle tabs in the dashboard header for seamless switching.




Abbildung: User Weight Sliders (0-10 scale)

Tiered Explainability & Transparency Panels

- **Tier 1: Dynamic Banners (Plain Text)**

- Dynamic color schemes (Blue for MAUT, Green for Filtering).
- Brief, plain-language summaries explaining how weights/limits are aggregated.

- **Tier 2: Algorithmic Details (TeX)**

- Expandable KaTeX mathematical formulas for expert review and full algorithmic disclosure.

- **Tier 3: Step-by-Step Breakdown**

- On-demand card expansions showing exact computations (Normalization $\times$ Weight).



Abbildung: Step-by-Step Mathematical Breakdown

Demonstration

Real-Time Strategy Toggling & Weight Adjustments

Algorithm A: Weighted MAUT (Compensatory)

- **Compensatory Utility Scoring [6]:**

- Attributes: Price, Location, Stars, Guest Review, Transport.
- Allows high performance in one attribute (e.g. location) to compensate for low performance in another (e.g. price).

- **Weights on a 0-10 Scale:**

- Range: 0 (completely unimportant) to 10 (most important).
- Mathematically normalized by the total sum of user-specified weights:

$$U = \frac{\sum w_i \cdot u_i}{\sum w_i} \times 100\%$$

(w_i : attribute weight [0–10], u_i : normalized utility [0–1], U : match score %)

Weighted Aggregation:

$$U = \frac{\sum_{i=1}^5 w_i \cdot u_i}{\sum_{i=1}^5 w_i} \times 100\%$$

Relative Normalization (Price & Distance):

$$u(v) = \frac{v_{\max} - v}{v_{\max} - v_{\min}}$$

Absolute Normalization (Stars & Review/Transport):

$$u_{\text{stars}}(v) = \frac{v - 1}{4} \quad \text{and} \quad u_{\text{rating/transport}}(v) = \frac{v - 1}{9}$$

Abbildung: User Weight Sliders (0-10 scale)

Normalization Strategies in Weighted MAUT

To aggregate attributes with different units, they are normalized to a 0 – 1 scale [7]:

- **Relative Normalization (Cost attributes: Price, Distance):**

- Normalizes value v relatively based on the active city's min/max values:

$$u(v) = \frac{v_{\max} - v}{v_{\max} - v_{\min}}$$

- Normalizing cost relatively maximizes the contrast between the local hotel options.

- **Absolute Normalization (Benefit attributes: Stars, Rating, Transit):**

- Normalizes value v on fixed scale bounds to prevent artificial distortion:

$$u_{\text{stars}}(v) = \frac{v-1}{4} \quad \text{and} \quad u_{\text{rating/transport}}(v) = \frac{v-1}{9}$$

Algorithm B: Constraint-Based Filtering

- **Non-Compensatory Logic [3]:**

- User defines absolute thresholds (e.g. maximum price, minimum stars).
- A hotel must satisfy all active limits simultaneously to be recommended.
- Over-performing in one area cannot compensate for a single constraint violation.

- **DSA-Compliant Simplicity:**

- Unordered subset of matching hotels.
- Easy-to-understand inclusion/exclusion criteria.
- Complete profiling-free predictability.


Transparency: Constraint-Guided Filtering

In accordance with the EU Digital Services Act (DSA), we believe in transparent algorithms. Here is the logical foundation of your recommendations:

Hide Mathematical Details #

$$\text{Price} \leq P_{\max} \wedge \text{Distance} \leq D_{\max} \wedge \text{Stars} \geq S_{\min} \wedge \text{Rating} \geq R_{\min} \wedge \text{Transport} \geq T_{\min}$$

- **Logical Conjunction:**
 - $P_{\max}$: The maximum price threshold defined by the user.
 - $D_{\max}$: The maximum distance threshold defined by the user.
 - $S_{\min}, R_{\min}, T_{\min}$: The minimum stars, guest review rating, and public transport access scores thresholds defined by the user.
 - Price, Distance, Stars, Rating, Transport: The raw values of the hotel.
 - $\wedge$: The logical AND operator (all constraints must be met simultaneously).
- **Non-Compensatory Logic:** Scoring highly in one category cannot compensate for a single constraint violation.
- **Complete Predictability:** A hotel is either included in the final results or excluded entirely based on your exact constraints.

Abbildung: Constraint Filtering Interface

The Satisficing Model of Constraint Filtering

- **Logical Conjunction Formulations:**

- A hotel is recommended if and only if:

$$\text{Price} \leq P_{\max} \wedge \text{Distance} \leq D_{\max} \wedge \text{Stars} \geq S_{\min} \wedge \text{Rating} \geq R_{\min} \wedge \text{Transport} \geq T_{\min}$$

- **Psychological Background (Satisficing):**

- Based on Herbert Simon's bounded rationality theory (1957).
- Decision-makers do not seek the mathematically optimal hotel, but rather a "good enough" hotel that meets all minimal conditions.
- Drastically reduces cognitive load during selection.
- Perfect for users with rigid conditions (e.g., maximum budget).

UI Redesign & User Experience Challenges

Initial Usability Issues:

- Implicit strategy selection (no clear entry point).
- Cluttered landing state with premature disclosure of complex DSA transparency panels.
- Sliders scaled from 0 – 100%, confusing users into thinking weights must sum to 100%.

Applied Redesign:

- **Interactive Strategy:** landing page.
- Importance scale changed to **0-10 range** to prevent percentage-summing confusion.




Abbildung: Previous Cluttered Transparency Board

Different Explanation Levels

- **The Explanation Dilemma [8]:**
 - Giving too little explanation makes the system look like a black box.
 - Giving too much explanation causes cognitive overload and user fatigue.
- **Tiered Disclosure (Satisfying Different User Persona):**
 - **Novice Pathway (Banners):** Brief text explanations focusing on the meaning of user controls. Satisfies general transparency.
 - **Expert Pathway (KaTeX Formulas):** Raw equations. Satisfies transparency audits and regulators.
 - **Curious Pathway (Math Breakdown):** Step-by-step breakdown. Explains individual recommendations, boosting user trust.

Future Work: Proposed Hybrid Recommender

Addresses individual limitations of MAUT and Filtering:

- **Limitation of Weighted MAUT:** Compiles complete lists; does not filter out completely irrelevant options (e.g. extremely expensive hotels).
- **Limitation of Constraint Filtering:** Screens items but does not rank remaining candidates (higher cognitive effort).

Proposed Two-Stage Hybrid Approach:

1. **Stage 1: Constraint Filtering (Non-Compensatory screening):** Filter out hotels violating basic requirements (e.g. price > \$250).
2. **Stage 2: Weighted MAUT (Compensatory ranking):** Apply preference weights to rank remaining candidates.

⇒ Maintains complete mathematical transparency, remains profiling-free, and mimics realistic human decision-making.

Proposed User Study & Evaluation Design

- **Hypotheses:**

- **H1 (Perceived Control):** Users interacting with the Weighted MAUT or Constraint Filtering interfaces report a higher sense of control over recommendations compared to a baseline "black-box" interface.
- **H2 (System Trust):** Exposing the collapsible mathematical breakdown panels increases user trust in the system's recommendations without causing information overload.
- **H3 (DSA Compliance Impact):** The presence of the global explanation banner and KaTeX formulas increases user comprehension of the algorithm's inner workings.

- **Within-Subjects Laboratory Study ($N = 30$):**

- **Condition 1 (Baseline):** Traditional black-box hotel list.
- **Condition 2 (Weighted MAUT):** Slider controls with collapsible breakdowns.
- **Condition 3 (Constraint Filtering):** Threshold sliders.

Summary & Conclusion

- **Successfully Completed Deliverables:**

- Developed an interactive, responsive tourism recommender SPA (React + Vite).
- Redesigned selection flow with a strategy landing page to prevent early transparency board clutter.
- Configured sliders on an intuitive 0-10 scale to eliminate weight-summing misunderstandings.
- Integrated tiered explainability panels (plain-language summaries, LaTeX formulas, math breakdowns).

- **Key Takeaway:**

- Demonstrates that EU DSA compliance (Article 27 & 38) can be harmonized with rich user controls, mathematical transparency, and premium UI/UX aesthetics.

Thank you for your attention!

Questions?

References I

- [1] Gediminas Adomavicius und Alexander Tuzhilin. „Toward the next generation of recommender systems: A survey of the state-of-the-art and possible extensions“. In: *IEEE Transactions on Knowledge and Data Engineering* 17.6 (2005), S. 734–749. DOI: 10.1109/TKDE.2005.99.
- [2] Joan Borras, Antonio Moreno und Aida Valls. „Intelligent tourism recommender systems: A survey“. In: *Expert Systems with Applications* 41.16 (2014), S. 7370–7389. DOI: 10.1016/j.eswa.2014.06.007.
- [3] Francesco Ricci. „Travel recommender systems“. In: *Recommender Systems Handbook*. Springer, 2011, S. 527–556. DOI: 10.1007/978-0-387-85820-3_17.
- [4] Bart P. Knijnenburg u. a. „Explaining the user experience of recommender systems“. In: *User Modeling and User-Adapted Interaction* 22.4-5 (2012), S. 441–504. DOI: 10.1007/s11257-011-9118-4.
- [5] European Parliament and Council of the European Union. *Regulation (EU) 2022/2065 of the European Parliament and of the Council of 19 October 2022 on a Single Market For Digital Services and amending Directive 2000/31/EC (Digital Services Act)*. <http://data.europa.eu/eli/reg/2022/2065/oj>. 2022.
- [6] Christian Schmitt, Dietmar Dengler, Michael Bauer u. a. „The MAUT-Machine: An Adaptive Recommender System“. In: *Proceedings of the ABIS Workshop*. Hannover, Germany, 2002.

References II

- [7] Ralph Keeney, Howard Raiffa und David Rajala. „Decisions with Multiple Objectives: Preferences and Value Trade-Offs“. In: *Systems, Man and Cybernetics, IEEE Transactions on* 9 (Aug. 1979), S. 403–403. DOI: 10.1109/TSMC.1979.4310245.
- [8] Nava Tintarev und Judith Masthoff. „A Survey of Explanations in Recommender Systems“. In: *Mai 2007*, S. 801–810. ISBN: 978-1-4244-0832-0. DOI: 10.1109/ICDEW.2007.4401070.