



Mr. Ralph Gambone

Proposal for

Precision Unitized Cutting Machine

ALLtra Model US-612 with XPR300 Plasma System and Down Draft Table

Approximate Cutting Area ~ 6' by 12'

Distributed by
 **MID ATLANTIC**
M A C H I N E R Y
Chris Barsanti ~ 610.256.0711

Prepared by

Randy Damas ~ 216.534.3612

Proposal Number 244006-1

January 22nd, 2024



ALLtra Corporation

1600 Patridge Road, Dewey OK 74029

Phone: (918) 534-5100 Fax: (918) 534-5101

Website: www.alltracorp.com

Proposal for Gambone Steel Co., Inc.
ALLtra Unitized-Series Machine Model US-612
Approximate Cutting Area ~ 6' by 12'



1 EA. UNITIZED MACHINE FRAME

Fabricated and machined in-house to strict tolerance requirements
Heavy-duty leveling pads for accurate and fast installation and setup
Linear ways and helical drive rack on both sides (dual drive)
Outside machine width (8' 8"), outside machine length (18' 0")
Approximate weight: machine 5,500 pounds // table 5,800 pounds

1 EA. MACHINE BRIDGE

Dual linear ways mounted to twin 5" by 7" steel tubes
Helical gear rack for smooth, accurate motion

1 EA. UNDER-BRIDGE HEAT SHIELD

Provides thermal protection to critical machine components

1 EA. CARRIAGE & STATION BRACKET

Heavy-duty carriage mounted to the machine beam via four linear bearings and driven by servo motor with enclosed power track to protect cables and hoses

1 EA. **MACHINE I/O & AC BRUSHLESS SERVO DRIVE SYSTEM**

Digitally linked to the CNC for faster response & noise immunity
High-precision, Bosch-Rexroth® Indradrive Cs servo drive system
1,500 inches per minute rapid traverse speed (standard)
Power required: 480VAC, 15 amps, three-phase (wye configuration)

1 EA. **CABLE TRACK SYSTEM**

Dual-loop, fully-enclosed cable track for rail axis

1 EA. **DOWN DRAFT TABLE**

Outer dimensions: 7' 0" (84") wide by 13' 2" (158") long
Internal clearance: 6' 5" (77") wide by 12' 7" (151") long
(8) 18" zones with mechanically operated damper doors
Material support slats spaced on 4" centers (1/4" or 10 ga.)
Recommended cubic feet per minute: 3,500 to 4,500
Removable slag pallets for easier cleaning
Clearance from slats to heat shields is 5-3/4"
Price does not include fan, filtration system or duct
Table pricing subject to change without notice due to steel price fluctuation



1 EA. **OPERATOR'S CONSOLE**

Connected to machine via crush-resistant, flexible conduit
Available with leveling pads or casters for ease of movement
Adjustable rotation and tilt for optimal viewing angle

1 EA. **CONTROL PANEL**

Features Tilt (+/-) 15° and Rotate (+/-) 150° capability

Emergency stop switch and reset switches
Manual jog, speed and process control switches
Plasma power supply control (if equipped)
Down-draft table fan on/off control (if equipped)

1 EA. **ALLTRA MACHINE CONTROLLER**

15" HD TFT LCD (16:9) with capacitive touch screen
Microsoft® Windows® 10 operating system
2.9 GHz Intel® Core i7-7700t 7th generation CPU
8 GB DDR4 2133 MHz 288-pin DIMM RAM
2 x 64 GB solid-state hard drives
2 x USB 3.0 ports on control panel
Dual-band 802.11ac WI-FI card with antennas
Digital interface to amplifiers & I/O module



OR

0 EA. **HYPERTHERM EDGE CONNECT CONTROLLER**

15" HD TFT LCD (16:9) with capacitive touch screen
Microsoft® Windows® 10 operating system
≥128GB Intel S3500 2.5", 4GB DDR3-1600 RAM
Intel® J1900 Quad-Core mobile processor
(1) front-panel & (1) back-panel USB port
Dual-band 802.11ac Wi-Fi card with antennas
EtherCAT interface to amplifiers & I/O module

PLASMA CUTTING SYSTEM

1 EA. Hypertherm XPR300 With CorePlus Gas Connect Console

Recommended application: mostly mild steel cutting (up to 2"), occasional stainless steel and/or aluminum cutting with lower edge quality requirements, and basic or enhanced plasma marking capability.

Unmatched mild steel cutting performance and superior angularity and edge finish on stainless steel up to 12mm (1/2"). This is delivered through a new Hydefinition® Innox (HDi) process that prevents the mixing of air into the plasma gas, creating an improved, brighter edge finish.

30 amp to 300 amp cut capacity, 15 amp to 18 amp marking capacity

Available gases: oxygen, nitrogen, air, and argon

1.75" mild steel - production pierce capacity (standard oxygen/air)

2.00" mild steel - production pierce capacity (argon assist)

3.12" mild steel - maximum cutting capacity (edge start)

1.50" stainless steel - production pierce capacity

2.00" stainless steel - maximum cutting capacity (edge start)

1.50" aluminum - production pierce capacity

2.00" aluminum - maximum cutting capacity (edge start)

Requires 480VAC, 91 amps (@66.5 kw output), three-phase power

Recommended time-delay, high-inrush fuse size: 110 amps

Please contact a certified electrician for local code requirements



PLASMA SYSTEM START-UP TOOL KIT

1 EA. Tool Kit

Includes nozzle/electrode tool and torch spanner wrench

1 EA. Electrode Pit Depth Gauge

Dial indicator with base used to measure electrode pit depth

PLASMA SYSTEM START-UP CONSUMABLE KIT

1 EA. Quick-Disconnect Torch Head

Additional, spare torch head

1 EA. Consumable Start-up Kit ~ Mild Steel

Provides consumables for start-up and initial training

\$2,000.00 worth at 20% off list price



PLASMA HEIGHT CONTROL

1 EA. Plasma Automatic Torch Height Control

Enclosed lifter with dual linear guides and precision ball screw with

13 inch stroke and a 1,000 inch/minute maximum speed

A pneumatic collision switch stops the machine when a collision occurs, the torch automatically resets when the obstruction is cleared

Shield to plate contact is monitored at all times, the torch will retract automatically until the contact is cleared

Fully-enclosed power track and fire sleeve protect cables and hoses



GAS SUPPLY REGULATORS

- 1 EA. Single-stage, high-flow regulator (oxygen)
- 2 EA. Single-stage, high-flow regulator (argon/nitrogen)
Intended for use on high-pressure cylinders only, please contact ALLtra Corporation for low-pressure, bulk supply applications

LASER POINTER

- 1 EA **Laser Pointer Assembly**
 Used by the machine operator to locate the torch position during plate alignment, turns on with station enable and off with cut start or time out
Select red dot, red crosshair or green dot

COMPRESSED AIR BOOSTER PUMP

- 1 EA. **Compressed Air Booster Pump**
 Compresses incoming air (up to 2:1 ratio) and helps maintain consistent air pressure for high-definition plasma system and/or oxy-fuel regulator panel
Plasma system requires compressed air pressure of 115 psi (+/- 10%)



NESTING SOFTWARE (LOCAL LICENSE)

- 1 EA. **Hypertherm ProNest 2023 - Advanced Interactive Nesting**
 Integrated 2D CAD program & variable shape library to create common parts, automatic CAD and CNC import with file correction and spline/ellipse smoothing, material database including grade and gauge, customer database input capable, automatic or manual nest sequencing, safe zones for plate clamping obstructions, drag, drop, and bump parts on the nest; move, mirror, rotate or array parts; nest parts within other parts, part interference detection, edit lead-in and lead-out position & properties, control cut direction, plate cropping, job reporting and costing, DXF output
- 1 EA. **Hypertherm ProNest 2023 - Automatic Nesting Option**
 Comprised of various powerful and intelligent profile nesting algorithms, including pattern array and true shape nesting with part-in-part void filling.
- 1 EA. **Hypertherm ProNest 2023 - Advanced Plasma Post-Processor Option**
 Adds functionality for Burny advanced command messaging and Hypertherm automatic gas console support. Required for True Hole cutting technology.
- 1 EA. **Hypertherm ProNest 2023 - Collision Avoidance Option**
 Positions the lead-ins/lead-outs of interior and exterior profiles so that the torch moves away from the previous cut, thus minimizing the amount of torch retract distance required. It also optimizes the internal cut sequence to minimize unnecessary traverse movements.
- 1 EA. **Hypertherm ProNest 2023 - Software Maintenance Plan**
 Annual subscription provides additional online training, technical support, updates and upgrades, when available. Price applies to initial orders and annual renewals.

MACHINE INSTALLATION

Includes:

Travel time, onsite labor, & expenses

**ALLtra technicians install drive rails, drive rack, gantry, power pole,
power track trays, power track, machine interface cables, and hoses.**

Please see "Customer Responsibilities" below for additional details

TRAINING (MACHINE OPERATORS, PROGRAMMERS & MAINTENANCE PERSONNEL)

Includes:

Travel time, onsite labor, & expenses

Onsite training for machine operators

Onsite training for maintenance personnel

Online training for programmers on nesting software

PARTS WARRANTY

Two (2) years on included components (except plasma torch & leads)

One (1) year warranty on plasma torch & leads

Additional manufacturer's warranties extended to end user

Does not include damage from abuse, misuse or acts of nature

SERVICE WARRANTY

One (1) year on included components

Includes: labor & expenses

Does not include damage from abuse, misuse or acts of nature

PHONE SUPPORT

No contract and no fee for phone support for the life of the machine
Also applies to after-hours and weekend phone support

REMOTE DIAGNOSTICS SUPPORT

Allows ALLtra technicians to troubleshoot system issues via internet connection
Requires high-speed internet connection to the machine controller

CONSUMABLE LOYALTY & PREVENTATIVE MAINTENANCE PROGRAM

Purchasing an ALLtra cutting machine makes you eligible for enrollment into our *Consumable Loyalty and Preventative Maintenance* programs, which allow you to receive discounted pricing for genuine Hypertherm consumables and an annual preventative maintenance service visit at no charge (replacement parts not included).

Please contact ALLtra Corporation for enrollment forms and additional details

TOTAL PRICE FOR ABOVE SYSTEM	\$ 228,884.00
MID ATLANTIC MACHINERY STEEL TECH SHOW DISCOUNT	-\$ 8,011.00
GRAND TOTAL	\$ 220,873.00

Special Pricing valid thru 3/31/2024.

(Price does not include shipping charges or tax, if applicable)

PAYMENT TERMS

Thirty-five percent (35%) due with order

Fifty-five percent (55%) due prior to machine shipment

Balance due thirty (30) days upon completion of installation with customer acceptance

Customer is responsible for any additional taxes and/or fees assessed on this purchase, unless a tax exemption certificate or other proof of exemption can be provided prior to shipment.

Unless otherwise stated in this proposal, shipping charges have not been included. Shipping charges will be billed separately and at cost or the customer may make their own arrangements. Machines must be shipped in a Conestoga or soft-sided trailer with air suspension. Tables may be shipped on a flat-bed trailer with appropriate tarping to protect the table from the weather. An estimate for shipping charges will be provided upon request.

DELIVERY

Due to economic and pandemic-related supply chain issues, some of our suppliers are experiencing unusually high product lead times. We are actively pre-ordering spare parts, consumables, and complete systems to maintain our inventory and to help reduce lead times. Currently, we have every indication that we can meet the estimated delivery dates shown, based upon quoted supplier deliveries, as well as staffing levels. Unforeseen supply chain issues could extend the delivery.

Estimated system delivery: 14-16 weeks after receipt of order & down payment

Estimated Donaldson delivery: 18-20 weeks after receipt of order & down payment

Delivery is subject to factory backlog & the timely return of approved drawings

Proposal is valid for sixty (60) days

EXPLOSION NOTICE

Hydrogen gas is formed when aluminum or magnesium are cut on a water table, regardless of the torch or cutting gas used. The hydrogen gas bubbles can form pockets under the plate and within the air chamber. These pockets of hydrogen gas can ignite and explode from the cutting process. Formation of hydrogen gas can continue long after the cutting process has ended. Frequent cleaning of the table is recommended to reduce the amount of dross present. A sufficient water level needs to be maintained to allow all the air to be forced out of the air chamber. Frequent "stirring" of the water is recommended to dissipate pockets of hydrogen gas. Do not cut plates that have been left on the table for extended periods of time without completely lowering the water level first and/or lifting the plate. These measures can help dissipate hydrogen gas pockets but does not preclude an explosion from happening.

OPTIONAL ACCESSORIES not included in PROPOSAL**PLASMA SYSTEM GAS CONSOLE UPGRADE (COREPLUS™ TO VENTED WATER INJECTION™)**

1 EA. **Hypertherm® XPR300 Vented Water Injection Gas Connect Console** 3,665.00

Enhanced stainless steel and aluminum cutting capabilities are delivered with the addition of F5 HDi and vented water injection processes

30 amp to 300 amp cut capacity, 15 amp to 18 amp marking capacity

Available gases: oxygen, nitrogen, air, argon, F5, and water

1.75" mild steel - production pierce capacity (standard oxygen/air)

2.00" mild steel - production pierce capacity (argon assist)

3.12" mild steel - maximum cutting capacity (edge start)

1.50" stainless steel - production pierce capacity

2.00" stainless steel - maximum cutting capacity (edge start)

1.50" aluminum - production pierce capacity

2.00" aluminum - maximum cutting capacity (edge start)

Note: Using the vented water-injection process on a down draft table with an air filtration system could decrease the life of the filters due to moisture.

CONFIGURATION CUSTOMIZATION

1 EA. **Plasma System Cable & Hoses Extension (20')** 1,098.00

Extends the length of the plasma system cables/hoses by twenty feet

1 EA. **Plasma System Cable & Hoses Extension (40')** 1,945.00

Extends the length of the plasma system cables/hoses by forty feet

1 EA. **Machine Power Lead Extension (20')** 156.00

Extends the length of the machine power and ground cable (#6) by twenty feet

1 EA. **Machine Power Lead Extension (40')** 221.00

Extends the length of the machine power and ground cable (#6) by forty feet

1 EA. **Gas Supply Hose Extension (20')** 381.00

Extends the length of the gas supply hoses by twenty feet

1 EA. **Gas Supply Hose Extension (40')** 767.00

Extends the length of the gas supply hoses by forty feet

PLASMA CUTTING SYSTEM**1 EA. Hypertherm HPR400XD With Autogas Console****23,534.00****Additional**

Recommended application: mild steel cutting (up to 2"), frequent stainless steel and/or aluminum cutting with the high edge quality requirements, and standard or enhanced plasma marking capability.

30 amp to 400 amp cut capacity, 7 amp to 18 amp marking capacity

Available gases: oxygen, nitrogen, air, argon, F5, and H35

2.00" mild steel - production pierce capacity

3.20" mild steel - maximum cutting capacity (edge start)

1.75" stainless steel - production pierce capacity

3.20" stainless steel - maximum cutting capacity (edge start)

1.50" aluminum - production pierce capacity

3.20" aluminum - maximum cutting capacity (edge start)

Requires 480vac, 110 amps (@80 kw output), three-phase power

Recommended time delay, high inrush fuse size: 150 amps

Please contact a certified electrician for local code requirements

ALLTRA H₂OHMIC™ PLATE HEIGHT SENSE**1 EA. ALLtra H₂Ohmic™ Plate Height Sense**

1,473.00

Allows the automatic plasma torch height control system to sense the plate height when submerged under water or when a water shield is used, such as with the N₂/H₂O process

OXYFUEL TORCH**1 EA. Oxyfuel Torch for Unitized Series Machine Model**

10,310.00

Oxyfuel torch mounted on quick-change adapter utilizes the plasma lifter assembly for vertical movement while oxyfuel cutting

Gas pressures to be set manually at the wall or bottle connection

Torch brand (Victor®, Harris®, etc.) and fuel gas type to be selected

Maximum cutting thickness: water table ~ 6" // down draft table ~ 3"

GAS SUPPLY REGULATORS**1 EA. Single-stage, high-flow regulator (propane/natural gas)**

476.00

Intended for use on high-pressure cylinders only, please contact

ALLtra Corporation for low-pressure, bulk supply applications

1 EA. WATER-FILLED WORK TABLE**1,220.00****Additional**

Outer dimensions: 7' 0" (84") wide by 13' 2" (158") long

Internal clearance: 6' 5" (77") wide by 12' 7" (151") long

Material support slats spaced on 4" centers (1/4" or 10 ga.)

Removable slag pallets for easier cleaning

Clearance from slats to heat shields is 8"

Manual water level control from table end

Table pricing subject to change without notice due to steel price fluctuation

AIR FILTRATION SYSTEM

- 1 EA. **Donaldson® Model DFLS-6 Air Filtration System (Dust Collector)** 39,357.00
4,000 CFM @ 6" WG, AMR 2.62, 15 hp fan, 14" diameter inlet
(6) Ultra-Web Nano-fiber filters, MERV 15 rated
Integrated Delta P+ electrical control panel (460v, 60Hz, 3-phase)
Low inlet torturous path with integrated backdraft damper
In-line spark trap - helps reduce fire risk
Sprinkler package for connection to water source
Hinged filter access covers
22-gallon (3 ft³) dust bin
Approximate dimensions: 65" (L) by 78" (W) by 101" (H)
Price does not include duct work from table to filtration system
Unit must be installed indoors or be fully covered

Explosion Notice

Extra precautions must be taken when processing and/or capturing combustible materials like aluminum. Dust collection systems must be placed outside the facility, the exhaust air cannot be recirculated back into the facility, and the dust collector must have explosion vents. Failure to follow these precautions could result in damages and/or injuries. Please research your local industrial ventilation code requirements for proper combustible material handling. Common referenced standards used in determining these requirements include: the National Fire Protection Association (NFPA), the International Mechanical Code, the International Fire Code and the Occupational Safety and Health Administration (OSHA).

DONALDSON® AIR FILTRATION SYSTEM OPTION

- 1 EA. **External Remote-Mounted Control Panel - Model DFLS-6** 3,106.00
Relocates the control panel away from the collector
Required if collector is installed outdoors and uncovered

DONALDSON® AIR FILTRATION SYSTEM OPTION

- 1 EA. **Side-Mounted Weather Hood - Model DFLS-6** 1,223.00
Required if collector is installed outdoors and uncovered

DONALDSON® AIR FILTRATION SYSTEM OPTION

- 1 EA. **Cold Climate Kit - Model DFLS-6** 211.00
Adds heaters to the cleaning solenoid enclosure to keep the solenoids from freezing in cold weather. Heaters are powered by the control panel.

16" ROUND DUCT SECTIONS - EXAMPLE

6 EA. 58.75" straight-pipe, 20 ga, galvanized	191.00	1,146.00
3 EA. 90° elbow, 20 ga, galvanized	295.00	885.00
0 EA. 60° elbow, 20 ga, galvanized	281.00	
0 EA. 45° elbow, 20 ga, galvanized	225.00	
0 EA. 30° elbow, 20 ga, galvanized	178.00	
1 EA. Wall or roof flashing	150.00	150.00
3 EA. Adjustable sleeve, 10.625", 20 ga, galvanized	64.00	192.00
# EA. Clamp with nitrile seal, joins two duct sections	27.00	324.00
		2,697.00

The required number of duct sections depends upon the distance and route of the duct from the table to the air filtration system.

Purchased duct sections are to be installed by the customer

Duct pricing subject to change without notice due to steel price fluctuation

CUSTOMER RESPONSIBILITIES

Customer responsibilities include, but are not limited to the following:

- Federal, state and local code compliance and inspections
- Provide appropriate equipment (forklift, crane, rigging, etc.) to unload the machine and other equipment from the delivery truck and for movement within the facility.
- Provide trained personnel to operate the equipment needed to unload and move the new equipment into position and to remove old equipment from the area.
- Remove the existing machine, table, and associated equipment from the area as needed. ALLtra may choose to remove existing machines if they are to be traded in.
- Provide appropriate utilities (electrical panels, gas regulators, fittings, etc.) for the equipment included with the order. The utilities must be in place and functional prior to the arrival of the installation technicians. Delays may result in additional fees.
- Provide an appropriate foundation to support the machine, table and associated Equipment
In some cases, a new concrete floor or pad may need to be poured
- Prepare the facility for movement of the machine and table from the unload point to the installation site.
- Prepare the site for installation of the machine (i.e., move equipment and material, sweep the floor, mark any floor conduit locations, provide overhead power track supports, etc.).
- If purchasing part creation and nesting software, you must provide a computer that meets or exceeds the minimum requirements set by the software provider.
- Notify ALLtra Corporation of any personal protection equipment requirements (safety glasses, steel toe shoes, hard hats, etc.) needed while onsite.
- Provide additional assistance as required.

TERMS & CONDITIONS OF MACHINE SALES

- 1) **PRICE:** Prices are quoted F.O.B. Seller's factory. Prices are firm for 60-days from the proposal date. Prices are subject to change without notice on any order received after the proposal date.
- 2) **DELIVERY:** A delivery estimate for planning purposes is included on the proposal. The shipment commitment is dependent upon the Seller's machine backlog when the purchase order is received from the Buyer.
- 3) **TERMS OF PAYMENT:** Unless otherwise specified in the proposal and approved by the Seller's credit department, terms are as follows:

Thirty-Five Percent (35%) Due with Order

Fifty-Five Percent (55%) Due Prior to Machine Shipment

Balance Due Thirty (30) Days Upon Completion of Installation with Customer Acceptance

The Buyer is responsible for payment of all sales, use, or excise taxes and any duties where applicable.

- 4) **WARRANTY:** The Seller warrants machines and systems shipped to be free from defects in material and workmanship for the lesser of twelve (12) months from the installation date or (15) months from the shipment date.

The Warranty only applies to the original Buyer. The machine and systems must be shipped on enclosed equipment having air-ride suspension systems. Buyer must provide normal and proper usage, care and maintenance as specified by the Seller's personnel and manuals. The Buyer must provide all electrical and mechanical connections to the Seller's specifications, local Electrical Code and local requirements. Installation and start up procedures must be performed by Seller's approved personnel.

Consumable items, such as plasma torch consumables, oxyfuel torch tips, filters, fuses, lightbulbs, etc. are not warranted. Upon receipt of a warranty claim, the Seller will proceed without unreasonable delay to remedy any defect. Parts found to be defective, will, at the Seller's option, be repaired or replaced with new or factory rebuilt components free of charge.

During the warranty period, if the machine is installed in the continental United States and the seller is required to replace a defective component, there will be no charge for labor or travel expenses.

Notice of any warranty claim must be made immediately after the Buyer discovers any defect. The Buyer must return all defective components and allow the Seller to inspect the components in the claimed defective condition. Without prior approval from the Seller, any attempt to repair a warranty part will void the claim for warranty.

Any vendor supplied components which have a component warranty period that exceeds the above WARRANTY shall be extended to the Buyer.

- 5) **THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION AND THE WARRANTIES CONTAINED HEREIN. THE WARRANTIES EXPRESSED HEREIN ARE IN LIEU OF ANY OTHER WARRANTIES, EXPRESSED OR IMPLIED. ANY IMPLIED WARRANTY OF MERCHANTABILITY AND IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. BUYER'S REMEDY IS LIMITED TO AND SELLER'S MAXIMUM LIABILITY SHALL NOT EXCEED EITHER,**
A) REPAIR OR REPLACEMENT OF THE DEFECTIVE PART OR PRODUCT OR, AT SELLER'S OPTION,
B) RETURN OF THE PRODUCT AND REFUND OF THE PURCHASE PRICE. SUCH REMEDY SHALL BE BUYER'S ENTIRE AND ONLY REMEDY.
- 6) **LIMITATION ON SELLER'S LIABILITY: UNDER NO CIRCUMSTANCES WILL SELLER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR FOR OTHER LOSS, DAMAGE OR EXPENSE OF ANY KIND INCLUDING LOSS OF PROFITS, ARISING IN CONNECTION WITH THE USE OR THE INABILITY TO USE THE PRODUCTS SUPPLIED BY THE SELLER.**
- 7) **CANCELLATION:** Termination of the purchase order by the Buyer will result in cancellation charges equal to the irrecoverable costs of the machine including, but not limited to, engineering, assembly, special order items, restocking and freight charges.