

Big data: architectures and data analytics

Spark - Exercises

Exercise #30

- Log filtering
 - Input: a simplified log of a web server (i.e., a textual file)
 - Each line of the file is associated with a URL request
 - Output: the lines containing the word "google"
 - Store the output in an HDFS folder

3

Exercise #30 - Example

■ Input file

```
66.249.69.97 - - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
66.249.69.97 - - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
66.249.69.97 - - [24/Sep/2014:22:28:44 +0000] "GET http://dbdmg.polito.it/course.html"
71.19.157.179 - - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
66.249.69.97 - - [24/Sep/2014:31:28:44 +0000] "GET http://dbdmg.polito.it/thesis.html"
```

■ Output

```
66.249.69.97 - - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
66.249.69.97 - - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
71.19.157.179 - - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
```

4

Exercise #31

- Log analysis
 - Input: log of a web server (i.e., a textual file)
 - Each line of the file is associated with a URL request
 - Output: the list of distinct IP addresses associated with the connections to a google page (i.e., connections to URLs containing the term "www.google.com")
 - Store the output in an HDFS folder

5

Exercise #31 - Example

■ Input file

```
66.249.69.97 - - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
66.249.69.97 - - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
66.249.69.97 - - [24/Sep/2014:22:28:44 +0000] "GET http://dbdmg.polito.it/course.html"
71.19.157.179 - - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
66.249.69.95 - - [24/Sep/2014:31:28:44 +0000] "GET http://dbdmg.polito.it/thesis.html"
66.249.69.97 - - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
56.249.69.97 - - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
```

■ Output

```
66.249.69.97
71.19.157.179
56.249.69.97
```

6

Exercise #32

- Maximum value
 - Input: a collection of (structured) textual csv files containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: report the maximum value of PM10
 - Print the result on the standard output

7

Exercise #32 - Example

- Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

- Output

60.2

8

Exercise #33

- Top-k maximum values
 - Input: a collection of (structured) textual csv files containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: report the top-3 maximum values of PM10
 - Print the result on the standard output

9

Exercise #33 - Example

- Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

- Output

```
60.2
55.5
52.5
```

10

Exercise #34

- Readings associated with the maximum value
 - Input: a collection of (structured) textual csv files containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: the line(s) associated with the maximum value of PM10
 - Store the result in an HDFS folder

11

Exercise #34 - Example

- Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,60.2
S2,2016-01-03,52.5
```

- Output

```
S1,2016-01-02,60.2
S1,2016-01-03,60.2
```

12

Exercise #35

- Dates associated with the maximum value
 - Input: a collection of (structured) textual csv files containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: the date(s) associated with the maximum value of PM10
 - Store the result in an HDFS folder

33

Exercise #35 - Example

Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,60.2
S2,2016-01-03,52.5
```

Output

```
2016-01-02
2016-01-03
```

34

Exercise #36

- Average value
 - Input: a collection of (structured) textual csv files containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: compute the average PM10 value
 - Print the result on the standard output

35

Exercise #36 - Example

Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

Output

```
39.86
```

36

Big data: architectures and data analytics

Exercise #31

- Log analysis
 - Input: log of a web server (i.e., a textual file)
 - Each line of the file is associated with a URL request
 - Output: the list of distinct IP addresses associated with the connections to a google page (i.e., connections to URLs containing the term "www.google.com")
 - Store the output in an HDFS folder

2

Exercise #31 - Example

Input file


```
66.249.69.97 - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
66.249.69.97 - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
66.249.69.97 - [24/Sep/2014:22:28:44 +0000] "GET http://dbdmg.polito.it/course.html"
71.19.157.179 - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
66.249.69.95 - [24/Sep/2014:31:28:44 +0000] "GET http://dbdmg.polito.it/thesis.html"
66.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
56.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
```

Output

```
66.249.69.97
71.19.157.179
56.249.69.97
```

3

Exercise #31 - DAG



4

Exercise #31 - Simulation

- Suppose that Sparks splits the RDD associated with the input file in two partitions

Part. #1

```
66.249.69.97 - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
66.249.69.97 - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
66.249.69.97 - [24/Sep/2014:22:28:44 +0000] "GET http://dbdmg.polito.it/course.html"
```

Part. #2

```
71.19.157.179 - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
66.249.69.95 - [24/Sep/2014:31:28:44 +0000] "GET http://dbdmg.polito.it/thesis.html"
66.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
56.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
```

5

Exercise #31 - Simulation

Part. #1


```
66.249.69.97 - [24/Sep/2014:22:25:44 +0000] "GET http://www.google.com/bot.html"
"GET http://www.google.com/how.html"
66.249.69.97 - [24/Sep/2014:22:26:44 +0000] "GET http://www.google.com/how.html"
66.249.69.97 - [24/Sep/2014:22:28:44 +0000] "GET http://dbdmg.polito.it/course.html"
```

Part. #2


```
71.19.157.179 - [24/Sep/2014:22:30:12 +0000] "GET http://www.google.com/faq.html"
66.249.69.95 - [24/Sep/2014:31:28:44 +0000] "GET http://dbdmg.polito.it/thesis.html"
66.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
56.249.69.97 - [24/Sep/2014:56:26:44 +0000] "GET http://www.google.com/how.html"
```

6


Exercise #31 - Simulation




Exercise #31 - Simulation




Exercise #31 - Simulation




Exercise #31 - Simulation



Exercise #31 - Simulation



Exercise #31 - Simulation



Big data: architectures and data analytics

Spark - Exercises

Exercise #37

- Maximum values
 - Input: a textual csv file containing the daily value of PM₁₀ for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM₁₀ value (µg/m³)\n
 - Output: the maximum value of PM₁₀ for each sensor
 - Store the result in an HDFS file

3

Exercise #37 - Example

■ Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

■ Output

```
(S1,60.2)
(S2,52.5)
```

4

Exercise #38

- Pollution analysis
 - Input: a textual csv file containing the daily value of PM₁₀ for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM₁₀ value (µg/m³)\n
 - Output: the sensors with at least 2 readings with a PM₁₀ value greater than the critical threshold 50
 - Store in an HDFS file the sensorIds of the selected sensors and also the number of times each of those sensors is associated with a PM₁₀ value greater than 50

5

Exercise #38 - Example

■ Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

■ Output

```
(S1,2)
```

6

Exercise #39

- Critical dates analysis
 - Input: a textual csv file containing the daily value of PM₁₀ for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM₁₀ value (µg/m³)\n
 - Output: an HDFS file containing one line for each sensor
 - Each line contains a sensorId and the list of dates with a PM₁₀ values greater than 50 for that sensor

7

Exercise #39 - Example

- Input file

```
s1,2016-01-01,20.5
s2,2016-01-01,30.1
s1,2016-01-02,60.2
s2,2016-01-02,20.4
s1,2016-01-03,55.5
s2,2016-01-03,52.5
```

- Output

```
(s1,[2016-01-02,2016-01-03])
(s2,[2016-01-03])
```

8

Big data: architectures and data analytics

Spark - Exercises

2

Exercise #40

- Order sensors by number of critical days
 - Input: a textual csv file containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - Output: an HDFS file containing the sensors ordered by the number of critical days
 - Each line of the output file contains the number of days with a PM10 values greater than 50 for a sensor *s* and the sensorId of sensor *s*

3

Exercise #40 - Example

■ Input file

```
s1,2016-01-01,20.5
s2,2016-01-01,30.1
s1,2016-01-02,60.2
s2,2016-01-02,20.4
s1,2016-01-03,55.5
s2,2016-01-03,52.5
```

■ Output

```
2, s1
1, s2
```

4

Exercise #41

- Top-k most critical sensors
 - Input:
 - A textual csv file containing the daily value of PM10 for a set of sensors
 - Each line of the files has the following format
sensorId,date,PM10 value ($\mu\text{g}/\text{m}^3$)\n
 - The value of k
 - It is an argument of the application

5

Exercise #41

- Top-k most critical sensors
 - Output:
 - An HDFS file containing the top-k critical sensors
 - The "criticality" of a sensor is given by the number of days with a PM10 values greater than 50
 - Each line contains the number of critical days and the sensorId

6

Exercise #41 - Example

Input file

```
S1,2016-01-01,20.5
S2,2016-01-01,30.1
S1,2016-01-02,60.2
S2,2016-01-02,20.4
S1,2016-01-03,55.5
S2,2016-01-03,52.5
```

▪ $k = 1$

Output

2, S1

7

Exercise #42

Mapping Question-Answer(s)

Input:

- A large textual file containing a set of questions
 - Each line contains one question
 - Each line has the format
 - QuestionId,TimeStamp,TextOfTheQuestion
- A large textual file containing a set of answers
 - Each line contains one answer
 - Each line has the format
 - AnswerId,QuestionId,TimeStamp,TextOfTheAnswer

8

Exercise #42

Output:

- A file containing one line for each question
- Each line contains a question and the list of answers to that question
 - QuestionId, TextOfTheQuestion, list of Answers

9

Exercise #42- Example

Questions

```
Q1,2015-01-01,What is ..?
Q2,2015-01-03,Who invented ..
```

Answers

```
A1,Q1,2015-01-02,It is ..
A2,Q2,2015-01-03,John Smith
A3,Q1,2015-01-05,I think it is ..
```

Exercise #42 - Example

Output

```
(Q1,([What is ..?],[It is .., I think it is ..]))
(Q2,([Who invented ..],[John Smith]))
```

Big data: architectures and data analytics

Spark - Exercises

Exercise #43 – 1

- Critical bike sharing station analysis
- Input:
 - A textual csv file containing the occupancy of the stations of a bike sharing system
 - The sampling rate is 5 minutes
 - Each line of the files contains one sensor reading/sample has the following format
stationId,date,hour,minute,num_of_bikes,num_of_free_slots
 - Some readings are missing due to temporarily malfunctions of the stations
 - Hence, the number of samplings is not exactly the same for all stations
 - The number of distinct stations is 100

3

Exercise #43 – 2

- Input:
 - A second textual csv file containing the list of neighbors of each station
 - Each line of the files has the following format
stationId_x, list of neighbors of stationId_x
 - E.g.,
s1,s2 s3
means that s2 and s3 are neighbors of s1

4

Exercise #43 – 3

- Outputs:
 - Compute the percentage of critical situations for each station
 - A station is in a critical situation if the number of free slots is below a user provided threshold (e.g., 3 slots)
 - The percentage of critical situations for a station Si is defined as (number of critical readings associated with Si)/(total number of readings associated with Si)

5

Exercise #43 – 4

- Store in an HDFS file the stations with a percentage of critical situations higher than 80% (i.e., stations that are almost always in a critical situation and need to be extended)
 - Each line of the output file is associated with one of the selected stations and contains the percentage of critical situations and the stationId
 - Sort the stored stations by percentage of critical situations

6

Exercise #43 – 5

- Compute the percentage of critical situations for each pair (timeslot, station)
 - Timeslot can assume the following 6 values
 - [0-3]
 - [4-7]
 - [8-11]
 - [12-15]
 - [16-19]
 - [20-23]

7

Exercise #43 – 6

- Store in an HDFS file the pairs (timeslot, station) with a percentage of critical situations higher than 80% (i.e., stations that need rebalancing operations in specific timeslots)
 - Each line of the output file is associated with one of the selected pairs (timeslot, station) and contains the percentage of critical situations and the pair (timeslot, stationId)
 - Sort the result by percentage of critical situations

8

Exercise #43 – 7

- Select a reading (i.e., a line) of the first input file if and only if the following constraints are true
 - The line is associated with a full station situation
 - i.e., the station S_i associated with the current line has a number of free slots equal to 0
 - All the neighbor stations of the station S_i are full in the time stamp associated with the current line
 - i.e., bikers cannot leave the bike at Station S_i and also all the neighbor stations are full in the same time stamp
- Store the selected readings/lines in an HDFS file and print on the standard output the total number of such lines

9

Big data: architectures and data analytics

Spark - Exercises

2

Exercise #44

- Misleading profile selection
- Input:
 - A textual file containing the list of movies watched by the users of a video on demand service
 - Each line of the file contains the information about one visualization
 - userid,movieid,start-timestamp,end-timestamp
 - The user with id *userid* watched the movie with id *movieid* from *start-timestamp* to *end-timestamp*

3

Exercise #44

- Input:
 - A second textual file containing the list of preferences for each user
 - Each line of the file contains the information about one preference
 - userid,movie-genre
 - The user with id *userid* liked the movie of type *movie-genre*

4

Exercise #44

- Input:
 - A third textual file containing the list of movies with the associated information
 - Each line of the file contains the information about one movie
 - movieid,title,movie-genre
 - There is only one line for each movie
 - i.e., each movie has one single genre

5

Exercise #44

- Output:
 - Select the userids of the list of users with a misleading profile
 - A user has a misleading profile if more than **threshold%** of the movies he/she watched are not associated with a movie genre he/she likes
 - **threshold** is an argument/parameter of the application and it is specified by the user
 - Store the result in an HDFS file

6

Exercise #45

- Profile update
- Input:
 - A textual file containing the list of movies watched by the users of a video on demand service
 - Each line of the file contains the information about one visualization
userid,movieid,start-timestamp,end-timestamp
 - The user with id *userid* watched the movie with id *movieid* from *start-timestamp* to *end-timestamp*

7

Exercise #45

- Input:
 - A second textual file containing the list of preferences for each user
 - Each line of the file contains the information about one preference
userid,movie-genre
 - The user with id *userid* liked the movie of type *movie-genre*

8

Exercise #45

- Input:
 - A third textual file containing the list of movies with the associated information
 - Each line of the file contains the information about one movie
movieid,title,movie-genre
 - There is only one line for each movie
 - i.e., each movie has one single genre

9

Exercise #45

- Output:
 - Select for each user with a misleading profile (according to the same definition of Exercise #44) the list of movie genres that are not in his/her preferred genres and are associated with at least 5 movies watched by the user
 - Store the result in an HDFS file
 - Each line of the output file is associated with one pair (user, selected misleading genre) associated with him/her
 - The format is
userid, selected (misleading) genre
 - Users associated with a list of selected genres are associated with multiple lines of the output file

10

Exercise #46

- Time series analysis
- Input:
 - A textual file containing a set of temperature readings
 - Each line of the file contains one timestamp and the associated temperature reading
timestamp, temperature
 - The format of the timestamp is the Unix timestamp that is defined as the number of seconds that have elapsed since 00:00:00 Coordinated Universal Time (UTC), Thursday, 1 January 1970
 - The sample rate is 1 minute
 - i.e., the difference between the timestamps of the two consecutive readings is 60

11

Exercise #46

- Output:
 - Consider all the windows containing 3 consecutive temperature readings and
 - Select the windows characterized by an increasing trend
 - A window is characterized by an increasing trend if for all the temperature readings in it
temperature(t)>temperature(t-60seconds)
 - Store the result into an HDFS file

12

Exercise #46 - Example

- Input file

```
1451606400,12.1  
1451606460,12.2  
1451606520,13.5  
1451606580,14.0  
1451606640,14.0  
1451606700,15.5  
1451606760,15.0
```

- Output file

```
1451606400,12.1,1451606460,12.2,1451606520,13.5  
1451606460,12.2,1451606520,13.5,1451606580,14.0
```

13

Big data: architectures and data analytics

Spark - Exercises

2

Exercise #47

- Full station identification in real-time
- Input:
 - A textual file containing the list of stations of a bike sharing system
 - Each line of the file contains the information about one station
 - id\tlongitude\tlatitude\tname
 - A streaming of readings about the status of the stations
 - Each reading has the format
 - StationId,# free slots,#used slots,timestamp

3

Exercise #47

- Output:
 - For each reading with a number of free slots equal to 0
 - print on the standard output timestamp and name of the station

4

Big data: architectures and data analytics

Spark - Exercises

2

Exercise #49

- Input:
 - A csv file containing a list of profiles
 - Header: name,surname,age
 - Each line of the file contains one profile
 - name,surname,age
- Output:
 - A csv file containing one line for each profile. The original age attribute is substituted with an new attributed called rangeage of type String
 - rangeage = "[" + (age/10)*10 + "-" + (age/10)*10 + 1 "]"

3

Exercise #49

- Input:
 - name,surname,age
 - Paolo,Garza,42
 - Luca,Boccia,41
 - Maura,Bianchi,16
- Expected output:
 - name,surname,rangeage
 - Paolo,Garza,[40-49]
 - Luca,Boccia,[40-49]
 - Maura,Bianchi,[10-19]

4

Exercise #50

- Input:
 - A csv file containing a list of profiles
 - Header: name,surname,age
 - Each line of the file contains one profile
 - name,surname,age
- Output:
 - A csv file containing one single column called "name_surname" of type String
 - name_surname = name+" "+surname

5

Exercise #50

- Input:
 - name,surname,age
 - Paolo,Garza,42
 - Luca,Boccia,41
 - Maura,Bianchi,16
- Expected output:
 - name_surname
 - Paolo Garza
 - Luca Boccia
 - Maura Bianchi

6