

- For “Input coordinates”, enter 1ubq.pdb
- “Forcefield” is the set of parameters and functions that describes the energy of a system. Let’s keep “AMBER99sb-ildn”
- “Water Model” includes
  - descriptions that vary in the number of point charges
  - a description that doesn’t actually model water at all, but its effect on the electrostatic energy and a penalty for forming surfaces. For computational speed, let’s pick this “Implicit Solvent” version
- “Platform” describes the version of the code and the hardware it will run on
  - “Reference” is meant to be the most readable code
  - “CUDA” and “OpenCL” are meant for GPUs, which make MD simulations much faster. “CUDA” only works with Nvidia GPUs and “OpenCL” on others
  - “CPU” is a faster version of Reference.
  - Since the laboratory machines don’t have GPUs, let’s use “CPU”
- The other options are GPU-specific

General System Integrator Simulation

Input coordinates

Input topology

Forcefield

Water Model

Platform

Precision

Device index

OpenCL platform indx

General System Integrator Simulation

Input coordinates

Input topology

Forcefield

Water Model

Platform

Precision

Device index

OpenCL platform indx

General System Integrator Simulation

Input coordinates

Input topology

Forcefield

Water Model

Platform   
TIP3P  
TIP4P-Ew  
TIP5P  
Implicit Solvent (OBC)

Precision

Device index

OpenCL platform indx

General System Integrator Simulation

Input coordinates

Input topology

Forcefield

Water Model

Platform   
Reference  
OpenCL  
CPU  
CUDA

Precision

Device index

OpenCL platform indx

- “Nonbonded method” describes how long-range interactions are treated. The more interactions that need to be computed, the slower an MD simulation will be.
- Cutoffs don’t perform calculations if two particles are beyond a certain distance apart.
- Ewald methods calculate long-range interaction energies between a system and its periodic images. It assumes the system repeats indefinitely.
- Since we are using implicit solvent, we don’t need periodicity.
- Let’s use “CutoffNonPeriodic”.
- “Constraints”
  - force a degree of freedom to be a certain value
  - allow a larger time step, giving you more bang (simulation time) for the buck (compute time)
- Let’s keep the other “System” parameters as is

General	System	Integrator	Simulation
Nonbonded method	CutoffNonPeriodic ▼		
Ewald error tolerance	0.0005		
Constraints	HBonds ▼		
Constraint error tol.	0.00001		
Rigid water?	True ▼		
Nonbonded cutoff	1.0 nm		
Random init vels.	True ▼		
Generation temp.	300 K		