

Released geometry

Main fascia	480 × 320 × 1.5 CR4 mild steel; R8 corners
Dashboard rough cut	440 × 280 nominal; transfer actual shape in vehicle
Rear stiffener	460 × 300 × 2.0 mild steel ring
LCD carrier	310 × 200 × 2.0; actual screen aperture HOLD
Vent carriers	2 × 165 × 82 × 2.0; actual vent aperture HOLD
HVAC controls	2 × Ø22.5, confirm bought selector thread/body
Hazard	Ø16.2, confirm bought pushbutton thread/body
Carrier mounting	12 × Ø4.5 for M4 low-profile screws + captive nuts
Fascia mounting	8 × Ø5.5 for M5 button-head screws + rivnuts/nutplates

PRODUCTION HOLD POINTS

1. Scan or cardboard-template the actual dash cut boundary; preserve gauge and glovebox structure.
2. Caliper-measure LCD visible face, rear body, connector sweep and fixing pattern.
3. Measure vent face, flange, neck OD and total rear depth; prove 63.5 mm hose connection.
4. Dry-fit screen, carriers, ducts and switch contact blocks; steering/wiper/heater interference must clear.
5. Owner signs the 1:1 paper plot before cutting the vehicle or the final carrier apertures.

