

J40 PARTS TO SEND FOR REFURBISHMENT

A simple photo guide for selecting the correct parts

Purpose: Every photographed item in this guide should be selected, labelled and taken for refurbishment, specialist assessment or reconstruction.

Not included: Parts planned for replacement or interior modernisation have been removed, including wiper arms/blades, lights, washer pump/bottles, failed lock, old interior pulls and padded trim, window crank and pedal rubber.

Uncertain items: Send them, but attach an IDENTIFY FIRST label. The workshop should identify and assess them before blasting, dismantling or coating.

Simple rule for the workshop

Mechanical/electrical work: Route the pedal switches, latch sets, handbrake linkage, window regulator and wiper motor to the appropriate specialist before cosmetic work.


Before painting: Label where every part came from and check that it is not cracked, badly worn, bent or rusted too thin.

During painting: Do not paint threads, pivots, gear teeth, latch faces, seals, electrical contacts, fluid passages or mounting faces.

After painting: Fit new clips, bushes, seals or screws where needed, lubricate moving parts and test them before installation.

Bump stops: They are included because the metal fixtures need rust treatment and preparation. Protect the new rubber throughout the work.

Select and send these parts

Photo	Item	What to do
	Pedal-area plunger-switch bracket	Owner identifies the location as the brake/clutch pedal area. It looks like two adjustable plunger switches rather than a hydraulic junction. Label its position; test the switches and wiring; replace failed electrical parts; derust and refinish only the bracket.
	Single stamped latch / adjuster bracket	Not a seatbelt. Send it with an IDENTIFY FIRST tag. It may be a bonnet/hood or other single control latch. Confirm its function and safe operation before cleaning, lubricating and refinishing reusable metal.
	Likely front-door latch and central-locking sets	These appear to be two separate door sets: each has latch rods and an aftermarket electric lock actuator. Keep them separate as LH/RH candidates. Preserve the mechanical latches as fitment samples; replace old actuators if central locking is modernised; do not blast or paint motors, rods, pivots, catches or plated faces.
	Parking-brake cable / linkage sample	Use this to reconstruct the complete handbrake system. Send to a brake/cable specialist, not just a painter. Record length, bends and both end fittings; inspect or reproduce the cable/linkage; renew adjusters, clevises, pins and clips as needed; prove full application and free return.
	Glove-box lid	Dry-fit first. Repair dents, remove rust, epoxy-prime and paint in the chosen interior colour. Renew the hinge, latch and buffers if worn.



Manual window regulator

Clean out old grease. Check sector teeth, arms, rivets and rollers. Refinish exposed metal only, lubricate after the coating cures and bench-cycle through its full travel.



Likely windscreen-wiper motor and crank

This is a one-per-vehicle powered mechanism and its motor/gearbox/crank layout is consistent with a wiper motor, not steering. Send to an auto-electric specialist for identification and bench test. Rebuild only if worthwhile; do not blast or paint the motor, gearbox, connector, shaft or ball joint.



Unidentified lever pieces

Send with IDENTIFY FIRST tags. If the refurbisher confirms they are useful and sound, clean, derust and refinish the non-working surfaces. Mask pivots, bushes, shafts, holes and mating faces.



Likely engine oil-filler / breather tube

Origin is not proven, but the large neck and small side breather are consistent with an engine filler/breather tube. Identify first. Degrease internally, inspect for deep pitting or cracks, preserve all sealing faces and coat only the sound exterior.



New bump-stop metal fixtures

Label all four positions. Protect the new rubber from solvent, heat and abrasives. Remove loose rust from the metal plates, inspect for pitting/cracks/distortion, apply compatible rust treatment, epoxy-prime and paint the metal, then trial-fit.

Workshop sign-off

Instruction: Record what was accepted, rejected and completed. Return every unidentified or rejected piece with its original label.

Sent to: _____

Date: _____

Items rejected: _____

Items completed: _____

Checked by: _____