

R Training Session 2: Matrices, Data Frames, and Data Manipulation

Data Avicenna

Department of Economics
Universitas Gadjah Mada

May 14, 2025

Outline

- 1 Review
- 2 Matrices
- 3 Data Frames
- 4 Importing Data
- 5 The Tidyverse
- 6 Assignment

R Training Session 2: Matrices, Data Frames, and Data Manipulation

All materials can be accessed through:

<https://github.com/davicenna/R-Training-FEB-UGM>

Review of Previous Session

In our previous session, we covered:

- Basic operations and functions in R
- Vectors - the fundamental data structure
- Factors for categorical data
- Logical operations and comparisons
- Conditional statements (if, else, if-else)
- Creating and using functions

Today, we'll expand our knowledge to:

- Working with directories and importing data
- Matrices - two-dimensional data structures
- Data frames - tabular data with mixed types
- Introduction to data manipulation with tidyverse packages

Matrices: Introduction

- Matrices are collections of vectors.
- All elements must be of the same type (numeric, character, etc.)
- The dimensions are $r \times k$, where r is the number of rows and k is the number of columns.

Creating Matrices

There are multiple ways to create matrices in R:

Method 1: From a vector with matrix() function

```
vec <- 1:12
```

```
mat1 <- matrix(vec, nrow = 4, ncol = 3)
```

Method 2: By binding vectors together

```
x <- c(1, 2, 3, 4)
```

```
y <- c(5, 6, 7, 8)
```

```
z <- c(9, 10, 11, 12)
```

Column binding

```
mat2 <- cbind(x, y, z)
```

Row binding

```
mat3 <- rbind(x, y, z)
```

Creating Matrices

```
# Method 3: Changing dimensions of a vector  
vec2 <- 1:9  
dim(vec2) <- c(3, 3) # Converts vector to a 3x3 matrix
```

Matrix Options

Control how data fills matrices with options:

Data is filled by column by default

```
matrix(1:6, nrow = 2, ncol = 3)
```

```
##           [,1] [,2] [,3]
```

```
## [1,]        1     3     5
```

```
## [2,]        2     4     6
```

Fill by row instead

```
matrix(1:6, nrow = 2, ncol = 3, byrow = TRUE)
```

```
##           [,1] [,2] [,3]
```

```
## [1,]        1     2     3
```

```
## [2,]        4     5     6
```


Matrix Options

```
# Create a matrix with specific values
matrix(0, nrow = 3, ncol = 4) # Matrix of zeros
##      [,1] [,2] [,3] [,4]
## [1,]    0    0    0    0
## [2,]    0    0    0    0
## [3,]    0    0    0    0
```

Matrix Indexing

Accessing elements, rows, or columns in a matrix:

```
mat <- matrix(1:9, nrow = 3, ncol = 3)
```

```
mat
```

```
##           [,1] [,2] [,3]
```

```
## [1,]      1    4    7
```

```
## [2,]      2    5    8
```

```
## [3,]      3    6    9
```

```
# Entire second row
```

```
mat[2, ]    # [1] 2 5 8
```

```
# Entire third column
```

```
mat[, 3]    # [1] 7 8 9
```

Matrix Indexing

Accessing elements, rows, or columns in a matrix:

```
# Individual element at row 2, column 3  
mat[2, 3]  # [1] 8
```

Matrix Operations

Matrices support various mathematical operations:

```
A <- matrix(1:4, nrow = 2)
```

```
B <- matrix(5:8, nrow = 2)
```

```
# Element-wise operations
```

```
A + B           # Addition
```

```
##           [,1] [,2]
```

```
## [1,]      6   10
```

```
## [2,]      8   12
```

```
A * B           # Element-wise multiplication
```

```
##           [,1] [,2]
```

```
## [1,]      5   21
```

```
## [2,]     14   32
```

Matrix Operations

Matrices support various mathematical operations:

```
# Matrix multiplication
```

```
A %*% B      # True matrix multiplication
```

```
##           [,1] [,2]
```

```
## [1,]      19   22
```

```
## [2,]      43   50
```

More Matrix Operations

```
# Transpose
t(A)
##      [,1] [,2]
## [1,]    1    2
## [2,]    3    4

# Matrix diagonal
diag(A)      # [1] 1 4

# Create diagonal matrix
diag(1, 3)    # 3x3 identity matrix
##      [,1] [,2] [,3]
## [1,]    1    0    0
## [2,]    0    1    0
## [3,]    0    0    1

# Matrix inversion (requires square matrix)
C <- matrix(c(3, 1, 2, 4), nrow = 2)
solve(C)      # Inverse of matrix C
```

Matrix Functions

Useful functions for working with matrices:

```
mat <- matrix(1:9, nrow = 3)
```

Dimensions

```
dim(mat)      # [1] 3 3
```

```
nrow(mat)     # [1] 3
```

```
ncol(mat)     # [1] 3
```

Row and column names

```
rownames(mat) <- c("row1", "row2", "row3")
```

```
colnames(mat) <- c("col1", "col2", "col3")
```

Apply functions to rows or columns

```
rowSums(mat)  # [1] 12 15 18
```

```
colMeans(mat) # [1] 2 5 8
```

Apply any function to rows or columns

```
apply(mat, 1, sum)      # Apply sum to rows (margin = 1)
```

```
apply(mat, 2, min)     # Apply min to columns (margin = 2)
```

Data Frames: Introduction

- Data frames are the most common data structure for analysis in R
- Unlike matrices, data frames can contain different types of data in each column
- Each column is a vector of the same length (but different types allowed)

Creating a basic data frame

```
economic_data <- data.frame(  
  country = c("Indonesia", "Malaysia", "Thailand",  
              "Vietnam"),  
  gdp_billion = c(1119, 364, 505, 261),  
  population_million = c(270, 32, 70, 97),  
  inflation_rate = c(3.2, 2.8, 1.7, 4.1)  
)
```


Data Frame Structure

Let's examine the structure of the data frame:

```
# View the data frame
```

```
economic_data
```

```
View(economic_data)
```

```
# Check the structure
```

```
str(economic_data)
```

Accessing Data Frame Elements

```
# Access a column using $ notation
```

```
economic_data$country
```

```
# [1] "Indonesia" "Malaysia" "Thailand" "Vietnam"
```

```
# Access a column using bracket notation
```

```
economic_data[, "gdp_billion"]
```

```
# [1] 1119 364 505 261
```

```
# Access a row
```

```
economic_data[2, ]
```

```
# country gdp_billion population_million inflation_rate
```

```
# 2 Malaysia 364 32 2.8
```

Accessing Data Frame Elements

Access a specific element

```
economic_data[3, "inflation_rate"]
```

```
# [1] 1.7
```

Multiple rows or columns

```
economic_data[1:2, c("country", "gdp_billion")]
```

Manipulating Data Frames

Add a new column

```
economic_data$gdp_per_capita <-  
economic_data$gdp_billion * 1e9 /  
(economic_data$population_million * 1e6)
```

Modify values

```
economic_data$inflation_rate[1] <- 3.5  
# Update Indonesia's inflation rate
```

Manipulating Data Frames

```
# Add a new row
```

```
new_country <- data.frame(  
  country = "Philippines",  
  gdp_billion = 331,  
  population_million = 110,  
  inflation_rate = 4.5,  
  gdp_per_capita = 331 * 1e9 / (110 * 1e6)  
)
```

```
economic_data <- rbind(economic_data, new_country)
```

Data Frame Operations

Common operations with data frames:

Sorting a data frame

```
sorted_by_gdp <-  
economic_data[order(economic_data$gdp_billion,  
                     decreasing = TRUE), ]
```

Filtering rows based on conditions

```
high_inflation <-  
economic_data[economic_data$inflation_rate > 3, ]
```

Select subset of columns

```
gdp_data <- economic_data[, c("country",  
                              "gdp_billion", "gdp_per_capita")]
```

Data Frame Operations

```
# Summary statistics
summary(economic_data)

# Number of rows and columns
dim(economic_data)  # [1] 5 5
nrow(economic_data) # [1] 5
ncol(economic_data) # [1] 5
```

Built-in Data Sets in R

R includes many datasets for learning:

```
# List all available datasets
```

```
data()
```

```
# Load a dataset into your environment
```

```
data(mtcars) # Motor Trend Car Road Tests
```

```
head(mtcars)
```


Importing Data: Smoking Data Overview

We will be using a dataset on smoking for the rest of the module:

- Cross-sectional dataset with observations on 10,000 indoor workers
- Collected as part of the National Health Interview Survey (1991 & 1993)
- Contains information on:
 - Whether individuals were subject to a workplace smoking ban
 - Smoking status
 - Demographic characteristics
- Used in the paper "Do Workplace Smoking Bans Reduce Smoking?" (Evans, Farrelly, & Montgomery, 1999)

Smoking Data Variables

| Variable | Definition |
|----------|--|
| smoker | =1 if current smoker, =0 otherwise |
| smkban | =1 if there is a work area smoking ban, =0 otherwise |
| age | age in years |
| hsdrop | =1 if high school dropout, =0 otherwise |
| hsgrad | =1 if high school graduate, =0 otherwise |
| colsome | =1 if some college, =0 otherwise |
| colgrad | =1 if college graduate, =0 otherwise |
| black | =1 if black, =0 otherwise |
| hispanic | =1 if Hispanic, =0 otherwise |
| female | =1 if female, =0 otherwise |

Note: The educational binary indicators refer to the highest level attained and are mutually exclusive.

Working Directories in R

Understanding working directories is essential for importing data:

```
# Check current working directory
```

```
getwd()
```

```
# [1] "C:/Users/username/Documents"
```

```
# Set working directory
```

```
setwd("/path/to/your/folder")
```

```
# List files in current directory
```

```
list.files()
```

```
# [1] "Smoking.csv" "Smoking.xlsx" "Smoking.dta"
```

Importing Smoking Data - CSV Format

```
# Importing Data ####  
# Using base R  
smoking_df <- read.csv("Smoking.csv")  
  
# Common parameters  
smoking_df <- read.csv("Smoking.csv",  
                        header = TRUE, # First row contains headers  
                        sep = ";", # Delimiter (semi-colon)  
                        )  
  
# Using readr package from tidyverse  
# install.packages("tidyverse")  
# install.packages("readr")  
library(tidyverse) # Or alternatively, library(readr)  
smoking_df <- read_delim("Smoking.csv")
```

Importing Smoking Data - Excel Format

```
# Using readxl package
# install.packages("readxl")
library(readxl)

# Basic import
smoking_df_xl <- read_excel("Smoking.xlsx")

# We can also specify the sheet if there are multiple sheets
smoking_df_xl <- read_excel("Smoking.xlsx", sheet = 1)

# Compare dimensions of our imported data
dim(smoking_df)      # From CSV
dim(smoking_df_xl)   # From Excel
# Should be the same: [1] 10000    10
```

Importing Smoking Data - Stata Format

```
# Using haven package
# install.packages("haven")
library(haven)

# Import Stata file
smoking_df_dta <- read_dta("Smoking.dta")
```

Introduction to tidyverse

- The tidyverse is a collection of R packages designed mostly for data manipulation and visualization.
- Core packages include:
 - **dplyr**: data manipulation (filter, sort, summarize)
 - **tidyr**: data reshaping and cleaning
 - **ggplot2**: data visualization
 - **readr**: data import
 - **tibble**: modern data frames
- Benefits:
 - Consistent syntax and grammar
 - More readable code with the pipe operator (`%>%`)
 - Optimized for working with data frames
 - Designed for data analysis workflows

Installing and Loading tidyverse

To get started with tidyverse:

```
# Install the complete tidyverse (one-time setup)
```

```
# install.packages("tidyverse")
```

```
# Or install individual packages as needed
```

```
# install.packages("dplyr")
```

```
# install.packages("tidyr")
```

```
# Load the entire tidyverse
```

```
library(tidyverse)
```

```
# Or load individual packages
```

```
library(dplyr)
```

```
library(tidyr)
```

```
# Let's use our smoking dataset for all examples
```

```
# Convert to a tibble for better printing
```

```
smoking_df <- as_tibble(smoking_df)
```


dplyr: Key Functions - filter()

The first key dplyr function is `filter()`, which subsets rows:

1. filter() - subset rows based on values

Find only smokers

```
smokers <- filter(smoking_df, smoker == 1)
```

```
dim(smokers) # Should have fewer rows than the original dataset
```

Find smokers who are subject to workplace smoking bans

```
banned_smokers <- filter(smoking_df, smoker == 1 & smkban == 1)
```

Find female smokers with at least some college education

```
female_educated_smokers <- filter(smoking_df,  
                                smoker == 1,  
                                female == 1,  
                                colsome == 1 | colgrad == 1)
```

dplyr: Key Functions - select()

The second key dplyr function is `select()`, which selects columns:

```
# 2. select() - select columns
```

```
# Select only demographic variables
```

```
demographics <- select(smoking_df, age, female, black, hispanic)  
head(demographics)
```

```
# Select variables related to education
```

```
education <- select(smoking_df, hsdrop, hsgrad, colsome, colgrad)  
head(education)
```

```
# You can also exclude columns with -
```

```
no_race <- select(smoking_df, -black, -hispanic)  
head(no_race)
```

```
# Select columns that match a pattern
```

```
education_vars <- select(smoking_df, starts_with("hs"), starts_with("col"))  
head(education_vars)
```

dplyr: Key Functions - arrange()

The third key dplyr function is `arrange()`, which reorders rows:

```
# 3. arrange() - reorder rows
```

```
# Sort by age (youngest first)
```

```
youngest_first <- arrange(smoking_df, age)
head(youngest_first)
```

```
# Sort by age (oldest first)
```

```
oldest_first <- arrange(smoking_df, desc(age)) # desc = descending
head(oldest_first)
```

```
# Sort by multiple columns: education level then age
```

```
educated_by_age <- arrange(smoking_df,
                           desc(colgrad),
                           desc(colsome),
                           desc(hsgrad),
                           age)
```

dplyr: Key Functions - mutate()

The fourth key dplyr function is `mutate()`, which creates new variables:

```
# 4. mutate() - create new variables

# Create an age category variable
smoking_with_age_cat <- mutate(smoking_df,
                               age_category = case_when(
                                 age < 30 ~ "Young",
                                 age < 50 ~ "Middle",
                                 TRUE ~ "Senior" # default case
                               ))

# Convert string variables of the categories as factors
smoking_with_age_cat$age_category <- factor(smoking_with_age_cat$age_category)
class(smoking_with_age_cat$age_category)
# Check the generated age categories
levels(smoking_with_age_cat$age_category)
```

dplyr: Key Functions - summarize()

The fifth key dplyr function is `summarize()`, which creates summaries:

5. summarize() - reduce multiple values to a single summary

Overall smoking rate

```
smoking_rate <- summarize(smoking_df,  
                           pct_smokers = (sum(smoker==1)/n()) * 100,  
                           count = n())
```

smoking_rate

Often used with group_by() for group summaries

```
by_gender <- group_by(smoking_df, female)  
gender_summary <- summarize(by_gender,  
                             pct_smokers = (sum(smoker==1)/n()) * 100,  
                             avg_age = mean(age),  
                             pct_banned = (sum(smkbanned==1)/n()) * 100,  
                             count = n())
```

The Pipe Operator ($\%>\%$)

The pipe operator makes code more readable by chaining operations:

Without pipes

```
banned_smokers_age <- filter(smoking_df, smkban == 1, smoker ==  
banned_smokers_age <- select(banned_smokers_age, age)  
banned_smokers_age <- summarize(banned_smokers_age,  
                                mean(age))  
  
banned_smokers_age
```

With pipes

```
banned_smokers_age <- smoking_df %>%  
  filter(smkban == 1, smoker == 1) %>%  
  select(age) %>%  
  summarize(mean(age))  
  
banned_smokers_age
```

Complex Data Analysis with Pipes

Example: Analyzing smoking rates by demographic characteristics

```
# Smoking rates by gender and education level
```

```
smoking_by_demo <- smoking_df %>%
```

```
# Group by gender and education level
```

```
group_by(female, colgrad) %>%
```

```
# Calculate summary statistics for each group
```

```
summarize(
```

```
  avg_age = mean(age),
```

```
  smoking_rate = mean(smoker) * 100,
```

```
  ban_rate = mean(smkbanned) * 100,
```

```
  count = n()
```

```
) %>%
```

```
# Sort by smoking rate
```

```
arrange(desc(smoking_rate))
```

```
# View results
```

```
smoking_by_demo
```

Data Reshaping with tidyr

Let's reshape our smoking data to understand smoking patterns by gender and education levels:

First, create a summary by gender and education

```
education_summary <- smoking_df %>%  
  group_by(female, hsdrop, hsgrad, colsome, colgrad) %>%  
  summarize(  
    smoking_rate = mean(smoker) * 100,  
    count = n()  
  ) %>%  
  ungroup()
```

Convert from multiple education columns to a single column

```
edu_long <- education_summary %>%  
  pivot_longer(  
    cols = c(hsdrop, hsgrad, colsome, colgrad), # columns to collapse  
    names_to = "education_level", # new column with the level name  
    values_to = "is_level" # new column that holds the 0/1 values  
  ) %>%  
  filter(is_level == 1) %>% # Keep only the actual education level  
  select(-is_level) # Remove the indicator column
```


Merging Data with dplyr

Let's demonstrate joining with a small additional dataset:

```
# Create a small dataset with education descriptions
education_labels <- tibble(
  education_level = c("hsdrop", "hsgrad", "colsome", "colgrad", "higher"),
  description = c("High School Dropout", "High School Graduate",
                  "Some College", "College Graduate",
                  "Post-Graduate Degree"),
  years_edu = c(10, 12, 14, 16, 18)
)

# Join our long education data with the labels
edu_labeled <- edu_long %>%
  left_join(education_labels, by = "education_level")

# Now we have both the smoking rates and the education descriptions
head(edu_labeled)
```

Assignment 2

You need to submit your answers to this assignment to obtain a training certificate. Submit your R script to this link:

<https://tinyurl.com/R-Assignment-2-2025>. Contact dataavicenna@mail.ugm.ac.id for any questions.

Submission deadline: **20 May 2025 at 23.59pm**

Assignment 2

1. Write the answers to the following questions in an R script:
 - a Import the smoking dataset into RStudio and name the object "smoking_df". Convert the data into a tibble if you want.
 - b Create a categorical variable for education level (name the variable as "edu_level"). The categories are as follows: High school dropouts are coded as 1, high school graduates are coded as 2, those attended some college are coded as 3, and college graduates are coded as 4. (Hint: Use mutate() from dplyr)
 - c Create a **tibble** consisting of the following vectors:

```
edu_level = c(1,2,3,4)
edu_desc = c("Dropout", "Graduate", "Some College",
"College Graduate")
```
 - d Merge the tibble with "smoking_df" using the following code:

```
smoking_with_edu <- smoking_df %>%
  left_join(name_of_your_tibble, by = "edu_level")
```
 - e Lastly, convert edu_desc as factors and print smoking_with_edu.

Assignment 2

2. Using `smoking_df`, answer the following questions:
- a Using the `mutate()` function, make a new variable called `male_smoker`, which takes the value of 1 if the observed individual is both a male and a smoker.
 - b Print the data and check whether `male_smoker` is already generated.
 - c Calculate the percentage of male smokers.