PQC Function Evaluation

Carnegie Vacation Scholarship

David Amorim

Week 4
(22/07/2024 - 26/07/2024)

Aims for the Week

The following aims were set at the last meeting (22/07/2024):

1. Change Input Layer Structure

Improve the connectivity of input layers. Each input qubit should ideally control each target qubit at some point in the network.

2. Fix Parameters

Add the option to keep parameters fixed for each type of network layer.

3. Improve Loss Function

Develop a distance measure taking into account digital encoding. Either incorporate this into weights for an existing loss function or define a new loss function on this basis.

Glossary

Acronym	Meaning
CL	convolutional layer
AA-CL	all-to-all convolutional layer
NN-CL	neighbour-to-neighbour convolutional layer
IL	input layer
SAM	sign-adjusted mismatch

Table 1: Acronyms and short-hands used in the following.

Variable	Meaning
n	input register size
m	target register size
L	number of network layers

Table 2: Variables used in the following.

Table of Contents

Changing Input Layer Structure

- Previously, the jth input qubit controlled an operation on the jth target qubit (with wrap-around for $n > m$)
- An optional shift parameter, s, has now been added so that the jth input qubit controls an operation on the $j + s$th target qubit
- This shift parameter is incremented for each successive IL
- The QCNN is padded with additional ILs to ensure that the number of ILs is $\geq m$
- Thus, each input qubit now controls an operation on each target qubit at some point in the QCNN
- Note that ILs still alternate between control states 0 and 1

.

Changing Input Layer Structure



Figure 1: Effects of shifted ILs for $\Psi(f) \sim f$ and $m = 3$ ($L = 6$, 600 epochs, SAM)



Figure 2: Effects of shifted ILs for $\Psi(f) \sim f^2$ and $m = 3$ ($L = 6$, 600 epochs, SAM)

Changing Input Layer Structure



Figure 3: Effects of shifted ILs for $\Psi(f) \sim f$ and $m = 4$ ($L = 6$, 600 epochs, SAM)



Figure 4: Effects of shifted ILs for $\Psi(f) \sim f^2$ and $m = 4$ ($L = 6$, 600 epochs, SAM)

Changing Input Layer Structure

- The data for 'no shifts' was obtained by setting $s = 0$ for all ILs instead of incrementing s
- This should be equivalent to last week's circuit structure
- However, the 'no shifts' results are significantly worse than the results shown last week (???)
- Thus, the improvements due to the new IL structure are somewhat exaggerated
- Nonetheless, increased IL connectivity clearly leads to improved performance



Figure 5: Effects of shifted ILs for $\Psi_{\text{Hayes2023}}$ and $m = 3$ ($L = 6$, 600 epochs, SAM)

Table of Contents

Fixing Parameters

- Implemented the option to fix parameters for each layer type
- This means that each instance of a layer type (IL, AA-CL, NN-CL) uses the same set of parameters
- This significantly reduces the number of trainable parameters at large L
- Surprisingly, reducing the parameter space produces no noticeable speed-up (so-called qiskit primitives, i.e. the sampler, take up roughly 95% of the computational time)

Fixing Parameters



Figure 6: Effects of fixing parameters ILs for $\Psi(f) \sim f$ and $m = 4$ ($L = 6$, 600 epochs, SAM)



Figure 7: Effects of fixing parameters for $\Psi(f) \sim f^2$ and $m = 4$ ($L = 6$, 600 epochs, SAM)

Fixing Parameters

- Legend for the plots on the previous slide:
  - '*none*' : no parameters fixed
  - '*CL*': only CL parameters fixed
  - '*IL*': only IL parameters fixed
  - '*both*': all parameters fixed
- Evidently, keeping parameters fixed leads to (slightly, for '*CL*', or drastically, for '*IL*' and '*both*') worse performance
- This is likely due to a reduction of the search space
- Note that '*IL*' as well as '*both*' lead to incomplete phase extraction (formalise this concept!) and hence somewhat meaningless results
- Thus, especially taking into account the equivalent computational times, not keeping parameters fixed yields better results
- These results suggest a particular importance of ILs compared to CLs

Table of Contents

Preliminary Definitions

- Consider a computational basis state, $|k\rangle$, of the combined input-register-target-register system
- The state $|k\rangle$ is associated with a bit string $k = \{0,1\}^{n+m}$
- Denote by $[k]_n$ and $[k]_m$ the bit strings of length n and m, respectively, associated with each of the registers and write their concatenation as

$$k \equiv [k]_n \diamond [k]_m \tag{1}$$

- A general state of the two-register system is then written as

$$|z\rangle = \sum_{k=0}^{2^{n+m}-1} z_k |k\rangle \tag{2}$$

and referred to via its coefficients z_k

Preliminary Definitions

- When training in superposition, the desired state of the system is

$$|y\rangle = \sum_{j=0}^{2^n-1} \frac{1}{\sqrt{2^n}} |j\rangle_i |\Psi(j)\rangle_t \,, \tag{3}$$

  where the subscripts i and t indicate basis states of the input and target registers, respectively
- This state $|y\rangle$ can be written in terms of the combined basis $\{|k\rangle\}$ via

$$y_k = \begin{cases} \frac{1}{\sqrt{2^n}} & \text{if } k = [k]_n \diamond \Psi([k]_n) \\ 0 & \text{else} \end{cases} \tag{4}$$

- Further denote the output state produced by the QCNN by $|x\rangle$, with associated coefficients x_k

SAM and Beyond

- Recall the definition of SAM:

$$\mathrm{SAM}(|x\rangle, |y\rangle) = \left| 1 - \sum_k x_k y_k \right| \tag{5}$$

- By construction, this is closely related to the mismatch

$$\mathrm{M}(|x\rangle, |y\rangle) = 1 - |\langle x|y\rangle| \tag{6}$$

- While effective, SAM's fundamental flaw is that it does not directly take into account the amplitudes x_k for k where $y_k = 0$ (i.e. where $[k]_m \neq \Psi([k]_n)$

SAM and Beyond

- Consider $k = a$ and $k = b$ with $[k]_m \neq \Psi([k]_n)$ for both and

$$\left|[a]_m - \Psi([a]_n)\right| \geq \left|[b]_m - \Psi([b]_n)\right| \tag{7}$$

- To improve performance, the loss function should punish a non-zero x_a more than a non-zero x_b which is not the case for SAM
- This could be achieved via a weighted mismatch,

$$\text{WIM}(|x\rangle, |y\rangle) = \left|1 - \sum_k \tilde{w}_k x_k y_k\right|, \tag{8}$$

where $\tilde{w}_k \in \mathbb{R}_+$ are appropriate weights

SAM and Beyond

- It was discussed at the last meeting to base the weights on

$$w_k = \sum_{\substack{l=0,\\ l\neq[k]_m}}^{2^m-1} \left|x_{[k]_n \diamond l}\right| \left|l - \Psi([k]_n)\right|, \tag{9}$$

  with the $\tilde{w}_k$ obtained from the w_k via normalisation and smoothing ($\tilde{w}_k \sim e^{\tau w_k}$)
- Implementing this proved to be uneffective, with no improvement on SAM
- This raises broader questions about the feasibility of WIM

The Limits of WIM

- SAM is effective as it learns to maximise the x_k for k with $y_k \neq 0$ without regard for the remaining x_k
- It effectively optimises over a reduced set of states
- This is, presumably, why it outperforms more global loss functions, which directly take into account all coefficients, like L_1 loss
- Thus, it seems that SAM's 'fundamental flaw', of disregarding most x_k, is really the basis of its success
- Adding weights to SAM (WIM) likely is insufficient to alter its fundamental dynamic (or will alter it detrimentally)
- Therefore, WIM will be abandoned for the foreseeable future

Introducing WILL

- To improve on SAM, it could be beneficial to return to a loss function, which more directly takes into account all x_k (e.g. L_1 loss)
- More generally, define L_p loss as

$$\mathrm{LL_p}(|x\rangle, |y\rangle) = \left(\sum_k |x_k - y_k|^p \right)^{1/p} \tag{10}$$

- Note that for phase encoding, computational basis states are not equidistant: their distance depends on the value they encode on the input and target registers
- A weighted L_p loss (WILL) can factor in an appropriate distance measure for the state space:

$$\mathrm{WILL_{p,q}} = \left(\sum_k \left| x_k - y_k \right|^p \left| [k]_m - \Psi([k]_n) \right|^q \right)^{1/p} \tag{11}$$

Testing WILL

- SPEND SOME TIME PLAYING AROUND WITH p AND q!
- training (e600, L6, m3) p=1 1.25 2 with q 0, 0.5, 1, 1.5, 2, 2.5, 3 [REPEAT THIS FOR p 1.75 !; p 1.5 in progress] ==¿ make heatmap plots with mean and std mismatch!

Table of Contents

Results

Show phase encoding with improved methods show the full waveform [new frame]

Table of Contents

Next Steps

- formalise and investigate ‘completeness of phase extraction’
- look into adding more ILs compared to CLs ?