

Package ‘carbonpredict’

August 18, 2025

Title Predict Carbon Emissions for UK SMEs
Version 0.0.5
Description Predict scope 1 and 2 carbon emissions using pretrained models for UK SMEs.
License MIT + file LICENSE
Encoding UTF-8
Roxygen list(markdown = TRUE)
RoxygenNote 7.3.2
Imports dplyr,
ggplot2,
progress,
lmerTest
Suggests testthat (>= 3.0.0),
mockery
Config/testthat/edition 3

Contents

batch_predict_emissions	1
batch_sme_plots	2
plot_sme_emissions	3
sme_emissions_profile	3
sme_scope1	4
sme_scope2	4
Index	6

batch_predict_emissions
<i>Batch Predict Emissions</i>

Description

Prediction entry point for batch SME and agriculture emissions

Usage

```
batch_predict_emissions(data, company_type, output_path = NULL)
```

Arguments

data	A single entry (list or named vector), a data frame, or a path to a CSV file. The data should contain company_name, 2-digit UK sic_code, and annual turnover columns.
company_type	A single parameter "sme" or "farm" to determine which emission prediction funtions to call.
output_path	Optional file path to save the results as a CSV. If NULL, results are not saved to a file.

Value

A data frame with input columns and predicted emissions for each scope (in tCo2e). Optionally saved to a CSV file.

Examples

```
sample_data <- read.csv(system.file("extdata", "sme_examples.csv", package = "carbonpredict"))
sample_data <- head(sample_data, 3)
batch_predict_emissions(data = sample_data, company_type = "sme", output_path = NULL)
```

batch_sme_plots

Batch SME Plots

Description

Batch plot SME Scope 1 & 2 emissions

Usage

```
batch_sme_plots(data, output_path = NULL)
```

Arguments

data	A data frame or path to a CSV file with columns "sic_code", "turnover", and optionally "company_name".
output_path	Optional directory to save plots. If NULL, plots are not saved.

Value

Donut chart plots showing scope 1 and 2 predicted emissions (in tCo2e) for each row in the data. Optionally saved to a directory as PNG files.

Examples

```
sample_data <- read.csv(system.file("extdata", "sme_examples.csv", package = "carbonpredict"))
sample_data <- head(sample_data, 3)
batch_sme_emissions <- batch_predict_emissions(
  data = sample_data,
  company_type = "sme",
  output_path = NULL)
batch_sme_plots(data = batch_sme_emissions, output_path = NULL)
```

plot_sme_emissions	<i>Plot SME Emissions</i>
--------------------	---------------------------

Description

Plot a donut chart of Scope 1 and Scope 2 emissions

Usage

```
plot_sme_emissions(scope1_emissions, scope2_emissions, company_name = NULL)
```

Arguments

scope1_emissions	Value for Scope 1 emissions (numeric).
scope2_emissions	Value for Scope 2 emissions (numeric).
company_name	Optional company name to include in the chart title (character string).

Value

A ggplot2 donut chart.

Examples

```
scope_1 = sme_scope1(85, 12000000)
scope_2 = sme_scope2(85, 12000000)
plot_sme_emissions(
  scope1_emissions = scope_1$predicted_emissions,
  scope2_emissions = scope_2$predicted_emissions,
  company_name = "ABC")
```

sme_emissions_profile	<i>SME Emissions Profile</i>
-----------------------	------------------------------

Description

Calls the Scope 1 and Scope 2 emissions prediction functions and returns their results as a list and plots a donut chart

Usage

```
sme_emissions_profile(sic_code, turnover, company_name = NULL)
```

Arguments

sic_code	A 2-digit UK SIC code (numeric).
turnover	Annual turnover value (numeric).
company_name	Optional company name for labeling plots (character string).

Value

A list with two elements: scope1 and scope2, each containing the predicted emissions data frame (in tCo2e), as well as a donut chart.

Examples

```
sme_emissions_profile(sic_code = 85, turnover = 12000000, company_name = "ABC")
```

sme_scope1

Predict SME Scope 1 Emissions

Description

This function loads a pre-trained emission model to predict scope 1 carbon emissions for a given SIC code and turnover.

Usage

```
sme_scope1(sic_code, turnover)
```

Arguments

sic_code	A 2-digit UK SIC code (numeric).
turnover	Annual turnover value (numeric).

Value

A data frame with predicted emissions (in tCo2e) and input variables.

Examples

```
sme_scope1(sic_code = 85, turnover = 12000000)
```

sme_scope2

Predict SME Scope 2 Emissions

Description

This function loads a pre-trained emission model to predict scope 2 carbon emissions for a given SIC code and turnover.

Usage

```
sme_scope2(sic_code, turnover)
```

Arguments

sic_code	A 2-digit UK SIC code (numeric).
turnover	Annual turnover value (numeric).

Value

A data frame with predicted emissions (in tCo2e) and input variables.

Examples

```
sme_scope2(sic_code = 85, turnover = 12000000)
```

Index

`batch_predict_emissions`, [1](#)

`batch_sme_plots`, [2](#)

`plot_sme_emissions`, [3](#)

`sme_emissions_profile`, [3](#)

`sme_scope1`, [4](#)

`sme_scope2`, [4](#)