UNAIDS 2020 REFERENCE



Instructions for using the Naomi model

V2.3.1

Table of Contents

Data preparation	2
Running the Naomi Model	3
Step 1 and 2: Upload input data	3
Step 3: Model options	5
Step 4: Fit the model	7
Step 5: Calibration	7
Step 6: Review the output	8
Step 7: Download the results	8


Data preparation

Prior to using the Naomi Model

The generation of subnational estimates using Naomi is one of the last steps in the process of HIV estimation. Ensure that you have a finalised Spectrum file, as well as validated your subnational program data (numbers on ART and ANC prevalence). If you use DHIS, the generation of the ART and ANC program data can be automated through the AIDS Data Repository (review training presentations). If you do not use DHIS or do not want to automate the process through ADR please compile the data as per the Naomi specifications. The templates with the indicator definitions and required specifications are available here https://adr.unaids.org/dataset/unaids-inputs-2021-templates.

Populate your Input Data Package in ADR for your 2021 estimates.

- There are 6 required input files used in the Naomi model:
 - 1. Geojson: Defines boundaries of your national and subnational geographical areas.
 - 2. Population: By five-year age groups and sex and district.
 - 3. Survey: Prevalence from your population-based survey and if available, incidence and ART coverage.
 - 4. ART programme data number receiving treatment Men, women, children.
 - 5. ANC programme data HIV prevalence, ART coverage among pregnant women.
 - 6. **Updated** Spectrum AIM file. Countries with subnational Spectrum files need to use the tool in Spectrum to create a 1 zip file for Naomi. (Tools>More tools>Naomi district estimates tool>Generate district results>add the subnational Spectrum files and click open. It will create a zip file in the same folder as your final Spectrum files. Upload this file into ADR.
- A prepopulated folder called "CountryName Inputs UNAIDS Estimates 2021" within your ADR country page containing items 1-3 has been created for you. You will need to add in files 4-6 above (your program data and your final Spectrum file).
- We strongly recommend that once this package is created you use the ShinyRob application to review and ensure the quality and consistency of the ANC and ART data (review training presentations). Make any improvements to the ANC or ART data based on your review.



Running the Naomi Model


Open and login to the Naomi application (Naomi.unaids.org). Once you are logged into Naomi, you will need to create a **project** or if you had previously created a project then you can load an existing project. Name your **project** and click "Create project" button.

Note you can have **multiple projects.** This is primarily for users that have been granted access to view multiple countries or if a country would like to try different model runs for comparison. On the 'Projects' page, you can see a list of all your projects and manage them.



Step 1 and 2: Upload input data

Either upload the 6 country input files manually from your computer or connect to your ADR by entering your ADR access key to directly pull in the 6 required input files from your country ADR page. We strongly recommend the second option as this ensures that everyone on the national HIV estimates team is using the same set of input data. It also allows for a more transparent estimates process and facilitates continuity and a well-documented handover between successive estimation teams. Start by clicking "get access key from ADR" link.




Copy your API Key by clicking the button.

Click 'add' and paste your ADR access key and click "Save".




After saving your ADR access key, click "Select ADR dataset", browse to the dataset you want, select it and click "Import". When your data sets are correctly imported, you will see a red check mark next to your files.



Clicking the "Edit" button next to the name of your dataset you selected will take you back to the browsing window ('Browse ADR') and allows you to select a different one if you wish.

Once you have connected to a dataset in ADR you will need to go through the following 7 steps. To advance through the steps, click 'Continue'. If "Continue" is greyed out, it indicates that there is a requirement that has not been fulfilled and you will not be able to advance until that is addressed first.



Step 3: Model options

Use the following parameters for the Naomi model. These fall into 5 categories.

A. General

Area Scope: Ensure the country is selected.

Area level: Select the lowest level of your geography/area hierarchy for which you have programme and population data. In this example it is the health district.

Calendar quarter to generate estimates: Select the last quarter of the year for which data are available. As we are generating estimates up to the end of 2020, select "December 2020"

Calendar quarter to generate short term projection: Allows generation of estimates in the future.

B. Survey

Calendar quarter at midpoint of survey: Use the default which is the midpoint of your most recent population-based survey

Prevalence: Use the default which is your most recent population-based survey

ART coverage: If any population-based survey in your country has measured ART coverage, select the most recent population-based survey.


General		
Select general model options:		
Area scope (required)	Burundi x	*
Area level (required)	District Sanitaire	•
Calendar quarter to generate estimates (required)	December 2020	•
Calendar quarter to generate short-term projection ③ (required)	September 2021	•
Survey		
Select which survey to use for each indicator and whether to run the	e model with survey ART coverage or VLS.	
Calendar quarter at midpoint of survey (required)	December 2016	•
Prevalence (required)	BDI2016DHS ×	*
ART coverage	Select	*

C. ANC

This section allows you to include HIV prevalence from antenatal clinic attendees to inform the subnational estimations. For 'Prevalence Time 1", select the year matching the midpoint of the survey and for "Prevalence Time 2", select the Year you are running your estimate for. Note: If you do not have accurate ANC data at time 1 you can select a more recent year for which you have accurate ANC data. Similarly, incorporate the proportion of ANC clients already on ART. This is used to inform the spatial pattern of ART coverage in the model.

- Time 1: Year of the population-based survey or most recent year for which they have reliable ANC data (in this example it is 2017).
- Time 2: Year of HIV estimates (up to December 2020)).

For each year selected, choose the number of months included in reporting. Ideally this will be a full year reporting (12 months). But for example, if 2020 data are only available for January through September, choose '9' months.



D. ART


Ensure that you include the number of people receiving ART as reported through programmes by indicating yes. The uploaded programme data will be interpolated to align to the quarters selected for the survey midpoint (Time 1) and the quarter to generate estimates (Time 2) selected above.

Note: If you do not have accurate ART data at time 1, we suggest that you leave time 1 blank Also, in this section we are recommending that you turn on the adjustment for people receiving ART in neighbouring districts (by selecting "Yes").



E. Population calibration options

To ensure that the Spectrum file and the Naomi results are aligned, the Naomi results will be calibrated to match the national results. Ensure you calibrate to the National level. This calibration to Spectrum's population will be completed **before** the model fitting.




F. Advanced: Keep the default advanced options as shown below

Awareness of HIV status: If you uploaded a Spectrum file that did not have a shiny 90 file in it you can run the model but will have to select "No" in order to proceed.

Use aggregate survey dataset: Set to yes if your survey dataset only has prevalence values for the broad 15-49 age group category. This includes Benin, Central African Republic, Equatorial Guinea, Guinea Bissau and Niger.

Proportion recently infected: For this round of estimates <u>please do not use this option</u>. Keep this blank.



At the end of the page, click "Validate" to validate all the selected options. When everything is validated, you will see a red check mark before proceeding. Click 'Continue' to fit the Naomi model.



Step 4: Fit the model

Click 'Fit the model'. It will take between 2 minutes to 1 hour depending on your country.



Step 5: Calibration

Calibrate your Naomi results to your Spectrum file. This should be done for the following four indicators (PLHIV, ART, aware of HIV status and new infections). This is to ensure that the mean aggregate estimates from Spectrum and Naomi are consistent. All these should be adjusted to match your Spectrum file either the national or sub-national Spectrum files with the following age sex stratification: (sex and age <15 /15+ years).

Calibration method: use the default which is logistic and which scales the prevalence, ART coverage, proportion unaware, and incidence on the logit scale within each district / sex / age stratum in order to match to Spectrum. This ensures that ART coverage does not go above 100%

in any

Options for calibrating to Spectrum outputs. If national S _i invalidate model inference to survey, ART programme, an results and Naomi input data rather than accept large cali	d ANC testing data. If calibration adjus	al' options will return the same result. Some calibrations will tments are large, it is recommended to review Spectrum
Adjust to Spectrum PLHIV	Level (?) (required)	Stratification ② (required)
	National	▼ Sex and age <15 / 15+ ▼
Adjust to Spectrum number on ART	Level (? (required)	Stratification ② (required)
	National	▼ Sex and age <15 / 15+ ▼
Adjust to Spectrum number aware of HIV status	Level (? (required)	Stratification ② (required)
	National	▼ Sex and age <15 / 15+ ▼
Adjust to Spectrum number of new infections	Level ② (required)	Stratification ② (required)
	National	▼ Sex and age <15 / 15+ ▼
Calibration method (required)	Logistic	<u> </u>

district / sex / age stratification.

Step 6: Review the output

In the maps and in the tables available through the Download function. Review coverage estimates for values that are over 100% or implausibly high; review prevalence and incidence data for values that are not realistic (e.g., outlying compared to most other districts or to other quarters/years).

Step 7: Download the results

There are 3 options

- Export model outputs for Spectrum. Use this option to download a zip file which
 can then be uploaded into Spectrum and used to create a Data pack. You can also
 use this file to view the results on a Naomi-Spectrum viewer available at NaomiSpectrum.unaids.org. This provides some additional viewing options and a table
 format of the data both at district and province level.
- 2. Download coarse age group outputs.
- 3. Download summary report. This option provides a summary of your results which you can share with key stakeholders.

Note: If you encounter any issues using these options, kindly let us know what the issue is and share your project with your facilitator so we can review your model inputs and model run.



UNAIDS

20 Avenue Appia CH-1211 Geneva 27 Switzerland

+41 22 791 3666

unaids.org