



Note: Radiometric Version only has 9/13/18mm Lens

Model	Mini640-4	Mini640-7	Mini640-9	Mini640-13	Mini640-15	Mini640-18	Mini640-25	Mini640-35	Mini640-50	Mini640-60	Mini640-75
Resolution	640*512										
Detector Type	Vox										
Detector Frame	25Hz(Radiometric)/60Hz(Non-Radiometric)										
Pixel Spacing	12μm										
Response Wave Band	8~14μm										
NETD	≤50mK@25℃,F#1.0（≤40mK optional）										
Lens											
Focus	4mm	7mm	9mm	13mm	15mm	18mm	25mm	35mm	50mm	60mm	75mm
Field of View	100°*82°	80°*62°	48.7°*38.6°	31.9°*25.7°	29.3°*23.5°	24.2°*19.5°	17.5°*14.0°	12.5°*10°	8.8°*7°	7.3°*5.9°	5.9°*4.7°
F-number	1										
Image Adjustment											
Polarity	White heat/Black heat										
Image Adjustment											
Supply Voltage	5V or 12V										
Typical Dissipation @25℃	<0.5W										
Video output											
Digital Video	YUV、USB、BT.656										
Analog Video	CVBS、PAL、NTSC										
Serial Communication	UART、RS232、RS422										
Module Physical Properties (Without Lenses and Flanges)											
Weight	<20 g										
Size	21mm*21mm*28mm										
Temperature Measurement											

Temp Measure Rang	From -20°C to +550°C
Environmental Adaptability	
Work Temperature	From -40°C to +80°C
Storage Temperature	From -50°C to +85°C
Humidity	5%-95%, no condensation