

Note: The Radiometric Version only has 9/13/18mm lenses

Model	Mini640-4	Mini640-7	Mini640-9	Mini640-13	Mini640-15	Mini640-18	Mini640-25	Mini640-35	Mini640-50	Mini640-60	Mini640-75
Resolution	640*512										
Detector Type	Vox										
Detector Frame	25 Hz/30Hz/60 Hz										
Pixel Spacing	12μm										
Response Wave Band	8～14μm										
NETD	≤50mK@25℃, F#1.0 (≤40mK optional)										
Lens											
Focus	4mm	7mm	9mm	13mm	15mm	18mm	25mm	35mm	50mm	60mm	75mm
Field of View	100°*82°	64°*52°	48.7°*38.6°	31.9°*25.7°	29.3°*23.5°	24.2°*19.5°	17.5°*14.0°	12.5°*10°	8.8°*6.4°	7.3°*5.9°	5.9°* 4.7
F-number	1/1.1/1.2										
Image Adjustment											
Polarity	White hot/black hot/support multiple pseudo colors										
Image Adjustment											
Supply Voltage	5V or 12V										
Typical Dissipation @25℃	＜0.7W / ＜3W										
Video output											
Digital Video	YUV /USB /BT.656 /DVP/MIPI/Ethernet										
Analog Video	CVBS, PAL, NTSC										
Communication interface	UART/ RS232/ RS422/I2C/USB2.0/RJ45/GMSL										
Module Physical Properties (Without Lenses and Flanges)											
Weight	<14.9 g										
Size	21mm*21mm*10.3mm										
Temperature Measurement											

thermal-image.com

Temp Measure Range	From -20℃ to +550℃
Environmental Adaptability	
Work Temperature General/ RJ45 Eth	From -40℃ to +80℃/-20℃~+60℃
Storage Temperature	From -50℃ to +85℃
Humidity	5%-95%, no condensation

thermal-image.com