

Forwarding: Store Queue

Store Queue


- Holds all in-flight stores
- CAM: searchable by address
- Age logic: determine youngest matching store older than load

Store execution

- Write Store Queue
 - Address + Data

Load execution

- Search SQ
 - Match? Forward
- Read D\$



101

Load scheduling

Store→Load Forwarding:

- Get value from executed (but not committed) store to load
- Load Scheduling:
 - Determine when load can execute with regard to older stores

Conservative load scheduling:

- All older stores have executed
- Some architectures: split store address / store data
 - Only require known address
- Advantage: always safe
- Disadvantage: performance (limits out-of-orderness)

102

Our example from before

```
ld [r1] → r5
ld [r2] → r6
add r5, r6 → r7
st r7 → [r3]
ld 4[r1] → r5
ld 4[r2] → r6
add r5, r6 → r7
st r7 → 4[r3]
// loop control here
```

With conservative load scheduling,
what can go out of order?

103

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1			
2	ld [p2] → p6	1			
3	add p5, p6 → p7				
4	st p7 → [p3]				
5	ld 4[p1] → p8				
6	ld 4[p2] → p9				
7	add p8, p9 → p4				
8	st p4 → 4[p3]				

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 1:
Dispatch insns #1, #2

104

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	
2	ld [p2] → p6	1			
3	add p5, p6 → p7	2			
4	st p7 → [p3]	2			
5	ld 4[p1] → p8				
6	ld 4[p2] → p9				
7	add p8, p9 → p4				
8	st p4 → 4[p3]				

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 2:
Why don't we issue #2?

105

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	
2	ld [p2] → p6	1	3	6	
3	add p5, p6 → p7	2			
4	st p7 → [p3]	2			
5	ld 4[p1] → p8	3			
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4				
8	st p4 → 4[p3]				

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 3:
Why don't we issue #3?
Why don't we issue #4?

106

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	
2	ld [p2] → p6	1	3	6	
3	add p5, p6 → p7	2			
4	st p7 → [p3]	2			
5	ld 4[p1] → p8	3			
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 4:
Why don't we issue #5?

107

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	
3	add p5, p6 → p7	2	6	7	
4	st p7 → [p3]	2			
5	ld 4[p1] → p8	3			
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 6:
Finally some action!

108

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	
4	st p7 → [p3]	2	7	8	
5	ld 4[p1] → p8	3			
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 7:
Getting somewhere....

109

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	
5	ld 4[p1] → p8	3	8	11	
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 8:
Etc...

110

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	
6	ld 4[p2] → p9	3	9	12	
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 9:
Etc...

111

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	12
6	ld 4[p2] → p9	3	9	12	
7	add p8, p9 → p4	4	12	13	
8	st p4 → 4[p3]	4			

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 12:
Yawn...

112

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	12
6	ld 4[p2] → p9	3	9	12	13
7	add p8, p9 → p4	4	12	13	
8	st p4 → 4[p3]	4	13	14	

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 13:
Stretch...

113

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	12
6	ld 4[p2] → p9	3	9	12	13
7	add p8, p9 → p4	4	12	13	14
8	st p4 → 4[p3]	4	13	14	

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 14:
Zzzzzz...

114

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	12
6	ld 4[p2] → p9	3	9	12	13
7	add p8, p9 → p4	4	12	13	14
8	st p4 → 4[p3]	4	13	14	15

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 15:
2-wide ooo = 1-wide inorder
I am going to cry.

115

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	8	11	12
6	ld 4[p2] → p9	3	9	12	13
7	add p8, p9 → p4	4	12	13	14
8	st p4 → 4[p3]	4	13	14	15

- 2 wide, conservative scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

What was #5 waiting for??
Can I speculate?

116


Load Speculation

- Speculation requires two things....
 - Detection of mis-speculations
 - How can we do this?
 - Recovery from mis-speculations
 - Squash from offending load
 - Saw how to squash from branches: same method

117

Load Queue

- Detects ld ordering violations
- Execute load: write addr to LQ
 - Also note any store forwarded from
- Execute store: search LQ
 - Younger load with same addr?
 - Didn't forward from younger store?



118

Store Queue + Load Queue

- Store Queue: handles forwarding
 - Written by stores (@ execute)
 - Searched by loads (@ execute)
 - Read SQ when you write to the data cache (@ commit)
- Load Queue: detects ordering violations
 - Written by loads (@ execute)
 - Searched by stores (@ execute)
- Both together
 - Allows aggressive load scheduling
 - Stores don't constrain load execution

119

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	
2	ld [p2] → p6	1	3	6	
3	add p5, p6 → p7	2			
4	st p7 → [p3]	2			
5	ld 4[p1] → p8	3	4	7	
6	ld 4[p2] → p9	3			
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, **aggressive** scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 4:
Speculatively execute #5
before the store (#4).

120

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	
2	ld [p2] → p6	1	3	6	
3	add p5, p6 → p7	2			
4	st p7 → [p3]	2			
5	ld 4[p1] → p8	3	4	7	
6	ld 4[p2] → p9	3	5	8	
7	add p8, p9 → p4	4			
8	st p4 → 4[p3]	4			

- 2 wide, **aggressive** scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Cycle 5:
Speculatively execute #6
before the store (#4).

121

Our example from before

		Disp	Issue	WB	Commit
1	ld [p1] → p5	1	2	5	6
2	ld [p2] → p6	1	3	6	7
3	add p5, p6 → p7	2	6	7	8
4	st p7 → [p3]	2	7	8	9
5	ld 4[p1] → p8	3	4	7	9
6	ld 4[p2] → p9	3	5	8	10
7	add p8, p9 → p4	4	8	9	10
8	st p4 → 4[p3]	4	9	10	11

- 2 wide, **aggressive** scheduling
- issue 1 load per cycle
- loads take 3 cycles to complete

Fast forward:
4 cycles faster
Actually ooo this time!

122

Aggressive Load Scheduling

- Allows loads to issue before older stores
 - Increases out-of-orderness
 - + When no conflict, increases performance
 - Conflict → squash → worse performance than waiting
- Some loads might forward from stores
 - Always aggressive will squash a lot
- Can we have our cake AND eat it too?

123

Predictive Load Scheduling

- Predict which loads must wait for stores
- Fool me once, shame on you—fool me twice?
 - Loads default to aggressive
 - Keep table of load PCs that have been caused squashes
 - Schedule these conservatively
 - + Simple predictor
 - Makes “bad” loads wait for *all* older stores: not great
- More complex predictors used in practice
 - Predict which stores loads should wait for

124

Out of Order: Window Size

- Scheduling scope = ooo window size
 - Larger = better
- Constrained by physical registers (#preg)
 - ROB roughly limited by #preg = ROB size + #logical registers
 - Big register file = hard/slow
- Constrained by issue queue
 - Limits number of un-executed instructions
 - CAM = can't make big (power + area)
- Constrained by load + store queues
 - Limit number of loads/stores
 - CAMs
 - Active area of research: scaling window sizes
- Usefulness of large window: limited by branch prediction
 - 95% branch mis-prediction rate: 1 in 20 branches, 1 in 100 insns

125

Out of Order: Benefits

- Allows speculative re-ordering
 - Loads / stores
 - Branch prediction
- Schedule can change due to cache misses
 - Different schedule optimal from on cache hit
- Done by hardware
 - Compiler may want different schedule for different hw configs
 - Hardware has only its own configuration to deal with

126

Static vs. Dynamic Scheduling

- If we can do this in software...
- ...why build complex (slow-clock, high-power) hardware?
 - + Performance portability
 - Don't want to recompile for new machines
 - + More information available
 - Memory addresses, branch directions, cache misses
 - + More registers available
 - Compiler may not have enough to schedule well
 - + Speculative memory operation re-ordering
 - Compiler must be conservative, hardware can speculate
 - But compiler has a larger scope
 - Compiler does as much as it can (not much)
 - Hardware does the rest

127

Out of Order: Top 5 Things to Know

- Register renaming
 - How to perform it and how to recover it
- Commit
 - Precise state (ROB)
 - How/when registers are freed
- Issue/Select
 - Wakeup: CAM
 - Choose N oldest ready instructions
- Stores
 - Write at commit
 - Forward to loads via SQ
- Loads
 - Conservative/aggressive/predictive scheduling
 - Violation detection via LQ

128

Summary: Dynamic Scheduling

- Dynamic scheduling
 - Totally in the hardware
 - Also called "out-of-order execution" (OoO)
- Fetch many instructions into instruction window
 - Use branch prediction to speculate past (multiple) branches
 - Flush pipeline on branch misprediction
- Rename to avoid false dependencies
- Execute instructions as soon as possible
 - Register dependencies are known
 - Handling memory dependencies more tricky
- "Commit" instructions in order
 - Anything strange happens pre-commit, just flush the pipeline
- Current machines: 100+ instruction scheduling window

129