

Binary Search

Jyh-Shing Roger Jang (張智星)
CSIE Dept, National Taiwan University

Binary Search Algorithm

○ Definition

- Find the position of a specified input key value within an array **sorted by key value**

★
Keyword: Sorted!

已經排序好value才有binary search
例如 頁碼 英文字典

○ Daily life example

- Find a specific page in a book (翻書找頁碼)
- Search for a word in a dictionary (從字典中找單字)

○ Numerical example

Example: The list to be searched: $L = 1\ 3\ 4\ 6\ 8\ 9\ 11$. The value to be found: $X = 4$.

Compare X to 6. X is smaller. Repeat with $L = 1\ 3\ 4$.

Compare X to 3. X is bigger. Repeat with $L = 4$.

Compare X to 4. They are equal. We're done, we found X .

Recursive Function for Binary Search

Recursive function

recursive
好簡單
壞 stack overflow 難debug

index → left mid right

```
int binarySearch(int A[], int key, int left, int right){
    if (left > right) // test if array is empty
        return KEY_NOT_FOUND;

    int mid = midpoint(left, right); // calculate midpoint to cut set in half

    // three-way comparison
    if (A[mid] > key) // key is in lower subset
        return binary_search(A, key, left, mid - 1);
    else if (A[mid] < key) // key is in upper subset
        return binary_search(A, key, mid + 1, right);
    else // key has been found
        return mid;
}
```

/2 右移一位

Quiz: How to compute mid?

- $\text{mid} = (\text{left} + \text{right}) / 2 \rightarrow$ Overflow risk! if array 太大
- $\text{mid} = \text{left} + (\text{right} - \text{left}) / 2 \rightarrow$ More reliable!
長度的一半


Example usage

- `index = binarySearch(vec, key, 0, vec.size()-1)`

Iterative Function for Binary Search

○ Iterative function

```
int binarySearch(int A[], int key, int imin, int right){
    while (left <= right){ // continue searching while [left,right] is not empty
        int mid = midpoint(left, right); // calculate the midpoint for roughly
        equal partition
        if(A[mid] == key) // key found at index mid
            return mid;
        // determine which subarray to search
        if (A[mid] < key) // change min index to search upper subarray
            left = mid + 1;
        else // change max index to search lower subarray
            right = mid - 1;
    }
    return KEY_NOT_FOUND; // key was not found
}
```



Quiz: A better way to compute mid
→ By interpolation

如果是線性
可以用內差

Summary

○ Comparisons

Quiz!

• Linear search

壞

○ Complexity $O(n)$ 正比於 n

好

○ For any unsorted arrays → Fast when appending new elements
Considerable speedup if frequently searched items are placed at the beginning

• Binary search

好

○ Complexity $O(\log(n))$ *log*

要先排序好 ○ For sorted arrays → Slow when inserting new elements

• Hash search

好

○ Complexity $O(1)$

○ For arrays pre-processed by hash functions

Extensions

Other similar problems

- Interval finding (e.g., insertion sort)
 - Given a sorted vector, find the interval of a given value.
- Non-zero element finding
 - Given a sign-sorted vector, find the no. of positive elements.


負號一邊 正號一邊

Binary search using multiple keys

Quiz!

- Preprocessing stage:** Stable-sort with multiple keys, starting from the least-significant key (LSK)
- Search stage:** Binary search starting from the most-significant key (MSK)

sort前 二個值一樣
在sort後位置不交換




For instance: search for [Year, Month, Date]
3 keys

Example of Binary Search with Multiple Keys

Quiz!

- **Preprocessing stage:** Stable-sort data with multiple keys, starting from LSK



- **Search stage:** Binary search starting from MSK

- Let's search for (2012, 03, 29)