Database's Models

Nutr.io

March 23, 2020

1 Conceptual Model

2 Relational Model

• Submitter

- Attributes: <u>submitterId</u>, SubmitterName
- Primary Key(s): submitterId
- Foreign Key(s): -

• User

- Attributes: email, *submitterId*, sessionSecret, submitterName
- Primary Key(s): email, submitterId
- Foreign Key(s): submitterId

• API

- Attributes: *submitterId*, apiToken, submitterName
- Primary Key(s): *submitterId*
- Foreign Key(s): <u>submitterId</u>

• Submission

- Attributes: submissionId, restaurantId, submitterId
- Primary Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>
- Foreign Key(s): <u>submitterId</u>

• Report

- Attributes: reportId, $\underline{submitterId}, \, \underline{submissionId}, \, \underline{restaurantId}, \, \text{description}$
- Primary Key(s): reportId, <u>submitterId</u>, <u>submissionId</u>, <u>restaurantId</u>
- Foreign Key(s): <u>submitterId</u>, <u>submissionId</u>, <u>restaurantId</u>

• Votable

- Attributes: <u>submitterId</u>, <u>submissionId</u>, <u>restaurantId</u>, votes
- Primary Key(s): <u>submitterId</u>, <u>submissionId</u>, <u>restaurantId</u>
- Foreign Key(s): <u>submitterId</u>, <u>submissionId</u>, <u>restaurantId</u>

• Restaurant

- Attributes: <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, restaurantName, location
- Primary Key(s): submissionId, restaurantId, submitterId
- Foreign Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>

• SubmittedMeal

- Attributes: <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>

- Primary Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>
- Foreign Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>

• Portion

- Attributes: <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>, quantity
- Primary Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>
- Foreign Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>, <u>mealId</u>

• Meal

- Attributes: mealId, submissionId, restaurantId, submitterId, mealName
- Primary Key(s): mealId, submissionId, restaurantId, submitterId
- Foreign Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>

• Ingredient

- Attributes: ingredient Id, $\underline{mealId}, \, \underline{submissionId}, \, \underline{restaurantId}, \, \underline{submitterId}, \, \text{ingredientName}$
- Primary Key(s): mealId, submissionId, restaurantId, submitterId
- Foreign Key(s): <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>

• Cuisine

- Attributes: <u>cuisineName</u>
- Primary Key(s): <u>cuisineName</u>
- Foreign Key(s): -

• RestaurantCuisines

- Attributes: <u>cuisineName</u>, <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>
- Primary Key(s): <u>cuisineName</u>, <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>
- Foreign Key(s): <u>cuisineName</u>, <u>submissionId</u>, <u>restaurantId</u>, <u>submitterId</u>