

Claude Fit Logger

API / Tool Reference

1 Overview

Four MCP tools are exposed by the server. All calls require the `tz` argument (IANA timezone, e.g. `America/Toronto`), which determines what counts as “today” for totals, undo, and remove.

2 `log_food`

Logs a food item. Two-call pattern for unmatched items.

Parameters:

Name	Type	Required
<code>item_name</code>	string	yes
<code>quantity_g</code>	number	yes
<code>tz</code>	string	yes
<code>calories</code>	number	only on retry after <code>not_found</code>
<code>protein_g</code>	number	optional
<code>carbs_g</code>	number	optional
<code>fat_g</code>	number	optional
<code>fiber_g</code>	number	optional
<code>sugar_g</code>	number	optional

Response (match found):

```
{
  "status": "logged",
  "entry_id": 12,
  "matched_name": "Chicken, broiler or fryers, breast...",
  "source": "usda",
  "estimated": false,
  "nutrients": {"calories": 226.5, "protein_g": 45.8, "..."},
  "today_totals": {"calories": 429.0, "...", "entry_count": 2}
}
```

Response (no match — caller should estimate and retry):

```
{
  "status": "not_found",
  "item_name": "Kirkland Protein Bar",
  "quantity_g": 60,
}
```

```
"message": "No match in USDA or Open Food Facts. Estimate calories  
          (required) and macros, then call log_food again..."  
}
```

3 undo_entry

Removes the most recently logged item today, from both Google Health and the entry log.

Parameters: `tz` (string, required).

Response:

```
{"status": "undone", "item_name": "...", "today_totals": {...}}
```

or, if nothing was logged today: `{"status": "empty", "message": "..."}.`

4 remove_entry

Removes a specific item logged today, matched by (partial, case-insensitive) name.

Parameters: `item_name` (string, required), `tz` (string, required).

Response:

```
{"status": "removed", "item_name": "...", "today_totals": {...}}
```

or, if no match: `{"status": "not_found", "message": "..."}.`

5 get_totals

Returns today's running totals and the individual entries.

Parameters: `tz` (string, required).

Response:

```
{  
  "status": "ok",  
  "today_totals": {"calories": ..., "protein_g": ..., "entry_count": 2},  
  "entries": [ {"id": 1, "item_name": "...", "calories": ..., ...}, ... ]  
}
```

6 Authentication

All tool calls are transported over the MCP Streamable HTTP connection established via the OAuth 2.1 shim (`oauth.py`). The bearer token issued by that flow is the server's static `MCP_API_KEY` under the hood — callers do not need to know this, but it explains why token “expiry” is effectively infinite (`expires_in`: 1 year) in the token endpoint's response.