

Claude Fit Logger

Troubleshooting / Runbook

1 How to Use This Document

Each entry: symptom, root cause, fix. Ordered roughly by where in the stack the problem sits (Google auth → hosting → application logic → Claude connector).

2 Google OAuth: `invalid_grant` on token refresh

Symptom: Server logs show `400 Bad Request` from `oauth2.googleapis.com/token`, with body `{"error": "invalid_grant"}`.

Cause: The refresh token in use does not match the currently active client secret — most commonly after rotating the OAuth client secret without regenerating the refresh token against the new secret.

Fix: Ensure only one client secret is active in Google Cloud Console (delete old ones). Re-download `client_secret.json` matching the active secret. Re-run the token script to mint a fresh refresh token, and update `GOOGLE_REFRESH_TOKEN` everywhere it's stored (Render env vars, local notes).

3 Google Fit: “Mismatched `dataStreamId`” (legacy API, historical)

Symptom: 400 on data source creation, message mentions an expected `dataStreamId` format.

Cause: Legacy Google Fit requires `dataStreamId` to follow an exact deterministic pattern:

```
raw:{dataType}:{projectNumber}:{applicationName}:{deviceModel}:{deviceUid}
```

where `projectNumber` is the numeric prefix of the OAuth client ID.

Status: Moot — this project migrated off legacy Google Fit entirely (see §5). Documented here for historical record.

4 Google Fit: “Mismatched value count” (legacy API, historical)

Cause: `com.google.nutrition` required exactly three value entries per point (`nutrients` map, `meal_type` int, `food_item` string), not just the nutrient map alone.

Status: Moot post-migration; documented for historical record.

5 Data writes succeed but never appear in the app

Symptom: API calls return 200, reads via the same API confirm the data exists, but nothing shows in the phone’s health app.

Root cause (this project’s actual case): Two entirely different backends were involved. Legacy Google Fit (`fitness.googleapis.com`) is a separate, disconnected data store from the current *Google Health* app (relaunched from Fitbit in 2026), which reads from the newer `health.googleapis.com` API instead. Writing to one does not populate the other.

Fix: Confirm which backend the app you’re checking actually reads from before building against any specific API. If already built against the wrong one, migrate the client module (see `health_client.py`) rather than debugging visibility settings.

Secondary cause to also check: missing `startUtcOffset` / `endUtcOffset` on Google Health writes silently defaults to UTC+0, which can place an entry on the wrong calendar day for the viewer’s timezone — worth ruling out even after confirming the correct backend.

6 GitHub: push rejected, “Push cannot contain secrets”

Cause: GitHub’s secret-scanning push protection detected a real credential in a commit (e.g. a script with a hardcoded token, or a credentials file not excluded via `.gitignore` *before* it was first committed).

Fix: Adding a path to `.gitignore` does not retroactively remove it from history. Either:

- `git reset --soft HEAD~N` back past the offending commit(s), fix the file(s), re-commit; or
- If history isn’t worth preserving: delete `.git` entirely, `git init` fresh, and force-push.

Treat any credential that reached this point as compromised regardless of whether the push ultimately succeeded — rotate it.

7 Claude connector: “Couldn’t register with sign-in service”

Cause: Claude’s custom connector UI attempts OAuth Dynamic Client Registration against every remote MCP server, even ones with no OAuth system at all. A server that only checks a static API key (via header or query parameter) fails this handshake before ever receiving a real request.

Fix: Implement a minimal OAuth 2.1 authorization-server shim (discovery endpoints, DCR, auto-approved authorize step, token issuance wrapping the existing static key). See `oauth.py` and the OAuth Shim section of the Architecture document.

8 Claude connector: “A server with this URL already exists”

Cause: A prior failed connection attempt left a stale connector entry registered.

Fix: Delete all connector entries pointing at the server’s URL before re-adding.

9 Render: cold-start delay on first request

Symptom: First tool call after a period of inactivity is slow or appears to hang briefly.

Cause: Render’s free tier spins the service down after ~15 minutes idle. This is expected behavior, not a bug.

Mitigation: Manually visit `/health` to wake the service before a time-sensitive log, if needed.