



V102AR406/3.5M-X6

Low profile scintillation detector for environmental monitoring

Description: This large volume scintillation detector provides the optimum efficiency/energy resolution ratio and is ideally suited for environmental monitoring from cars or (small) airplanes.

Features

- 4 liter (14.7 kg) NaI(Tl) scintillation crystal.
- Low radiological background due to quartz optical window.
- High QE photomultiplier tube.
- 14 pins connector for coupling to digital base.

Scintillation material	:	NaI(Tl), 102 x 102 x 406 mm (4"x4"x16").
Drawing	:	VS-0116-250.
Crystal read out	:	89 mm diameter SBA cathode PMT
Housing	:	1.0 mm thick Aluminum.
Maximum dimensions	:	109x109x538 mm long (up to 14 pins connector).
Connectors	:	Standard 14 pins.
Typical high voltage	:	+ 700 V to +1000 V.
High voltage polarity	:	Positive.
Temperature range	:	-20 to + 65°C.
Temperature gradient	:	Max. 10 degrees per hour.
Energy resolution	:	< 8 % FWHM sideways halfway at 30 cm off-axis.

Last revision: 30-07-2020

Revision number: 1

Document Name: V102ARS406_3.5M-X6

Scionix Holland B.V.

Regulierenring 5

3981 LA Bunnik

The Netherlands

Tel: + 31 30 657 03 12

Fax: +31 30 656 75 63

Website: www.scionix.nl

E-mail: sales@scionix.nl

Berkeley Nucleonics Corporation
2955 Kerner Blvd. San Rafael CA 94901

E-mail: Info@berkeleynucleonics.com

Phone: 800-234-7858

Website: www.berkeleynucleonics.com