

GRPS39

Library of the groups of order 19683

0.1

31 July 2022

David Burrell

David Burrell

Email: davidburrell@ufl.edu

Homepage: <https://davidburrell.github.io/>

Contents

1	Groups of Order 19683	3
1.1	Overview	3
2	Functionality	5
2.1	Methods	5
	References	7
	Index	8

Chapter 1

Groups of Order 19683

1.1 Overview

This library gives complete access to the following groups of order 19683:

- The rank 1 group
- All rank 2 groups
- All rank 3 groups with p-class not equal to 3
- All rank 4 groups with p-class at least 4
- All rank 5 groups with p-class at least 4
- All rank 6 groups with p-class at least 4
- All rank 7 groups with p-class at least 4
- All rank 8 groups with p-class at least 3
- The rank 9 group

This library gives partial information on the remaining groups of order 19683:

- Rank 3 groups with p-class 3
- Rank 4 groups with p-class 2
- Rank 4 groups with p-class 3
- Rank 5 groups with p-class 2
- Rank 5 groups with p-class 3
- Rank 6 groups with p-class 2
- Rank 6 groups with p-class 3
- Rank 7 groups with p-class 2

- Rank 7 groups with p-class 3

For the groups that are not explicitly available the following information is available:

- Parent Group ID
- Parent Group Order
- p-class
- Rank
- Age

The groups are sorted first by their parent group ids and then by the pc codes of the standard presentations for the groups. The data contained in this library was used in the 2022 enumeration of the groups of order 19683 [Bur22]. The computational tools used were developed in the 2021 enumeration of the groups of order 1024 [Bur21]. The available groups were generated using the p-group generation algorithm [O'B90] as implemented in the ANUPQ package [GNOH19]. The information on the remaining groups was calculated using the cohomological methods for enumerating p-groups as introduced in [EO99].

Chapter 2

Functionality

2.1 Methods

Once the package is loaded the user may call `SmallGroup(1024,i)` and receive either a group if available or a *partially constructed group* which has the following attributes set

- `p-class`
- `Rank`
- `Heritage`
- `Order`

Example

```
gap> SmallGroup(19683,1);
<pc group of size 19683 with 9 generators>
gap> G:=SmallGroup(19683,1);
<pc group of size 19683 with 9 generators>
gap> RankPGroup(G);
3
gap> PClassPGroup(G);
2
gap> GRPS39_Heritage(G);
[ 27, 5, 1 ]
gap> H:=SmallGroup(19683,2); #this is a partially constructed group
<pc group with 0 generators>
gap> PClassPGroup(H);
2
gap> RankPGroup(H);
4
gap> GRPS39_Heritage(H);
[ 81, 15, 1 ]
gap> K:=SmallGroup(19683,3); #this is a partially constructed group
<pc group with 0 generators>
gap> PClassPGroup(K);
2
gap> RankPGroup(K);
4
gap> GRPS39_Heritage(K);
```

```
[ 81, 15, 2 ]
#notice that H,K have the same parent group but their age differs
```

2.1.1 GRPS39_AvailableMap

▷ GRPS39_AvailableMap(N) (function)

Returns: int

For $1 \leq i \leq 203,045,160$ this function will return the SmallGroup ID of the i th available group among all the groups of order 19683.

Example

```
#group 1 is available
#groups 2-66668 are not available
#SmallGroup(19683,66668) is not available
gap> g:=SmallGroup(19683,66668);
<pc group with 0 generators> #this is a partially constructed group
gap> g:=SmallGroup(19683,66669);
<pc group of size 19683 with 9 generators> #this is an available group
gap> GRPS39_AvailableMap(2);
66669
#access the ith available group of order 19683
gap> SmallGroup(19683,GRPS39_AvailableMap(i)); #for i <= 203,045,160
```

2.1.2 GRPS39_InverseAvailableMap

▷ GRPS39_InverseAvailableMap(N) (function)

Returns: int

For $1 \leq i \leq 5,937,876,645$ if SmallGroup(19683, i) is available this will return its position in the available groups list or else it will print a message telling you that it is not available and return 0.

Example

```
gap> GRPS39_InverseAvailableMap(GRPS39_AvailableMap(i)) = i;
gap> GRPS39_InverseAvailableMap(2);
This is an immediate descendant of 81#15 and is not available
0
```

2.1.3 GRPS39_Heritage (for IsGroup)

▷ GRPS39_Heritage(G) (attribute)

Returns: list

Returns as a list the following information for a group of order 19683 loaded from the library [ParentGroupID, ParentGroupOrder, Age]. The Age of a group is the position of the group among its siblings in the ordered list of their standard PC codes.

2.1.4 GRPS39_ImmediateDescendantGroupShell

▷ GRPS39_ImmediateDescendantGroupShell(arg) (function)

References

- [Bur21] D. Burrell. On The Number of Groups of Order 1024. *Communications in Algebra*, 0(0):1–3, 2021. [4](#)
- [Bur22] D. Burrell. On The Number of Groups of Order 3^9 . *Preprint*, pages 1–5, 2022. [4](#)
- [EO99] B. Eick and E. A. O’Brien. Enumerating p -Groups. *Journal of the Australian Mathematical Society. Series A. Pure Mathematics and Statistics*, 67(2):191–205, dec 1999. [4](#)
- [GNOH19] G. Gamble, W. Nickel, E. O’Brien, and M. Horn. ANU p -Quotient, 2019. [4](#)
- [O’B90] E. A. O’Brien. The p -group generation algorithm. *Journal of Symbolic Computation*, 9(5):677–698, oct 1990. [4](#)

Index

GRPS39_AvailableMap, [6](#)
GRPS39_Heritage
 for IsGroup, [6](#)
GRPS39_ImmediateDescendantGroupShell, [6](#)
GRPS39_InverseAvailableMap, [6](#)