

SOC LOG ANALYSIS & THREAT INTELLIGENCE REPORT

Prepared By: David Chimburuoma Odum

Host Environment: Kali Linux (~/.log)

Date of Investigation: Tuesday, July 28, 2026

Executive Summary

This report summarizes forensic analysis of access-1.log, apache_logs and access-2.log based on the supplied evidence screenshots.

Phase I: access-1.log

Metric	Value	Verification Command
Total GET Requests	127	grep -c 'GET' access-1.log
Unique HTTP Status Codes	6	awk ...
CONNECT Attempts	10	grep -c CONNECT
Invalid Lines	60	grep -v ...
Unique User Agents	85	awk -F
Firefox Requests	0	grep -ic firefox



7.

```
(david@Attacker) ~/Downloads
$ grep -o '".*"' access-1.log | sort -u | grep -v '"_"' | wc -l
85
```

8.

```
(david@Attacker) ~/Downloads
$ grep -c firefox access-1.log
0
```

B EXERCISE 2: APACHE_LOGS

1.

```
(david@Attacker) ~/Downloads
$ wc -l apache_logs
10000 apache_logs
```

2.

```
(david@Attacker) ~/Downloads
$ awk '{print $1}' apache_logs | sort | uniq | wc -l
1753
```

3.

```
(david@Attacker) ~/Downloads
$ awk '{print $1}' apache_logs | sort | uniq -c | sort -nr | head -1
482 66.249.73.135
```

4.

```
(david@Attacker) ~/Downloads
$ awk '{print $7}' apache_logs | sort | uniq -c | sort -nr | head
807 /favicon.ico
546 /style2.css
538 /reset.css
533 /images/jordan-80.png
516 /images/web/2009/banner.png
488 /blog/tags/puppet?flav=rss20
224 /projects/xdotool/
217 /?flav=rss20
197 /
180 /robots.txt
```

```
Session Actions Edit View Help
(david@Attacker)-[~]
$ cd
(david@Attacker)-[~]
$ cd Downloads
(david@Attacker)-[~/Downloads]
$ ls
access-1.log access-2.log apache_logs
(david@Attacker)-[~/Downloads]
$ grep -c GET access-1.log
127
```

2.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $9}' access-1.log | sort | uniq | wc -l
6
```

3.

```
(david@Attacker)-[~/Downloads]
$ grep -c CONNECT access-1.log
10
```

4.

```
(david@Attacker)~/Downloads
$ awk '{print $9}' access-1.log | sort -u
-_-
163
200
304
400
404
```

Status codes and there meanings:

200 OK – The request was successful.

304 Not Modified – The requested file has not changed since the client's last request, so the browser can use its cached copy.

400 Bad Request- the server could not understand the request because it was malformed.

404 Not Found- The requested resource does not exist on the server.

5.

```
(david@Attacker)~/Downloads
$ grep -c \\x access-1.log
60
```

6.

Some of the common reasons are:

HTTPS traffic sent to an HTTP port

Port scanning or vulnerability scanning

Misconfigured clients or applications

Malicious or malformed requests

7.

```
(david@Attacker)~/Downloads
$ grep -o '".*"' access-1.log | sort -u | grep -v '"_"' | wc -l
85
```

Phase II: apache_logs

Metric	Value	Verification Command
Total Events	10000	wc -l
Unique IPs	1753	awk
Top IP	66.249.73.135	awk sort
Top URI	/favicon.ico	awk
HTTP 200	9126	awk

8.

```
(david@Attacker)-[~/Downloads]
$ grep -c firefox access-1.log
0
```

B EXERCISE 2: APACHE_LOGS

1.

```
(david@Attacker)-[~/Downloads]
$ wc -l apache_logs
10000 apache_logs
```

2.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' apache_logs | sort | uniq | wc -l
1753
```

3.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' apache_logs | sort | uniq -c | sort -nr | head -1
482 66.249.73.135
```

4.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $7}' apache_logs | sort | uniq -c | sort -nr | head
807 /favicon.ico
546 /style2.css
538 /reset.css
533 /images/jordan-80.png
516 /images/web/2009/banner.png
488 /blog/tags/puppet?flav=rss20
224 /projects/xdotool/
217 /?flav=rss20
197 /
180 /robots.txt
```

5.

```
(david@Attacker)-[~/Downloads]
$ awk '$9 == 200' apache_logs | wc -l
9126
```

C EXERCISE: 3 ACCESS-2.LOG

1.

```
(david@Attacker)-[~/Downloads]
$ grep -c GET access-2.log
60
```

2.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' access-2.log | sort | uniq | wc -l
48
```

3.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' access-2.log | sort -u | wc -l
48
```

4.

```
(david@Attacker)-[~/Downloads]
$ awk '$9 == 200' access-2.log | wc -l
19
```

5.

```
(david@Attacker)-[~/Downloads]
$ awk '$9 == 400' access-2.log | wc -l
16
```

6.

```
(david@Attacker)-[~/Downloads]
$ grep -m1 . access-2.log | awk '{print $1}'
104.245.97.236
```

Phase III: access-2.log

Metric	Value	Verification Command
GET Requests	60	grep
Unique IPs	48	awk
HTTP 200	19	awk
HTTP 400	16	awk
Top Scanner	104.245.97.236	awk
Googlebot	2.1	grep
Method	GET	awk

```
(david@Attacker)-[~/Downloads]
$ grep -c GET access-2.log
60
```

2.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' access-2.log | sort | uniq | wc -l
48
```

3.

```
(david@Attacker)-[~/Downloads]
$ awk '{print $1}' access-2.log | sort -u | wc -l
48
```

4.

```
(david@Attacker)-[~/Downloads]
$ awk '$9 == 200' access-2.log | wc -l
19
```

5.

```
(david@Attacker)-[~/Downloads]
$ awk '$9 == 400' access-2.log | wc -l
16
```

6.

```
(david@Attacker)-[~/Downloads]
$ grep -m1 . access-2.log | awk '{print $1}'
104.245.97.236
```

7.

```
(david@Attacker)-[~/Downloads]
$ grep -o 'Googlebot/[0-9.]+' access-2.log | sort -u
Googlebot/2.1
```

8.

```
(david@Attacker)-[~/Downloads]
$ grep -o 'Firefox/[0-9.]+' access-2.log | sort | uniq -c | sort -nr | head -1
1
9 Firefox/31.0
```

9.

```
(david@Attacker)-[~/Downloads]
$ awk -F'"' '{print $2}' access-2.log | awk '{print $1}' | sort | uniq -c | s
ort -nr | head -1
60 GET
```


4.

```
(david@Attacker)~/Downloads
$ awk '{print $9}' access-1.log | sort -u
"_"
163
200
304
400
404
```

Status codes and there meanings:

200 OK – The request was successful.

304 Not Modified – The requested file has not changed since the client's last request, so the browser can use its cached copy.

400 Bad Request- the server could not understand the request because it was malformed.

404 Not Found- The requested resource does not exist on the server.

5.

```
(david@Attacker)~/Downloads
$ grep -c \|x access-1.log
60
```

6.

Some of the common reasons are:

HTTPS traffic sent to an HTTP port

Port scanning or vulnerability scanning

Misconfigured clients or applications

Malicious or malformed requests

7.

```
(david@Attacker)~/Downloads
$ grep -o '".*"' access-1.log | sort -u | grep -v '"_"' | wc -l
85
```

Conclusion & Recommendations

Monitor high-volume IPs, restrict CONNECT requests, investigate malformed traffic, and implement continuous log monitoring.