(no subject)

1 message

David Dung <daviddung10k@gmail.com>   Thu, Aug 3, 2023 at 6:54 AM
To: Amber Bob bate <amberbobbate@gmail.com>

Here is a list of 100 CSS codes and their uses:

1. `color: red;` - Changes the text color to red.
2. `background-color: #f1f1f1;` - Sets the background color to a light gray shade.
3. `font-size: 16px;` - Sets the font size to 16 pixels.
4. `text-align: center;` - Centers the text horizontally.
5. `font-family: Arial, sans-serif;` - Sets the font family to Arial or any sans-serif font.
6. `border: 1px solid black;` - Applies a 1 pixel solid black border around an element.
7. `padding: 10px;` - Adds 10 pixels of padding around an element's content area.
8. `margin: 20px;` - Adds 20 pixels of margin around an element, pushing other elements away.
9. `display: flex;` - Turns an element into a flex container.
10. `height: 200px;` - Sets the height of an element to 200 pixels.
11. `width: 300px;` - Sets the width of an element to 300 pixels.
12. `text-decoration: underline;` - Adds an underline to the text.
13. `text-transform: uppercase;` - Converts text to uppercase.
14. `opacity: 0.5;` - Sets the opacity of an element to 50%.
15. `background-image: url('image.jpg');` - Sets an image as the background.
16. `box-shadow: 2px 2px 4px rgba(0, 0, 0, 0.2);` - Adds a small shadow to an element.
17. `float: left;` - Floats an element to the left.
18. `position: absolute;` - Positions an element absolutely.
19. `z-index: 10;` - Sets the stacking order of elements.
20. `border-radius: 10px;` - Rounds the corners of an element.
21. `cursor: pointer;` - Sets the cursor to a hand icon when hovering over an element.
22. `visibility: hidden;` - Hides an element without affecting the document layout.
23. `outline: none;` - Removes the outline when an element is selected.
24. `overflow: scroll;` - Adds a scroll bar to an element if the content exceeds its size.
25. `font-weight: bold;` - Sets the font weight to bold.
26. `line-height: 1.5;` - Sets the line height to 1.5 times the font size.
27. `border-collapse: collapse;` - Collapses the borders of a table.
28. `border-spacing: 5px;` - Specifies the space between table cells.
29. `text-shadow: 2px 2px 4px rgba(0, 0, 0, 0.5);` - Adds a shadow to text.
30. `transition: background-color 0.3s ease;` - Applies a smooth transition effect to the background color.
31. `transform: rotate(45deg);` - Rotates an element by 45 degrees.
32. `list-style-type: none;` - Removes the default bullet points of an unordered list.
33. `columns: 2;` - Divides content into columns.
34. `content: "•";` - Adds a bullet point before a content.
35. `text-overflow: ellipsis;` - Truncates text and appends an ellipsis if it overflows its container.
36. `box-sizing: border-box;` - Includes padding and border in the element's total width and height.
37. `border: none;` - Removes the border of an element.
38. `background-position: center;` - Centers the background image.
39. `clear: both;` - Clears floats on both sides.
40. `text-indent: 20px;` - Indents the first line of text.
41. `overflow-x: hidden;` - Hides the horizontal overflow of an element.
42. `word-spacing: 5px;` - Adds a space between words.
43. `text-decoration: line-through;` - Adds a line through the text.
44. `fill: green;` - Sets the color to fill an SVG element.
45. `animation: rotate 2s infinite;` - Applies a rotation animation that lasts for 2 seconds and repeats infinitely.
46. `mix-blend-mode: multiply;` - Blends the color of an element with its background.
47. `column-count: 3;` - Divides content into multiple columns.
48. `background-size: cover;` - Scales the background image to cover the entire element.
49. `list-style-position: outside;` - Positions the list item marker outside the content flow.
50. `flex-direction: row;` - Specifies the direction of flex items horizontally.
51. `border-top: 1px solid black;` - Adds a 1 pixel solid black border to the top of an element.

52. `visibility: visible;` - Makes an element visible.
53. `font-style: italic;` - Applies italic styling to text.
54. `transition: all 0.3s ease-in-out;` - Applies a smooth transition effect to all CSS properties.
55. `background-repeat: no-repeat;` - Prevents the background image from repeating.
56. `position: relative;` - Positions an element relative to its normal position.
57. `cursor: not-allowed;` - Sets the cursor to a 'no-entry' sign when hovering over an element.
58. `text-align: justify;` - Distributes text evenly in a line.
59. `display: inline-block;` - Makes an element an inline-level block container.
60. `text-transform: lowercase;` - Converts text to lowercase.
61. `opacity: 1;` - Sets the opacity of an element to 100%.
62. `justify-content: center;` - Centers the flex items horizontally.
63. `background-position: top right;` - Positions the background image in the top right corner.
64. `border-radius: 50%;` - Creates a circular element by rounding its corners.
65. `visibility: collapse;` - Hides an element similar to `visibility: hidden`, but also collapses the space it occupies.
66. `outline: 1px dashed blue;` - Adds a dashed blue outline to an element.
67. `overflow-y: scroll;` - Hides the vertical overflow of an element and adds a scroll bar if necessary.
68. `font-weight: normal;` - Sets the font weight to normal.
69. `line-height: inherit;` - Inherits the line height from its parent element.
70. `border-collapse: separate;` - Separates the borders of a table.
71. `border-spacing: 10px 5px;` - Specifies different space values between table cells vertically and horizontally.
72. `text-shadow: none;` - Removes the shadow from text.
73. `transition-property: background-color, color;` - Defines which CSS properties should be transitioned.
74. `transform: scale(1.5);` - Scales an element by 150%.
75. `column-gap: 20px;` - Specifies the gap between columns.
76. `content: url('image.jpg');` - Inserts an image as content before or after an element.
77. `text-overflow: clip;` - Clips the overflowed text without adding an ellipsis.
78. `box-sizing: content-box;` - Includes only the content area in the element's total width and height.
79. `border-style: dotted;` - Adds a dotted border to an element.
80. `background-color: transparent;` - Makes the background color transparent.
81. `clear: left;` - Clears floats on the left side only.
82. `text-indent: -20px;` - Outdents the first line of text.
83. `overflow-x: scroll;` - Adds a horizontal scroll bar if the content overflows its container.
84. `word-spacing: normal;` - Keeps the default spacing between words.
85. `text-decoration: overline;` - Adds a line above the text.
86. `fill: none;` - Removes the color fill from an SVG element.
87. `animation: slide 1s alternate;` - Applies an animation called "slide" that lasts for 1 second and alternates between states.
88. `mix-blend-mode: screen;` - Blends the color of an element with the screen.
89. `column-count: auto;` - Automatically divides content into multiple columns based on available space.
90. `background-size: contain;` - Scales the background image to fit within the element without cropping.
91. `display: table;` - Converts an element into a table.
92. `border-top: none;` - Removes the top border of an element.
93. `visibility: collapse;` - Makes an element invisible and collapses the space it occupies.
94. `font-style: normal;` - Resets the text styling to normal.
95. `transition-duration: 0.5s;` - Sets how long a transition effect should take to complete.
96. `background-repeat: repeat-x;` - Repeats the background image horizontally.
97. `position: fixed;` - Positions an element relative to the browser window.
98. `cursor: move;` - Sets the cursor to indicate that an element can be moved.
99. `text-align-last: right;` - Aligns the last line of a block of text to the right.
100. `mix-blend-mode: exclusion;` - Blends the color of an element with its background using the exclusion formula.

These are just a few examples of commonly used CSS codes and their purposes. There are many more CSS properties and values available that can be used to style and design web pages.