Shipping domain model

SearchPriceLog

brand_name *string* ∗
corporate_name *string* ∗
cubic_meter *float* ∗
deadline *integer* ∗
domain *string* ∗
range *float* ∗
registration_number *string* ∗
search_date *datetime (6,0)* ∗
total_value_cents *integer* ∗
value_kilometer_cents *integer* ∗
value_min_cents *integer* ∗

Admin

email *string* ∗ U
encrypted_password *string* ∗
firstname *string* ∗
lastname *string* ∗
remember_created_at *datetime (6,0)*
reset_password_sent_at *datetime (6,0)*
reset_password_token *string*

ShippingCompany

brand_name *string* ∗
corporate_name *string* ∗
domain *string* ∗
full_address *string* ∗
registration_number *string* ∗ U
status *integer* ∗

User

email *string* ∗ U
encrypted_password *string* ∗
firstname *string* ∗
lastname *string* ∗
remember_created_at *datetime (6,0)*
reset_password_sent_at *datetime (6,0)*
reset_password_token *string*

Carrier

brand *string* ∗
code_model *string* ∗ U
license_plate *string* ∗ U
manufact_year *integer* ∗
weight *integer* ∗

DeliveryTime

range_end *float* ∗
range_start *float* ∗
working_day *integer* ∗

Price

cubic_end *float* ∗
cubic_start *float* ∗
value_kilometer_cents *integer* ∗
weight_end *integer* ∗
weight_start *integer* ∗

PriceSetting

value_min_cents *integer* ∗

Order

code *string* ∗ U
depth *float* ∗
full_address *string* ∗
height *float* ∗
range *float* ∗
status *integer* ∗
total_value_cents *integer* ∗
weight *float* ∗
width *float* ∗

OrderRoute

current_location *string* ∗
current_time *datetime (6,0)* ∗
status *integer* ∗

Receiver

first_name *string* ∗
full_address *string* ∗
last_name *string* ∗
registration_code *string* ∗ U