

$$m=0.1 \text{ kg}, M_1=0.3 \text{ kg}, d=0.5 \text{ m}, \theta_0=\frac{\pi}{6}$$

$$\text{Impulse } d((1-\sin\theta)) + M_1 d(1-\sin\theta) = g d ((1-\sin\theta)(m+\frac{m_1}{2})) = 0.61 \text{ J} \approx 60$$

$$E_0 = \frac{1}{2} m v_1^2 + \frac{1}{2} I_1 \omega_1^2 = \frac{1}{2} m v_1^2 + \frac{1}{2} \cdot \frac{1}{3} m_1 d^2 \omega_1^2 = v_1^2 \left(\frac{m}{2} + \frac{m_1}{6} \right), v_1 = \sqrt{\frac{6 E_0}{3m+m_1}} = 2.47 \text{ m/s}$$

$$m_1=2 \text{ kg}, r=0.15 \text{ m}, d=0.12 \text{ m}, m_2=0.3 \text{ kg}, \mu=0.23 \text{ Nm}, \Gamma=1.2 \text{ s}$$

$$\bar{I}_1 \alpha_1 = M - f d, \bar{I}_2 \alpha_2 = f d, \bar{I}_1 \alpha_1 + \bar{I}_2 \alpha_2 = M, \theta_1 = \frac{1}{2} \alpha_1 t_0, \theta_2 = \frac{1}{2} \alpha_2 t_0$$

$$\Delta = M t_0 = \bar{I}_1 \omega_1 + \bar{I}_2 \omega_2 - \frac{(\theta_1 = \theta_2, 2\pi d/m, g, \mu) + M \theta_1}{2\pi} = \frac{1}{2} \bar{I}_1 \omega_1^2 + \frac{1}{2} \bar{I}_2 \omega_2^2$$

$$m=2 \text{ kg}, v=0.5 \text{ m/s}, M=14.4 \text{ Nm}, K=3 \text{ Nm}, \Gamma=1.2 \text{ s}, m_2=1 \text{ kg}, \mu=0.2$$

$$\text{a) } \frac{dL}{dt} = M \cdot r, \int \frac{dL}{dt} dt = \int (M \cdot K \omega) dt, \frac{d}{dt} \int \omega dt = M - K \omega, \int \frac{d\omega}{M-K\omega} = \int dt$$

$$\frac{1}{K} \left[\frac{1}{K} \ln(M-K\omega) \right] = -\frac{1}{K} \ln(M-K\omega) + \frac{1}{K} \ln M = \frac{1}{K} \ln \frac{M}{M-K\omega}, \frac{M}{M-K\omega} = e^{\frac{Kt}{K}}$$

$$M \cdot \frac{K}{K} = M - K \omega, \omega_0 = \frac{M}{(1-e^{-\frac{Kt}{K}})}, \lim_{t \rightarrow \infty} \omega = \frac{M}{K} = 11.8 \text{ rad/s}$$

$$\text{b) } m_2 \square, \bar{I}_1 \omega = \bar{I}_2 \omega, \frac{m_1 v^2}{2} \omega = \left(\frac{m_1 r^2}{2} + \frac{m_2 r^2}{4} \right) \omega, \frac{m_1 v^2}{2} \omega = \frac{3}{4} \cdot \frac{1}{2} \omega^2, \omega = \frac{2}{3} \omega_0 = 1.2 \text{ rad/s}$$

$$\text{c) } m_2 \square, m=10 \text{ kg}, r=0.1 \text{ m}, M=0.2 \text{ kg}, \mu_1=5.88 \text{ Nm}, n_A=20 \text{ rev/s}, \Gamma=1.96 \text{ Nm}, \bar{I} = \frac{m r^2}{2} = I_A = I_B = 0.2 \text{ kg m}^2$$

$$I_A \alpha_A = M_A - M_{A0}, \alpha_A = 19.6 \text{ rad/s}, I_B \alpha_B = M_B - M_{B0}, \alpha_B = 9.8 \text{ rad/s}$$

$$20 \cdot 2\pi = \frac{1}{2} \alpha_A t^2, t = \sqrt{\frac{80\pi}{\alpha_A}} = 3.65 \text{ s}, L = M_A t = I \omega_A + I \omega_B$$

$$\text{Meff } I (\omega_A + \omega_B) \approx 40 \pi M_A = \frac{1}{2} I (\omega_A^2 + \omega_B^2) + 2\pi \nu_B (n_A - n_B) \text{ MATT}$$

$$80\pi M_A = I t^2 (\alpha_A^2 + \alpha_B^2) + 4\pi \nu_B M_{A0} n_A n_B = \frac{80\pi M_A}{I t^2} (\alpha_A^2 + \alpha_B^2) = 10, n_B = 10$$

$$m, r, M=3.6 \text{ Nm}, t_0=6.35, t'=10.55 \text{ s}, \omega_A(t') = \omega_B(t'), M(t_0, t_0) = 0$$

$$I_S \alpha_S = M - M_2, I_A \alpha_A = M_2, \omega_A(t_0) = \alpha_A t_0, \omega_B(t_0) = \alpha_B t_0, \alpha_A = \frac{\omega_A}{r}, \alpha_B = \frac{\omega_B}{r}$$

$$M_A t' \left(\frac{I_A + I_S}{I_A I_S} \right) = (\omega_{S0} - \omega_{A0}), \frac{I_A + I_S}{I_A I_S} = \frac{m r^2 + \frac{2}{5} m r^2}{\frac{2}{5} m r^2 r / 12} = \frac{7}{8} = \frac{7}{2 m r^2}, M_A = \frac{\omega_{S0} - \omega_{A0}}{7 t'^2}$$

$$M_A = \frac{2 m r^2 t_0}{7 t'} (\alpha_S - \alpha_A) = \frac{2 m r^2 t_0}{7 t'} \left(\frac{M - M_2}{M_2} - \frac{M_2}{m r^2} \right) = \frac{2 t_0}{7 t'} (5M - 5M_2 - 2M_2) = \frac{10}{7 t'} (5M - 7M_2)$$

$$M_A + \frac{t_0}{7 t'} M_A = \frac{5 t_0}{7 t'} M, M_A = \frac{5 t_0 M}{7 t' (1 + \frac{5}{7})} = \frac{5 t_0 M}{7 (t' + t_0)} = 2.3 \text{ Nm}, \omega_S = \omega_{S0} - \frac{M_2}{I_S} (t' - t_0)$$

$$\omega_S = 0, \alpha_S t_0 = \frac{M_2}{I_S}, \frac{M - M_2}{I_S} t_0 = \frac{M_2}{I_S} + t, t = 8.34 = t' + 4.14 \text{ s}, \rho_{PM} = \frac{1200 \cdot 2.7 \text{ rad/s}}{60} = 125.7 \text{ rad/s}$$

$$P_d = 7 \cdot 10^3 \text{ kg/m}^3, r_1 = 0.3, r_2 = 0.5, \text{ force } M_2 \cos \theta \omega_{20} = 1200, \text{ force } 2, M_1, M_2 = 0, M_2 \text{ opposite to } \omega_2 = 0, t_0 = 100 \text{ s}, \omega_2 = 0.2 \text{ rad/s}, t_0 = 100 \text{ s}, \omega_2 = 0.2 \text{ rad/s}$$

$$m_1 = P \cdot \pi r_1^2 d_1 = 1979 \text{ kg}, m_2 = P (\pi r_2^2 d_2 - \pi r_1^2 d_2) = 704 \text{ kg}, I_1 = \frac{1}{2} m_1 r_1^2 = 89.1 \text{ kg m}^2, I_2 = \frac{1}{2} P \pi d_2 (r_2^4 - r_1^4) = 119.6 \text{ kg m}^2$$

$$\text{I), } I_1 \alpha_1 = M_2 - M_1, I_2 \alpha_2 = M_1 - M_2, \text{ II), } \omega_{20} = \alpha_2 t_0, \alpha_2 = 1.26 \text{ rad/s}$$

$$\text{III), } I_2 \omega_{20} = (I_1 + I_2) \omega_1, \omega_1 = 72 \text{ rad/s}, \omega_{20} - \frac{M_2}{I_2} (t_0 - t) = \omega_1, M_2 = \frac{I_2 (\omega_{20} - \omega_1)}{t_0 - t_0} = 128.4 \text{ Nm} = M_2$$

$$M_1 = M_2 + I_1 \alpha_1 = 279.1 \text{ Nm}$$