Advanced Cybersecurity Topics


Returned Oriented Programming

19-20


Call Frame

	local vars {	
FRAME	saved EBP ->	
	saved EIP ->	
	argument ->	
	argument ->	
local vars {		
	saved EBP ->	
saved EIP -> argument ->		
	local vars $igg\{$	
	saved EBP ->	


- PUSH EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8




- PUSH EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8




- PUSH EAX
 - o SUB ESP, 0x4
 - MOV [ESP], EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8




- PUSH EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8




- PUSH EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8



- PUSH EAX
- PUSH EBX
- CALL
- ADD ESP, 0x8



- PUSH EAX
- PUSH EBX
- CALL FUN
 - PUSH EIP
 - JUMP FUN
- ADD ESP, 0x8




Fun

- RET
 - MOV RIP, [ESP]
 - o ADD ESP, 0x4
- After RET the caller clean the stack

	ptr to ADDESP
argument ->	Content of EBX
argument ->	Content of EAX
local vars ${ig\{}$	
saved EBP ->	
saved EIP ->	
argument ->	
local vars {	
saved EBP ->	

- PUSH EAX
- PUSH EBX
- CALL FUN
- ADD ESP, 0x8




- PUSH EAX
- PUSH EBX
- CALL FUN
- ADD ESP, 0x8

	ptr to ADDESP
argument ->	Content of EBX
argument ->	Content of EAX
local vars {	
saved EBP ->	
saved EIP ->	
argument ->	
local vars $igg\{$	
saved EBP ->	


Buffer overflow

Overwrite EIP and jump to a shellcode




Return to Function (LibC)

- Overwrite EIP and jump to a function
- Setup the arguments




Return to Function (LibC)

- Overwrite EIP and jump to a function
- Setup the arguments




Return to Function (LibC)

- Overwrite EIP and jump to a function
- Setup the arguments



Chain


- Overwrite EIP and jump to a function
- Setup the arguments
- Multiple times





Chain Functions (aka ROP)

- Overwrite EIP and jump to a function
- Setup the arguments
- Multiple times



Gadget


- Instructions followed by a ret
- or a int 0x80
- or a **syscall**

```
pop eax ; ret
pop ebp ; ret
```

pop edx ; pop eax ; ret

ROP 64-bit

- Arguments on regs
- Setup the arguments
- Cleaner Gadget become Setter



Weird Machines

- Vulnerabilities and abstractions create weird machines
 - ROP, etc.
- Writing an Exploit is Programming a Weird Machines. ~Sergey Bratus