

RISC-V REFERENCE

James Zhu <jameszhu@berkeley.edu>

RISC-V Instruction Set

Core Instruction Formats

| | | | | | | | | | | | | | | |
|-----------------------|----|----|----|-----|----|-----|----|--------|----|-------------|---|--------|---|--------|
| 31 | 27 | 26 | 25 | 24 | 20 | 19 | 15 | 14 | 12 | 11 | 7 | 6 | 0 | |
| funct7 | | | | rs2 | | rs1 | | funct3 | | rd | | opcode | | R-type |
| imm[11:0] | | | | | | rs1 | | funct3 | | rd | | opcode | | I-type |
| imm[11:5] | | | | rs2 | | rs1 | | funct3 | | imm[4:0] | | opcode | | S-type |
| imm[12 10:5] | | | | rs2 | | rs1 | | funct3 | | imm[4:1 11] | | opcode | | B-type |
| imm[31:12] | | | | | | | | | | rd | | opcode | | U-type |
| imm[20 10:1 11 19:12] | | | | | | | | | | rd | | opcode | | J-type |

RV32I Base Integer Instructions

| Inst | Name | FMT | Opcode | funct3 | funct7 | Description (C) | Note |
|--------|-------------------------|-----|---------|--------|--------|------------------------------|--------------|
| add | ADD | R | 0110011 | 0x0 | 0x00 | rd = rs1 + rs2 | |
| sub | SUB | R | 0110011 | 0x0 | 0x20 | rd = rs1 - rs2 | |
| xor | XOR | R | 0110011 | 0x4 | 0x00 | rd = rs1 ^ rs2 | |
| or | OR | R | 0110011 | 0x6 | 0x00 | rd = rs1 rs2 | |
| and | AND | R | 0110011 | 0x7 | 0x00 | rd = rs1 & rs2 | |
| sll | Shift Left Logical | R | 0110011 | 0x1 | 0x00 | rd = rs1 << rs2 | |
| srl | Shift Right Logical | R | 0110011 | 0x2 | 0x00 | rd = rs1 >> rs2 | |
| sra | Shift Right Arith* | R | 0110011 | 0x3 | 0x20 | rd = rs1 >> rs2 | msb-extends |
| slt | Set Less Than | R | 0110011 | 0x2 | | rd = (rs1 < rs2)?1:0 | |
| sltu | Set Less Than (U) | R | 0110011 | 0x3 | | rd = (rs1 < rs2)?1:0 | zero-extends |
| addi | ADD Immediate | I | 0010011 | 0x0 | 0x00 | rd = rs1 + imm | |
| xori | XOR Immediate | I | 0010011 | 0x4 | 0x00 | rd = rs1 ^ imm | |
| ori | OR Immediate | I | 0010011 | 0x6 | 0x00 | rd = rs1 imm | |
| andi | AND Immediate | I | 0010011 | 0x7 | 0x00 | rd = rs1 & imm | |
| slli | Shift Left Logical Imm | I | 0010011 | 0x1 | 0x00 | rd = rs1 << imm | |
| srlr | Shift Right Logical Imm | I | 0010011 | 0x1 | 0x00 | rd = rs1 >> imm | |
| srai | Shift Right Arith Imm | I | 0010011 | 0x3 | 0x20 | rd = rs1 >> imm | msb-extends |
| slti | Set Less Than Imm | I | 0010011 | 0x2 | | rd = (rs1 < imm)?1:0 | |
| sltiu | Set Less Than Imm (U) | I | 0010011 | 0x3 | | rd = (rs1 < imm)?1:0 | zero-extends |
| lb | Load Byte | I | 0000011 | 0x0 | | rd = M[rs1+imm][0:7] | |
| lh | Load Half | I | 0000011 | 0x1 | | rd = M[rs1+imm][0:15] | |
| lw | Load Word | I | 0000011 | 0x2 | | rd = M[rs1+imm][0:31] | |
| lbu | Load Byte (U) | I | 0000011 | 0x4 | | rd = M[rs1+imm][0:7] | zero-extends |
| lhu | Load Half (U) | I | 0000011 | 0x5 | | rd = M[rs1+imm][0:15] | zero-extends |
| sb | Store Byte | S | 0100011 | 0x0 | | M[rs1+imm][0:7] = rs2[0:7] | |
| sh | Store Half | S | 0100011 | 0x1 | | M[rs1+imm][0:15] = rs2[0:15] | |
| sw | Store Word | S | 0100011 | 0x2 | | M[rs1+imm][0:31] = rs2[0:31] | |
| beq | Branch == | B | 1100011 | 0x0 | | if(rs1 == rs2) PC += imm | |
| bne | Branch != | B | 1100011 | 0x1 | | if(rs1 != rs2) PC += imm | |
| blt | Branch < | B | 1100011 | 0x4 | | if(rs1 < rs2) PC += imm | |
| bge | Branch ≥ | B | 1100011 | 0x5 | | if(rs1 ≥ rs2) PC += imm | |
| bltu | Branch < (U) | B | 1100011 | 0x6 | | if(rs1 < rs2) PC += imm | zero-extends |
| bgeu | Branch ≥ (U) | B | 1100011 | 0x7 | | if(rs1 ≥ rs2) PC += imm | zero-extends |
| jal | Jump And Link | J | 1101111 | | | rd = PC+4; PC += imm | |
| jalr | Jump And Link Reg | I | 1100111 | 0x0 | | rd = PC+4; PC = rs1 + imm | |
| lui | Load Upper Imm | U | 0110111 | | | rd = imm << 12 | |
| auipc | Add Upper Imm to PC | U | 0010111 | | | rd = PC + (imm << 12) | |
| ecall | Environment Call | I | 1110011 | 0x0 | 0x00 | Transfer control to OS | imm: 0x000 |
| ebreak | Environment Break | I | 1110011 | 0x0 | 0x00 | Transfer control to debugger | imm: 0x001 |

Standard Extensions

RV32M Multiply Extension

| Inst | Name | FMT | Opcode | funct3 | funct7 | Description (C) |
|-------|------------------|-----|---------|--------|--------|-------------------------|
| mul | MUL | R | 0110011 | 0x0 | 0x01 | rd = (rs1 * rs2)[31:0] |
| mulh | MUL High | R | 0110011 | 0x1 | 0x01 | rd = (rs1 * rs2)[63:32] |
| mulsu | MUL High (S) (U) | R | 0110011 | 0x2 | 0x01 | rd = (rs1 * rs2)[63:32] |
| mulu | MUL High (U) | R | 0110011 | 0x3 | 0x01 | rd = (rs1 * rs2)[63:32] |
| div | DIV | R | 0110011 | 0x4 | 0x01 | rd = rs1 / rs2 |
| divu | DIV (U) | R | 0110011 | 0x5 | 0x01 | rd = rs1 / rs2 |
| rem | Remainder | R | 0110011 | 0x6 | 0x01 | rd = rs1 % rs2 |
| remu | Remainder (U) | R | 0110011 | 0x7 | 0x01 | rd = rs1 % rs2 |

RV32A Atomic Extension

| | | | | | | | | | | | | | | | | | | | | | | | |
|-----------|-------------------|----|--|----|----|-----|---------|--------|--------|---|----|--|--------|----|----|----|---|--------|---|---|--|--|--|
| 31 | | 27 | | 26 | 25 | | 24 | 20 | | 19 | 15 | | 14 | 12 | | 11 | 7 | | 6 | 0 | | | |
| funct5 | | | | aq | | rl | | rs2 | | rs1 | | | funct3 | | rd | | | opcode | | | | | |
| 5 | | | | 1 | | 1 | | 5 | | 5 | | | 3 | | 5 | | | 7 | | | | | |
| Inst | Name | | | | | FMT | Opcode | funct3 | funct5 | Description (C) | | | | | | | | | | | | | |
| lr.w | Load Reserved | | | | | R | 0101111 | 0x2 | 0x02 | rd = M[rs1], reserve M[rs1] | | | | | | | | | | | | | |
| sc.w | Store Conditional | | | | | R | 0101111 | 0x2 | 0x03 | if (reserved) { M[rs1] = rs2; rd = 0 } else { rd = 1 } | | | | | | | | | | | | | |
| amoswap.w | Atomic Swap | | | | | R | 0101111 | 0x2 | 0x01 | rd = M[rs1]; swap(rd, rs2); M[rs1] = rd | | | | | | | | | | | | | |
| amoadd.w | Atomic ADD | | | | | R | 0101111 | 0x2 | 0x00 | rd = M[rs1] + rs2; M[rs1] = rd | | | | | | | | | | | | | |
| amoand.w | Atomic AND | | | | | R | 0101111 | 0x2 | 0x0C | rd = M[rs1] & rs2; M[rs1] = rd | | | | | | | | | | | | | |
| amoor.w | Atomic OR | | | | | R | 0101111 | 0x2 | 0x0A | rd = M[rs1] rs2; M[rs1] = rd | | | | | | | | | | | | | |
| amoxor.w | Atomix XOR | | | | | R | 0101111 | 0x2 | 0x04 | rd = M[rs1] ^ rs2; M[rs1] = rd | | | | | | | | | | | | | |
| amomax.w | Atomic MAX | | | | | R | 0101111 | 0x2 | 0x14 | rd = max(M[rs1], rs2); M[rs1] = rd | | | | | | | | | | | | | |
| amomin.w | Atomic MIN | | | | | R | 0101111 | 0x2 | 0x10 | rd = min(M[rs1], rs2); M[rs1] = rd | | | | | | | | | | | | | |

RV32F Single-Precision Floating-Point Extension

| R4-type instructions | | | | | | | | |
|--|------------------------|-----|---------|-----------|---------|---------------|-----|---------------------------|
| <div> <div>31</div> <div>27 26 25 24 20 19</div> <div>15 14</div> <div>12 11</div> <div>7 6</div> <div>0</div> </div> | | | | | | | | |
| <div> <div>rs3</div> <div>fmt</div> <div>rs2</div> <div>rs1</div> <div>funct3</div> <div>rd</div> <div>opcode</div> </div> | | | | | | | | |
| <div> <div>5</div> <div>2</div> <div>5</div> <div>5</div> <div>3</div> <div>5</div> <div>7</div> </div> | | | | | | | | |
| Inst | Name | FMT | Opcode | funct3/rm | funct7 | rs2 [20...24] | fmt | Description (C) |
| f1w | Flt Load Word | I | 0000111 | 010 | | | | rd = M[rs1 + imm] |
| fsw | Flt Store Word | I | 0100111 | 010 | | | | M[rs1 + imm] = rs2 |
| fadd.s | Flt Add | R | 1010011 | | 0000000 | | | rd = rs1 + rs2 |
| fsub.s | Flt Sub | R | 1010011 | | 0000100 | | | rd = rs1 - rs2 |
| fmul.s | Flt Mul | R | 1010011 | | 0001000 | | | rd = rs1 * rs2 |
| fdiv.s | Flt Div | R | 1010011 | | 0001100 | | | rd = rs1 / rs2 |
| fsgnj.s | Flt Sign Injection | R | 1010011 | 000 | 0010000 | | | rd = abs(rs1) * sgn(rs2) |
| fsgnjn.s | Flt Sign Neg Injection | R | 1010011 | 001 | 0010000 | | | rd = abs(rs1) * -sgn(rs2) |
| fsgnjx.s | Flt Sign Xor Injection | R | 1010011 | 010 | 0010000 | | | rd = rs1 * sgn(rs2) |
| fmin.s | Flt Minimum | R | 1010011 | | 0010100 | | | rd = min(rs1, rs2) |
| fmax.s | Flt Maximum | R | 1010011 | | 0010100 | | | rd = max(rs1, rs2) |
| fsqrt.s | Flt Square Root | R | 1010011 | | 0101100 | 00000 | | rd = sqrt(rs1) |
| fle.s | Float Less / Equal | R | 1010011 | 000 | 1010000 | | | rd = (rs1 <= rs2) ? 1 : 0 |
| flt.s | Float Less Than | R | 1010011 | 001 | 1010000 | | | rd = (rs1 < rs2) ? 1 : 0 |
| feq.s | Float Equality | R | 1010011 | 010 | 1010000 | | | rd = (rs1 == rs2) ? 1 : 0 |
| fcvt.w.s | Flt Convert to Int | R | 1010011 | | 1100000 | 00000 | | rd = (int32_t) rs1 |
| fcvt.wu.s | Flt Convert to Int | R | 1010011 | | 1100000 | 00001 | | rd = (uint32_t) rs1 |
| fmv.x.w | Move Float to Int | R | 1010011 | 000 | 1110000 | 00000 | | rd = *((int*) &rs1) |
| fclass.s | Float Classify | R | 1010011 | 001 | 1110000 | 00000 | | rd = 0..9 |
| fcvt.s.w | Flt Conv from Sign Int | R | 1010011 | | 1101000 | 00000 | | rd = (float) rs1 |
| fcvt.s.wu | Flt Conv from Uns Int | R | 1010011 | | 1101000 | 00001 | | rd = (float) rs1 |
| fmv.w.x | Move Int to Float | R | 1010011 | 000 | 1111000 | 00000 | | rd = *((float*) &rs1) |
| fmadd.s | Flt Fused Mul-Add | R4 | 1000011 | | | | 00 | rd = rs1 * rs2 + rs3 |
| fmsub.s | Flt Fused Mul-Sub | R4 | 1000111 | | | | 00 | rd = rs1 * rs2 - rs3 |
| fnmadd.s | Flt Neg Fused Mul-Add | R4 | 1001011 | | | | 00 | rd = -rs1 * rs2 + rs3 |
| fnmsub.s | Flt Neg Fused Mul-Sub | R4 | 1001111 | | | | 00 | rd = -rs1 * rs2 - rs3 |

RV32D Double-Precision Floating-Point Extension

| Inst | Name | FMT | Opcode | funct3/rm | funct7 | rs2 [20...24] | fmt | Description (C) |
|-----------|------------------------|-----|---------|-----------|---------|---------------|-----|---------------------------|
| fld | Flt Load Word | I | 0000111 | 011 | | | | rd = M[rs1 + imm] |
| fsd | Flt Store Word | I | 0100111 | 011 | | | | M[rs1 + imm] = rs2 |
| fadd.d | Flt Add | R | 1010011 | | 0000001 | | | rd = rs1 + rs2 |
| fsub.d | Flt Sub | R | 1010011 | | 0000101 | | | rd = rs1 - rs2 |
| fmul.d | Flt Mul | R | 1010011 | | 0001001 | | | rd = rs1 * rs2 |
| fdiv.d | Flt Div | R | 1010011 | | 0001101 | | | rd = rs1 / rs2 |
| fsgnj.d | Flt Sign Injection | R | 1010011 | 000 | 0010001 | | | rd = abs(rs1) * sgn(rs2) |
| fsgnjn.d | Flt Sign Neg Injection | R | 1010011 | 001 | 0010001 | | | rd = abs(rs1) * -sgn(rs2) |
| fsgnjx.d | Flt Sign Xor Injection | R | 1010011 | 010 | 0010001 | | | rd = rs1 * sgn(rs2) |
| fmin.d | Flt Minimum | R | 1010011 | | 0010101 | | | rd = min(rs1, rs2) |
| fmax.d | Flt Maximum | R | 1010011 | | 0010101 | | | rd = max(rs1, rs2) |
| fsqrt.d | Flt Square Root | R | 1010011 | | 0101101 | 00000 | | rd = sqrt(rs1) |
| fle.d | Float Less / Equal | R | 1010011 | 000 | 1010001 | | | rd = (rs1 <= rs2) ? 1 : 0 |
| flt.d | Float Less Than | R | 1010011 | 001 | 1010001 | | | rd = (rs1 < rs2) ? 1 : 0 |
| feq.d | Float Equality | R | 1010011 | 010 | 1010001 | | | rd = (rs1 == rs2) ? 1 : 0 |
| fcvt.w.d | Flt Convert to Int | R | 1010011 | | 1100001 | 00000 | | rd = (int32_t) rs1 |
| fcvt.wu.d | Flt Convert to Int | R | 1010011 | | 1100001 | 00001 | | rd = (uint32_t) rs1 |
| fcvt.s.d | Double Flt to Single | R | 1010011 | 000 | 0100000 | 00001 | | rd = *((float*) &rs1) |
| fmv.x.d | Move Int to Float | R | 1010011 | 000 | 1111001 | 00000 | | rd = *((float*) &rs1) |
| fclass.d | Float Classify | R | 1010011 | 001 | 1110001 | 00000 | | rd = 0..9 |
| fcvt.d.w | Flt Conv from Sign Int | R | 1010011 | | 1101001 | 00000 | | rd = (float) rs1 |
| fcvt.d.wu | Flt Conv from Uns Int | R | 1010011 | | 1101001 | 00001 | | rd = (float) rs1 |
| fcvt.d.s | Single Flt to Double | R | 1010011 | 000 | 0100001 | 00001 | | rd = *((float*) &rs1) |
| fmadd.d | Flt Fused Mul-Add | R4 | 1000011 | | | | 01 | rd = rs1 * rs2 + rs3 |
| fmsub.d | Flt Fused Mul-Sub | R4 | 1000111 | | | | 01 | rd = rs1 * rs2 - rs3 |
| fnmadd.d | Flt Neg Fused Mul-Add | R4 | 1001011 | | | | 01 | rd = -rs1 * rs2 + rs3 |
| fnmsub.d | Flt Neg Fused Mul-Sub | R4 | 1001111 | | | | 01 | rd = -rs1 * rs2 - rs3 |

RV32Q Quad-Precision Floating-Point Extension

| Inst | Name | FMT | Opcode | funct3/rm | funct7 | rs2 [20...24] | fmt | Description (C) |
|-----------|------------------------|-----|---------|-----------|---------|---------------|-----|---------------------------|
| f1q | Flt Load Word | I | 0000111 | 100 | | | | rd = M[rs1 + imm] |
| fsq | Flt Store Word | I | 0100111 | 100 | | | | M[rs1 + imm] = rs2 |
| fadd.q | Flt Add | R | 1010011 | | 0000011 | | | rd = rs1 + rs2 |
| fsub.q | Flt Sub | R | 1010011 | | 0000111 | | | rd = rs1 - rs2 |
| fmul.q | Flt Mul | R | 1010011 | | 0001011 | | | rd = rs1 * rs2 |
| fdiv.q | Flt Div | R | 1010011 | | 0001111 | | | rd = rs1 / rs2 |
| fsgnj.q | Flt Sign Injection | R | 1010011 | 000 | 0010011 | | | rd = abs(rs1) * sgn(rs2) |
| fsgnjn.q | Flt Sign Neg Injection | R | 1010011 | 001 | 0010011 | | | rd = abs(rs1) * -sgn(rs2) |
| fsgnjx.q | Flt Sign Xor Injection | R | 1010011 | 010 | 0010011 | | | rd = rs1 * sgn(rs2) |
| fmin.q | Flt Minimum | R | 1010011 | | 0010111 | | | rd = min(rs1, rs2) |
| fmax.q | Flt Maximum | R | 1010011 | | 0010111 | | | rd = max(rs1, rs2) |
| fsqrt.q | Flt Square Root | R | 1010011 | | 0101111 | 00000 | | rd = sqrt(rs1) |
| fle.q | Float Less / Equal | R | 1010011 | 000 | 1010011 | | | rd = (rs1 <= rs2) ? 1 : 0 |
| flt.q | Float Less Than | R | 1010011 | 001 | 1010011 | | | rd = (rs1 < rs2) ? 1 : 0 |
| feq.q | Float Equality | R | 1010011 | 010 | 1010011 | | | rd = (rs1 == rs2) ? 1 : 0 |
| fcvt.w.q | Flt Convert to Int | R | 1010011 | | 1100011 | 00000 | | rd = (int32_t) rs1 |
| fcvt.wu.q | Flt Convert to Int | R | 1010011 | | 1100011 | 00001 | | rd = (uint32_t) rs1 |
| fcvt.s.q | Quad Flt to Single | R | 1010011 | 000 | 0100000 | 00001 | | rd = *((float*) &rs1) |
| fcvt.d.q | Quad Flt to Double | R | 1010011 | 000 | 0100001 | 00001 | | rd = *((float*) &rs1) |
| fmv.x.q | Move Int to Float | R | 1010011 | 000 | 1111011 | 00000 | | rd = *((float*) &rs1) |
| fclass.q | Float Classify | R | 1010011 | 001 | 1110011 | 00000 | | rd = 0..9 |
| fcvt.q.w | Flt Conv from Sign Int | R | 1010011 | | 1101011 | 00000 | | rd = (float) rs1 |
| fcvt.q.wu | Flt Conv from Uns Int | R | 1010011 | | 1101011 | 00001 | | rd = (float) rs1 |
| fcvt.q.s | Single Flt to Quad | R | 1010011 | 000 | 0100011 | 00000 | | rd = *((float*) &rs1) |
| fcvt.q.d | Double Flt to Quad | R | 1010011 | 000 | 0100011 | 00001 | | rd = *((float*) &rs1) |
| fmadd.q | Flt Fused Mul-Add | R4 | 1000011 | | | | 11 | rd = rs1 * rs2 + rs3 |
| fmsub.q | Flt Fused Mul-Sub | R4 | 1000111 | | | | 11 | rd = rs1 * rs2 - rs3 |
| fnmadd.q | Flt Neg Fused Mul-Add | R4 | 1001011 | | | | 11 | rd = -rs1 * rs2 + rs3 |
| fnmsub.q | Flt Neg Fused Mul-Sub | R4 | 1001111 | | | | 11 | rd = -rs1 * rs2 - rs3 |

RV32C Compressed Extension

| | | | | | | | | | | | | | | | | |
|--------|----|--------|--------|----------|----|-----|-----|------|---|---------|----|---------|---------|----------|---|--|
| 15 | 14 | 13 | 12 | 11 | 10 | 9 | 8 | 7 | 6 | 5 | 4 | 3 | 2 | 1 | 0 | |
| funct4 | | | | rd/rs1 | | | | rs2 | | | | op | | CR-type | | |
| funct3 | | imm | rd/rs1 | | | | imm | | | | op | | CI-type | | | |
| funct3 | | imm | | | | | | rs2 | | | | op | | CSS-type | | |
| funct3 | | imm | | | | | | | | rd' | | op | | CIW-type | | |
| funct3 | | imm | | rs1' | | imm | | rd' | | op | | CL-type | | | | |
| funct3 | | imm | | rd'/rs1' | | imm | | rs2' | | op | | CS-type | | | | |
| funct3 | | imm | | rs1' | | imm | | op | | CB-type | | | | | | |
| funct3 | | offset | | | | | | | | | | op | | CJ-type | | |

| Inst | Name | FMT | OP | Funct | Description |
|------------|-------------------------|-----|----|----------|------------------------|
| c.lwsp | Load Word from SP | CI | 10 | 010 | lw rd, (4*imm)(sp) |
| c.swsp | Store Word to SP | CSS | 10 | 110 | sw rs2, (4*imm)(sp) |
| c.lw | Load Word | CL | 00 | 010 | lw rd', (4*imm)(rs1') |
| c.sw | Store Word | CS | 00 | 110 | sw rs1', (4*imm)(rs2') |
| c.j | Jump | CJ | 01 | 101 | jal x0, 2*offset |
| c.jal | Jump And Link | CJ | 01 | 001 | jal ra, 2*offset |
| c.jr | Jump Reg | CR | 10 | 1000 | jalr x0, rs1, 0 |
| c.jalr | Jump And Link Reg | CR | 10 | 1001 | jalr ra, rs1, 0 |
| c.beqz | Branch == 0 | CB | 01 | 110 | beq rs', x0, 2*imm |
| c.bnez | Branch != 0 | CB | 01 | 111 | bne rs', x0, 2*imm |
| c.li | Load Immediate | CI | 01 | 010 | addi rd, x0, imm |
| c.lui | Load Upper Imm | CI | 01 | 011 | lui rd, imm |
| c.addi | ADD Immediate | CI | 01 | 000 | addi rd, rd, imm |
| c.addi16sp | ADD Imm * 16 to SP | CI | 01 | 011 | addi sp, sp, 16*imm |
| c.addi4spn | ADD Imm * 4 + SP | CIW | 00 | 000 | addi rd', sp, 4*imm |
| c.slli | Shift Left Logical Imm | CI | 10 | 000 | slli rd, rd, imm |
| c.srli | Shift Right Logical Imm | CB | 01 | 100x00 | srli rd', rd', imm |
| c.srai | Shift Right Arith Imm | CB | 01 | 100x01 | srai rd', rd', imm |
| c.andi | AND Imm | CB | 01 | 100x10 | andi rd', rd', imm |
| c.mv | MoVe | CR | 10 | 1000 | add rd, x0, rs2 |
| c.add | ADD | CR | 10 | 1001 | add rd, rd, rs2 |
| c.and | AND | CS | 01 | 10001111 | and rd', rd', rs2' |
| c.or | OR | CS | 01 | 10001110 | or rd', rd', rs2' |
| c.xor | XOR | CS | 01 | 10001101 | xor rd', rd', rs2' |
| c.sub | SUB | CS | 01 | 10001100 | sub rd', rd', rs2' |
| c.nop | No OPeration | CI | 01 | 000 | addi x0, x0, 0 |
| c.ebreak | Environment BREAK | CR | 10 | 1001 | ebreak |

Pseudo Instructions

| Pseudoinstruction | Base Instruction(s) | Meaning |
|---------------------------|--|---------------------------------|
| la rd, symbol | auipc rd, symbol[31:12] addi rd, rd, symbol[11:0] | Load address |
| l{b h w d} rd, symbol | auipc rd, symbol[31:12] l{b h w d} rd, symbol[11:0](rd) | Load global |
| s{b h w d} rd, symbol, rt | auipc rt, symbol[31:12] s{b h w d} rd, symbol[11:0](rt) | Store global |
| fl{w d} rd, symbol, rt | auipc rt, symbol[31:12] fl{w d} rd, symbol[11:0](rt) | Floating-point load global |
| fs{w d} rd, symbol, rt | auipc rt, symbol[31:12] fs{w d} rd, symbol[11:0](rt) | Floating-point store global |
| nop | addi x0, x0, 0 | No operation |
| li rd, immediate | <i>Myriad sequences</i> | Load immediate |
| mv rd, rs | addi rd, rs, 0 | Copy register |
| not rd, rs | xori rd, rs, -1 | One's complement |
| neg rd, rs | sub rd, x0, rs | Two's complement |
| negw rd, rs | subw rd, x0, rs | Two's complement word |
| sext.w rd, rs | addiw rd, rs, 0 | Sign extend word |
| seqz rd, rs | sltiu rd, rs, 1 | Set if = zero |
| snez rd, rs | sltu rd, x0, rs | Set if \neq zero |
| sltz rd, rs | slt rd, rs, x0 | Set if < zero |
| sgtz rd, rs | slt rd, x0, rs | Set if > zero |
| fmv.s rd, rs | fsgnj.s rd, rs, rs | Copy single-precision register |
| fabs.s rd, rs | fsgnjx.s rd, rs, rs | Single-precision absolute value |
| fneg.s rd, rs | fsgnjn.s rd, rs, rs | Single-precision negate |
| fmv.d rd, rs | fsgnj.d rd, rs, rs | Copy double-precision register |
| fabs.d rd, rs | fsgnjx.d rd, rs, rs | Double-precision absolute value |
| fneg.d rd, rs | fsgnjd.d rd, rs, rs | Double-precision negate |
| beqz rs, offset | beq rs, x0, offset | Branch if = zero |
| bnez rs, offset | bne rs, x0, offset | Branch if \neq zero |
| blez rs, offset | bge x0, rs, offset | Branch if \leq zero |
| bgez rs, offset | bge rs, x0, offset | Branch if \geq zero |
| bltz rs, offset | blt rs, x0, offset | Branch if < zero |
| bgtz rs, offset | blt x0, rs, offset | Branch if > zero |
| bgt rs, rt, offset | blt rt, rs, offset | Branch if > |
| ble rs, rt, offset | bge rt, rs, offset | Branch if \leq |
| bgtu rs, rt, offset | bltu rt, rs, offset | Branch if >, unsigned |
| bleu rs, rt, offset | bgeu rt, rs, offset | Branch if \leq , unsigned |
| j offset | jal x0, offset | Jump |
| jal offset | jal x1, offset | Jump and link |
| jr rs | jalr x0, rs, 0 | Jump register |
| jalr rs | jalr x1, rs, 0 | Jump and link register |
| ret | jalr x0, x1, 0 | Return from subroutine |
| call offset | auipc x1, offset[31:12] jalr x1, x1, offset[11:0] | Call far-away subroutine |
| tail offset | auipc x6, offset[31:12] jalr x0, x6, offset[11:0] | Tail call far-away subroutine |
| fence | fence iorw, iorw | Fence on all memory and I/O |

Registers

| Register | ABI Name | Description | Saver |
|----------|----------|-----------------------|--------|
| x0 | zero | Zero constant | — |
| x1 | ra | Return address | Caller |
| x2 | sp | Stack pointer | — |
| x3 | gp | Global pointer | — |
| x4 | tp | Thread pointer | Callee |
| x5 | t0-t2 | Temporaries | Caller |
| x8 | s0 / fp | Saved / frame pointer | Callee |
| x9 | s1 | Saved register | Callee |
| x10-x11 | a0-a1 | Fn args/return values | Caller |
| x12-x17 | a2-a7 | Fn args | Caller |
| x18-x27 | s2-s11 | Saved registers | Callee |
| x28-x31 | t3-t6 | Temporaries | Caller |
| f0-7 | ft0-7 | FP temporaries | Caller |
| f8-9 | fs0-1 | FP saved registers | Callee |
| f10-11 | fa0-1 | FP args/return values | Caller |
| f12-17 | fa2-7 | FP args | Caller |
| f18-27 | fs2-11 | FP saved registers | Callee |
| f28-31 | ft8-11 | FP temporaries | Caller |