

# Scale Features and Build Model

## Scales Raw Features

Import CSV of Aggregated Darshan Logs

Apply Log10 and Percent Scaling

```
In [1]: import os
import pandas as pd
import numpy as np
import math
import matplotlib.pyplot as plt
import random

from sklearn.preprocessing import StandardScaler
from sklearn.model_selection import train_test_split
```

```
In [2]: df = pd.read_csv("./raws.csv",lineterminator='\n',sep = ',' ,error_bad_line
#df.mean())
```

```
In [3]: df = df.drop(df.columns[0],axis = 1)
df = df.drop(df.columns[0],axis = 1)
f = pd.DataFrame()
```

```
In [4]: df
```

Out[4]:

	posix_read_time	posix_write_time	posix_meta_time	posix_bytes_read	posix_bytes_read_100
0	0.000000	0.000000	0.000000	0.000000e+00	0.0
1	104.611641	10.024055	20.060841	2.390891e+10	147688.0
2	124.560730	42.051125	54.839272	5.019637e+10	332059.0
3	25763.292969	582.297363	24.895737	5.488943e+12	30785.0
4	154.534821	681.548279	658.484985	2.293203e+10	588029.0
...	...	...	...	...	...
875282	138.354477	82.278084	194.485565	5.593977e+10	216146.0
875283	54.443073	231.440857	25.271391	1.465277e+09	3099.0
875284	0.000000	0.000000	0.000000	0.000000e+00	0.0
875285	0.000000	0.000000	0.000000	0.000000e+00	0.0
875286	227.063828	191.747269	172.671997	1.077412e+11	775359.0

875287 rows × 50 columns

In [5]:

```
df = df.dropna(axis=0, how='any')
df.columns
```

```
Out[5]: Index(['posix_read_time', 'posix_write_time', 'posix_meta_time',
              'posix_bytes_read', 'posix_bytes_read_100', 'posix_bytes_read_1K',
              'posix_bytes_read_10K', 'posix_bytes_read_100K', 'posix_bytes_read_
              _11M', 'posix_bytes_read_4M', 'posix_bytes_read_10M', 'posix_bytes_read_1
              00M', 'posix_bytes_read_1G', 'posix_bytes_read_PLUS', 'posix_bytes_writ
              e', 'posix_bytes_write_100', 'posix_bytes_write_1K',
              'posix_bytes_write_10K', 'posix_bytes_write_100K',
              'posix_bytes_write_1M', 'posix_bytes_write_4M', 'posix_bytes_write_
              _10M', 'posix_bytes_write_100M', 'posix_bytes_write_1G',
              'posix_bytes_write_PLUS', 'posix_opens', 'posix_reads', 'posix_writ
              es', 'posix_seeks', 'posix_stats', 'posix_mmaps', 'posix_fsyncs',
              'posix_fdsyncs', 'posix_rename_sources', 'posix_rename_targets',
              'posix_renamed_from', 'posix_renamed_mode', 'posix_number_of_file
              s', 'nprocs', 'posix_f_align', 'posix_m_align', 'lustre_number_of_file
              s', 'lustre_mdts', 'lustre_osts', 'lustre_stripe_size',
              'lustre_stripe_offset', 'lustre_stripe_width', 'lustre_number_of_o
              sts', 'jobid', 'path'],
              dtype='object')
```

In [6]: #files

```
f['log10_p_files'] = df['posix_number_of_files']
f['log10_l_files'] = df['lustre_number_of_files']
```

In [7]: #accesses

```
df['p_accesses'] = df['posix_reads'] + df['posix_writes']
f['log10_p_accesses'] = df['p_accesses']

f['log10_p_accesses']
```

```
Out[7]: 0          0.0
1      880136.0
2     2379598.0
3     8903411.0
4     7846387.0
...
875282    2234152.0
875283    197651.0
875284         0.0
875285         0.0
875286    6065006.0
Name: log10_p_accesses, Length: 875287, dtype: float64
```

```
In [8]: #bytes
f['log10_p_bytes'] = df['posix_bytes_read']
```

```
In [9]: f['log10_p_opens'] = df['posix_opens']
f['log10_p_seeks'] = df['posix_seeks']
f['log10_p_stats'] = df['posix_stats']
f['log10_p_mode'] = df['posix_renamed_mode']
```

```
In [10]: f['log10_l_n_osts'] = df['lustre_number_of_osts']
f['log10_l_stripe_w'] = df['lustre_stripe_width']
f['log10_l_mdts'] = df['lustre_mdts']
```

```
In [11]: f['log10_p_nprocs'] = df['nprocs']
f['log10_p_falign'] = df['posix_f_align']
f['log10_p_malign'] = df['posix_m_align']
```

```
In [12]: f['perc_p_reads'] = df['posix_reads']
f['perc_p_writes'] = df['posix_writes']
```

```
In [13]: f['perc_p_bytes_read_100'] = df['posix_bytes_read_100']
f['perc_p_bytes_read_1K'] = df['posix_bytes_read_1K']
f['perc_p_bytes_read_10K'] = df['posix_bytes_read_10K']
f['perc_p_bytes_read_100K'] = df['posix_bytes_read_100K']
f['perc_p_bytes_read_1M'] = df['posix_bytes_read_1M']
f['perc_p_bytes_read_4M'] = df['posix_bytes_read_4M']
f['perc_p_bytes_read_10M'] = df['posix_bytes_read_10M']
f['perc_p_bytes_read_100M'] = df['posix_bytes_read_100M']
f['perc_p_bytes_read_1G'] = df['posix_bytes_read_1G']
f['perc_p_bytes_read_PLUS'] = df['posix_bytes_read_PLUS']
```

```
In [14]: f['perc_p_bytes_write_100'] = df['posix_bytes_write_100']
f['perc_p_bytes_write_1K'] = df['posix_bytes_write_1K']
f['perc_p_bytes_write_10K'] = df['posix_bytes_write_10K']
f['perc_p_bytes_write_100K'] = df['posix_bytes_write_100K']
f['perc_p_bytes_write_1M'] = df['posix_bytes_write_1M']
f['perc_p_bytes_write_4M'] = df['posix_bytes_write_4M']
f['perc_p_bytes_write_10M'] = df['posix_bytes_write_10M']
f['perc_p_bytes_write_100M'] = df['posix_bytes_write_100M']
f['perc_p_bytes_write_1G'] = df['posix_bytes_write_1G']
f['perc_p_bytes_write_PLUS'] = df['posix_bytes_write_PLUS']
```

```
f = f.replace(-np.inf, -1)
f = f.replace(np.nan, 0)
```

```
In [15]: df['time'] = df['posix_write_time'].astype('float') + df['posix_read_time']
```

```
In [16]: df['bytes'] = df['posix_bytes_read'].astype('float') + df['posix_bytes_writ
```

```
In [17]: df = df[df['bytes'] > 9999999999]
```

In [18]:

```
f['throughput'] = df['bytes'].astype('float') / df['time']

f = f[f['throughput'] > 0]
```

In [19]:

```
#delete columns with all zeros
f = f.loc[:, (f != 0).any(axis=0)]

#remove infinite values
f = f.replace([np.inf, -np.inf], np.nan).dropna(axis=0)

f.max()
```

Out[19]:

```
log10_p_files          1.219270e+05
log10_l_files          1.219270e+05
log10_p_accesses      2.251942e+10
log10_p_bytes         3.038456e+14
log10_p_opens         5.531094e+08
log10_p_seeks         1.445220e+10
log10_p_stats         6.522921e+07
log10_p_mode          5.337293e+07
log10_l_n_osts        3.600000e+02
log10_l_stripe_w      3.718294e+06
log10_l_mdts         1.000000e+00
log10_p_nprocs        1.106880e+05
log10_p_falign        1.414592e+11
log10_p_malign        1.079248e+06
perc_p_reads          2.237846e+10
perc_p_writes          1.302770e+10
perc_p_bytes_read_100 5.221517e+08
perc_p_bytes_read_1K  2.074657e+10
perc_p_bytes_read_10K 1.536278e+09
perc_p_bytes_read_100K 1.515506e+08
perc_p_bytes_read_1M  4.044503e+08
perc_p_bytes_read_4M  6.561462e+07
perc_p_bytes_read_10M 2.083200e+06
perc_p_bytes_read_100M 2.872090e+05
perc_p_bytes_read_1G  1.792000e+06
perc_p_bytes_write_100 1.302770e+10
perc_p_bytes_write_1K 2.852127e+09
perc_p_bytes_write_10K 3.867477e+08
perc_p_bytes_write_100K 8.347452e+07
perc_p_bytes_write_1M 1.357245e+07
perc_p_bytes_write_4M 3.839488e+06
perc_p_bytes_write_10M 6.190660e+05
perc_p_bytes_write_100M 1.249280e+06
perc_p_bytes_write_1G 1.937500e+04
throughput            2.344536e+09
dtype: float64
```

```
In [20]: t = pd.DataFrame()
t['throughput'] = f['throughput']
f = f.drop(labels = 'throughput', axis = 1)
f
```

Out[20]:

	log10_p_files	log10_l_files	log10_p_accesses	log10_p_bytes	log10_p_opens	log10_p_seeks
<b>1</b>	799.0	176.0	880136.0	2.390891e+10	8858.0	319241.0
<b>2</b>	360.0	224.0	2379598.0	5.019637e+10	62398.0	1107764.0
<b>3</b>	290.0	290.0	8903411.0	5.488943e+12	8711.0	2010273.0
<b>4</b>	319.0	201.0	7846387.0	2.293203e+10	23158.0	6015926.0
<b>6</b>	428.0	190.0	6647935.0	5.209185e+10	69261.0	4608438.0
...	...	...	...	...	...	...
<b>875275</b>	358.0	251.0	2241175.0	9.369952e+09	13700.0	1579710.0
<b>875276</b>	288.0	288.0	7814478.0	5.522966e+12	8709.0	2067127.0
<b>875280</b>	1.0	1.0	57344.0	3.006477e+10	1808.0	59128.0
<b>875282</b>	624.0	124.0	2234152.0	5.593977e+10	35112.0	1035457.0
<b>875286</b>	582.0	128.0	6065006.0	1.077412e+11	119432.0	2750807.0

367631 rows × 34 columns

```
In [21]: df = df[df.index.isin(t.index)]
t = t.reset_index()
f = f.reset_index()
f = f.drop(f.columns[0], axis = 1)
t = t.drop(t.columns[0], axis = 1)
```

```
In [22]: f = StandardScaler().fit_transform(f)
```

```
In [23]: t
```

```
Out[23]:
```

	throughput
0	1.803194e+08
1	2.282342e+08
2	2.083669e+08
3	1.724841e+07
4	4.581690e+07
...	...
367626	3.614622e+07
367627	2.073475e+08
367628	5.482767e+08
367629	1.362498e+08
367630	1.842942e+08

367631 rows × 1 columns

```
In [24]: print(t.min())
print(t.max())
```

```
throughput      1347.758654
dtype: float64
throughput      2.344536e+09
dtype: float64
```

```
In [25]: rseed = 0
t_size = 0.1
```

```
In [26]: from sklearn.metrics import r2_score
from sklearn.metrics import mean_squared_error
from sklearn.metrics import mean_absolute_error
from sklearn.metrics import mean_squared_log_error
from sklearn.metrics import mean_absolute_percentage_error
```

```
In [27]: from sklearn.linear_model import LinearRegression
for i in range(3):

    rseed = random.randint(1,10000)
    print(rseed)
    train_data, test_data, train_labels, test_labels = train_test_split(f,t

    reg = LinearRegression().fit(train_data, train_labels)

    predicted_labels = reg.predict(test_data)

    print("Mean True Value: \t",int(test_labels.mean() ))
    print("Mean Absolute Error: \t", int(mean_absolute_error(test_labels, p
    print("Mean Squared Error: ", mean_squared_error(test_labels, predicted
    print("Root Mean Squared Error: ", mean_squared_error(test_labels, pred
    print("MAPE : " + str(mean_absolute_percentage_error( test_labels, predi
    print("R2: " + str(r2_score(test_labels,predicted_labels)) + "\n")
```

6948

Mean True Value: 128424644  
Mean Absolute Error: 63933540  
Mean Squared Error: 9882209768047526.0  
Root Mean Squared Error: 99409304.23279063  
MAPE :23.41393187869545  
R2: 0.30904583916905504

9866

Mean True Value: 128952961  
Mean Absolute Error: 63689784  
Mean Squared Error: 9857616847277842.0  
Root Mean Squared Error: 99285531.9131536  
MAPE :18.397959972240464  
R2: 0.3114636461788841

2304

Mean True Value: 128834304  
Mean Absolute Error: 63647197  
Mean Squared Error: 1.1106494673390154e+16  
Root Mean Squared Error: 105387355.37715212  
MAPE :30.711675225455277  
R2: 0.23529938494322822

```
In [28]: import xgboost as xg
```

In [29]: *#EXTREME GRADIENT BOOST*

```

for i in range(3):
    rseed = random.randint(1,10000)
    print(rseed)

    train_data, test_data, train_labels, test_labels = train_test_split(f,t
    xgb_r = xg.XGBRegressor(n_estimators = 1000, seed = 123)
    xgb_r.fit(train_data, train_labels)
    predicted_labels = xgb_r.predict(test_data)

    print("Mean True Value: \t",int(test_labels.mean() ))
    print("Mean Absolute Error: \t", int(mean_absolute_error(test_labels, p
    print("Mean Squared Error: ", mean_squared_error(test_labels, predicted
    print("Root Mean Squared Error: ", mean_squared_error(test_labels, pred
    print("MAPE : " + str(mean_absolute_percentage_error( test_labels, predi
    print("R2: " + str(r2_score(test_labels,predicted_labels)) + "\n")

```

9599

```

Mean True Value:          128121664
Mean Absolute Error:      24752332
Mean Squared Error:      2067481876076148.0
Root Mean Squared Error:  45469570.880712606
MAPE :1.063409954385179
R2: 0.8533375369184322

```

4383

```

Mean True Value:          128437506
Mean Absolute Error:      24556168
Mean Squared Error:      1925905003584448.0
Root Mean Squared Error:  43885134.1980909
MAPE :1.2918286088874988
R2: 0.8672105067337241

```

5344

```

Mean True Value:          128144355
Mean Absolute Error:      24750720
Mean Squared Error:      1935684984741891.0
Root Mean Squared Error:  43996420.13552797
MAPE :0.9433847550892414
R2: 0.8629954914666573

```

In [ ]:



```
In [30]: from sklearn.tree import DecisionTreeRegressor

for i in range(3):
    rseed = random.randint(1,10000)
    print(rseed)

    train_data, test_data, train_labels, test_labels = train_test_split(f,t

    reg = DecisionTreeRegressor(max_depth = 4)

    reg.fit(train_data, train_labels)
    predicted_labels = reg.predict(test_data)

    print("Mean True Value: \t",int(test_labels.mean() ))
    print("Mean Absolute Error: \t", int(mean_absolute_error(test_labels, p
    print("Mean Squared Error: ", mean_squared_error(test_labels, predicted
    print("Root Mean Squared Error: ", mean_squared_error(test_labels, pred
    print("MAPE : " + str(mean_absolute_percentage_error( test_labels, predi
    print("R2: " + str(r2_score(test_labels,predicted_labels)) + "\n")
```

6057

Mean True Value: 128743819  
Mean Absolute Error: 36491635  
Mean Squared Error: 3825263460730505.5  
Root Mean Squared Error: 61848714.301353954  
MAPE :9.10759222985107  
R2: 0.7344798040096301

165

Mean True Value: 129363113  
Mean Absolute Error: 37004128  
Mean Squared Error: 3896705567691740.0  
Root Mean Squared Error: 62423597.84321743  
MAPE :10.768492009710119  
R2: 0.7227367946018776

279

Mean True Value: 128666190  
Mean Absolute Error: 36899065  
Mean Squared Error: 3939214583622533.0  
Root Mean Squared Error: 62763162.63241148  
MAPE :6.5055417532282735  
R2: 0.7256359823093199

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]:

In [ ]: