

# Scale Features and Build Model

## Scales Raw Features

Import CSV of Aggregated Darshan Logs

Apply Log10 and Percent Scaling

```
In [1]: import os
import pandas as pd
import numpy as np
import math
import matplotlib.pyplot as plt
from sklearn.preprocessing import StandardScaler

from sklearn.model_selection import train_test_split
```

```
In [2]: df = pd.read_csv("./raws.csv",lineterminator='\n',sep = ',' ,error_bad_line
#df.mean())
```

```
In [3]: df = df.drop(df.columns[0],axis = 1)
df = df.drop(df.columns[0],axis = 1)
f = pd.DataFrame()
```

```
In [4]: df
```

Out[4]:

	posix_read_time	posix_write_time	posix_meta_time	posix_bytes_read	posix_bytes_read_100
0	0.000000	0.000000	0.000000	0.000000e+00	0.0
1	104.611641	10.024055	20.060841	2.390891e+10	147688.0
2	124.560730	42.051125	54.839272	5.019637e+10	332059.0
3	25763.292969	582.297363	24.895737	5.488943e+12	30785.0
4	154.534821	681.548279	658.484985	2.293203e+10	588029.0
...	...	...	...	...	...
875282	138.354477	82.278084	194.485565	5.593977e+10	216146.0
875283	54.443073	231.440857	25.271391	1.465277e+09	3099.0
875284	0.000000	0.000000	0.000000	0.000000e+00	0.0
875285	0.000000	0.000000	0.000000	0.000000e+00	0.0
875286	227.063828	191.747269	172.671997	1.077412e+11	775359.0

875287 rows × 50 columns

In [5]:

```
df = df.dropna(axis=0, how='any')
df.columns
```

```
Out[5]: Index(['posix_read_time', 'posix_write_time', 'posix_meta_time',
'posix_bytes_read', 'posix_bytes_read_100', 'posix_bytes_read_1K',
'posix_bytes_read_10K', 'posix_bytes_read_100K', 'posix_bytes_read_
_11M',
'posix_bytes_read_4M', 'posix_bytes_read_10M', 'posix_bytes_read_1
00M',
'posix_bytes_read_1G', 'posix_bytes_read_PLUS', 'posix_bytes_writ
e',
'posix_bytes_write_100', 'posix_bytes_write_1K',
'posix_bytes_write_10K', 'posix_bytes_write_100K',
'posix_bytes_write_1M', 'posix_bytes_write_4M', 'posix_bytes_write
_10M',
'posix_bytes_write_100M', 'posix_bytes_write_1G',
'posix_bytes_write_PLUS', 'posix_opens', 'posix_reads', 'posix_wri
tes',
'posix_seeks', 'posix_stats', 'posix_mmaps', 'posix_fsyncs',
'posix_fdsyncs', 'posix_rename_sources', 'posix_rename_targets',
'posix_renamed_from', 'posix_renamed_mode', 'posix_number_of_file
s',
'nprocs', 'posix_f_align', 'posix_m_align', 'lustre_number_of_file
s',
'lustre_mdts', 'lustre_osts', 'lustre_stripe_size',
'lustre_stripe_offset', 'lustre_stripe_width', 'lustre_number_of_o
sts',
'jobid', 'path'],
dtype='object')
```

In [6]: #files

```
f['log10_p_files'] = df['posix_number_of_files']
f['log10_l_files'] = df['lustre_number_of_files']
```

In [7]: #accesses

```
df['p_accesses'] = df['posix_reads'] + df['posix_writes']
f['log10_p_accesses'] = df['p_accesses']

f['log10_p_accesses']
```

```
Out[7]: 0          0.0
1      880136.0
2     2379598.0
3     8903411.0
4     7846387.0
...
875282    2234152.0
875283    197651.0
875284         0.0
875285         0.0
875286    6065006.0
Name: log10_p_accesses, Length: 875287, dtype: float64
```

```
In [8]: #bytes
f['p_bytes'] = df['posix_bytes_read']
```

```
In [9]: f['p_opens'] = df['posix_opens']
f['p_seeks'] = df['posix_seeks']
f['p_stats'] = df['posix_stats']
f['p_mode'] = df['posix_renamed_mode']
```

```
In [10]: f['l_n_osts'] = df['lustre_number_of_osts']
f['l_stripe_w'] = df['lustre_stripe_width']
f['l_mdts'] = df['lustre_mdts']
```

```
In [11]: f['log10_p_nprocs'] = df['nprocs']
f['log10_p_falign'] = df['posix_f_align']
f['log10_p_malign'] = df['posix_m_align']
```

```
In [12]: f['perc_p_reads'] = df['posix_reads']
f['perc_p_writes'] = df['posix_writes']
```

```
In [13]: f['perc_p_bytes_read_100'] = df['posix_bytes_read_100']
f['perc_p_bytes_read_1K'] = df['posix_bytes_read_1K']
f['perc_p_bytes_read_10K'] = df['posix_bytes_read_10K']
f['perc_p_bytes_read_100K'] = df['posix_bytes_read_100K']
f['perc_p_bytes_read_1M'] = df['posix_bytes_read_1M']
f['perc_p_bytes_read_4M'] = df['posix_bytes_read_4M']
f['perc_p_bytes_read_10M'] = df['posix_bytes_read_10M']

f['perc_p_bytes_read_100M'] = df['posix_bytes_read_100M']
f['perc_p_bytes_read_1G'] = df['posix_bytes_read_1G']
f['perc_p_bytes_read_PLUS'] = df['posix_bytes_read_PLUS']
```

```
In [14]: f['perc_p_bytes_write_100'] = df['posix_bytes_write_100']
f['perc_p_bytes_write_1K'] = df['posix_bytes_write_1K']
f['perc_p_bytes_write_10K'] = df['posix_bytes_write_10K']
f['perc_p_bytes_write_100K'] = df['posix_bytes_write_100K']
f['perc_p_bytes_write_1M'] = df['posix_bytes_write_1M']
f['perc_p_bytes_write_4M'] = df['posix_bytes_write_4M']
f['perc_p_bytes_write_10M'] = df['posix_bytes_write_10M']
f['perc_p_bytes_write_100M'] = df['posix_bytes_write_100M']
f['perc_p_bytes_write_1G'] = df['posix_bytes_write_1G']
f['perc_p_bytes_write_PLUS'] = df['posix_bytes_write_PLUS']

f = f.replace(-np.inf, -1)
f = f.replace(np.nan, 0)
```

```
In [15]: df['time'] = df['posix_write_time'].astype('float') + df['posix_read_time']
```

```
In [16]: df['bytes'] = df['posix_bytes_read'].astype('float') + df['posix_bytes_writ
```

```
In [17]: #df = df[df['bytes'] > 9999999]
```

```
In [18]: f['throughput'] = df['bytes'].astype('float') / df['time']

f = f[f['throughput'] > 0]
```

```
In [19]: #delete columns with all zeros
f = f.loc[:, (f != 0).any(axis=0)]

#remove infinite values
f = f.replace([np.inf, -np.inf], np.nan).dropna(axis=0)

f.max()
```

```
Out[19]: log10_p_files          1.219270e+05
log10_l_files          1.219270e+05
log10_p_accesses       2.251942e+10
p_bytes                3.038456e+14
p_opens                5.531094e+08
p_seeks                1.445220e+10
p_stats                6.522921e+07
p_mode                5.337293e+07
l_n_osts               3.600000e+02
l_stripe_w             7.438575e+06
l_mdts                 1.000000e+00
log10_p_nprocs         3.520000e+05
log10_p_falign         1.422540e+11
log10_p_malign         1.085312e+06
perc_p_reads           2.237846e+10
perc_p_writes          1.302770e+10
perc_p_bytes_read_100  5.221517e+08
perc_p_bytes_read_1K   2.074657e+10
perc_p_bytes_read_10K  1.536278e+09
perc_p_bytes_read_100K 1.515506e+08
perc_p_bytes_read_1M   4.044503e+08
perc_p_bytes_read_4M   6.561462e+07
perc_p_bytes_read_10M  2.083200e+06
perc_p_bytes_read_100M 2.872090e+05
perc_p_bytes_read_1G   1.792000e+06
perc_p_bytes_write_100 1.302770e+10
perc_p_bytes_write_1K  2.852127e+09
perc_p_bytes_write_10K 3.867477e+08
perc_p_bytes_write_100K 8.347452e+07
perc_p_bytes_write_1M  1.357245e+07
perc_p_bytes_write_4M  3.839488e+06
perc_p_bytes_write_10M 6.190660e+05
perc_p_bytes_write_100M 1.249280e+06
perc_p_bytes_write_1G  1.937500e+04
throughput             2.344536e+09
dtype: float64
```

```
In [20]: t = pd.DataFrame()
t['throughput'] = f['throughput']
f = f.drop(labels = 'throughput', axis = 1)
f
```

Out[20]:

	log10_p_files	log10_l_files	log10_p_accesses	p_bytes	p_opens	p_seeks	p_stats
1	799.0	176.0	880136.0	2.390891e+10	8858.0	319241.0	34901.0
2	360.0	224.0	2379598.0	5.019637e+10	62398.0	1107764.0	270222.0
3	290.0	290.0	8903411.0	5.488943e+12	8711.0	2010273.0	28432.0
4	319.0	201.0	7846387.0	2.293203e+10	23158.0	6015926.0	400399.0
6	428.0	190.0	6647935.0	5.209185e+10	69261.0	4608438.0	410846.0
...	...	...	...	...	...	...	...
875280	1.0	1.0	57344.0	3.006477e+10	1808.0	59128.0	12.0
875281	13.0	4.0	102439.0	7.467916e+08	193.0	91.0	385.0
875282	624.0	124.0	2234152.0	5.593977e+10	35112.0	1035457.0	159180.0
875283	1088.0	1088.0	197651.0	1.465277e+09	2112.0	12509.0	4198.0
875286	582.0	128.0	6065006.0	1.077412e+11	119432.0	2750807.0	578508.0

671063 rows × 34 columns

```
In [21]: df = df[df.index.isin(t.index)]
t = t.reset_index()
f = f.reset_index()
f = f.drop(f.columns[0], axis = 1)
t = t.drop(t.columns[0], axis = 1)
```

```
In [22]: f = StandardScaler().fit_transform(f)
```

In [23]: t

Out[23]:

	throughput
0	1.803194e+08
1	2.282342e+08
2	2.083669e+08
3	1.724841e+07
4	4.581690e+07
...	...
671058	5.482767e+08
671059	2.136637e+07
671060	1.362498e+08
671061	1.942413e+07
671062	1.842942e+08

671063 rows × 1 columns

In [24]: `print(t.min())`  
`print(t.max())`

```
throughput      0.39201
dtype: float64
throughput      2.344536e+09
dtype: float64
```


In [25]: `rseed = 2`  
`t_size = 0.4`  
`train_data, test_data, train_labels, test_labels = train_test_split(f,t, te`

```
In [26]: fig = plt.figure()
fig.suptitle('Bytes Read vs. Bytes Written Shaded by Throughput', fontsize=

ax = fig.add_subplot(111)
sp = ax.scatter(df['posix_bytes_read'],df['posix_bytes_write'], marker = 'x'

ax.set_xlabel('Bytes Read s')
ax.set_ylabel('Bytes Written s')
ax.loglog()
#plt.autoscale(enable=True, axis='y')
plt.xlim(10**0,10**15)
plt.ylim(10**0,10**15)
fig.colorbar(sp)
plt.show()
```

**Bytes Read vs. Bytes Written Shaded by Throughput**




```
In [27]: fig = plt.figure()
fig.suptitle('Read Time vs. Write Time Shaded by Throughput', fontsize=14,

ax = fig.add_subplot(111)
sp = ax.scatter(df['posix_read_time'], df['posix_write_time'], marker = 'x',

ax.set_xlabel('Read Time s')
ax.set_ylabel('Write Time s')
ax.loglog()
#plt.autoscale(enable=True, axis='y')
plt.xlim(10**0, 10**9.5)
plt.ylim(10**0, 10**9)
fig.colorbar(sp)
plt.show()
```

**Read Time vs. Write Time Shaded by Throughput**



```
In [28]: from sklearn.cluster import KMeans

k = 3
# Create a KMeans instance with k clusters: model
model = KMeans(n_clusters=k, max_iter = 20**10, random_state=rseed)

# Fit model to samples
model.fit(f)

cluster_labels = model.predict(f)
```



```
In [29]: print('c0',(cluster_labels ==0).sum())
print('c1',(cluster_labels ==1).sum())
print('c2',(cluster_labels ==2).sum())
print('c3',(cluster_labels ==3).sum())
print('c4',(cluster_labels ==4).sum())
print('c5',(cluster_labels ==5).sum())
print(t.shape)
#How many items in each cluster
```

```
c0 584703
c1 86346
c2 14
c3 0
c4 0
c5 0
(671063, 1)
```

```
In [30]: #cluster splits
t5 = t[pd.Series((cluster_labels == 5).tolist()).astype('bool')]
t4 = t[pd.Series((cluster_labels == 4).tolist()).astype('bool')]
t3 = t[pd.Series((cluster_labels == 3).tolist()).astype('bool')]
t2 = t[pd.Series((cluster_labels == 2).tolist()).astype('bool')]
t1 = t[pd.Series((cluster_labels == 1).tolist()).astype('bool')]
t0 = t[pd.Series((cluster_labels == 0).tolist()).astype('bool')]

f5 = f[pd.Series((cluster_labels == 5).tolist()).astype('bool')]
f4 = f[pd.Series((cluster_labels == 4).tolist()).astype('bool')]
f3 = f[pd.Series((cluster_labels == 3).tolist()).astype('bool')]
f2 = f[pd.Series((cluster_labels == 2).tolist()).astype('bool')]
f1 = f[pd.Series((cluster_labels == 1).tolist()).astype('bool')]
f0 = f[pd.Series((cluster_labels == 0).tolist()).astype('bool')]
```

```
In [31]: reagggregated_predictions = pd.DataFrame()
reagggregated_truths = pd.DataFrame()
print(reagggregated_predictions.shape)
print(reagggregated_truths.shape)
```

```
(0, 0)
(0, 0)
```

```
In [ ]:
```

```
In [32]: import xgboost as xg
train_data, test_data, train_labels, test_labels = train_test_split(f0,t0,
xgb_r = xg.XGBRegressor(n_estimators = 10000, seed = 123)
print(train_labels)
xgb_r.fit(train_data, train_labels)
predicted_labels = xgb_r.predict(test_data)

print(reaggregated_predictions.shape)
print(reaggregated_truths.shape)
```

```
          throughput
571868  1.715855e+08
28548   1.535711e+07
171230  1.251804e+08
463935  9.396838e+06
538688  6.472607e+08
...      ...
640614  5.594519e+08
96763   1.072660e+08
502313  1.680178e+06
233145  1.786503e+08
115557  2.409774e+08

[350821 rows x 1 columns]
(0, 0)
(0, 0)
```

```
In [33]: from sklearn.metrics import r2_score
from sklearn.metrics import mean_squared_error
from sklearn.metrics import mean_absolute_error
from sklearn.metrics import mean_squared_log_error
print("Mean True Value: \t",int(test_labels.mean() ))
print("Mean Absolute Error: \t", int(mean_absolute_error(test_labels, predi
print("Mean Squared Error: ", mean_squared_error(test_labels, predicted_lab
print("Root Mean Squared Error: ", mean_squared_error(test_labels, predi

#print("Mean Squared Logarithmic Error : ", mean_squared_log_error( test_la
from sklearn.metrics import mean_absolute_percentage_error
print("MAPE : " + str(mean_absolute_percentage_error( test_labels, predicted

print("R2: " + str(r2_score(test_labels,predicted_labels)) + "\n")

print(xgb_r.feature_importances_)
```

```
Mean True Value:          70418112
Mean Absolute Error:      16922975
Mean Squared Error:  1330836910885212.0
Root Mean Squared Error:  36480637.47915066
MAPE :158.4811714600214
R2: 0.8883643185610324
```

```
[0.04014796 0.01621007 0.00416625 0.08866216 0.02670798 0.00918213
 0.00340308 0.00980443 0.00254938 0.02183332 0.          0.02294224
 0.00334234 0.          0.01832204 0.01092182 0.01700442 0.12422542
 0.00820399 0.01091366 0.05778398 0.09182693 0.02174425 0.01186846
 0.00178021 0.00455562 0.00444354 0.00896775 0.00585728 0.00718879
 0.13389695 0.04370737 0.01824899 0.14958718]
```

```
In [34]: train_data, test_data, train_labels, test_labels = train_test_split(f1,t1,
xgb_r = xg.XGBRegressor(n_estimators = 10000, seed = 123)
xgb_r.fit(train_data, train_labels)
predicted_labels = xgb_r.predict(test_data)

reaggregated_predictions = pd.concat([reaggregated_predictions, pd.DataFrame
reaggregated_truths = pd.concat([reaggregated_truths,pd.DataFrame(test_labe

print(reaggregated_predictions.shape)
print(reaggregated_truths.shape)

print(xgb_r.feature_importances_)
```

```
(34539, 1)
(34539, 1)
[5.8138679e-04 7.7009707e-04 8.0624846e-04 7.7334011e-04 3.2373724e-04
 1.1743202e-03 2.0416400e-03 7.6972612e-04 8.1915507e-04 1.5721084e-01
 0.0000000e+00 2.5098358e-04 0.0000000e+00 0.0000000e+00 9.1563875e-04
 1.2366761e-03 5.5349655e-03 3.9286646e-03 2.7289148e-03 4.3575233e-03
 3.9586211e-03 1.2407434e-03 1.0580322e-03 7.0952433e-06 7.8965867e-01
 9.9825370e-04 8.8718458e-04 1.3097321e-02 6.1927291e-05 5.6193647e-05
 4.0496774e-03 7.1586146e-05 6.3077523e-04 0.0000000e+00]
```

```
In [35]: print("Mean Squared Error: ", mean_squared_error(test_labels, predicted_labels))
print("Mean Absolute Error: ", mean_absolute_error(test_labels, predicted_labels))
print("Root Mean Squared Error: ", mean_squared_error(test_labels, predicted_labels))
#print("Mean Squared Logarithmic Error : ", mean_squared_log_error(test_labels, predicted_labels))
print("MAPE : " + str(mean_absolute_percentage_error(test_labels, predicted_labels)))
print("R2: " + str(r2_score(test_labels, predicted_labels)) + "\n")
```

```
Mean Squared Error: 1069219832687237.4
Mean Absolute Error: 21486600.418642566
Root Mean Squared Error: 32698927.0877079
MAPE :0.35145425988435075
R2: -0.13876728125699
```

```
In [36]: train_data, test_data, train_labels, test_labels = train_test_split(f2,t2,
xgb_r = xg.XGBRegressor(n_estimators = 10000, seed = 123)
xgb_r.fit(train_data, train_labels)
predicted_labels = xgb_r.predict(test_data)
reaggregated_predictions = pd.concat([reaggregated_predictions, pd.DataFrame(predicted_labels)])
reaggregated_truths = pd.concat([reaggregated_truths, pd.DataFrame(test_labels)])

print("Mean Squared Error: ", mean_squared_error(test_labels, predicted_labels))
print("Mean Absolute Error: ", mean_absolute_error(test_labels, predicted_labels))
print("Root Mean Squared Error: ", mean_squared_error(test_labels, predicted_labels))
#print("Mean Squared Logarithmic Error : ", mean_squared_log_error(test_labels, predicted_labels))
print("MAPE : " + str(mean_absolute_percentage_error(test_labels, predicted_labels)))
print("R2: " + str(r2_score(test_labels, predicted_labels)) + "\n")

print(reaggregated_predictions.shape)
print(reaggregated_truths.shape)

print(xgb_r.feature_importances_)
```

```
Mean Squared Error: 11219182482344.465
Mean Absolute Error: 1368734.0548686876
Root Mean Squared Error: 3349504.811512362
MAPE :0.21196740392176538
R2: -0.19964454339891802
```

```
(34545, 1)
(34545, 1)
[0.012561 0.95878863 0. 0. 0. 0.02572362
 0. 0. 0.00292679 0. 0. 0.
 0. 0. 0. 0. 0. 0.
 0. 0. 0. 0. 0. 0.
 0. 0. 0. 0. 0. 0.
 0. 0. 0. 0. ]
```

```
In [37]: print("Mean Absolute Error: ", mean_absolute_error(reaggregated_truths, reagg
print("Mean Squared Error: ", mean_squared_error(reaggregated_truths, reagg
print("MAPE : " + str(mean_absolute_percentage_error( reaggregated_truths, r
print("R2: " + str(r2_score(reaggregated_truths, reaggregated_predictions))

print(reaggregated_predictions.shape)
print(reaggregated_truths.shape)
```

```
Mean Absolute Error:  21483106.21692936
Mean Squared Error:  1069036072261670.0
MAPE :0.35143003290111796
R2: -0.13212475706732008
```

```
(34545, 1)
(34545, 1)
```

```
In [ ]:
```


```
In [ ]:
```

```
In [38]: e = reaggregated_predictions[0].values - reaggregated_truths['throughput'].
e
```

```
Out[38]: array([-4.87030979e+06, -1.24654003e+07,  4.21480073e+07, ...,
          9.61034818e+02, -1.71110309e+03, -8.20457629e+06])
```


```
In [39]: plt.hist(reaggregated_predictions, bins = 300)
plt.title('predictions')
```

```
Out[39]: Text(0.5, 1.0, 'predictions')
```



```
In [40]: plt.hist(reaggregated_truths, bins = 300)  
plt.title('truth')
```

```
Out[40]: Text(0.5, 1.0, 'truth')
```




```
In [41]: from sklearn.metrics import mean_absolute_percentage_error  
mean_absolute_percentage_error( test_labels, predicted_labels )
```

```
Out[41]: 0.21196740392176538
```

```
In [42]: plt.hist(e, bins = 1000)  
plt.title('error')
```

```
Out[42]: Text(0.5, 1.0, 'error')
```



In [ ]:

In [43]:

```

fig = plt.figure()
fig.suptitle('Bytes Read vs. Bytes Written Shaded by Throughput', fontsize=

ax = fig.add_subplot(111)
sp = ax.scatter(f0['posix_bytes_read'],d['posix_bytes_write'], marker = 'x'

ax.set_xlabel('Bytes Read s')
ax.set_ylabel('Bytes Written s')
ax.loglog()
#plt.autoscale(enable=True, axis='y')
plt.xlim(10**0,10**15)
plt.ylim(10**0,10**15)
fig.colorbar(sp)
plt.show()

```

```

--
IndexError                                Traceback (most recent call las
t)

```

```

<ipython-input-43-1a3c85cc9c15> in <module>

```

```

3
4 ax = fig.add_subplot(111)
----> 5 sp = ax.scatter(f0['posix_bytes_read'],d['posix_bytes_write'], ma
rker = 'x',c = np.log10(t['throughput']),cmap='viridis')
6
7 ax.set_xlabel('Bytes Read s')


```

```

IndexError: only integers, slices (`:`), ellipsis (`...`), numpy.newaxis
(`None`) and integer or boolean arrays are valid indices

```

### Bytes Read vs. Bytes Written Shaded by Throughput



In [ ]:

In [ ]:

