```
Time
                      Source
                                           Destination
                                                                 Protocol Length Info
No.
    404 144.041870
                     128.119.245.12
                                           192.168.1.195
                                                                 HTTP
                                                                          540
                                                                                HTTP/1.1 200 OK (text/html)
Frame 404: 540 bytes on wire (4320 bits), 540 bytes captured (4320 bits) on interface 0
Ethernet II, Src: Verizon_68:c5:b8 (48:5d:36:68:c5:b8), Dst: Foxconn_d1:d3:8c (00:01:6c:d1:d3:8c)
Internet Protocol Version 4, Src: 128.119.245.12, Dst: 192.168.1.195
   0100 .... = Version: 4
    .... 0101 = Header Length: 20 bytes (5)
    Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
       0000 00.. = Differentiated Services Codepoint: Default (0)
        .... ..00 = Explicit Congestion Notification: Not ECN-Capable Transport (0)
    Total Length: 526
    Identification: 0x41b1 (16817)
    Flags: 0x4000, Don't fragment
       0... .... = Reserved bit: Not set
        .1.. .... = Don't fragment: Set
        ..0. .... = More fragments: Not set
        ...0 0000 0000 0000 = Fragment offset: 0
    Time to live: 53
    Protocol: TCP (6)
    Header checksum: 0xca49 [validation disabled]
    [Header checksum status: Unverified]
    Source: 128.119.245.12
   Destination: 192.168.1.195
Transmission Control Protocol, Src Port: 80, Dst Port: 50737, Seq: 1, Ack: 419, Len: 486
Hypertext Transfer Protocol
Line-based text data: text/html (4 lines)
```