


Breadth-first search

David Gries

Breadth-first search of a graph visits all nodes of a graph that are reachable along unvisited paths from node u in the following order:

First u .
Then all nodes that are 1 edge from u .
Then all nodes that are 2 edges from u ,
And so forth.



Here is the iterative depth-first search algorithm that we developed earlier:

```
/** Visit every node reachable along a path of unvisited nodes from node u.
    Precondition: u has not been visited. */
public static void dfsIterative(Node u) {
    Stack s = (u); // Not Java!
    // Invariant: all nodes (and only those nodes) that have to be visited are
    // reachable along a path of unvisited nodes from some node in s.
    while (s is not empty) {
        u = s.pop();
        if (u is not visited) {
            Visit u;
            For each neighbor w of u:
                s.push(w);
        }
    }
}
```

We change it into a breadth-first search simply by changing s from a stack to a queue!

```
/** Visit every node reachable along a path of unvisited nodes from node u.
    Precondition: u has not been visited. */
public static void bfs(Node u) {
    Queue s = (u); // Not Java!
    // Invariant: all nodes (and only those nodes) that have to be visited are
    // reachable along a path of unvisited nodes from some node in s.
    while (s is not empty) {
        u = s.remove(); // remove first element of queue and store it in u
        if (u is not visited) {
            Visit u;
            For each neighbor w of u:
                s.add(w); // append w to queue
        }
    }
}
```

We explain why this results in a breadth-first search. First, for any integer $i \geq 0$, nodes that are i edges from u are put in the queue before nodes that are $i+1$ edges from u . Second, nodes are removed from the *front* of the queue and visited (if not yet visited), so those closer to u are visited first.