

Sorting an array using an anonymous function

We show how easy it is to sort an array in various ways using anonymous functions.

Check out class `Person` to the right. We have made the fields public only to make our anonymous functions shorter and easier to understand. Generally, they would be private, and getter functions would have to be used.

```
public class Person {  
    public String first;  
    public String last;  
    public int age;  
    ...  
}
```

Suppose we have declared array

```
Person[] p = ...;
```

and have filled `p` with a bunch of `Person` objects. We want to sort `p` based on the ages of the `Persons`. API class `Arrays` contains a procedure that lets us do it with this procedure call¹:

```
Arrays.sort(p, (Person b, Person c) -> b.age - c.age);
```

The second argument of the call on `sort` is an anonymous function with two `Person` parameters. It returns:

- a negative number if `Person b` is younger than `Person c` (i.e. `b` comes before `c`)
- 0 if `Person b` and `Person c` are the same age (i.e. neither comes before the other)
- a positive number if `Person b` is older than `Person c` (i.e. `c` comes after `b`)

We can leave out the types of `b` and `c`, since they can be inferred. So, we write this call more simply as:

```
Arrays.sort(p, (b, c) -> b.age - c.age);
```

We have flexibility! To sort `p` in reverse order of age, use:

```
Arrays.sort(p, (b, c) -> c.age - b.age);
```

So you see how easy it is to sort `p` in some order; just give a second argument that indicates which of `b` and `c` comes before the other.

Sorting by Strings

Class `String` already has a function `s.compareTo(t)` that returns a negative number, 0, or a positive number depending on whether `String s` is smaller than `String t`, equal to it, or larger. Therefore, to sort `p` on the last name of the people, use

```
Arrays.sort(p, (b, c) -> b.last.compareTo(c.last));
```

More complicated sorting

Suppose we want to sort `p` in order of first name, but if people have the same first name, sort them based on their age, with younger people first.

Writing the anonymous function for this case is messy. So, it is best to write static function `before`, which appears to the right. Then, it is a simple matter to write the call on `sort` that appears below.

```
/** If b's and c's first names are the same, return b's age - c's age.  
 * Return -1 (or 1) if b's first name comes before (or after)  
 * c's first name. */  
public static int before(Person b, Person c) {  
    int n = b.first.compareTo(c.first);  
    if (n != 0) return n;  
    return b.age - c.age;  
}
```

```
Arrays.sort(p, (b, c) -> before(b, c));
```

¹ Sorting procedures also exist to sort only a portion of an array. For example, to sort only array segment `p[1..6]`, use `Arrays.sort(p, 1, 7, (Person b, Person c) -> b.age - c.age);`

Sorting an array using an anonymous function