

# EUROSTATDATA filter syntax

```
=EUROSTATDATA(datasetCode; "geo=DE;time=2023;unit=CP_MEUR")
```

The second argument is a semicolon-separated list of `key=value` pairs. Every pair is passed straight through as a query-string parameter to Eurostat's own REST API — this sheet covers what's known to work.

## SYNTAX

| FORM                       | MEANING                                                               |
|----------------------------|-----------------------------------------------------------------------|
| <code>""</code>            | No filtering — return every dimension value in the dataset.           |
| <code>"key=value"</code>   | One filter: restrict <code>key</code> to <code>value</code> .         |
| <code>"k1=v1;k2=v2"</code> | Multiple filters, separated by <code>;</code> — order doesn't matter. |

## GOTCHAS

!

- **One value per key.** The filter string is parsed into a plain key → value map, so `geo=DE;geo=FR` doesn't select both — the second occurrence silently overwrites the first and only France comes back. There's no repeated-key or comma-list syntax for "OR" across a dimension; to compare several countries, leave `geo` off and filter the resulting table in the sheet instead.
- **Don't pass `format=`.** The add-in always requests JSON under the hood to parse the response — overriding it will break parsing, not change the output shape.
- **Keys and valid values are dataset-specific.** `geo`, `time`, and `unit` exist on most datasets, but the exact code list (which units, which age bands) varies dataset to dataset. See [Finding exact codes](#).

## RESERVED EUROSTAT PARAMETERS

Not dimensions of the dataset — instructions to the API itself. Any of these can sit in the same filter string alongside dimension filters.

| KEY                                        | DOES                                                                                                                | EXAMPLE              |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------|----------------------|
| <b>sinceTimePeriod</b> <span>DEMOED</span> | Return every period from this one to the most recent, instead of a single point.                                    | sinceTimePeriod=2015 |
| <b>lastTimePeriod</b>                      | Return only the N most recent periods.                                                                              | lastTimePeriod=5     |
| <b>lang</b>                                | Language for dimension/category labels in the response ( <span>en</span> , <span>fr</span> , <span>de</span> ).     | lang=fr              |
| <b>precision</b>                           | Decimal precision of returned values: <span>1</span> or <span>3</span> .                                            | precision=3          |
| <b>geoLevel</b>                            | Expand a geo grouping (e.g. <span>EU27_2020</span> ) into its member countries rather than returning the aggregate. | geoLevel=country     |

Only sinceTimePeriod and lastTimePeriod are exercised in this repo's demo sheet; the rest are documented at the Eurostat API level and pass through unmodified like any other key.

## FREQUENTLY-SEEN DIMENSION KEYS

Every Eurostat dataset defines its own dimensions, but these recur across most of them. Treat this as a starting guess, not a guarantee for any specific dataset.

| KEY              | DIMENSION                | TYPICAL VALUES          |
|------------------|--------------------------|-------------------------|
| geo              | Country / region         | DE, FR, IT, EU27_2020   |
| time             | Single period            | 2023, 2023-Q1, 2023-06  |
| unit             | Unit of measure          | CP_MEUR, PC_ACT, PC_GDP |
| sex              | Sex                      | M, F, T                 |
| age              | Age band                 | Y15-74, Y_GE65, TOTAL   |
| freq             | Frequency                | A (annual), Q, M        |
| indic_de / indic | Indicator code           | dataset-specific        |
| nace_r2          | Economic activity (NACE) | dataset-specific        |
| s_adj            | Seasonal adjustment      | SA, NSA, CA             |

FINDING EXACT CODES FOR A DATASET

Open the dataset in the [Eurostat Data Browser](#), set the filters you want in its UI, then use its "API request" / data-access panel — it shows the live query string with every key and value already spelled out correctly. Copy those `key=value` pairs straight into the filters argument.

EXAMPLES

```
=EUROSTATDATA("nama_10_gdp"; "geo=DE;time=2023;unit=CP_MEUR")
-- GDP, Germany, 2023, million EUR

=EUROSTATDATA("une_rt_a"; "geo=FR;time=2023;unit=PC_ACT;age=Y15-74")
-- unemployment rate, France, 2023, % of active population, 15-74

=EUROSTATDATA("tec00118"; "geo=DE;sinceTimePeriod=2015")
-- HICP inflation, Germany, every year from 2015 to latest

=EUROSTATDATA("demo_pjan"; "")
-- population on 1 January, no filtering -- every country, every year
```

Covers the `filters` argument of `EUROSTATDATA` in the [java\\_eurostats](#) add-in. Enter formulas with **Ctrl+Shift+Enter** to spill the result table.