

```
logan@vm:~/net2300/dbmigrate$ mysql -h 127.0.0.1 -u logapp -plogapp123 logdb -e "SELECT * FROM logs;"
mysql: [Warning] Using a password on the command line interface can be insecure.
+-----+-----+-----+-----+
| id | message | status | timestamp |
+-----+-----+-----+-----+
| 1 | ls | pending | 2026-04-16 14:21:34 |
| 2 | pwd | pending | 2026-04-16 14:33:28 |
| 3 | abc | pending | 2026-04-16 14:33:32 |
+-----+-----+-----+-----+
logan@vm:~/net2300/dbmigrate$
```

Put in random commands for startengine to run as tests.

```
mysql: [Warning] Using a password on the command line interface can be insecure.
logan@vm:~/net2300/dbmigrate$ ./start-engine.sh
Running ls
logan@vm:~/net2300/dbmigrate$ mysql -h 127.0.0.1 -u logapp -plogapp123 logdb -e "SELECT * FROM logs;"
mysql: [Warning] Using a password on the command line interface can be insecure.
+-----+-----+-----+-----+
| id | message | status | timestamp |
+-----+-----+-----+-----+
| 1 | ls | pending | 2026-04-16 14:21:34 |
| 2 | pwd | pending | 2026-04-16 14:33:28 |
| 3 | abc | pending | 2026-04-16 14:33:32 |
+-----+-----+-----+-----+
logan@vm:~/net2300/dbmigrate$ ./start-engine.sh
Running ls
Running pwd
Running abc
logan@vm:~/net2300/dbmigrate$ mysql -h 127.0.0.1 -u logapp -plogapp123 logdb -e "SELECT * FROM logs;"
mysql: [Warning] Using a password on the command line interface can be insecure.
+-----+-----+-----+-----+
| id | message | status | timestamp |
+-----+-----+-----+-----+
| 1 | ls | done | 2026-04-16 14:21:34 |
| 2 | pwd | done | 2026-04-16 14:33:28 |
| 3 | abc | error | 2026-04-16 14:33:32 |
+-----+-----+-----+-----+
logan@vm:~/net2300/dbmigrate$
```

Ran start-engine and it updated the status

```
logan@vm:~/net2300/dbmigrate$ mysql -h 127.0.0.1 -u logapp -plogapp123 logdb -e "UPDATE logs SET log_id=1;"
mysql: [Warning] Using a password on the command line interface can be insecure.
logan@vm:~/net2300/dbmigrate$ mysql -h 127.0.0.1 -u logapp -plogapp123 logdb -se "SELECT * FROM execution_log;"
+-----+-----+-----+-----+
| id | log_id | command | output | exit_code | executed_at |
+-----+-----+-----+-----+
| 1 | 1 | ls | /home/logan/net2300/dbmigrate | 0 | 2026-04-17 02:11:51 |
| 2 | 2 | pwd | /home/logan/net2300/dbmigrate | 0 | 2026-04-17 02:11:51 |
| 3 | 3 | abc | bash: line 1: abc: command not found | 127 | 2026-04-17 02:11:51 |
| 4 | 1 | ls | APACHE.md\nbackend\nbackup.sh\ndocker-compose.override.yml.example\ndocker-compose.yml\ndOCKER.md\nDocker-SHARE.md\nexecution.log\nexport-images.sh\nfrontend\ninit-dat\nabases.sql\nINSTALL-Docker.md\ninstall-docker-rocky.sh\nMakefile\nmysqlsampledatabase.sql\nNODEJS-Docker.md\nopen-ports.sh\nREADME.md\nstart-engine.sh\nSTATUS-FIELD-UPDATE.md\nverify-docker.s | 0 | 2026-04-17 02:13:31 |
| 5 | 2 | pwd | /home/logan/net2300/dbmigrate | 0 | 2026-04-17 02:13:31 |
| 6 | 3 | abc | bash: line 1: abc: command not found | 127 | 2026-04-17 02:13:31 |
+-----+-----+-----+-----+
logan@vm:~/net2300/dbmigrate$
```

Results were put into execution log

Everything's doubled since I didn't reset it

				id	log_id	command	output	exit_code	executed_at
	Edit	Copy	Delete	1	1	ls	APACHE.md backend backup.sh docker-compose.override...	0	2026-04-17 02:11:51
	Edit	Copy	Delete	2	2	pwd	/home/logan/net2300/dbmigrate	0	2026-04-17 02:11:51
	Edit	Copy	Delete	3	3	abc	bash: line 1: abc: command not found	127	2026-04-17 02:11:51
	Edit	Copy	Delete	4	1	ls	APACHE.md backend backup.sh docker-compose.override...	0	2026-04-17 02:13:31
	Edit	Copy	Delete	5	2	pwd	/home/logan/net2300/dbmigrate	0	2026-04-17 02:13:31
	Edit	Copy	Delete	6	3	abc	bash: line 1: abc: command not found	127	2026-04-17 02:13:31

phpmyadmin looking at execution log

Showing rows 0 - 2 (3 total, Query took 0.0003 seconds.)

SELECT * FROM `logs`

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key

Extra options

			id	message	status	timestamp	
☐				1	ls	done	2026-04-16 14:21:34
☐				2	pwd	done	2026-04-16 14:33:28
☐				3	abc	error	2026-04-16 14:33:32

phpmyadmin looking at logs

```
#!/bin/bash

DB_USER="logapp"
DB_PASS="logapp123"
DB_NAME="logdb"

data=$(mysql -h 127.0.0.1 -u$DB_USER -p$DB_PASS $DB_NAME -Nse \
"SELECT id, message FROM logs WHERE status='pending';" 2>/dev/null)

echo "$data" | while read -r id cmd; do
    echo "Running $cmd"

    output=$(bash -c "$cmd" 2>&1)
    result=$?
```

```
# escape single quotes for MySQL safety
cmd_esc=$(echo "$cmd" | sed "s/'/'/'g")
output_esc=$(echo "$output" | sed "s/'/'/'g")

mysql -h 127.0.0.1 -u$DB_USER -p$DB_PASS $DB_NAME -e \
"UPDATE logs SET status=IF($result=0,'done','error') WHERE
id=$id;" 2>/dev/null

mysql -h 127.0.0.1 -u$DB_USER -p$DB_PASS $DB_NAME -e \
"INSERT INTO execution_log (log_id, command, output, exit_code)
VALUES ($id, '$cmd_esc', '$output_esc', $result);" 2>/dev/null

echo "[$result] $cmd -> $output" >> execution.log
done
```

start-engine script.