



HOLE DOZER™

BI-METAL HOLE SAWS RECOMMENDED RPMs

RPM recomendadas para sierras de perforación bimetalicas
Les r/min recommandés pour les scies-cloches bimétal

13

Size	mm	Mild Steel	Stainless Steel	Cast Iron	Aluminum	Size	mm	Mild Steel	Stainless Steel	Cast Iron	Aluminum
9/16"	14	580	300	400	900	2-1/4"	57	150	75	100	225
5/8"	16	550	275	365	825	2-5/16"	59	145	75	100	225
21/32"	17	510	255	335	765	2-3/8"	60	140	70	95	220
11/16"	18	500	250	330	750	2-1/2"	64	135	65	90	205
3/4"	19	460	230	300	690	2-9/16"	65	130	65	85	200
25/32"	20	440	220	290	660	2-5/8"	67	130	65	85	195
13/16"	21	425	210	280	630	2-11/16"	68	125	60	80	190
7/8"	22	390	195	260	585	2-3/4"	70	125	60	80	185
15/16"	24	370	185	245	555	2-7/8"	73	120	60	80	180
1"	25	350	175	235	525	3"	76	115	55	75	170
1-1/16"	27	325	160	215	480	3-1/8"	79	110	55	70	165
1-1/8"	29	300	150	200	450	3-1/4"	83	105	50	70	155
1-3/16"	30	285	145	190	425	3-3/8"	86	100	50	65	150
1-1/4"	32	275	140	180	410	3-1/2"	89	95	45	65	145
1-5/16"	33	260	135	175	390	3-5/8"	92	95	45	60	140
1-3/8"	35	250	125	165	375	3-3/4"	95	90	45	60	135
1-7/16"	37	240	120	160	360	3-7/8"	98	90	45	60	135
1-1/2"	38	230	115	150	345	4"	102	85	40	55	130
1-9/16"	40	220	110	145	330	4-1/8"	105	80	40	55	120
1-5/8"	41	210	105	140	315	4-1/4"	108	80	40	55	120
1-11/16"	43	205	105	135	305	4-3/8"	111	80	40	50	120
1-3/4"	44	195	95	130	295	4-1/2"	114	75	35	50	105
1-13/16"	46	190	95	125	285	4-3/4"	121	70	35	45	95
1-7/8"	48	180	90	120	270	5"	127	65	30	45	90
1-59/64"	50	175	85	115	260	5-1/4"	133	60	25	40	85
2"	51	170	85	115	255	5-1/2"	140	60	25	40	85
2-1/16"	52	165	80	110	245	5-3/4"	146	55	25	35	80
2-1/8"	54	160	80	105	240	6"	152	55	25	35	75

Due to types of materials and conditions, these speeds are subject to variation.
Debido a los diferentes tipos de materiales y condiciones, estas velocidades están sujetas a variaciones.

Ces vitesses peuvent varier en raison des types de matériaux utilisés et des conditions d'utilisation.

MILWAUKEE® HOLE DOZER™ HOLE SAW TOOTH BREAK LIMITED LIFETIME WARRANTY

MILWAUKEE® HOLE DOZER™ hole saw accessory products sold in the U.S.A. and Canada ("Products") are warranted to the original retail purchaser only to be free from tooth breakage or fracture caused by material defects in material or workmanship under normal use and service for the lifetime of the Product. This warranty does not apply to damage from misuse, alterations, abuse or normal wear and tear. MILWAUKEE® will replace the Product which, after examination, is determined by MILWAUKEE® to have tooth breakage or fracture caused by material defective material or workmanship. Return of the Product to a MILWAUKEE® factory Service Center location, freight prepaid and insured, is required. A copy of the proof of purchase should be included with the return product. Call 1.800.SAWDUST (1.800.729.3878) or refer to the MILWAUKEE® website www.milwaukeeool.com to locate your nearest MILWAUKEE® factory Service Center location.

REPLACEMENT OF THE PRODUCT WITH NEW OR SUBSTANTIALLY SIMILAR PRODUCT OR, AT MILWAUKEE'S OPTION A REFUND OF THE PURCHASE PRICE PAID BY THE PURCHASER, IS THE PURCHASER'S EXCLUSIVE REMEDY AND MILWAUKEE'S EXCLUSIVE OBLIGATION UNDER THIS WARRANTY. IN NO EVENT SHALL MILWAUKEE® BE LIABLE FOR INCIDENTAL, SPECIAL, INDIRECT, CONSEQUENTIAL OR PUNITIVE DAMAGES ARISING OUT OF ANY DAMAGE TO, FAILURE OF, OR DEFECT IN ANY PRODUCT. SOME STATES DO NOT ALLOW THE EXCLUSION OR LIMITATION OF INCIDENTAL OR CONSEQUENTIAL DAMAGES, SO THE ABOVE LIMITATION OR EXCLUSION MAY NOT APPLY TO YOU. THIS WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER EXPRESS WARRANTIES, WRITTEN OR ORAL. TO THE EXTENT PERMITTED BY LAW, MILWAUKEE® DISCLAIMS ANY IMPLIED WARRANTIES, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR PURPOSE. SOME STATES DO NOT ALLOW LIMITATIONS ON HOW LONG AN IMPLIED WARRANTY LASTS, SO THE ABOVE LIMITATION MAY NOT APPLY TO YOU. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.



HOLE DOZER™

BI-METAL HOLE SAWS RECOMMENDED RPMs

RPM recomendadas para sierras de perforación bimetalicas
Les r/min recommandés pour les scies-cloches bimétal

ARBORS Mandriles Arbres

	Part No.		Min. Chuck	Use With Pilot Bits
Up to 1-3/16" Hasta 30 mm Jusqu'à 30 mm	49-56-7000		1/2" 12,7 mm	49-56-8000, 49-56-8010, 49-56-8005
	49-56-7010		3/8" 9,5 mm	
	49-56-6950		1/4" 6,4 mm	49-56-8000, 49-56-8005
1-1/4" & Larger 32 mm y más grandes Largeur de 32 mm ou plus	49-56-7055	Quick Change	1/2" 12,7 mm	
	49-56-7040		3/8" 9,5 mm	49-56-8000, 49-56-8010, 49-56-8005
	49-56-7240	Quick Change	1/2" 12,7 mm	
	49-56-7250	Quick Change	3/8" 9,5 mm	
	49-56-9100	Quick Change	1/2" 12,7 mm	

***Using hole saws larger than 1-1/2" may result in unintended lock-ups.
This condition may require tool to release collar and reset mechanism.**

* El uso de sierras de perforación de más de 38 mm (1-1/2") puede derivar en bloqueos no deseados. Es posible que, de darse esta situación, se requiera una herramienta para liberar el collar y reiniciar el mecanismo.

* À l'aide d'une scie-cloche d'une largeur supérieure à 38 mm (1 1/2") peut provoquer un blocage non intentionnel. Cette situation peut nécessiter le dégagement du collet et la réinitialisation du mécanisme.

PILOT BITS Brocas piloto Mèches pilotes

Part No.	Description	Available in Bulk/12 Pack
49-56-8010	1/4" x 3-1/2" HSS THUNDERBOLT® Bit	49-56-8033
49-56-8000	1/4" x 4" HSS THUNDERBOLT® Bit	49-56-8031
49-56-8005	1/4" x 4" Carbide Tipped Bit	n/a

EXTENSIONS Extensiones Rallonges

Part No.	Description	Use With Arbor
48-28-4008	12" Length	Small Shank Arbors 49-56-7010, 49-56-7040, 49-56-7250
48-28-4001	5-1/2" Length	
48-28-4006	12" Length	Large Shank Arbors 49-56-7000, 49-56-7055, 49-56-7240, 49-56-9100
48-28-4011	18" Length	
48-28-4016	24" Length	
48-28-1030	5-1/2" Length QUIK-LOK®	
48-28-1040	12" Length QUIK-LOK®	
48-28-1050	18" Length QUIK-LOK®	
48-28-1060	24" Length QUIK-LOK®	

Manual - Milwaukee Hole Saw.pdf