

Manual - buffingCompound.pdf

Please read and save these instructions. Read carefully before attempting to assemble, install, operate or maintain the product described. Protect yourself and others by observing all safety information. Failure to comply with instructions could result in personal injury and/or property damage! Retain instructions for future reference.

Dayton® Buff and Compound

Description

Dayton Buff and Compound are used to polishing metal, plastic and other non ferrous materials to make perfect surface.

E
N
G
L
I
S
H

Buffing Wheel and Compound selection Chart

Materials	Steel, Iron stainless, or other hard metals	Soft Metals, brass, copper, Aluminum, etc	Gold, silver, etc	Plastic
Step 1- Rough Compound buff	Emery(black)	Tripoli (brown)		Tripoli (brown)
Step 2 – intermediate Compound buff	Stainless (white)	White rouge	White rouge	Plastic tube (yellow)
Step 3- final compound, buff	Chrome (green)	Jeweler (red)	Jeweler (red)	
Recommend RPM	3600	3600	1800-3600	1800

Buffing Instruction.

1. Choose the motor and buffing wheel matched.
2. Attach the buffing wheel to the buffing motor spindle, making sure that it is mounted securely between the flange washers.
3. Gently touch the appropriate tube of compound to the face of the wheel for several seconds.
4. It's very important that only one type of compound be used on each buffing wheel.
5. Place each wheel and its compound tube in separate to prevent accidentally applying the wrong compound to your buffing wheel.
6. Ues great care when buffing plated metal. Thin plating is easily buffed off.
7. Before you begin, double check the surface of the piece to ensure that there are no deep scratches in the surface. If you can catch your fingernail in the scratch, you'll have to file and sand it out before buffing.

Warning:

Always wear safety glasses and a dust mask.

