

VEVOR[®]

TOUGH TOOLS, HALF PRICE

Technical Support and E-Warranty Certificate www.vevor.com/support

LATHE CHUCK

MODEL: K11-100, K11-125, K11-160, K11-200, K11-250

K11-200A, K11-250A

We continue to be committed to provide you tools with competitive price.
"Save Half", "Half Price" or any other similar expressions used by us only represents an estimate of savings you might benefit from buying certain tools with us compared to the major top brands and does not necessarily mean to cover all categories of tools offered by us. You are kindly reminded to verify carefully when you are placing an order with us if you are actually saving half in comparison with the top major brands.

VEVOR[®]

TOUGH TOOLS, HALF PRICE

Technical Support and E-Warranty Certificate

www.vevor.com/support

MODEL: K11-100, K11-125, K11-160, K11-200A, K11-250A
K11-200, K11-250



NEED HELP? CONTACT US!

Have product questions? Need technical support? Please feel free to contact us:


✉ CustomerService@vevor.com

This is the original instruction, please read all manual instructions carefully before operating. VEVOR reserves a clear interpretation of our user manual. The appearance of the product shall be subject to the product you received. Please forgive us that we won't inform you again if there are any technology or software updates on our product.

Geometry accuracy (mm)


(table 6) mm

Diagram of test	Test item	Chuck Diameter				
		≤165	200~250	315~400	00~630	800~1000
	a.Radial run-out	a:0.005 b:0.005				
	b.axial run out					
	Radial run-out chuck	0.040	0.050	0.060	0.080	0.100
	Axial run out chuck	0.050	0.050	0.060	0.080	0.100
	Radial run-out of test bar	$\alpha=0.08$ L=50	$\alpha=0.080$ L=50(75)	$\alpha=0.100$ L=75	$\alpha=0.125$ ≈ 100	$\alpha=0.160$ L=100
	Radial run-out of test ring	0.060	0.060	0.080	0.100	0.120
	Axial run-out of test ring	0.032	0.040	0.048	0.064	0.080

	Radial run-out of test ring	0.060	0.060	0.080	0.100	0.120
	Axial run-out of test ring	0.032	0.040	0.048	0.064	0.080

SPECIFICATIONS

SEPC. /MODEL	D1	D2	D3	H	H1	H2	h	z-d
K1180	55	66	16	66	50	-	3.5	3-M6
K11100	72	84	22	74.5	55	-	3.5	3-M8
K11125	95	108	30	85	58	-	4	3-M8
K11130	100	115	30	85	58	-	4	3-M8
K11160	130	142	40	95	65	-	5	3-M8
K11160A	130	142	40	109	65	71	5	3-M8
K11165	130	145	40	95	65	-	5	3-M8
K11165A	130	145	40	109	65	71	5	3-M8
K11190	155	172	55	109	75	-	5	3-M10
K11190A	155	172	55	122	75	80	5	3-M10
K11200	165	180	65	109	75	-	5	3-M10
K11200A	165	180	65	122	75	80	5	3-M10
K11240	195	215	70	120	80	-	8	3-M12
K11240A	195	215	70	133	80	85	8	3-M12
K11250	206	226	80	120	80	-	5	3-M12
K11250A	206	226	80	133	80	85	5	3-M12
K11315	260	285	100	142.5	90	-	6	3-M16
K11315A	260	285	100	155.5	90	96.5	6	3-M16
K11320	270	290	100	142.5	90	-	6	3-M16
K11320A	270	290	100	155.5	90	96.5	6	3-M16
K11325	272	296	100	142.5	90	-	6	3-M16
K11325A	272	296	100	155.5	90	96.5	6	3-M16
K11380	325	350	130	155.5	100	-	6	3-M16
K11380A	325	350	130	170.5	100	96.5	6	3-M16
K11400	340	368	130	155.5	100	-	6	3-M16
K11400A	340	368	130	170.5	100	108.5	6	3-M16
K11500	440	465	200	176	115	-	6	6-M16
K11500A	440	465	200	203	115	123	6	6-M16
K11630	560	595	260	192	130	-	7	6-M16
K11630A	560	595	260	218	130	138	7	6-M16
K11800A	710	760	385	249	148	158	8	6-M20
K111000A	910	950	460	266	165	-	8	6-M24
K111250A	910	950	500	281	180	-	10	6-M24



(Fig. 2)

The jaws of the series chucks have two types:

- ① Model k11 is of solid jaw. One chuck has each set of internal and external jaws which can be used separately.
- ② Model K11A(or K11C) is of two-piece jaw, which is composed of Base jaw and reversible top jaw. The two-piece jaws can perform. As internal or external jaws through adjustment. According to chucking diameters, soft top jaws can bere-machined so as to achieve ideal clamping accuracy. The connection dimensions for two-picce jaws of model K11A conform to GB4346 (IS03442) Standards.



Caution

- a)Don't add tube on the wrench when clampworkpiece to avoid the input torque exceed limit will break chuck.
- b)Don't.clamp workpiece in the max clamping range if possible.
- c)Don'g run at the max speed when approach to the max clamping limit.
- d)The chucks with "0"gear in clamping at last to ensure the accuracy.
- e)Don't exceed chuck max speed during operation.

Maintenance and inspection


- 1 Chucks should be maintained while the machine tools maintain.
- 2 Lubricate (at the grease cup)and clean(use the compressed air) the chucks every day, in order to maintain its accuracy and durability.
- 3 Wash and lubricate all the working surface of the chucks at least two times every year.When the using frequency of the machine tool grow or at the special operation conditions,add the maintenance times of the chucks.

Troubleshooting

Troubleshooting and measurement see Table.5.

(Table 5)

Problem	Cause	Countermeasures
Insufficient clamping	The clamping are taper not conform with dimension	Replace jaws
	The axial clamping Length short	Increase clamping length
	The taper in workpiece	Process workpiece surface
	The input torque small	Increase the input torque
	Over the clamping range	Replace chucks
	Lubrication is poor	More lubricate
Poor accuracy	In using clamping are or working dirty	Maintenance jaws and workpiece clean when working
	When replace jaws, No. 1, 2, 3 jaws wrong	Mount the jaw in order
	Something wrong with the short-taper chucks	Adjust the chucks mounting position
	Short-taper surface dirty when mounting chucks	Maintain the short-taper clean
	Mismatched adapter not conform the mounting dimension	Matched adapter conform to demand
	Adapter plates with thickness or seton tolerance too large	Matched adapter conform to demand
	Impurity things in the top jaw and base jaw	Keep top jaws and base jaws mounting face clean when replace jaws
	The clamping arc taper not conform dimension	Replace jaws
Gear shall not work	Impurity thing in the chucks	Clean and lubricate
	Lubrication is poor	Lubricate



CLAMPING RANGE

D MODEL Size	Internal Jaws		External Jaws
	Clamping range	Clamping range	Clamping range
	A-A1	B-B1	C-C1
80	2~22	25~70	22~63
100	2~30	30~90	30~80
125	2.5~40	38~125	38~110
130	3~40	40~130	40~120
160	3~55	50~160	55~145
165	4~60	52~165	55~150
190	4~70	65~190	65~190
200	4~85	65~200	65~200
240	6~100	80~250	90~250
250	6~110	80~250	90~250
315	10~140	95~315	100~315
320	10~140	95~320	100~320
325	10~140	95~325	100~325
380	15~210	120~380	120~380
400	15~210	120~400	120~400
500	25~280	150~500	150~500
630	50~350	170~630	170~630
800	150~450	300~800	300~800
1000	290~600	430~1000	430~1000

STANDARD ACCESSORIES

K11-100, K11-125, K11-160, K11-200, K11-250

PART NO.	DESCRIPTION	QTY
1	Key chuck	1
2	Screw	3
3	Reverse jaws (3 pieces)	1

K11-200A, K11-250A

PART NO.	DESCRIPTION	QTY
1	Key chuck	1
2	Screw	3
3	Hexagon wrench	1

Manufacturer: Shanghaimuxinmuyeyouxiangongsi

Address: Shuangchenglu 803nong11hao1602A-1609shi, baoshanqu, shanghai 200000 CN.

Imported to AUS: SIHAO PTY LTD, 1 ROKEVA STREETEASTWOOD NSW 2122 Australia

Imported to USA: Sanven Technology Ltd., Suite 250, 9166 Anaheim Place, Rancho Cucamonga, CA 91730

EC	REP
----	-----

E-CrossStu GmbH

Mainzer Landstr.69, 60329 Frankfurt am Main.

UK	REP
----	-----

YH CONSULTING LIMITED.

C/O YH Consulting Limited Office 147, Centurion House, London Road, Staines-upon-Thames. Surrey. TW18 4AX

Made In China