jax-experiments writeups Milestone M3

# M3 — Sweeps as one program, optimisers, gradient noise (N1, O3, N2)

A writeup in the jax-experiments series, built on 2026-10-30 from `docs/m3-sweeps-optimisers-noise.md`. Its data, scripts and the work order (`PLAN.md`) are in the same repository.

## Contents


**N1 — Hyperparameter sweeps as one program** **1**
- Question . . . 1
- The idea . . . 1
- The math . . . 2
- What we measure and why . . . 2
- What I built . . . 2
- Results . . . 2
- What surprised me . . . 5
- Open threads . . . 5

**O3 — Optimisers beyond Adam** **5**
- Question . . . 5
- The idea . . . 5
- The math . . . 6
- What we measure and why . . . 6
- What I built . . . 6
- Results . . . 7
- What surprised me . . . 8
- Open threads . . . 8

**N2 — Gradient noise scale and the critical batch size** **9**
- Question . . . 9
- The idea . . . 9
- The math . . . 9
- What we measure and why . . . 9
- What I built . . . 10
- Results . . . 10
- What surprised me . . . 11
- Open threads . . . 12


### At a glance

**Status:** done (N1, O3, N2) ·
**Hardware:** Kaggle T4 ×2 (sm_75, one job per GPU), JAX 0.11.1; CPU (4 cores) for the equivalence tests ·
**Data:** N1: `data/n1-summary.json` and `data/n1/` (one JSON and log per job); O3: `data/o3-summary.json` and `data/o3/`; N2: `data/n2-summary.json` and `data/n2/`; ml-ladder's references from its `docs/writeups/data/c-gpu-lr.json` and `c-gpu-lr2-1024.json` ·
**Reproduce:** `uv run python tools/kaggle/push_r2.py <preset> --push` for `n1-calibrate`,

`n1`, `n1-fork` and `n1-fork-torch`, then `uv run python experiments/n1_vmap_sweep/analyze.py`; O3: presets `o3-stage1` to `o3-stage4`, then `uv run python experiments/o3_optimizers/analyze.py`; N2: presets `n2`, `n2-ext` and `n2-noise32`, then `uv run python experiments/n2_noise_scale/analyze.py`. CPU tests: `uv run pytest tests/test_n1_sweep.py tests/test_o3_optimizers.py tests/test_n2_noise.py`

## N1 — Hyperparameter sweeps as one program

### Question

ml-ladder's Part C §7 tuned the 4M transformer's learning rate with 18 separate runs. Can one vmapped program train all of them at once, and how much faster is it?

### The idea

**A sweep is K copies of the same computation.** In JAX, training is a pure function `step(params, opt_state, batch, lr)`. Stack K copies of every argument on a leading axis, and `jit(vmap(step))` trains all of them in one compiled program. The learning rate is just another vmapped argument.

So is everything else that differs between the runs:

- each copy's loss scale;
- its skipped steps;
- its batch stream: ml-ladder's runs of one seed share batches, so copies of one seed share one draw per step.

**Two questions, kept apart:**

- **Is it the same experiment?** Each copy of (lr, seed) starts from ml-ladder's initial weights for that seed and sees that seed's batches, so it can be paired with ml-ladder's run.
- **Is it faster?** Total throughput of K copies in one program, against one copy, which is the rate of K sequential runs.

### The math

`vmap` turns every operation on a $[\ldots]$-shaped array into one on a $[K, \ldots]$-shaped array:

- a matmul $xW$ becomes a batched matmul $x_k W_k$;
- per-copy scalars (the loss, the gradient norm used for clipping, the loss-scale decision) become $[K]$-vectors.

Nothing couples the copies, so copy $k$ computes exactly what its sequential run would, up to the order of floating-point reductions.

The speedup has a simple ceiling. If one copy already keeps the GPU's arithmetic units busy, K copies take K times as long. vmap can only win back idle time: kernel-launch overhead, small matmuls that underfill the device, Python between steps.

### What we measure and why

- **Equivalence (CPU).** Two seeds × two learning rates, vmapped against four sequential runs. Checked in fp32 and fp16, for a GRU and a transformer.

- **The sweep (T4).** ml-ladder's §7 grid: peak learning rates {3e-4, 6e-4, 1e-3, 2e-3, 4e-3, 8e-3} × seeds 0–2, for the 4M transformer at T=1024. Each run is 3,000 steps of 16 × 1024 bytes, then per-position bits/byte on 262,144 validation bytes. It ran as six programs of three copies.
- **Memory.** XLA's compiled temp memory for K = 1 to 18 copies, with and without per-block remat.
- **Throughput.** Steady tokens/s for K = 1, 2, 4, 8 (and up to 32 for small models), over 200 steps each. Measured on ml-ladder's 4M model and on two much smaller transformers (width 128 and 64, depth 2) at the same 16 × 1024 tokens per step.

## What I built

- **`jaxexp.sweep.train_many`:**
  - stacks K copies of parameters, optimiser state and loss scale;
  - runs `jit(vmap(make_step(...)))`;
  - follows each copy's own schedule;
  - draws each unique batch stream once per step.

  It returns one `TrainResult` per copy.
- **`tests/test_n1_sweep.py`:** vmapped copies equal sequential runs.
- **`experiments/n1_vmap_sweep/`:**
  - `run.py`, with `memory`, `throughput` and `sweep` studies;
  - `analyze.py`.
- **The Kaggle runner** now accepts jobs for any experiment script, and gives JAX 92% of the card instead of 75%.

## Results

**On CPU, vmap computes what the sequential runs compute.**

| | loss histories | all parameters (relative) | outputs on held-out data |
|---|---|---|---|
| fp32 | within $10^{-6}$ | within $10^{-6}$ | within $10^{-6}$ |
| fp16 | within $3 \times 10^{-3}$ | within $3 \times 10^{-3}$ | within $3 \times 10^{-3}$ |

Measured, the fp32 parameter differences are $9 \times 10^{-8}$ to $3 \times 10^{-7}$.

One tensor needed explaining: the attention key bias. Per tensor it differs by up to 5% in fp16. Its true gradient is exactly zero, because adding a constant vector to every key shifts all of a query's logits equally, and the softmax ignores that. So its gradient is pure round-off, which Adam scales up to full-size steps in either program. It has no effect on the outputs.

**On the T4, the sweep reproduces ml-ladder's curve.**

| peak LR | ml-ladder bits/byte | JAX, vmapped (3 per program) | largest per-seed difference |
|---|---|---|---|
| 3e-4 | 3.0279 (3.0259–3.0322) | 3.0272 (3.0261–3.0312) | 0.0010 |
| 6e-4 | 2.4353 (2.4041–2.5574) | 2.4358 (2.4002–2.5548) | 0.0040 |

| peak LR | ml-ladder bits/byte | JAX, vmapped (3 per program) | largest per-seed difference |
|---|---|---|---|
| 1e-3 | 2.0441 (2.0123–2.2154) | 2.0470 (2.0140–2.2166) | 0.0029 |
| **2e-3** | **1.8250** (1.8229–1.8283) | **1.8239** (1.8203–1.8324) | 0.0095 |
| 4e-3 | 1.8427 (1.7427–2.0220) | 2.0378 (1.7692–2.0624) | 0.2197 |
| 8e-3 | 2.1271 (2.0509–2.2613) | 2.1067 (2.0571–2.1159) | 0.1454 |

- **The best learning rate is the same: 2e-3**, at 1.824 against 1.825.
- **Up to the optimum, all 12 pairs agree within 0.0095.** At these learning rates the seed-to-seed spread is often wider than that (6e-4: 0.15 in ml-ladder's own runs). So pairing by seed is doing real work: it takes the seed noise out of the comparison.
- **Above the optimum, pairs diverge** by up to 0.22 bits/byte. Yet our ranges overlap ml-ladder's, and its own seed spread there is 0.28 (4e-3) and 0.21 (8e-3). The largest gap, seed 2 at 4e-3, is a fork. Both runs are together through step 750 (2.153 against 2.137). Then ours stalls near 1.67 from step 1,250 to 1,750, while ml-ladder's falls to 1.45.

  **A control traced this fork to PyTorch's own run, not to JAX or vmap.**

| seed 2, lr 4e-3, 3,000 steps | bits/byte |
|---|---|
| ml-ladder's recorded PyTorch run (2026-10-08) | 1.8427 |
| ml-ladder's script, rerun twice (same torch 2.11.0+cu128, T4) | 2.0121, 2.0413 |
| JAX, sequential (R2's runner), twice | 2.0545, 2.0479 |
| JAX, vmapped group of 3, twice | 2.0624, 2.0485 |

  - **All six fresh runs land together,** PyTorch and JAX, sequential and vmapped (2.01–2.06). The recorded 1.8427 is the outlier: PyTorch took the other branch once and did not reproduce it.
  - **Neither framework's T4 runs are deterministic,** so above the optimum one run per (lr, seed) samples a distribution. Its spread at 4e-3 is at least 0.22 bits/byte.

**vmap does not make this sweep faster.**

| copies K | 4M, total tok/s (no remat) | 4M, with remat | width-128 transformer | width-64 transformer |
|---|---|---|---|---|
| 1 | 132.5k (1.00×) | 103.2k (1.00×) | 385k (1.00×) | 436k (1.00×) |
| 2 | 130.9k (0.99×) | 104.4k (1.01×) | 370k (0.96×) | 456k (1.04×) |
| 4 | 132.4k (1.00×) | 106.1k (1.03×) | 402k (1.04×) | 473k (1.08×) |
| 8 | out of memory | 107.6k (1.04×) | 400k (1.04×) | 484k (1.11×) |





**Figure 1.** Left: the learning-rate sweep, ours (vmapped) against ml-ladder's sequential runs. Right: throughput of K copies relative to one

- **A single copy already saturates the T4** at 16 × 1024 tokens per step. So K copies take K times as long, and total throughput is flat in K.
- **It stays nearly flat even for a 0.2M-parameter transformer** (1.11× at K=8). With T=1024 and 16 sequences per step, each step's attention and matmuls are large enough to fill the GPU whatever the model width.
- **Memory caps K before speed matters.** XLA's temp memory is 2.87 GiB per copy without remat, so K=4 fits (12.0 GiB) and K=6 does not (15.0 GiB, against 13.8 GiB available). Per-block remat cuts it to 1.26 GiB per copy, so K=8 fits, at 0.78× the speed.
- **The whole sweep cost 1.97 GPU-hours** (six programs of 1,137–1,233 s), against ml-ladder's 1.03 (18 runs × 205 s median). That 0.52× is the same JAX-against-PyTorch gap R2 measured for this model (0.53×), not a cost of vmap.

What vmap *does* buy is that the sweep is one program:

- each group compiles once (9–17 s), not once per run;
- all the copies share one data pipeline;
- the grid is one command and one JSON. N1's sweep tool is now ready for O3 and N2.

## What surprised me

**PLAN's premise came from the wrong regime.** The image probe found that K = 8 copies cost 4.4× one copy, which promised a 1.8× speedup. That probe was a small recurrence whose single copy left the GPU idle. ml-ladder's protocol feeds 16,384 tokens per step, which fills a T4 even with a 0.2M model. The speedup from vmap is the GPU's idle fraction, and here there is almost none.

**The attention key bias.** Its gradient is exactly zero by symmetry. That showed up as a 5% per-tensor mismatch in what should have been an equality test, and it is invisible in any loss.

**The biggest disagreement in the sweep was PyTorch disagreeing with itself.** The one pair that looked like a framework difference (0.22 bits/byte) did not survive reruns. ml-ladder's own script, on the same torch version and the same GPU type, landed with JAX (2.01 and 2.04), not at its recorded 1.84. At learning rates above the optimum, runs with identical weights and batches split apart, and nondeterministic GPU arithmetic decides which side a run lands on. The R3 copy task (M2) showed the same thing near its plateau. A single run per configuration in this regime is a draw, not a measurement.

### Open threads

- **The small-batch regime.** vmap should pay when one copy cannot fill the device: small batches, short contexts, small models. That is the setting of many hyperparameter studies, and it was not measured here.
- **Deterministic GPU runs** (`--xla_gpu_deterministic_ops`; `torch.use_deterministic_algorithms`) to separate implementation from nondeterminism without repeats.
- **The fork's distribution.** How often does seed 2 at 4e-3 reach about 1.84 rather than about 2.05? Ten repeats would put a number on ml-ladder's luck. The same applies to its 4e-3 entry in §7's table.
- **O3 and N2,** using this sweep tool.

## O3 — Optimisers beyond Adam

### Question

ml-ladder's B5 thread asks about Lion and Shampoo, and whether second-moment scaling is the right primitive at all. On R2's 4M transformer, with every optimiser at its own tuned learning rate, does anything beat AdamW?

### The idea

**Three answers to "how should a step be shaped?"**

- **AdamW** divides each coordinate's momentum by a running RMS of its gradient: second-moment scaling.
- **Lion** keeps only the *sign* of an interpolated momentum, so every coordinate moves by exactly the learning rate. It has no second moment at all.
- **Muon** orthogonalises the momentum of each weight matrix. It replaces $M = U\Sigma V^\top$ by roughly $UV^\top$, so every direction in the matrix's row and column spaces moves equally. That is Shampoo's preconditioner $(GG^\top)^{-1/4}\,G\,(G^\top G)^{-1/4}$ without its running accumulation: second-moment scaling of a whole matrix, rather than of each coordinate.

**Tune every arm** (ml-ladder §7, and CLAUDE.md). An untuned baseline produces a fake winner. Each optimiser gets its own learning-rate sweep on seed 0, extended until the best value is interior. Seeds 1–2 then run at that value.

**N1's sweep tool makes this cheap to run:** each grid is one or two vmapped programs.

### The math

With momentum $m_t$, gradient $g_t$ and peak LR $\eta$ (on ml-ladder's schedule), and decoupled weight decay $\lambda$:

- **AdamW:** $\theta \mathrel{-}= \eta\,(\hat{m}_t/(\sqrt{\hat{v}_t}+\epsilon)+\lambda\theta)$, with $\beta = (0.9, 0.95)$ and $\lambda = 0.1$ (the protocol).
- **Lion:** $\theta \mathrel{-}= \eta\,(\mathrm{sign}(\beta_1 m_{t-1} + (1-\beta_1)g_t) + \lambda\theta)$, $m_t = \beta_2 m_{t-1} + (1-\beta_2)g_t$, with $\beta = (0.9, 0.99)$. Since $|\text{update}| = \eta$, Lion's good learning rates are 3–10× smaller than AdamW's. So $\lambda = 1.0$, ten times AdamW's, to keep $\eta\lambda$ comparable, as the Lion paper recommends.
- **Muon** on each hidden matrix $W \in \mathbb{R}^{n_{\text{in}} \times n_{\text{out}}}$: $W \mathrel{-}= \eta\,(\sqrt{\max(1, n_{\text{out}}/n_{\text{in}})}\ \mathrm{NS}_5(\tilde{m}_t) + \lambda W)$.
  - $\tilde{m}_t$ is Nesterov momentum with $\beta = 0.95$.

  - $NS_5$ is five steps of the quintic Newton–Schulz iteration that pushes the singular values towards 1.
  - $\lambda = 0.1$.

  Embeddings, the output head, biases and LayerNorm stay on the protocol's AdamW, at AdamW's tuned peak, on the same schedule.

### What we measure and why

- **Setting:** the 4M transformer (learned positions) at T=256, batch 64 (16,384 tokens per step), 3,000 steps, fp16 with fused attention. Every run starts from ml-ladder's initial weights.
- **Anchor:** the AdamW arm at 2e-3, 4e-3 and 8e-3 must match ml-ladder's own runs at this setting (`c-gpu-lr2-256.json`).
- **Per optimiser:**
  - the LR curve on seed 0;
  - bits/byte at the best LR over seeds 0–2, as median (min–max);
  - steps to reach AdamW's training loss, at two levels: its level at step 1,500, and its final level. The loss is smoothed as the mean of 8 consecutive logs (200 steps), placed at the window's centre step. With a fixed-length cosine schedule, every run reaches the final level only near the end, so the halfway level is the informative one.

### What I built

- **`jaxexp.train.optimizer(kind=adamw|lion|muon).`** The AdamW path is unchanged: R2's parity tests pass.
- **Muon is assembled from `optax.contrib.scale_by_muon` and the protocol's AdamW, via `optax.partition`.** optax's ready-made `muon(nesterov=True)` also applies Nesterov to its AdamW branch, which makes that branch NAdam, with first steps 1.47× larger. A test caught it.

  The AdamW part has its own peak. It follows the schedule through an injected `schedule` multiplier, so one vmapped program can sweep Muon's LR while the AdamW part holds still.
- **`tests/test_o3_optimizers.py`:**
  - Lion's first step is exactly $\pm\eta$ per element;
  - Muon orthogonalises exactly the eight block matrices (singular values in the Newton–Schulz band);
  - everything else gets AdamW's exact first step;
  - both optimisers give the same losses vmapped as sequentially.
- **`n1_vmap_sweep/run.py`** gains `--optimizer`, `--weight-decay` and `--adam-peak`; `experiments/o3_optimizers/analyze.py` scores the results.

### Results

**The AdamW arm lands on ml-ladder's runs** at this setting (seed 0): 1.7141 against 1.7155 at 2e-3, 1.6462 against 1.6436 at 4e-3, and 1.6357 against 1.6239 at 8e-3. ml-ladder's grid stopped at 8e-3, its best value. Extending it shows that 8e-3 really is the optimum: 1.6e-2 gives 1.6912, and 3.2e-2 gives 1.7475.





**Figure 2.** Left: each optimiser's LR sweep on seed 0, with seeds 0-2 at its best LR (squares). Right: smoothed training loss at each optimiser's best LR, seeds 0-2; dotted and dashed lines are AdamW's halfway and final levels

| optimiser (tuned) | peak LR | weight decay | bits/byte, seeds 0–2 | steps to AdamW's halfway loss | tokens/s (T4) |
|---|---|---|---|---|---|
| AdamW (protocol) | 8e-3 | 0.1 | 1.6335 (1.6333–1.6357) | 1,362–1,537 | 240k |
| **Muon** (+ AdamW at 8e-3) | 2e-2 | 0.1 | **1.6190** (1.6186–1.6212) | **1,212–1,462** | 172k (0.72×) |
| Lion | 3.2e-3 | 1.0 | 1.7056 (1.6976–1.7063) | 2,312–2,387 | 234k |

- **Muon is best, by 0.0145 bits/byte.** Its three seeds (1.6186–1.6212) and AdamW's (1.6333–1.6357) do not overlap. It reaches AdamW's halfway training loss about 1.13× sooner in steps (median 1,312 against 1,487).
- **But Muon costs more per step.** Five Newton–Schulz iterations on every matrix make it run at 0.72× AdamW's throughput on the T4. Measured in time, it reaches the halfway loss about 23% *later*: 1,312 steps at 1.40× the cost per step is worth about 1,830 AdamW steps. Whether AdamW given 40% more steps would close the 0.0145 gap was not measured.
- **Lion is clearly worse here, after tuning both of its knobs.**
  - Its LR curve is flat around its optimum: 1.7079, 1.7063 and 1.7096 at 2.4e-3, 3.2e-3 and 4.8e-3. It diverges from 1.28e-2.
  - Weight decay matters, and 1.0 is an interior optimum. At 3.2e-3, wd 0.1 gives 3.68 (unstable), 0.3 gives 2.07, and 1.0 gives 1.71; at 1.6e-3, wd 3.0 gives 1.79.
  - The gap to AdamW is 0.072 bits/byte, and Lion needs about 1.6× as many steps to reach AdamW's halfway loss.
- **fp16 was healthy at every tuned setting:** no skipped steps. Steps were skipped only in runs that diverged or nearly did (Lion at 1.28e-2 and above, or with wd 0.1).
- **Cost.** O3 took four kernels: 36 runs of 3,000 steps, as 14 vmapped programs of 2–3 copies, totalling 2.33 GPU-hours of program time on T4s.

### What surprised me

**Lion needs its weight decay.** Lion's step has a fixed size, so without enough decay the weights grow until the sign updates are relatively too small to steer them. Lowering λ from 1.0 to 0.3 cost 0.37 bits/byte at 3.2e-3, and 0.1 made the run unstable. The Lion paper's rule of thumb (λ 3–10× AdamW's) is not a nicety; here it is most of the tuning.

**Lion loses at this batch size.** Lion's own paper reports its gains at large batches. Here a step is 64 sequences of 256 bytes, and the sign of a noisy momentum throws away the magnitude information that AdamW keeps. That is a hypothesis, not a measurement; the batch-size axis is N2's.

**optax's Muon is not plain Muon.** `optax.contrib.muon(nesterov=True)` also turns the AdamW it applies to non-matrix parameters into NAdam: a 1.47× larger first step, and a different optimiser for embeddings and the head. It only showed up because the test computed AdamW's first step by hand. The first version of that test failed on gradient clipping and on Adam's ε before it was exact.

**A step-count win can be a wall-clock loss.** Muon's 1.13× fewer steps become a 23% slower time on a T4, where five Newton–Schulz iterations per matrix are not hidden behind anything.

### Open threads

- **Equal-time comparison.** Give AdamW 1.4× the steps, so it has Muon's wall-clock time, and see whether Muon's 0.0145 survives.
- **Muon's details:**
  - orthogonalise q, k and v separately rather than the fused 256×768 matrix;
  - tune its AdamW part's LR jointly;
  - try fewer Newton–Schulz steps, or bf16 iterations on hardware with fast bf16.
- **Lion at larger batches.** Use N2's critical batch size to choose where to look.
- **Longer runs and the 25M model.** 3,000 steps of a 4M model is a short horizon; the ranking may not hold at R2's 12,000 steps.
- **A Shampoo-family optimiser proper** (`distributed_shampoo`, SOAP or PSGD-Kron), once one runs with optax 0.2.8. `psgd-jax` 0.2.9 imports optax internals that no longer exist.

## N2 — Gradient noise scale and the critical batch size

### Question

ml-ladder's B5 thread names the learning-rate/batch-size scaling rule as a scaling-law question. The gradient noise scale (McCandlish et al., 2018) claims to predict, from gradients alone, the critical batch size: the batch beyond which doubling the batch no longer halves the steps. Measured on R2's 4M transformer, does it?

### The idea

**A step averages B noisy per-example gradients.** When the noise in that average dominates, a bigger batch buys a proportionally better step, and doubling B halves the steps. When the signal dominates, extra examples are wasted. The crossover is

where the noise in a batch-B gradient, tr Σ / B, is about as large as the signal |G|². That is, B ≈ tr Σ / |G|², the *simple noise scale*.

**JAX makes the measurement one line.** `vmap(grad)` over the batch axis gives every example's gradient at once.

**Test the prediction directly.** Train at three batch sizes, each with its own tuned learning rate, and count the steps to fixed losses. Fit the paper's step–batch relation, and compare its B_crit with B_simple measured at the same loss.

### The math

With per-example gradients $g_i$, their mean $G$ and covariance $\Sigma$: $\mathbb{E}\,\overline{|g_i|^2} = |G|^2 + \operatorname{tr}\Sigma$ and $\mathbb{E}\,|G_B|^2 = |G|^2 + \operatorname{tr}\Sigma/B$.

So one batch gives unbiased $\widehat{\operatorname{tr}\Sigma} = (\overline{|g_i|^2} - |G_B|^2)\,B/(B-1)$ and $\widehat{|G|^2} = (B|G_B|^2 - \overline{|g_i|^2})/(B-1)$. Then $B_{\text{simple}} = \widehat{\operatorname{tr}\Sigma}/\widehat{|G|^2}$, a ratio of averages over batches. A ratio of single-batch estimates would be biased.

McCandlish et al. find that the steps $S$ and examples $E$ to reach a fixed loss trade off as $(S/S_{\min} - 1)(E/E_{\min} - 1) = 1$. With $E = BS$, that means $S(B) = S_{\min}(1 + B_{\text{crit}}/B)$, where $B_{\text{crit}} = E_{\min}/S_{\min}$. They report $B_{\text{crit}} \approx B_{\text{simple}}$ when the Hessian is close to a multiple of the identity, and $B_{\text{simple}}$ underestimating it otherwise.

### What we measure and why

- **Model and protocol:** R2's 4M transformer at T=256, AdamW as the protocol, from ml-ladder's initial weights. B counts sequences of 256 bytes, and an "example" is one sequence.
- **Noise run.** B=64 (the protocol's 16,384 tokens per step) at O3's tuned LR of 8e-3, 6,000 steps. Every 250 steps, B_simple is computed in fp32 on 8 fresh batches of 64 from a sampler separate from training.
- **Batch runs.** B = 16, 64 and 256, with 12,000, 6,000 and 3,000 steps respectively. Each has a three-point LR grid centred on √-scaling from 8e-3 at B=64: {2, 4, 8}e-3, {4, 8, 16}e-3 and {8, 16, 32}e-3.
- **The schedule is warmup-then-constant, not the protocol's cosine.** With a cosine decay, the step at which a loss is first reached depends on the run's total length.
- **Steps to a target:** the first step at which the training loss, smoothed over 8 logs (200 steps), reaches L, at the best LR for that batch size. Targets L from 1.6 down to 1.2 nats.

### What I built

- **`jaxexp.noise`:**
  - `make_per_example`: `vmap(grad)` in chunks, returning each example's $|g_i|^2$ and the gradient sum;
  - `batch_estimates`: the unbiased pair above;
  - `noise_scale`: the ratio of averages.
- **`tests/test_n2_noise.py`:**
  - vmapped per-example gradients equal an explicit loop;
  - their mean equals the batch gradient;
  - the estimates are unbiased on a synthetic population (within 2% and 5%);
  - a known B_simple of 10 is recovered within 5%.

- **`jaxexp.train`:** a `warmup-constant` schedule, and an `on_log(step, params)` hook whose time is excluded from the training time.
- **`experiments/n2_noise_scale/`:** `run.py` (`noise` and `batch` studies) and `analyze.py`.

## Results





**Figure 3.** Left: B_simple through a B=64 run, three measurement series. Right: steps to reach six training losses at B = 16, 64, 256 (best LR each), the fit S_min(1 + B_crit/B), and the measured B_simple at each loss (dotted)

**The noise scale rises fast, then slowly.**

- **At initialisation** B_simple is about 1 sequence: every example's gradient points the same way.
- **At step 250** it is 9–15.
- **From step 500 to 2,750** the median is 44, with points ranging 29–60 (two seeds, 32 batches per point).
- **From step 3,000 to 6,000** the median is 62 (range 40–82).

Even at 32 batches per point the measurements scatter by up to ±30%, because $|G|^2$ is a small difference of large terms. The two seeds agree where it matters: at the losses below, they give B_simple = 42.0 and 42.4 (loss 1.6), and 38.6 and 42.6 (loss 1.5).

**Steps to each loss, at each batch size's best learning rate:**

| training loss | B=16 | B=64 | B=256 | fewer steps per 4× (16→64, 64→256) | B_crit (fit) | B_simple at that loss |
|---|---|---|---|---|---|---|
| 1.6 | 1,712 | 562 | 312 | 3.04×, 1.80× | 118 (fit within 5%) | 43 |
| 1.5 | 1,962 | 662 | 362 | 2.96×, 1.83× | 112 (3%) | 42 |
| 1.4 | 3,388 | 862 | 412 | 3.93×, 2.09× | 365 (17%) | 43 |
| 1.3 | 6,338 | 1,538 | 538 | 4.12×, 2.86× | 1,411 (14%) | 46 |

| training loss | B=16 | B=64 | B=256 | fewer steps per 4× (16→64, 64→256) | B_crit (fit) | B_simple at that loss |
|---|---|---|---|---|---|---|
| 1.25 | 8,438 | 2,162 | 662 | 3.90×, 3.26× | 1,140 (4%) | 45 |

*No B=16 run reaches 1.2 within its 12,000 steps (its best ends at 1.250), so that row is left out; with two points the fit would be exact. Every best LR is interior to its grid: the grid was extended downward once, and the new points changed no answer.*

- **Early in training, B_simple underestimates B_crit by about 2.7×.** At losses 1.6–1.5 the step–batch relation fits well (3–5%), with B_crit ≈ 112–118 sequences against a measured B_simple of 42–43. The direction is the one McCandlish et al. predict: B_simple is a lower estimate. Quantitatively, B_simple predicts 2.2× fewer steps for 16→64 and 1.4× for 64→256; the measured ratios are 3.0× and 1.8×.
- **Late in training, it fails as a predictor.** At losses 1.3–1.25, quadrupling the batch from 64 to 256 still saves 2.9–3.3× the steps, close to the perfect 4×. Yet B_simple has only risen to 45–46. At B=256 the run is still near-perfectly batch-efficient; B_simple would place the knee at about 45. Even B_crit = 256 would predict only 2.5× for 64→256, so the measured 2.9–3.3× puts B_crit above 256, more than 5× B_simple.
  - The fitted B_crit there (1,100–1,400) is an extrapolation: it lies well beyond the largest batch tried. Its size is not a measurement. The direction is: the critical batch outgrows the largest batch tested, while B_simple barely moves.
- **Learning rates.** At every loss, larger batches want equal or larger learning rates, and every batch size wants a lower one later. That is the expected shape for a constant schedule, and it is why each point needed its own grid.
- **Cost.** The batch study used about 2.2 GPU-hours of program time. The three 6,000-step noise runs took about 7 minutes each, and each measurement of 32 × 64 per-example gradients took 8.7 s.

### What surprised me

**The simple noise scale tracks the critical batch only early on.** McCandlish et al. present B_simple as a cheap stand-in for the critical batch. Here it is within a factor of 3 at the start of training, but late in training it misses by more than 5× (by the most conservative reading, B=256 is still nearly perfectly efficient). One explanation, not tested here: B_simple ignores curvature (the full noise scale is $\mathrm{tr}(H\Sigma)/G^\top HG$), and AdamW preconditions the gradient. The noise that matters for an Adam step is the noise in the *preconditioned* gradient, which the raw per-example gradients do not measure.

**My own measurement had a bias before the experiment did.** A trailing 200-step mean of the loss reports every crossing about 87 steps late. That is 22% of the B=256 step counts but 5% of the B=16 ones, enough to move the early B_crit from 82 to 118. It also changed O3's steps-to-target (Muon's advantage there is 1.13×, not 1.22×); O3's PR carries the correction.

**Per-example gradients really are one line.** `vmap(grad)` over the batch axis, in

chunks of 16, gave 2,048 per-example gradients of a 4M-parameter model in 8.7 s on a T4. The estimator was the hard part: its unbiasedness test needed a synthetic population, and its scatter needed four times the batches planned.

## Open threads

- **The preconditioned noise scale.** Measure B_simple on Adam's preconditioned gradients ($\hat{v}^{-1/2}g$), or the full $B_{\text{noise}}$ with a Hessian-vector product (`jax.jvp` of `grad`, as in O1). Does either track B_crit late in training?
- **Larger batches.** B = 1,024 and 4,096, to actually reach the late-training knee instead of extrapolating to it. On a T4 that needs gradient accumulation or remat (N1's memory table).
- **Seeds for the batch study.** One seed per (B, LR) here. The step counts' seed spread at fixed B is unmeasured.
- **The 25M model,** where ml-ladder's 12,000-step protocol sits.