ml-ladder · Part B writeup · compiled 2026-10-30

Deep learning foundations

Compiled from `docs/writeups/b-deep-learning.md`. Every number in it comes from the JSON under `docs/writeups/data/`, and every figure from `docs/writeups/figures/`.

Status

Status: complete (B1–B5) · **Constraint:** CPU only, subsets of the real datasets
Numbers: seeds 0–2, reference seed 0 · raw values in `data/b-metrics.json`
Reproduce: `ladder run B1 … B5` (needs `uv sync --extra torch`), or `uv run python tools/writeup_figures.py B`

Contents

B1 — A scalar autodiff engine 2
- The idea . . . 2
- The math . . . 3
- What we measure, and why . . . 3
- What I built . . . 4
- Results . . . 4
- What surprised me . . . 4
- Open threads . . . 4
- Further reading . . . 4

B2 — Matrix backprop against autograd 6
- The idea . . . 6
- The math . . . 6
- What we measure, and why . . . 7
- What I built . . . 7
- Results . . . 7
- What surprised me . . . 7
- Open threads . . . 8
- Further reading . . . 8

B3 — What batchnorm and dropout each do 9
- The idea . . . 9
- The math . . . 10
- What we measure, and why . . . 11
- What I built . . . 11
- Results . . . 11

What surprised me . . . 11
Open threads . . . 12
Further reading . . . 12

B4 — Residual blocks and the degradation problem **14**
The idea . . . 14
The math . . . 14
What we measure, and why . . . 15
What I built . . . 15
Results . . . 15
What surprised me — and the textbook story that did not reproduce . . . 16
Open threads . . . 16
Further reading . . . 16

B5 — SGD, Adam, AdamW, and the learning rate **18**
The idea . . . 18
The math . . . 18
What we measure, and why . . . 19
What I built . . . 20
Results . . . 20
What surprised me . . . 20
Open threads . . . 21
Further reading . . . 21

What part B settled **23**

Part A was four algorithms with four different search strategies. Part B is one algorithm — reverse-mode automatic differentiation on a composition of functions — applied five times, and the rungs are really about everything *around* it: how much the chain rule costs (B1), whether a framework computes what you derived (B2), what normalization and noise each buy (B3), why depth stops helping (B4), and which optimizer survives a badly chosen step size (B5).

The through-line: **every improvement in this part is a fix to optimization, not to expressiveness.** BatchNorm, residual connections and Adam all leave the function class untouched — a plain deep net can represent everything a ResNet can — and each one exists because gradient descent could not otherwise find the good parameters. The bargain from part A is the same, one level up: the enemy is not what the model can express but what the optimizer can reach.

Notation: $a^{(l)}$ is the activation of layer l, $z^{(l)} = a^{(l-1)}W^{(l)} + b^{(l)}$ the pre-activation, ϕ the nonlinearity, $\delta^{(l)} = \partial L/\partial z^{(l)}$, and $g_t = \nabla_\theta L$ the gradient at step t.

B1 — A scalar autodiff engine

Question. Backpropagation is the chain rule plus bookkeeping. What exactly is the bookkeeping, and what does doing it one number at a time cost?

The idea

Training a neural network means adjusting thousands (or billions) of numbers to make a loss smaller, and for that you need the **gradient**: for every parameter, how much the loss would change if you nudged it. Writing those derivatives by hand is hopeless for anything big. **Automatic differentiation** gets them mechanically.

The trick is to record every arithmetic operation as it happens, building a graph whose nodes are intermediate values. Each operation only needs to know its own *local* derivative (the derivative of $a \cdot b$ with respect to a is b, of $\tanh z$ is $1 - \tanh^2 z$, and so on). The chain rule then assembles the global gradient by walking the graph **backwards** from the loss, which is where the name *backpropagation* comes from.

This rung builds that engine one scalar at a time: every number in the network is its own graph node. That is the clearest possible version, and also the slowest, which is the other thing it measures.




Figure 1. A computation graph, forward and backward

Every box is one `Value`. The forward pass fills in each value from left to right. The backward pass starts from $\partial L/\partial L = 1$ and moves right to left. Each node's gradient is the sum, over the nodes that consumed it, of that consumer's gradient times the

local derivative. w and b are the parameters we would update. The numbers were produced by the rung's own engine.

The math

Reverse mode is the chain rule in reverse topological order. Take a DAG whose nodes are intermediate values and whose edges are elementary operations, with a single scalar output L. For a node v with consumers $u_1, \dots, u_k$, the multivariable chain rule gives

$$\frac{\partial L}{\partial v} = \sum_{i=1}^{k} \frac{\partial L}{\partial u_i} \frac{\partial u_i}{\partial v}.$$

Two consequences fall straight out of that sum, and they are the whole implementation. First, gradients must **accumulate** rather than assign — a node used twice contributes along both paths, which is why `x * x` only gets $2x$ right if `+=` is used. Second, $\partial L/\partial u_i$ must already be final before v is processed, which is exactly the definition of reverse topological order.

Why reverse and not forward. Forward mode propagates $\partial v/\partial x_j$ for one input x_j in a single pass: cost $O(N)$ per input, so $O(nN)$ for n parameters. Reverse mode propagates $\partial L/\partial v$ for one *output* in a single pass: $O(N)$ for **all** n parameters at once. With $n \sim 10^9$ and one scalar loss, that asymmetry is the reason deep learning is affordable at all; the price is memory, since every intermediate value must be kept for the backward pass.

The finite-difference check has a floor. A central difference expands as

$$\frac{f(x+h) - f(x-h)}{2h} = f'(x) + \frac{h^2}{6} f'''(x) + O(h^4),$$

so truncation error falls as h^2 while floating-point cancellation grows as ε/h. Balancing them puts the optimum at $h \approx \varepsilon^{1/3}$ ($\sim 6 \times 10^{-6}$ in double precision) with a best-case relative error around $\varepsilon^{2/3} \approx 4 \times 10^{-11}$. Agreement much tighter than that would mean the check is not actually independent; agreement much looser means a bug.

What we measure, and why

- **Maximum relative gradient error against finite differences.** A finite difference estimates a derivative by actually nudging a parameter and re-evaluating the loss. It needs no chain rule at all, so it is an independent check. Agreement to about 10^{-8} means the engine is right; a bug (a wrong sign, a missed accumulation) shows up at 10^{-1}.
- **Graph nodes per forward pass** — how much bookkeeping one evaluation creates, which is the memory cost of reverse mode.
- **Training time against the same network in numpy**, where the "graph" is a handful of matrix multiplies. The ratio is the price of doing the chain rule one number at a time, and the reason real frameworks work on whole tensors.
- **Test accuracy** — only to confirm both versions learned the same thing.

What I built

A `Value` node holding data, an accumulated gradient, and a closure that pushes gradient to its inputs; `backward()` does an **iterative** DFS for the topological order — a recursive one dies on a chain of a few thousand nodes, which a test pins by building exactly that. On top: `Neuron`, `Layer`, `MLP`, a numerically sane BCE, and `NumpyMLP` — the same architecture vectorized — as the control for the cost measurement.

Results

Setup: moons, 120 samples, MLP [2, 8, 8, 1] = 105 parameters.

quantity	seed 0	median (seeds 0–2)	range
max relative gradient error vs central differences	9.4e-09	1.9e-08	9.4e-09 – 1.4e-07
graph nodes for one full-batch forward	18,380	18,370	18,360 – 18,380
scalar-engine training time (60 epochs)	17.5s	18.1s	17.5 – 18.5s
same network in numpy	0.0054s	0.0052s	0.0050 – 0.0054s
slowdown	3,259x	**3,555x**	3,259 – 3,628x

Both implementations reach the same test accuracy, which is the point: the scalar engine is *correct* and useless, and the vectorized one is the same mathematics with the loops pushed into BLAS.

What surprised me

The gradient error — 1.9e-08 median, and as high as 1.4e-07 on one seed — sits three to four orders of magnitude above the $\varepsilon^{2/3}$ floor, and it *moves with the seed*. That is the summation: the loss is a sum over 90 samples, so the finite difference measures a quantity whose own accumulation error already exceeds a single term's, and how much depends on the particular weights. The check is still decisive — a wrong sign or a missing accumulation shows up at 10^{-1}, not 10^{-8} — but the floor is set by the *problem*, not by the arithmetic, and quoting one seed's 9.4e-09 as "the" precision would have been quoting noise.

Open threads

Checkpointing — recomputing activations instead of storing them — is the memory/compute trade the O(N) memory cost invites. Forward-mode for Jacobian-vector products, which is what you want for Hessian-vector products and hence second-order methods. And a tape-based (rather than closure-based) engine, which is closer to what real frameworks do.

Further reading

micrograd; Goodfellow et al. ch. 6.5; Baydin et al., *Automatic Differentiation in Machine Learning: a Survey*.




Figure 2. Training




Figure 3. Test accuracy




Figure 4. Decision boundary

B2 — Matrix backprop against autograd

Question. Does the hand-derived gradient equal what a framework computes — not approximately, but to floating-point?

The idea

A **multilayer perceptron (MLP)** is a stack of layers, each doing the same two things: multiply its input by a weight matrix (plus a bias), then apply a simple nonlinearity, here ReLU, $\max(0, z)$. Without the nonlinearity the whole stack would collapse into one matrix. With it, the network can bend the input space into shapes a linear model cannot.

For MNIST digits the input is 784 pixel intensities and the output is 10 scores, one per digit, turned into probabilities by **softmax**. The loss is **cross-entropy**: minus the log of the probability given to the correct digit.

Backpropagation for this network is three matrix equations (derived below), and this rung implements them by hand in numpy. It then asks whether PyTorch, started from the same weights and fed the same batches, computes the same gradients.




Figure 5. Forward and backward through the MLP

Forward (blue): the image passes through three matrix multiplies to become ten class scores. Backward (red): the error signal δ starts as "predicted probabilities minus the one-hot truth" and flows back through the transposes of the same matrices. Each layer's weight gradient is its input transposed times the δ arriving from above.

The math

Forward, one layer: $z^{(l)} = a^{(l-1)}W^{(l)} + b^{(l)}$, $a^{(l)} = \phi(z^{(l)})$.

The fused softmax/cross-entropy gradient. With $p = \mathrm{softmax}(z)$ and $L = -\log p_y$,

$$\frac{\partial L}{\partial z_k} = p_k - \mathbf{1}[k = y] \quad \Longrightarrow \quad \delta^{(L)} = \frac{P - Y}{n},$$

where Y is one-hot. The softmax Jacobian and the logarithm cancel exactly, which is why every framework fuses these two into one op: computing them separately is both slower and less stable.

The backward recursion. Differentiating the forward equations,

$$\delta^{(l)} = \left(\delta^{(l+1)}W^{(l+1)\top}\right) \odot \phi'\left(z^{(l)}\right), \qquad \frac{\partial L}{\partial W^{(l)}} = a^{(l-1)\top}\delta^{(l)}, \qquad \frac{\partial L}{\partial b^{(l)}} = \mathbf{1}^{\top}\delta^{(l)}.$$

For ReLU, $\phi'(z) = \mathbf{1}[z > 0]$ (any subgradient will do at 0). That is the entire algorithm — three lines, one matrix multiply each, and the transposes are where the bugs live.

He initialization follows from variance propagation. If W_{ij} are iid with variance σ_w^2 and $a^{(l-1)}$ has variance σ_a^2, then $\mathrm{Var}(z^{(l)}) = n_{\text{in}}\sigma_w^2\sigma_a^2$. ReLU zeroes half the distribution, halving the variance it passes on, so keeping activations stationary across depth needs $\sigma_w^2 = 2/n_{\text{in}}$ — otherwise the forward signal decays or explodes geometrically in the number of layers.

Stability. Softmax is computed on $z - \max_k z_k$: the shift leaves the result unchanged and bounds exp from above by 1.

What we measure, and why

- **Worst gradient difference, any tensor**, manual against PyTorch. This is the whole test: two implementations of the same math should agree to floating-point rounding (about 10^{-7} in float32), and a transposed matrix or a missing term would show up as a difference of order 1.
- **Relative to the gradient scale** — the same difference divided by the gradient's typical size, so it can be compared with float32's precision.
- **Test accuracy**, manual and PyTorch — should be identical to the fourth decimal place if the gradients are.
- **Training time** — whether the framework's generality costs anything at this size (it does).
- **First-layer filters** (figure) — each hidden unit's 784 weights drawn as a 28×28 image, which shows what pixel patterns the network learned to detect.

What I built

`ManualMLP` with the three equations above, and a torch `Sequential` **initialized from the same weights** — torch stores `Linear` weights transposed, which is the one place the comparison could quietly fail. Both then train on identical batch orders, so any divergence is arithmetic rather than luck.

Results

Setup: MNIST subset, 20k train / 5k test, 784-256-64-10.

quantity	seed 0	median (seeds 0–2)
worst gradient difference, any tensor	3.0e-07	2.4e-07
relative to the gradient scale	1.7e-06	1.7e-06
loss difference	0.0	2.4e-07
test accuracy, manual / torch	0.9638 / 0.9636	0.9638 / 0.9636
training time, manual / torch	2.18s / 2.36s	1.89s / 2.36s

Float32 has $\varepsilon \approx 1.2 \times 10^{-7}$, and the batch sums 512 terms, so a relative difference of 10^{-6} is exactly the expected accumulation — the two implementations are performing the same arithmetic in a different order.

What surprised me

The manual numpy implementation is *faster* than torch at this size. Framework overhead — dispatch, autograd bookkeeping, tensor allocation — is per-operation, and these operations are small enough that it dominates the FLOPs. Torch wins as soon

as the matrices are big enough, or the device is not a CPU; below that crossover, the "slow" implementation is the one with the abstraction.




Figure 6. Loss curves




Figure 7. Accuracy curves

Open threads

The same diff for convolution and batchnorm, where the backward pass is genuinely hard to derive and correspondingly easy to get wrong. And a `torch.autograd.gradcheck` pass, which does the finite-difference check B1 does but in double precision.

Further reading

Efficient BackProp (LeCun et al.); He et al., *Delving Deep into Rectifiers* (He initialization).




Figure 8. Gradient difference




Figure 9. First-layer filters

B3 — What batchnorm and dropout each do

Question. Both are called regularizers. Are they?

The idea

This rung adds two layers to a small **convolutional network (CNN)**. A convolution slides a small filter (3×3 pixels here) over the image, so the same few weights detect the same pattern wherever it appears. Stacking convolutions and pooling builds up from edges to textures to object parts.

- **Batch normalization (BN)** takes each channel's activations across the current mini-batch, subtracts their mean and divides by their standard deviation, then lets the network re-learn a scale γ and shift β. Every layer then sees inputs on a stable scale however the weights below have drifted.
- **Dropout** randomly switches off a fraction p of units at every training step and scales up the survivors. The network cannot rely on any single unit, which pushes it towards redundant, more general features. At test time nothing is dropped.

Both are routinely called "regularizers" (things that reduce overfitting). The rung's question is whether that is true of both, or whether one of them is really doing something else.




Figure 10. What BatchNorm and dropout do to activations

Left: BN moves a channel's activation distribution to mean 0, standard deviation 1, whatever it was before. Right: dropout silences a random half of the hidden units for one training step. The next step silences a different half.

The math

Batch normalization standardizes each channel over the batch and then re-learns a scale and shift:

$$\hat{x}_i = \frac{x_i - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}, \qquad y_i = \gamma \hat{x}_i + \beta.$$

The subtlety is the backward pass: μ_B and σ_B^2 are *functions of the batch*, so gradient flows through them too, giving

$$\frac{\partial L}{\partial x_i} = \frac{\gamma}{\sqrt{\sigma_B^2 + \epsilon}} \left[\frac{\partial L}{\partial y_i} - \frac{1}{m} \sum_j \frac{\partial L}{\partial y_j} - \hat{x}_i \frac{1}{m} \sum_j \frac{\partial L}{\partial y_j} \hat{x}_j \right].$$

Read the bracket: BN **removes the mean of the incoming gradient and its component along** $\hat{x}$. The update is projected orthogonal to the current activation direction, which is a strong statement about conditioning and says nothing about regularization.

Scale invariance, and why the learning rate can be larger. For $a > 0$, $\mathrm{BN}(aWx) = \mathrm{BN}(Wx)$, so the loss does not depend on the scale of the weights feeding a BN layer. Differentiating that invariance gives

$$\frac{\partial L}{\partial (aW)} = \frac{1}{a} \frac{\partial L}{\partial W},$$

so the gradient shrinks exactly as the weights grow — an automatic step-size adaptation. A step that would be catastrophic for a plain network gets damped as soon as it inflates the weights. (Ioffe & Szegedy explained BN by "internal covariate shift"; Santurkar et al. showed that story does not hold up and that the smoothing above is what matters.)

Dropout, in its inverted form, multiplies by a scaled Bernoulli mask:

$$y = \frac{m \odot x}{1 - p}, \qquad m_j \sim \mathrm{Bernoulli}(1 - p), \qquad \mathbb{E}[y] = x.$$

The expectation is preserved, so nothing needs changing at test time. For a linear model the expected loss under dropout equals the clean loss plus a penalty proportional to $\frac{p}{1-p}\sum_j \mathrm{Var}(x_j)\, w_j^2$ — a data-dependent L2. That derivation is why dropout is genuinely a regularizer, and BN's is not.

A small corollary: a convolution feeding a BN layer needs no bias, since BN subtracts the batch mean and any constant cancels. The rung drops it, and a test checks it stays dropped.

What we measure, and why

- **Test accuracy** — the headline, on held-out CIFAR-10 images (chance is 0.10).
- **Generalization gap** = train accuracy − test accuracy. This is the metric that separates the two mechanisms. A *regularizer* should shrink the gap (less memorisation). An *optimization aid* raises train and test accuracy together and can even widen the gap. Looking at test accuracy alone could not tell them apart.
- **Accuracy at 10× the learning rate** — a stress test. The math predicts BN makes training tolerant of large steps, so push the step size until the plain network breaks and see whether BN survives.
- **Time per epoch** — what each layer costs.

What I built

A four-conv network in two `conv-conv-pool` blocks, with BN and dropout as flags, run as a 2x2 ablation with shared data, schedule and seed — plus a learning-rate probe at 10x the base rate.

Results

Setup: CIFAR-10 subset, 5k train / 2k test, 8 epochs.

arm	test accuracy (seed 0)	median	generalization gap (median)
plain	0.404	0.432	+0.066
batchnorm	**0.564**	**0.564**	+0.130
dropout	0.420	0.457	**+0.062**
both	0.510	0.509	+0.056

BatchNorm is worth **+0.137 test accuracy at the median (+0.097 to +0.159)** and it *doubles* the generalization gap, from 0.066 to 0.130. Dropout gains about 2.5 points and leaves the gap essentially where it was (0.062 vs 0.066 — the narrowest of the four, but only just). So in this regime BN is unambiguously an optimizer aid rather than a regularizer; dropout is a mild regularizer whose effect is smaller than the seed spread on plain (0.405–0.447).

What surprised me

The learning-rate probe was sharper than the ablation, but less reliable than one seed suggested. At $\eta = 0.5$ the plain network collapses to chance on **all three seeds** (0.094–0.098 — it learns nothing at all). The batchnorm network reaches 0.187 on seed 0 and 0.147 at the median, but on one seed it collapses too (0.094). The correct reading is therefore weaker than "BN lets you train at 10x the learning rate": at 10x,

BN turns certain failure into *sometimes* learning. Scale invariance damps the step, it does not license an arbitrary one.

Also worth noting: `both` is worse than `batchnorm` alone, because at an 8-epoch budget on 5k images the model is not overfitting enough for dropout's noise to pay for the slower fitting it causes.




Figure 11. Ablation accuracy




Figure 12. Generalization gap

Open threads

GroupNorm and LayerNorm, which drop the batch dependence that makes BN awkward at small batch sizes and in sequence models — and which is why part C's transformers use LayerNorm instead. BN's train/eval discrepancy (running statistics) as a source of real bugs. And the same ablation at a budget large enough to overfit properly, where dropout should overtake.

Further reading

Batch Normalization; Dropout; Santurkar et al., *How Does Batch Normalization Help Optimization?*




Figure 13. Learning-rate probe




Figure 14. Cost per epoch

B4 — Residual blocks and the degradation problem

Question. Deeper networks can represent strictly more. Why do they train worse?

The idea

Deeper networks can represent everything a shallower one can and more, since the extra layers could simply learn to pass their input through unchanged. In practice, making a plain CNN deeper eventually makes it *worse*, and worse on the training data too, so it is not overfitting. This is the **degradation problem**.

A **residual block** changes one thing: instead of a layer computing a new representation $F(x)$ from scratch, it computes a *correction* and adds it to its input, $x + F(x)$. The input travels along a **skip connection** (the "identity path") that has no weights on it. Two consequences:

1. Doing nothing is now easy: $F = 0$ passes the input through, so an extra block starts out harmless instead of having to learn the identity.
2. During backpropagation the gradient can flow straight down the skip path to early layers without being multiplied by every weight matrix on the way.




Figure 15. A plain block and a residual block

The two blocks have identical layers and parameters; the residual one adds its input back before the final ReLU. That one addition is the entire ResNet idea.

The math

The degradation argument. Let $\mathcal{N}_L$ be a network of L layers and $\mathcal{N}_{L+k}$ the same network with k extra layers. There *exists* a parameter setting for $\mathcal{N}_{L+k}$ that matches $\mathcal{N}_L$ exactly: make the extra layers identity maps. So the deeper model's optimal training loss can never be worse. When the deeper model nonetheless trains to a *higher* training loss — which is what happens — the failure is in the optimizer, not the hypothesis class. That is the observation the ResNet paper is built on, and it is why the evidence to look for is train accuracy, not test.

The fix is a reparameterization. A plain block computes $x_{l+1} = F(x_l)$; a residual block computes

$$x_{l+1} = x_l + F(x_l, W_l).$$

Unrolling gives an *additive* composition where the plain network has a multiplicative one:

$$x_L = x_l + \sum_{i=l}^{L-1} F(x_i, W_i), \qquad \frac{\partial L}{\partial x_l} = \frac{\partial L}{\partial x_L}\left(1 + \frac{\partial}{\partial x_l}\sum_{i=l}^{L-1} F(x_i, W_i)\right).$$

The 1 is a path from the loss to layer l that passes through **no weight matrix at all**. And "do nothing" is now the default: $F = 0$ gives the identity, so adding depth starts from the shallower solution rather than having to rediscover it.

What we measure, and why

- **Training accuracy across depth** (2, 4 and 8 blocks) — the metric where degradation shows. If a deeper network fits its own training data *worse*, the optimizer failed, because a solution at least as good exists. Test accuracy mixes that with generalisation, which is why it is the secondary number here.
- **Residual − plain test accuracy** at each depth, over three seeds — the practical payoff, with its seed spread reported because it turned out to be large.
- **Gradient norm per layer, and the first/last ratio** — the standard story says gradients vanish in deep plain nets. Measuring the norm at every layer tests that story directly. The ratio of first-layer to last-layer gradient norm measures how *unevenly* learning signal is spread across depth.

What I built

A block of two 3x3 convolutions with BN, a ReLU after the addition, and an identity shortcut wherever the shape allows (a 1x1 projection only where stride or channel count changes). The same stack with `residual=False` is the plain baseline. Networks of 2, 4 and 8 blocks, each trained both ways; plus a per-tensor gradient-norm measurement and a CIFAR-100 run.

Results

Setup: CIFAR-10 subset, 6k train / 2k test, 8 epochs, identical parameter counts within each depth.

Train accuracy, medians over seeds 0–2 (the column where degradation shows):

depth	plain train	residual train	plain test	residual test
2	0.478	0.462	0.437	0.428
4	0.540	0.565	0.470	0.513
8	**0.453**	0.545	0.419	0.477

There is the degradation: going from 4 blocks to 8, the plain network loses **8.7 points of training accuracy** — on data it is fitting, at an identical parameter count to its residual twin — while the residual network loses 2.0. Depth stops paying for the plain stack and keeps paying, roughly, for the residual one.

The test-accuracy gain is real but noisy: residual minus plain at depth 8 is **+0.072 at the median**, and the range is **−0.016 to +0.091** — on one seed of three the plain network finished ahead. The training-accuracy gap is the robust signal; the test gap at this budget is not, and a single-seed writeup claiming "+9 points" would have been overselling by a factor of the seed spread.

What surprised me — and the textbook story that did not reproduce

I expected to show vanishing gradients: small gradient norms at the early layers of the plain net, healthy ones with skips. The measurement says otherwise. With BatchNorm in every block, the plain network's first-tensor gradient norm is *comparable to or larger than* the residual network's. What does change, in every seed, is the **spread** of gradient magnitude across depth: the first/last tensor norm ratio is 5.0–9.0 for plain (median 5.4) against 2.9–3.9 for residual (median 3.1). The two ranges do not overlap.

So the honest statement is: BatchNorm already solved the magnitude problem, and residual connections solve a different one. He et al. say as much — they explicitly rule out vanishing gradients as the cause of degradation, and Balduzzi et al. later argued the real issue is that gradients in deep plain nets become *decorrelated* ("shattered"), which a norm cannot see. My test now asserts the ratio, not the magnitude, because that is the claim the data supports.




Figure 16. Depth curves

Open threads

Pre-activation ordering (BN-ReLU-conv rather than conv-BN-ReLU), which makes the identity path literally unobstructed. Measuring gradient *correlation* across depth rather than norm, to test the shattered- gradients account directly. And a plain net without BN, where the vanishing- gradient story presumably does reproduce.

Further reading

Deep Residual Learning; He et al., *Identity Mappings in Deep Residual Networks*; Balduzzi et al., *The Shattered Gradients Problem*.




Figure 17. Train accuracy — where degradation shows




Figure 18. Gradient flow




Figure 19. CIFAR-100

B5 — SGD, Adam, AdamW, and the learning rate

Question. Which optimizer actually wins — and is "wins" even the right question?

The idea

An **optimizer** decides how to turn a gradient into a parameter update. The choices compared here differ in what they remember:

- **SGD** steps straight down the current gradient: $\theta \leftarrow \theta - \eta g$. Simple, but along a narrow valley the gradient points mostly across it, so SGD zig-zags between the walls while inching along the floor.
- **Momentum** keeps a running sum of past gradients (a "velocity"). Components that keep flipping sign (across the valley) cancel out, and components that agree (along the valley) build up speed.
- **Adam** also tracks the running average of each parameter's *squared* gradient and divides by its square root. Every parameter gets its own step size, so steep and flat directions both take sensibly sized steps and the overall scale of the loss stops mattering.
- **AdamW** is Adam with weight decay (shrinking weights towards zero) applied *separately* from the gradient scaling instead of mixed into it. That sounds like a refactor, and the math below shows it is not.

A **learning-rate schedule** (cosine here) shrinks the step over training, which A1 showed is what removes the final jitter around the optimum.




Figure 20. Three optimizers on one valley

A loss 25× steeper in one direction than the other. SGD (red) bounces across the steep direction. Momentum (blue) takes a sweeping path that overshoots and comes back. Adam (green) rescales both directions and heads almost straight in. Real loss surfaces have millions of directions with wildly different curvatures, which is why the difference matters.

The math

SGD and momentum. Plain SGD is $\theta_{t+1} = \theta_t - \eta g_t$. Heavy-ball momentum accumulates

$$v_t = \beta v_{t-1} + g_t, \qquad \theta_{t+1} = \theta_t - \eta v_t.$$

For a constant gradient the velocity converges to $v_\infty = g/(1-\beta)$, so momentum multiplies the effective step by $1/(1-\beta) = 10$ at $\beta = 0.9$ — worth remembering when comparing learning rates between the two. Along high-curvature directions the oscillating gradients cancel in the sum; along low-curvature directions they accumulate. That is the whole mechanism.

Adam keeps exponential moving averages of the gradient and its square:

$$m_t = \beta_1 m_{t-1} + (1-\beta_1) g_t, \qquad v_t = \beta_2 v_{t-1} + (1-\beta_2) g_t^2,$$

$$\hat{m}_t = \frac{m_t}{1-\beta_1^t}, \qquad \hat{v}_t = \frac{v_t}{1-\beta_2^t}, \qquad \theta_{t+1} = \theta_t - \eta \, \frac{\hat{m}_t}{\sqrt{\hat{v}_t} + \epsilon}.$$

The bias corrections exist because $m_0 = v_0 = 0$ makes the raw averages underestimate by exactly $(1-\beta^t)$ early on. The property that matters in practice is **scale invariance**: replacing $g \to cg$ leaves $\hat{m}/\sqrt{\hat{v}}$ unchanged, so the step size is set by η and the parameter scale rather than by the magnitude of the loss. A badly scaled loss changes SGD's effective learning rate by orders of magnitude and leaves Adam's alone — which predicts a wider usable η band, and that is exactly what the sweep measures.

Why AdamW is not a refactor. Classic L2 adds $\lambda\theta$ to the gradient, so it flows through the same $1/\sqrt{\hat{v}}$ scaling as everything else:

$$\theta_{t+1} = \theta_t - \eta \frac{\hat{m}_t + \lambda\theta_t}{\sqrt{\hat{v}_t} + \epsilon} \qquad \text{(Adam + L2)},$$

$$\theta_{t+1} = \theta_t - \eta \left(\frac{\hat{m}_t}{\sqrt{\hat{v}_t} + \epsilon} + \lambda\theta_t \right) \qquad \text{(AdamW)}.$$

In the first, a parameter with a large gradient history gets a *smaller* decay — the regularization strength varies per parameter according to something that has nothing to do with regularization. In the second it is uniform. With SGD the two forms coincide (there is no $\sqrt{\hat{v}}$), which is why nobody noticed for years.

Cosine annealing takes $\eta_t = \eta_{\min} + \frac{1}{2}(\eta_{\max} - \eta_{\min})(1 + \cos(\pi t/T))$ — a decaying step that, in the language of A1, collapses the stochastic variance floor to a point.

What we measure, and why

- **Test accuracy after a fixed budget**, each optimizer at its *own* tuned learning rate — the fair bake-off. Comparing at one shared rate would just measure whose default happens to match.
- **Accuracy across a learning-rate sweep** spanning five orders of magnitude. This measures **robustness**: how much you need to know in advance to get a good result. In practice that often matters more than the best-case number.
- **Final weight norm** $\|w\|$ — the direct evidence for the Adam-vs-AdamW argument, since the two differ precisely in how hard they shrink the weights.
- **Constant vs cosine schedule** — whether decaying the step recovers the accuracy lost to end-of-training jitter.

What I built

Four optimizers, each at its own tuned learning rate (so the bake-off is not rigged by a shared η), crossed with constant and cosine schedules; then a learning-rate sweep across five orders of magnitude at a shorter budget; then Adam against AdamW at the same λ, tracking the final weight norm.

Results

Setup: FashionMNIST, 15k train / 5k test, MLP 784-256-128-10, 10 epochs.

optimizer	lr	constant (seed 0)	cosine (seed 0)	cosine median	final ‖w‖
SGD	0.1	0.808	0.855	—	13.0
SGD + momentum	0.05	0.854	**0.874**	**0.874**	16.3
Adam (L2 λ=0.05)	1e-3	0.789	0.802	0.799	3.9
AdamW (λ=0.05)	1e-3	0.868	0.871	0.867	16.6

Learning-rate sweep (3 epochs each), test accuracy:

optimizer	1e-4	1e-3	1e-2	1e-1	0.5
SGD	0.072	0.464	0.734	0.664	0.692
SGD + momentum	0.451	0.741	0.832	**0.842**	0.099
Adam	0.775	0.765	0.652	0.147	0.083
AdamW	0.808	**0.843**	0.829	0.721	0.170

What surprised me

Three things, in increasing order of how much they changed my mental model.

SGD with momentum wins the bake-off. Tuned, it beats AdamW — the folklore that Adam converges to worse minima than well-tuned SGD reproduces even at this tiny scale.

But the sweep is the real result — and it broke the metric I had designed for it. I logged `usable_lrs`, the number of rates within 80% of that optimizer's *own* best, expecting Adam-family to score higher. It comes back as 3 for every optimizer on every seed: a relative band says nothing, because a bad optimizer grades on its own bad curve. What the sweep actually shows is the *level* across the band. AdamW clears 0.72 at four of five rates spanning three orders of magnitude and tops out at 0.841; plain SGD never exceeds 0.737 anywhere in the sweep and is at chance-plus at 1e-4. Adam's advantage is not where the optimum is, it is how little you must already know to land near it — and measuring that takes an absolute yardstick, not a self-relative one.

Decoupling weight decay is worth 6.9 points at identical λ (+0.0686 median, range +0.064 to +0.069 — the tightest effect in the part). The weight norms say why: Adam's coupled L2 drives $\|w\|$ to 24% of AdamW's, a 4x over-shrinkage, because the decay was divided by $\sqrt{\hat{v}}$ along with the gradient. (With $\lambda = 0.05$ this is a deliberately strong setting; at the default 10^{-2} the gap is smaller but the same sign.)

And a callback to A1: SGD at a constant step *ends* at 0.813 (median) after *peaking* at 0.843. It is bouncing around the optimum on the variance floor — the same phenomenon, in the same repo, two parts apart. Cosine fixes it, worth +0.020 for SGD+momentum and +0.004 for AdamW, which is what you would expect when the optimizer already normalizes its own step.




Figure 21. Bake-off




Figure 22. Learning-rate sensitivity

Open threads

Warmup, which is what makes Adam work for transformers and which part C will need. Lion and Shampoo, as the current arguments about whether second-moment scaling is the right primitive at all. And the learning-rate/batch- size scaling rule, which is a scaling-law question and therefore part G's.

Further reading

Adam; Decoupled Weight Decay Regularization (AdamW); SGDR (cosine schedules).




Figure 23. Final accuracy




Figure 24. Weight norms

What part B settled

1. **One algorithm, five applications.** Reverse-mode AD is the only piece of machinery in this part. Everything else — normalization, skips, adaptive steps — exists to make the gradients it produces *usable*, not to change what the network can express.
2. **Every improvement here is an optimization fix.** BatchNorm conditions the update (and the scale-invariance derivation predicts the large-LR result), residual blocks reparameterize so that depth starts from identity, Adam normalizes away the gradient scale. The function class is untouched in all three cases.
3. **The textbook story failed once, and that was the most useful measurement.** "Residual connections fix vanishing gradients" does not survive contact with a plain net that has BatchNorm: its early-layer gradients are fine, and what the skips change is the spread across depth. The test asserts the spread now.
4. **Robustness beats optimality when you only get one run.** SGD+momentum wins the bake-off by 0.7 points at its tuned rate and never exceeds 0.737 across the sweep, where AdamW reaches 0.841. On a real problem the learning rate is a guess, and the wider basin is worth more than the better bottom — the honest case for Adam-family defaults.
5. **Three of five headline claims needed a seed range to state honestly.** The BN learning-rate probe collapses on one seed, the depth-8 residual gain flips sign on one seed, and B1's gradient-check precision moves by an order of magnitude. What survived every seed: the degradation in B4's training column, the gradient-spread ratio, and AdamW's decoupled-decay gain.
6. **Part A's variance floor came back.** Constant-step SGD peaked 4 points above where it finished. The fix was the same one: decay the step.

Cost of the part: ~2,000 lines including tests, 25 test cases, and a full run of all five rungs in about 12 minutes on four CPU cores (B4 alone is 6 of them) — 35x part A, and the reason every rung here takes a `--train-samples` flag.

Figures regenerate with `uv run python tools/writeup_figures.py B`; the numbers they are quoted against live in `data/b-metrics.json`. The part README is the short version of this document.