Part F — Geometric & equivariant nets

ml-ladder writeup · part F

2026-09-24

Contents

F1 — Rotation-equivariant CNN on a rotated-MNIST task, compared against a standard CNN **2**
The idea . . . 2
The math . . . 3
What we measure, and why . . . 4
What I built . . . 5
Results . . . 5
What surprised me . . . 5
Open threads . . . 7
Further reading . . . 7

F2 — GCN and GraphSAGE on a node-classification benchmark **8**
The idea . . . 8
The math . . . 8
What we measure, and why . . . 10
What I built . . . 10
Results . . . 11
What surprised me . . . 12
Open threads . . . 15
Further reading . . . 15

What part F settled **15**

Status: complete (F1–F2) · **Constraint:** MNIST subsets and Cora; CPU-only, so widths and budgets are small and stated per rung
Numbers: seeds 0–2, reference seed 0 · raw values in `data/f-metrics.json`
Reproduce: `ladder run F1`, `ladder run F2` (needs `uv sync --extra torch`), or `uv run python tools/writeup_figures.py F`
Hardware: both rungs swept on CPU (4 cores); no GPU was available and none is needed at these sizes

ties directly to your algebraic topology / equivariant cohomology background

Every network in parts B and H was already equivariant to a group, and nobody said so: convolution commutes with translation, which is exactly why a feature learned in one corner of an image is available in the other corner without being relearned. Weight sharing *is* the symmetry constraint, written as an implementation detail.

Part F takes that observation seriously in two directions. **F1** asks what happens when the group is enlarged — from translations to translations plus quarter turns — and finds that the answer is not "better accuracy" but something sharper and easier to check: a guarantee that holds to floating point, on inputs the network never saw, and stops dead at the edge of the group. **F2** goes the other way, to a symmetry so large it leaves almost nothing behind: relabel a graph's nodes and it is the same graph, so a layer must treat each neighbourhood as a set. Nearly every graph network in use is what survives that constraint.

The two rungs share a shape. In both, the architecture is not really a design choice — it is whatever is left once the symmetry is imposed — and in both, the interesting question is not *whether the constraint holds* (it does, by construction, and the tests check it) but **what it buys, and where it stops**. F1's guarantee stops at 45°. F2's stops when the neighbours stop being informative, and that point can be derived before it is measured.

A note on what is *not* here. There is no `escnn`, no PyTorch Geometric: both rungs build their layers from `torch.nn.Linear` and `rot90` so that the constraint is visible in the code rather than imported. That costs performance and buys the thing this ladder is for.

F1 — Rotation-equivariant CNN on a rotated-MNIST task, compared against a standard CNN

Question. Rotation augmentation and rotation equivariance both aim at the same property. Is the difference between them worth parameters — and what, exactly, is the difference?

The idea

A **symmetry** of a task is a transformation of the input that should not change the answer. A digit is still the same digit when it moves, and for many tasks also when it is turned. A network can be taught a symmetry in two ways:

- **augmentation** — show it rotated copies during training and hope it learns to cope. The network is still free to treat each angle differently, so the result is approximate, and only covers what it was shown.
- **equivariance by construction** — build layers that *cannot* distinguish a rotated input except by rotating their output. A normal convolution already does this for shifts: shift the image and the feature map shifts with it, because the same filter is applied everywhere.

A **group-equivariant CNN** extends the convolution trick from shifts to quarter-turn rotations (the group $p4$). The first layer applies each filter in all four orientations and keeps the four responses as a new "orientation" axis. Later layers convolve over position *and* orientation. At the end, taking the maximum over the four orientations gives a feature that does not change at all when the input turns by a multiple of 90°. No training is involved: it is a property of the wiring.




Figure 1: Equivariance, measured on F1's own layer

Top: a digit and the four orientation maps of one lifting filter. Bottom: the same digit turned 90°. Every map is turned 90° and the four maps have moved one slot along, exactly, to 4×10^{-7}*, with random weights. That bookkeeping is the whole of "equivariance".*

The math

Equivariance, and why convolution already has it. A map Φ is equivariant to a group G acting on its input and output when

$$\Phi(g \cdot x) = g \cdot \Phi(x) \quad \text{for all } g \in G,$$

and *invariant* when the action on the output is trivial. Cross-correlation with a filter ψ,

$$[f \star \psi](x) = \sum_{y \in \mathbb{Z}^2} f(y)\, \psi(y - x),$$

satisfies this for $G = \mathbb{Z}^2$ acting by translation, which is the entire argument for using it. Nothing in that argument is special to translations.

The group $p4$. Let r denote a quarter turn, so $C_4 = \{e, r, r^2, r^3\}$, and let $p4 = \mathbb{Z}^2 \rtimes C_4$ — translations and rotations, composed as

$$(r_1, x_1)(r_2, x_2) = (r_1 r_2,\ x_1 + r_1 x_2).$$

The semidirect product is the content: rotating then translating is not translating then rotating, and every formula below inherits that.

Lifting: $\mathbb{Z}^2 \to p4$. The input image lives on $\mathbb{Z}^2$ but the feature map must live on $p4$, so the first layer correlates against every rotated copy of the filter:

$$[f \star \psi](r, x) = \sum_{y \in \mathbb{Z}^2} f(y)\, \psi(r^{-1}(y - x))\,.$$

In code this is one convolution with a filter bank of four `rot90` copies of the same weights — one filter, four outputs, so the *parameters* do not grow at all while the feature maps quadruple.

Group convolution: $p4 \to p4$. Once both sides live on the group the general definition applies,

$$[f \star \psi](g) = \sum_{h \in p4} f(h)\, \psi(g^{-1}h)\,,$$

and writing $g = (r, x)$, $h = (s, y)$ makes it concrete:

$$g^{-1}h = \big(r^{-1}s,\ r^{-1}(y - x)\big)\,.$$

Two things happen at once. The spatial part $r^{-1}(y-x)$ rotates the filter in the plane — the `rot90` again — and the orientation part $r^{-1}s$ **cyclically shifts the filter's orientation axis**, which in code is a `torch.roll`.

The roll is the whole layer. Drop it and the spatial rotation still looks right, so the layer still appears to do something rotational, but the four orientation channels have become four ordinary independent channels and the group structure is gone. The test `test_the_orientation_roll_is_load_bearing` makes that a number rather than an argument: the same layer measures **2.2 ×10^{-7}** equivariance error with the roll and **0.80** without it. Six orders of magnitude, from one line.

Invariance, on demand. Equivariance is a property of a *feature map*, and a classifier needs a vector. Max-pooling over the orientation fibre,

$$F(x) = \max_{s \in C_4} f(s, \cdot),$$

turns $p4$-equivariance into C_4-invariance exactly, because the rotation permutes the terms of a max. That step is where the guarantee becomes usable — and, as the results below show, it is also where it becomes easy to measure the wrong thing.

What this predicts, before any training. For $g \in C_4$ the error should be zero to floating point on *any* input, trained or not, in-distribution or not. For $45°$ there is no guarantee at all, because $45° \notin C_4$ — and the measured error there should be no better than a plain CNN's. The cost is parameters: the group-convolution layers gain a factor of $|C_4|$ on their input axis, so the network is roughly $1.5\times$ the plain one at equal feature width.

What we measure, and why

- **Accuracy on rotated test digits**, split into *on-group* angles (0°, 90°, 180°, 270°, which the architecture is built for) and *off-group* angles (45°, 135°, ..., which it is not). Every arm trains on upright digits only, so on-group accuracy measures how much of the symmetry the network gets for free.
- **Equivariance error** — how far the rotated input's feature map is from the rotated feature map of the original input, relative to its size. Zero means exact symmetry. It is measured

directly on feature maps because accuracy can look fine while the underlying invariance is only approximate.
- **Parameters** — the price of the extra orientation axis (1.46× here).

What I built

Four arms at matched feature width: a plain CNN, the same CNN trained with continuous rotation augmentation, a $p4$ CNN, and a $p4$ CNN with augmentation. All four train on **upright** MNIST; the test set is rotated at evaluation. The angles $\{0, 90, 180, 270\}$ are the group and $\{45, 135, 225, 315\}$ are deliberately off it. Rotation uses `affine_grid` + `grid_sample` rather than `rot90`, because the off-group angles need it — which puts a bilinear resampling error into every number and sets the floor.

Results

Medians over seeds 0–2, with the seed range where it matters. `equiv` is the feature-map equivariance error defined above; *on-group* averages $\{0, 90, 180, 270\}$ and *off-group* averages $\{45, 135, 225, 315\}$.

arm	params	upright	on-group acc	on-group equiv	off-group acc	off-group equiv
plain	19,338	0.599	0.274	0.722	0.203	0.844
plain + augmentation	19,338	0.537	0.535	0.373	0.571	0.541
p4	28,314	0.801	**0.801**	**3.93e-07**	0.389	0.574
p4 + augmentation	28,314	0.714	0.714	**3.82e-07**	**0.752**	0.464

Three readings.

The guarantee is real and it is not approximate. On the group, $p4$ measures 3.9×10^{-7} against augmentation's 0.373 — a factor of 9.2×10^5 (`exactness/p4_over_augmented`, range 8.8–9.5×10^5) — and augmentation *saw those rotations during training* while $p4$ never did. The residual is the bilinear resampler, not the network. Equally: $p4$'s on-group accuracy equals its upright accuracy at every seed, to four digits (0.8005 and 0.8005 at seed 0). Not "close to"; the same number, because it is the same function.

The edge of the group is a cliff. At 45° the $p4$ arm scores 0.389, against 0.801 on the group, and its equivariance error there (0.574) is no better than what plain augmentation achieves (0.541). C_4 says nothing about $45°$ and the measurement agrees exactly that far and no further.

The two mechanisms are complements, not substitutes. The only arm that holds up off the group is $p4$ *with* augmentation, at 0.752 — better off-group than on. The group buys exactness where it applies; augmentation covers what is left. The cost of the group is $1.46\times$ the parameters (`parameters/p4_over_plain`), spent on the orientation axis of the group convolutions.

What surprised me

Augmentation did not merely fail to match equivariance — it destabilized training. `plain_augmented`'s upright accuracy ranges 0.22 to 0.676 across three seeds, and at seed 0 it




Figure 2: F1 architectures




Figure 3: F1 equivariance




Figure 4: F1 accuracy by angle

was *worse than the unaugmented plain CNN at every single angle*. At 19k parameters, asking one filter bank to cover every orientation is a real capacity cost, and it is paid out of the upright performance that the benchmark started from. The $p4$ arm has that capacity by construction and pays 46% more parameters for it instead.

Both measurement traps produced a wrong answer before they were caught.

The first was the probe. Measuring invariance on iid uniform noise gave an *untrained* plain CNN an error of 0.005 — apparently near-perfect rotation invariance in a network with no reason to have any. The cause is that iid noise is statistically rotation-symmetric, so a network ending in a global average sees the same distribution either way. The probe was doing the talking. The tests now use structured asymmetric probes, and the rung itself probes with real digits, which have the same asymmetry for the same reason.

The second was the metric. Global average pooling is *itself* rotation-invariant — it cannot distinguish a permutation of spatial positions — so measuring the pooled vector flatters everything. An untrained plain CNN scores 0.019 pooled against 0.372 on its feature maps, twenty times better for no architectural reason. The headline metric is therefore feature-map equivariance, and the pooled number is kept and reported as `pooling_flattery` so the size of the confound stays visible: 1.6× for the plain CNN and 3.0× for $p4$ once trained and measured on digits.

Neither of these is a bug in the model. Both are bugs in the measurement that would have been invisible in the results, which is the reason they are written down here rather than quietly fixed.

Open threads

The $p4$ construction generalizes to $p4m$ (adding reflections) and, through steerable filters, to the continuous $SO(2)$ — which is the version that would actually close the off-group gap rather than documenting it. That is what `escnn` implements, and comparing this hand-rolled $p4$ against it is the obvious next rung.

Further reading

Cohen & Welling, *Group Equivariant Convolutional Networks* (2016); Bronstein et al., *Geometric Deep Learning* (2021) for the blueprint this rung is one instance of.

F2 — GCN and GraphSAGE on a node-classification benchmark

Question. Message passing assumes a node's neighbours say something about its label. Where does that assumption stop paying — and can the crossover be derived rather than discovered?

The idea

Much data is a **graph**: papers citing papers, users following users, atoms bonded to atoms. **Node classification** asks for a label per node (a paper's topic) given each node's own features (its words) and the edges.

A **graph neural network (GNN)** uses **message passing**: each layer replaces a node's representation with a combination of its own and its neighbours'. After k layers a node has "heard" from everything within k hops. The only hard constraint is that a graph's nodes have no natural order, so the combination must not depend on how neighbours are listed. Averaging satisfies that, which is why almost every GNN averages.

- **GCN** averages a node together with its neighbours (degree-normalised) and applies one shared weight matrix.
- **GraphSAGE** keeps *two* weight matrices, one for the node itself and one for the average of its neighbours, so it can learn how much to trust each.

The whole approach rests on **homophily**: the assumption that connected nodes tend to share labels. When it holds, averaging over neighbours pools evidence. When it fails, averaging mixes in the wrong classes.




Figure 5: Message passing at high and low homophily

Two graphs from the rung's own stochastic block model. Colours are classes. Grey edges join same-class nodes and pink edges join different classes. Left: most of the circled node's neighbours share its class, so averaging over them reinforces the right answer. Right: almost none do, and averaging dilutes it.

The math

The symmetry. A graph has no canonical node order, so the only admissible layers are those satisfying

$$\Phi(PX,\ PAP^\top) = P\,\Phi(X, A)$$

for every permutation matrix P. Any layer built as "aggregate a neighbourhood with a permutation-invariant function, then apply a shared transform" satisfies it, and essentially every graph network in use has that shape. `test_message_passing_is_permutation_equivariant` checks it for both arms to float32.

Where the GCN layer comes from. Start from a spectral filter on the graph Laplacian $L = I - D^{-1/2}AD^{-1/2} = U\Lambda U^\top$:

$$g_\theta \star x = U\, g_\theta(\Lambda)\, U^\top x.$$

That costs an eigendecomposition, so approximate g_θ by a Chebyshev polynomial and truncate at first order. With $\lambda_{\max} \approx 2$,

$$g_\theta \star x \approx \theta_0 x + \theta_1 (L - I)x = \theta_0 x - \theta_1 D^{-1/2}AD^{-1/2}x,$$

and constraining $\theta = \theta_0 = -\theta_1$ leaves

$$g_\theta \star x \approx \theta \left(I + D^{-1/2}AD^{-1/2}\right) x.$$

The operator in brackets has eigenvalues in $[0, 2]$, so stacking it amplifies; Kipf and Welling's *renormalization trick* replaces it with

$$\hat{A} = \tilde{D}^{-1/2}\tilde{A}\tilde{D}^{-1/2}, \qquad \tilde{A} = A + I,$$

which is the single line of linear algebra the whole architecture rests on. The self-loop is not cosmetic: without it a node's own features never reach its representation and a one-layer GCN cannot express the identity.

Why depth behaves differently here than in a CNN. $\hat{A}$ is an averaging operator with spectral radius 1, and its top eigenvector is explicit:

$$\hat{A}\,\tilde{D}^{1/2}\mathbf{1} = \tilde{D}^{-1/2}\tilde{A}\mathbf{1} = \tilde{D}^{-1/2}\tilde{d} = \tilde{D}^{1/2}\mathbf{1},$$

eigenvalue exactly 1. So $\hat{A}^k$ converges to a projector onto the span of those vectors, one per connected component, and every node's representation collapses toward the same direction within its component. A deep GCN is a diffusion that has run too long. This is **oversmoothing**, and it is a statement about $\hat{A}$ alone — no training required, which is how `test_repeated_diffusion_collapses_the_representations` can check it with zero parameters.

GraphSAGE's one extra degree of freedom. The mean aggregator variant is

$$H^{(\ell+1)} = \sigma\Big(H^{(\ell)}W^{(\ell)}_{\text{self}} + \bar{A}H^{(\ell)}W^{(\ell)}_{\text{neigh}}\Big), \qquad \bar{A} = D^{-1}A,$$

with no self-loop inside $\bar{A}$. Twice the parameters per layer, spent entirely on being able to weigh "me" against "my neighbourhood" — and in particular on being able to set $W_{\text{neigh}} = 0$. That makes the graph-blind MLP a *special case* of GraphSAGE and not of the GCN, which `test_graphsage_contains_the_graph_blind_model_and_the_gcn_does_not` checks by zeroing the neighbour weights and asserting the two models agree exactly.

Deriving the crossover. Take balanced classes with centroids μ_c summing to zero and features $x_i = \mu_{c_i} + \varepsilon_i$ with independent noise. On a graph with homophily h, the mean over d neighbours of a node in class c has expectation

$$h\,\mu_c + (1-h)\,\frac{-\mu_c}{C-1} = \underbrace{\frac{hC-1}{C-1}}_{s(h)}\,\mu_c.$$

Three readings of $s(h)$, all testable. It is **zero at** $h = 1/C$ — the random floor, where edges carry nothing. It is **negative below** it, where the neighbourhood carries the class signal *inverted*, which a learned weight can flip back and a fixed averaging cannot. And averaging d independent noise terms shrinks the noise by $\sqrt{d}$, so the aggregate's signal-to-noise relative to a node's own features is $\sqrt{d}\,|s(h)|$. Setting that to 1:

$$h^* = \frac{1}{C}\left(1 + \frac{C-1}{\sqrt{d}}\right).$$

For the four-class SBM at mean degree 8 this is $h^* = 0.515$. It is the crossover for a model using *only* the aggregate; both graph arms also see the node itself, so both should cross **lower** than h^*, and GraphSAGE — which can weigh the two — lower still. The sweep is a test of that ordering.

Label propagation, for scale. Seed a one-hot on each labelled node and iterate $Y^{(t+1)} = \alpha\hat{A}Y^{(t)} + (1-\alpha)Y^{(0)}$. No features, no parameters, no training: the graph's own answer to the task, and the number that says how much of a GNN benchmark is the graph rather than the network.

What we measure, and why

- **Test accuracy on Cora**, the standard citation benchmark (7 topics, 140 labelled nodes, 1000 test nodes), for a graph-blind MLP, a GCN and GraphSAGE. The MLP sees the same features and no edges, so *GCN − MLP* is the value of the graph.
- **Label propagation** — spread the 140 known labels along edges, with no features and no parameters. It measures how much of the task the graph solves on its own, which puts the GNN's gain in context.
- **Crossover homophily** — on a synthetic graph whose homophily is a dial, the homophily at which each GNN stops beating the MLP. It is derived in advance (below) and then measured, so the theory is tested rather than fitted.
- **Mean pairwise cosine similarity of final representations vs depth — oversmoothing** means all nodes' representations converge to the same vector as layers stack. This metric detects that directly, which accuracy alone cannot distinguish from other reasons deeper models do worse.

What I built

Three arms on identical features — a graph-blind MLP, a GCN, and GraphSAGE — plus label propagation as a parameter-free control. Cora with the standard Planetoid protocol (20 labels per class, 1000 test nodes) carries the real-data half; an SBM with a calibrated homophily dial carries the controlled half. A depth sweep on Cora measures accuracy *and* mean pairwise cosine similarity of the final representations, because the second distinguishes oversmoothing from the other stories a falling accuracy curve is consistent with.

Two implementation notes worth the space. The adjacency is **dense on purpose**: Cora's operator is 0.18% non-zero, which sounds like an obvious case for `torch.sparse`, but measured on this CPU the sparse multiply takes 46.8 ms against dense BLAS's 31.1 ms. At 2,708 nodes the dense

path is one cache-resident call; the sparsity argument is real but does not start here. And the depth sweep gets a **larger epoch budget than the headline runs**, for a reason given under *What surprised me*.

Results

Medians over seeds 0–2.

Cora, 2,708 nodes, 5,278 undirected edges, 7 classes, homophily 0.810 against a random floor of 0.143, mean degree 3.9, 140 labelled nodes:

arm	test accuracy	range
MLP (graph-blind)	0.550	0.501 – 0.565
GCN	**0.807**	0.777 – 0.807
GraphSAGE	0.790	0.765 – 0.800
label propagation — *no features, no parameters*	0.716	0.683 – 0.754

The GCN sits within 0.008 of Kipf & Welling's published 0.815. It beats the features-only model by **+0.257**, and it beats the graph's own untrained answer by **+0.091**. Those two numbers are the rung's first result: on this benchmark the graph is worth a great deal and the *network* is worth rather little. At homophily 0.81 against a derived crossover of 0.577, Cora is comfortably on the side where message passing should pay, and it does.

GCN and GraphSAGE are indistinguishable here (0.807 vs 0.790, overlapping ranges), which is what a homophilous graph predicts: there is nothing for the separate self-weight to buy when the neighbours agree with you.

Homophily. The sweep runs from deep heterophily to strong homophily on a four-class SBM at mean degree 8, with weak node features so the edges are what is being measured:

	predicted	measured (median)	range
aggregate only	**0.515**	—	—
GCN	*below 0.515*	**0.494**	0.480 – 0.507
GraphSAGE	*lower still*	**0.139**	0.115 – 0.157

The derivation got the number and the ordering. And at the heterophilous end, $h = 0.05$:

arm	accuracy	vs the graph-blind MLP
MLP	0.778	—
GCN	0.526	**−0.252**
GraphSAGE	0.852	**+0.074**

Depth. Every arm peaks at two layers and every arm degrades after that — including the one with no edges:

layers	MLP acc	GCN acc	SAGE acc	MLP cos	GCN cos	SAGE cos
1	0.544	0.761	0.737	*0.056*	*0.056*	*0.056*
2	**0.556**	**0.807**	0.786	0.528	0.626	0.525
3	0.495	0.795	**0.790**	0.497	0.502	0.489
4	0.413	0.790	0.756	0.483	0.478	0.436
6	0.387	0.731	0.740	0.599	0.449	0.452
8	0.304	0.645	0.690	**1.000**	0.580	0.426

(*The one-layer column is italicised because a one-layer model is a single linear map with no hidden representation — that 0.056 is Cora's bag of words, recorded as* `depth/input_features_smoothness`*, not any model's.*)

That table does not say what it was expected to say, and the next section is about why.




Figure 6: F2 architectures




Figure 7: F2 Cora

What surprised me

The oversmoothing story did not reproduce, and the control is what killed it. The arm whose representations collapse is the **graph-blind MLP** — mean pairwise cosine similarity 1.000 at eight layers, accuracy 0.304 — and it is also the arm that loses the most accuracy to depth




Figure 8: F2 depth accuracy




Figure 9: F2 depth smoothness




Figure 10: F2 collapse beyond the MLP




Figure 11: F2 homophily




Figure 12: F2 homophily gap

(`deepest_drop` 0.256, against the GCN's 0.162 and GraphSAGE's 0.101). The graph models go the other way: the GCN's representations become *less* collinear as it deepens (`smoothness_rise` −0.027) and GraphSAGE's more so (−0.088).

So at this width I cannot attribute the depth degradation to message passing. Everything the accuracy curve shows is reproduced, and reproduced *harder*, by a model with no edges at all — which makes it a deep-narrow-ReLU-network story (sixteen units, dropout 0.5, no residual connections), not a diffusion story. Reporting the GCN's falling curve as oversmoothing, without that control, would have been reporting the control's pathology under the graph's name.

None of which makes the theory wrong. $\hat{A}^k$ really does converge to a projector, and this rung demonstrates it cleanly — in the *parameter-free* test, where 64 rounds of $\hat{A}$ drive cosine similarity to 1.000 on a connected graph and to 0.988 on a two-component one, the shortfall being exactly the second eigenvalue-1 eigenvector. The gap between that and the trained sweep is the finding: at eight layers and width 16 the effect exists and is swamped. What would separate them is width and residual connections, and neither is here.

The GCN's learned advantage over an untrained diffusion is +0.091. Label propagation uses no features and fits no parameters, and it reaches 0.716 on Cora against the GCN's 0.807. The benchmark's headline number is mostly a statement about how homophilous citation networks are.

GraphSAGE reads heterophily as signal. At $h = 0.05$ the neighbours are actively anti-

correlated with a node's label, the GCN loses 0.252 against the graph-blind baseline, and GraphSAGE *gains* 0.074 — a 0.324 spread between two architectures that differ by one weight matrix. That is $s(h) = (hC - 1)/(C - 1)$ being negative rather than zero: there is real information in the inverted signal, and reaching it needs only the freedom to learn a negative neighbour weight, which a GCN's single shared W cannot express.

The budget guard was worth building and is still firing. At 300 epochs three to four of twelve depth arms were still improving when the budget ended. At 600 it is 4 of 18 — better, not solved. The deepest arms in the table above are therefore a mixture of depth and budget, and the honest version of "deeper is worse" here is "deeper is worse *and* slower to train, and this sweep does not fully separate them".

Open threads

The heterophilous regime is where current work lives — GAT's learned attention, GPR-GNN's learned polynomial of $\hat{A}$, and the "just concatenate the hops" baselines that often beat both. The SBM dial built here is the right harness for that comparison and none of it is run yet. Separately, PubMed is skipped because the dense adjacency would be 1.5 GB; the sparse rewrite that unlocks it is the same one the measurement above says is not worth it at Cora's size, which is a nice illustration that "the right data structure" is a function of n.

Further reading

Kipf & Welling, *Semi-Supervised Classification with Graph Convolutional Networks* (2017); Hamilton, Ying & Leskovec, *Inductive Representation Learning on Large Graphs* (2017); Li, Han & Wu, *Deeper Insights into Graph Convolutional Networks* (2018) for the oversmoothing analysis.

What part F settled

1. **An equivariant network gives a guarantee, not an improvement, and the guarantee has a hard edge.** On C_4 the $p4$ CNN's feature maps measure 3.9×10^{-7} against rotation augmentation's 0.373 — a factor of 9.2×10^5 — on inputs it never saw, while augmentation *trained* on those rotations. One step off the group, at 45°, its error is 0.574 and augmentation's is 0.541: indistinguishable. The symmetry you impose is exactly the symmetry you get.
2. **Equivariance and augmentation are complements.** $p4$ alone scores 0.801 on the group and 0.389 off it; $p4$ *with* augmentation is the only arm that holds up off the group, at 0.752. And augmentation on its own was not free — it destabilized the small plain CNN badly enough (upright accuracy ranging 0.22 to 0.676 across three seeds) that at seed 0 it lost to the unaugmented baseline at every angle.
3. **On Cora, the graph is worth +0.257 and the network is worth +0.091.** A GCN scores 0.807 against a graph-blind MLP's 0.550 — and against label propagation's 0.716, which uses no features and fits no parameters. Without that second control the benchmark reads as a result about graph networks rather than about how homophilous citation networks are.
4. **The crossover was derivable.** The neighbour mean scales class signal by $s(h) = (hC - 1)/(C - 1)$ and noise by $1/\sqrt{d}$, giving $h^* = \frac{1}{C}(1 + \frac{C-1}{\sqrt{d}}) = 0.515$ for the four-class SBM at mean degree 8. Measured: GCN 0.494, GraphSAGE 0.139 — below the prediction, and in the predicted order, because both arms also see the node itself and only one of them can weigh it separately.

5. **Heterophily is signal, not noise, for an architecture that can flip the sign.** At $h = 0.05$ the GCN loses 0.252 to a graph-blind MLP and GraphSAGE *gains* 0.074 — a 0.324 spread between two models that differ by one weight matrix. That is $s(h) < 0$ being readable rather than merely uninformative.
6. **The oversmoothing result did not reproduce, and saying so is the result.** The arm whose representations collapse is the graph-blind MLP (cosine similarity 1.000 at eight layers, accuracy 0.304); it also loses the most accuracy to depth (0.256 against the GCN's 0.162 and GraphSAGE's 0.101), and the GCN's representations get *less* collinear as it deepens (-0.027). At width 16 with dropout 0.5 and no residuals, everything the GCN's depth curve shows is reproduced harder by a model with no edges, so the curve is evidence about deep narrow networks and not about message passing. The theory is untouched — the parameter-free test drives $\widehat{A}^{64}$ to cosine similarity 1.000 on a connected graph — but the effect is swamped at this scale, and the version of this rung without the MLP control would have reported the control's pathology under the graph's name.
7. **Five things were wrong before the results were, and none of them would have shown up in the results.** A probe (iid noise is rotation-symmetric, so an untrained CNN scored 0.005 "invariance"); a metric (global average pooling is itself rotation-invariant, flattering every network by 1.6–3.0×); a second metric (ReLU puts every embedding in the non-negative orthant, so a cosine similarity of 0.71 means "ReLU", not "collapsed" — the graph-blind MLP out-scored the GCN); a generator (cross-class edges drawn by rejecting same-class pairs discard a $1/C$ share of them, so a homophily dial set to 0.25 delivered 0.31 — and that dial is the sweep's x-axis); and a budget (three to four of twelve depth arms were still improving when 300 epochs ran out, which would have made undertraining look like depth). Each was found by adding a control that could only embarrass the result, which is the only method here that has consistently worked.

Cost of the part: ~1,940 lines including tests, 19 test cases, and a three-seed sweep in about 62 minutes on four CPU cores (F1 ~153 s per seed, F2 ~1,094 s per seed). No GPU was available for this part and none is needed: Cora's dense adjacency is a 29 MB tensor and the whole homophily sweep is 1,200-node graphs.

Figures regenerate with `uv run python tools/writeup_figures.py F`*; the numbers they are quoted against live in* `data/f-metrics.json`*. The part README is the short version of this document.*