C7 — Signals and adaptivity: volatility, the deeper book, BTCUSDT, and a markout rule

Not a ladder phase. It comes from a request after C6's RL results. Lab notebook: `experiments/c7_signals/README.md`.

> **At a glance**
>
> - **C6's volatility estimate reads about 1.5× too low** on both deep assets. Correcting that bias helps the model-driven strategies on held-out data in 7 of 8 cases. HAR is the best *forecaster* but helps in only 4 of 8: what pays is wider quotes, not better timing.
> - **The book deeper than five ticks and BTCUSDT's book carry almost nothing a quoter can use.** Held-out R^2 gains are +0.2 points at 1 s at best, from deeper own-book levels; BTC adds ≈0 once our own book is known, in a linear model and in LightGBM, even with BTC aligned to 100 ms. Given to the RL policy as fourteen extra observations, they change nothing measurable.
> - **A markout rule — widen the half spread by κ × the recent adverse move of our own fills — beat C6's widened baseline on held-out data in 6 of 6 (strategy, asset) pairs**, by +0.1 to +7.8 points, and untuned (κ = 2) in 13 of 18 on seven assets it was never fitted on (median +0.85). Nothing else in Part C beats those baselines on held-out data in every pair tried, and it is three lines of arithmetic.

---

1. The task

The request, after C6's RL answer came back "mostly nothing":

> yes, do those three after the current runs finish, also try use more deep ob levels and maybe even ob of btcusdt, because they can contain hidden info

"Those three" were proposals made in answer to five questions about C6:

1. **a volatility bake-off** — estimate volatility several other ways, score them, and put the best into the strategies;
2. **imbalance in basis points** rather than ticks, because C2's five-level feature is 0.11 bp deep on ETHUSDC and 8 bp deep on ENAUSDC;
3. **a markout-driven spread rule** — widen after our own fills turn toxic — as a new, hand-written baseline.

And the addition: **deeper book levels, and BTCUSDT's book**, as possible hidden information.

2. The goal

C6 ended with a negative result for learning — state-conditioned multipliers do not beat well-chosen fixed ones — and a positive one for a fixed choice: the per-asset spread floor was the largest effect in Part C. So the natural next question is not "which RL algorithm" but "what information, and which simple rule, is the policy missing?"

Everything here is decided on the training days and reported on the held-out days C6 used: eleven sessions from 2025-09-15 on, for both ETHUSDC and XRPUSDC. A number chosen on held-out data would be worthless, so none is.

3. The data: per-second book snapshots

`snapshots.py` replays each session with no orders and writes, per second: the 100 ms mid path, cumulative resting quantity out to 1, 5, 20, 50 and 200 ticks and within 1, 2, 5, 10, 25, 50 and 100 bp of the mid, order-flow imbalance at the touch (Cont, Kukanov & Stoikov), and aggressive volume by side. About 9 MB a day.

BTCUSDT is 0.4–1.0 GB a day raw and the disk allowance does not hold three weeks of it, so it is streamed: download a day, extract, delete the raw file. One BTCUSDT session needs 6.3 GB of memory to replay, which is why it ran only after C6's training had finished — twice it did not, and was killed.

4. Volatility

4.1 Which estimator forecasts best

Every model-driven strategy in C6 uses one σ: the standard deviation of 100 ms mid changes over ten minutes, refit every five seconds. `vol_bakeoff.py` scores it against ten alternatives *as forecasts*: at each 5 s point, each estimator's trailing variance is compared with the realised variance over the next five minutes, with the QLIKE loss

$$L(y, f) = \frac{y}{f} - \ln \frac{y}{f} - 1,$$

which is 0 for a perfect forecast and — unlike squared error — stays consistent when the target y is itself a noisy realised measure (Patton, 2011). Each estimator is scored raw, and after multiplying by its median y/f on the training days, which separates "wrong level" from "wrong timing".




Figure — held-out QLIKE after bias correction, 1 s-return target. The 1-minute window is off the scale (ETH 133, XRP 1.38) and omitted.

estimator	ETH raw	ETH corrected	XRP raw	XRP corrected	bias (y/f) ETH / XRP
current (C6)	0.606	0.367	0.318	**0.192**	**1.47 / 1.44**
HAR (1 min, 10 min, 1 h)	**0.284**	**0.320**	**0.167**	**0.192**	0.83 / 0.83
EWMA, 10 min half-life	0.305	0.352	0.182	0.216	0.85 / 0.83
EWMA, 2 min	0.353	0.374	0.182	0.196	0.94 / 0.94
realised var., 1 s, 10 min	0.353	0.381	0.195	0.210	0.92 / 0.93
two-scale RV, 10 min	0.375	0.381	0.209	0.215	0.98 / 0.98
Parkinson, 1 s bars	1.673	0.396	1.282	0.211	2.59 / 2.71
bipower, 1 s	1.344	0.670	1.016	0.383	1.67 / 1.91


Three findings:

- **C6's σ is biased low by a factor of about 1.45 in variance** (1.2 in σ), on both assets, and the same on the 5 s-return target (1.71 / 1.76). Its *timing* is fine: bias-corrected, it ties HAR on XRP and is third on ETH. The bias is what sampling at 100 ms does to a mid that moves in steps: consecutive 100 ms changes are positively autocorrelated (lag-1 +0.12 to +0.18 on the days checked), so their variance scaled up by ten understates the one-second variance — measured directly, by a factor of 1.40–1.53, which is the bias above.
- **HAR is the best forecaster**, 13% better than corrected-current on ETH. Its weights are close on the two assets — about 0.2 on the last minute, 0.4 on the last ten, 0.25 on the last hour — which is the usual HAR shape (Corsi, 2009).
- **Short windows are bad.** A 30 s EWMA or a 1-minute window forecasts ~0 whenever the mid sits still, and XRPUSDC's mid sat still for twenty minutes on 2025-08-29. Every forecast is floored at one half-tick move per five minutes so that one quiet stretch

cannot dominate the mean.

4.2 What it does inside the strategies

Two variants were run on the held-out sessions, both fixed from the training days: `vol_scale` multiplies C6's variance by its measured bias, and `har_b*` replaces σ with the HAR forecast once an hour of data exists.



strategy	asset	C6 σ	bias-corrected	HAR	fills/day, C6 → corrected
glft	ETH	−15.13%	**−12.70%**	−13.47%	3,834 → 2,706
glft-wide	ETH	−7.07%	**−6.22%**	−7.28%	101 → 103
hfgrid	ETH	−1.98%	**−0.23%**	−1.66%	244 → 130
hfgrid-wide	ETH	−2.11%	**−0.65%**	−1.65%	72 → 54
glft	XRP	−13.17%	−12.55%	**−12.33%**	13,397 → 13,047
glft-wide	XRP	**−1.89%**	−2.14%	−2.07%	10 → 10
hfgrid	XRP	−1.58%	**−0.82%**	−2.59%	133 → 74
hfgrid-wide	XRP	−1.15%	**−0.50%**	−1.89%	5 → 5

The bias correction helps in 7 of 8, HAR in 4 of 8, and the better forecaster loses to the cruder fix in 6 of 8. The mechanism is visible in the fill column: both variants *raise* σ, so both widen the quotes and trade less, and §8.2 of C6 already established that on this venue wider is better. The bias correction raises σ uniformly; HAR raises it most after bursts and least in quiet spells, and quiet spells are where the fills that lose money are cheapest to avoid. A better forecast of volatility is not a better market-making input on its own.

Where the spread floor binds (`glft-wide` on both assets) σ cannot move the half spread at all, and what differences remain come through the skew.

5. Is there information deeper in the book, or in BTCUSDT's?

5.1 The test

`book_info.py` asks the market, not a strategy. Linear models are fitted on the training days to forecast the traded asset's mid return 1–60 s ahead, and scored by **held-out R²**. Feature groups are added one at a time, starting from what the RL state already has (touch imbalance, five-tick imbalance, signed flow over 1 s and 10 s: "C2"), and what each group *adds* out of sample is the number that matters.

BTCUSDT's per-second sample can be up to a second stale, because the two feeds' one-second grids start at different moments; a sub-second lead would be invisible. So BTC's returns are also taken on its 100 ms grid, aligned to within 100 ms of our clock. Then `book_info_gbm.py` repeats the comparison with small, regularised LightGBM models, in case the information is in interactions a linear model cannot see.

5.2 What it found




Figure — held-out R² each group adds on top of the previous ones (symlog scale). Negative means the group made held-out forecasts worse.

Linear, held-out R² in %, cumulative as groups are added:

added	ETH 1 s	ETH 10 s	ETH 60 s	XRP 1 s	XRP 10 s	XRP 60 s
C2 (the RL state)	2.79	0.43	0.09	4.89	0.85	0.14
+ levels to 20/50/200 ticks	**3.13**	**0.53**	0.11	4.89	0.83	0.04
+ bp bands	3.13	0.52	0.08	4.87	0.79	−0.06
+ OFI	3.20	0.53	0.06	4.90	0.80	−0.09
+ own returns	3.36	0.69	**0.55**	4.93	0.61	−0.26
+ BTCUSDT	3.34	0.59	0.42	4.87	0.53	−0.55

LightGBM, held-out R² in %:

features	ETH 1 s	ETH 10 s	XRP 1 s	XRP 10 s
C2	3.39	0.53	4.90	0.83
C2 + BTC 100 ms returns	3.44	0.55	5.00	0.82
own book, everything	3.58	0.58	5.07	0.88
everything incl. BTC	3.58	0.58	5.07	0.73

- **There is a little information deeper in our own book** on ETHUSDC: +0.34 points at 1 s from levels 20–200 ticks deep, which is 0.45–4.5 bp on ETH. On XRPUSDC, where five ticks is already 1.7 bp, there is none.
- **Imbalance in bp bands adds nothing once levels are in**, and on its own it is weaker than levels. The bp framing fixes the cross-asset comparison, not the information.
- **BTCUSDT adds nothing a held-out test can see.** Its 100 ms-aligned returns add +0.05 points at 1 s in LightGBM and hurt at 60 s, and its book adds nothing in either model. Whatever BTC leads by is already in our own book by the time a one-second decision could use it.
- **Our own recent returns help ETH at 30–60 s (+0.44) and hurt XRP**, which has four training days to fit on: a small, unstable momentum effect.

For scale: an R^2 of 3.5% at 1 s on ETH, where σ is about 1 bp per √s, is a forecast whose own spread is about 0.2 bp — against a 4 bp half spread. It could move a quote by a tick; it cannot change what a quote earns.

6. The markout rule

6.1 The rule

Every fill is marked five seconds later against the mid it was filled at, signed so that a loss is positive:

$$m = -\operatorname{sign}(\Delta q)\,\frac{p_{t+5\,\mathrm{s}} - p_t}{p_t} \times 10^4 \text{ bp},$$


Δq being the position change the fill made. An exponential average $\bar{m}$ over fills (half-life 20 fills, weighted by size) is kept, and the half spread becomes

$$h = h_{\mathrm{C6}} + \kappa\,\max(\bar{m}, 0).$$

Quote wider for as long as the fills we have been getting have been adversely selected; go back when they stop. $\kappa = 0$ is C6's quoter exactly. The lag and the half-life were fixed before any run; only κ was searched.

6.2 Chosen on training days, scored on held-out ones

$\kappa \in \{1, 2, 4\}$ was swept on four training sessions — the same four the spread floor was chosen on — and the best per (strategy, asset) run on the eleven held-out sessions:



strategy	asset	κ	C6 widened	+ markout	sessions better	fills/day (median session)
glft-wide	ETH	1	−7.07%	**−5.36%**	4 / 11	101 → 31
hfgrid-wide	ETH	1	−2.11%	**−1.99%**	4 / 11	72 → 31
obi-wide	ETH	4	−6.40%	**−0.62%**	8 / 11	3,355 → 1,173
glft-wide	XRP	4	−1.89%	**−0.55%**	6 / 11	10 → 6
hfgrid-wide	XRP	2	−1.15%	**+1.96%**	5 / 11	5 → 3
obi-wide	XRP	1	−2.91%	**+4.91%**	8 / 11	761 → 508

It helps in all six, and it helps most where the strategy trades most. `obi-wide` is the convincing case: better on eight of eleven sessions on both assets, with fills in the hundreds or thousands a day. The `glft` and `hfgrid` gains come from fewer, larger days (four to six of eleven better), and the widened `glft` and `hfgrid` on XRP trade a handful of times on a median day, so their +1.3 and +3.1 points are the least trustworthy numbers in the table.

Why this works when RL did not: the rule conditions on the one piece of state that measures the thing the spread is paying for — how toxic *our* fills have been — rather than on market features a policy has to learn to relate to it. C6's policies saw inventory, flow and imbalance, never their own markouts.

6.3 Without tuning, on the other seven assets

A κ chosen on four sessions of the same asset is a search, however small. So the rule was also run with **κ = 2 fixed in advance** — the middle of the swept grid — on the seven assets the sweep never saw, on their three held-out sessions each, with nothing searched at all.




Figure — held-out points gained over C6's widened baseline, κ = 2 (symlog scale).


strategy	better	median gain	worst	best
obi-wide	**6 / 7**	**+3.43**	−0.89 (SUIUSDT)	+13.57 (AVAXUSDC)
hfgrid-wide	5 / 7	+1.18	−1.76 (SUIUSDT)	+12.78 (AVAXUSDC)
glft-wide	4 / 7	+0.03	−1.05 (BNBUSDC)	+1.45 (XRPUSDT)
all	**15 / 21**	**+1.18**		
all but AVAXUSDC	13 / 18	+0.85		

The two AVAX gains are one session: on 2025-09-22 the rule made +11.2% (`hfgrid`) and +12.2% (`obi`) where C6 made +0.1% and +0.3% — the same session on which C6's single v1 policy made +8.6%. That is a large directional move caught by whichever variant happened to be positioned for it, not market making, so the row without AVAX is the one to quote.

It generalises where the strategy trades a lot and the fills are toxic — `obi`, the highest-turnover strategy — and it is a coin flip for `glft-wide`, whose floor already binds and whose fills are few. Three sessions per asset is thin; the direction agrees with the eleven-session results, the sizes are not to be relied on.

7. RL with the deeper book and BTCUSDT in the state

§5 says the extra information is small. That is a statement about linear and boosted-tree forecasts, and a policy is neither, so the direct test was run too: recipe **`v2-deep`** is C6's v2 recipe unchanged except for fourteen more observations, read per second from the same feature files the regressions used — own-book imbalance at 20/50/200 ticks and 1/5/25 bp, OFI over 1 s and 10 s, own returns over 10 s and 60 s, BTCUSDT's returns over 0.5 s and 5 s (on its 100 ms grid), and BTCUSDT's touch imbalance and OFI. Five seeds each of `glft-wide` and `obi-wide` on ETHUSDC, the asset with ten training sessions.



strategy	widened baseline	v2, median of 5	v2-deep, median of 5	v2-deep seeds
glft-wide	−7.07%	−6.30%	−6.94%	−11.03 to −2.88
obi-wide	−6.40%	−8.00%	−6.09%	−8.55 to −4.25

Worse by 0.6 points on one strategy, better by 1.9 on the other, and both differences are inside a seed spread of six to eight points. **The extra observations do not measurably change what the policy earns** — which is what §5 predicted, now checked on the object that would have used them. `obi-wide` with the extra observations does edge past its baseline on median (−6.09% against −6.40%); the markout rule on the same pair made −0.62%.

8. Checks with known answers

check	expected	result
C6's σ bias, measured directly	var(1 s) / (10 · var(100 ms)) ≈ the fitted bias 1.44–1.47	1.40–1.53 on three sessions
new quoter parameters at their defaults	C6's quoter exactly	`glft-wide` XRPUSDC 2025-08-26: return 2.0387e−5 and 10.00 fills, both C6 runs identical to every digit
`vol_scale = 1.5`	σ × √1.5	1.805 → 2.211 (×1.225)
cumulative depth, per snapshot	non-decreasing outward, in levels and in bands	all 86,399 seconds, both sides
bp band vs tick level on XRP (0.34 bp/tick)	1 bp ≈ 3 levels	35.4k between level-1 (10.5k) and level-5 (66.1k)
extra RL observation timing	the second in force, never a later one	row timestamp = environment clock, lag 0.0 s
C2's two imbalance features on ETH	nearly identical (5 ticks = 0.11 bp)	correlation with 10 s return +0.0901 vs +0.0896

9. What this changes

- **For the baselines:** a markout-conditioned spread is a better fixed rule than any fixed spread C6 found, and C6's σ should be scaled by its measured bias before anything is built on it.

- **For RL:** the missing information was not deeper in the book or in BTC; it was in our own fills. The obvious next RL experiment is the markout average in the state, with the markout rule as the residual policy's baseline — asking RL to improve the best thing found so far, not C6's.

10. Sources

what	source
QLIKE, and why it is robust to a noisy target	Patton (2011), *Volatility forecast comparison using imperfect volatility proxies*, J. Econometrics 160
HAR	Corsi (2009), *A simple approximate long-memory model of realized volatility*, J. Financial Econometrics 7
two-scale realised variance	Zhang, Mykland & Aït-Sahalia (2005), JASA 100
bipower variation	Barndorff-Nielsen & Shephard (2004), J. Financial Econometrics 2
range estimator	Parkinson (1980), J. Business 53
order-flow imbalance	Cont, Kukanov & Stoikov (2014)
the strategies, spreads and split	C6