



UNM SCHOOL of ENGINEERING

Department of Electrical & Computer Engineering

ECE 344L Knowledge Probe Solution

By

Dr. Edward Nava



What is the minimum number of bits that is needed to represent the unsigned decimal value of 12,375?

Some key relationships:

1 bit – 2 values, 0 and 1

4 bits – 16 values, 0..15

10 bits – 1,024 values 0..1023

12 bits – 4,096 values 0..4096

14 bits – 16,384 values 0..16383 ← we need at least 14 bits



UNM

SCHOOL of ENGINEERING

Department of Electrical & Computer Engineering

Fill in the following table showing the equivalent representation of the binary number 01010110.

One's complement:	10101001
-------------------	----------

Add 1	<u>00000001</u>
-------	-----------------

Two's complement:	10101010
-------------------	----------

Decimal Equivalent:	
---------------------	--

01010110	$64+16+4+2 = 86$
----------	------------------

Hexadecimal:	0101	0110
--------------	------	------

0 x	5	6
-----	---	---




UNM

SCHOOL of ENGINEERING

Department of Electrical & Computer Engineering

Boolean Function





Boolean Function & Truth Table

Complete Boolean Function:

$$Q = \overline{A} C + A B + A \overline{B} + B C$$

A	B	C	Q	
0	0	0	0	
0	0	1	1	$\neg A C$
0	1	0	0	
0	1	1	1	$\neg A C, B C$
1	0	0	1	$A \neg B$
1	0	1	1	$A \neg B$
1	1	0	1	$A B$
1	1	1	1	$A B, B C$

Boolean Reduction

AB \ C	C	
	0	1
00	0	1
01	0	1
11	1	1
10	1	1

Reduced Function: $Q = A + C$



Combinational & Sequential Circuits

A



Figure A – Functional equivalent to a combinational circuit as the output is only a function of the current input values.

B



Figure B – Functional equivalent of a sequential circuit as the output is a function of both the current and previous inputs.
