


Take Test: Lab 5 Quiz

Test Informa	ation	
Description	This quiz covers the content in the Lab 5 videos	and associated documentation.
nstructions		
Multiple Attemp	ots This test allows multiple attempts.	
Force Completi	ion This test can be saved and resumed later.	
QUESTIO	N 1	10 points Saved
	N 1 nmunication peripheral is used to communicate with	
	nmunication peripheral is used to communicate with	
Which com	nmunication peripheral is used to communicate with	
Which com	nmunication peripheral is used to communicate with	
Which com UART1 UART2	nmunication peripheral is used to communicate with	

QUESTION 2	10 points Saved
What baud rate is used for communication with Tera Term?	
O 57600	
115200	
O 4800	
9600	
QUESTION 3	10 points Saved
How many SFRs need to be configured for the UART?	
O 2	
O 1	
O 5	
QUESTION 4	10 points Saved
After initializations, the program will run in a continuous loop. • True	
False	
QUESTION 5	10 points Saved
Which PMOD connector is used for the 8 LED module?	
O PMOD A	
•	

PMOD B	
No PMOD, direct wiring	
O PMOD C	
QUESTION 6	5 points Saved
The UART is configured for 1 parity bit.	0
☐ True	
• False	
QUESTION 7	10 points Saved
Which of the following initializations are required for this lab assignment	t?
A. Initialize clocks	
○ B. Initialize count	
C. Initialize UART	
D. All of the above	
QUESTION 8	10 points Saved
How many data bits is the UART configured for?	•
O 16	
O 32	
O 9	



	What type of interface is the UART configured for?
	O RS-485
	O IEEE-488
	● RS-232
	O SPI
C	lick Save and Submit to save and submit. Click Save All Answers to save all answers. Save All Answers Save and Submit