
ECE440: Homework #3

DAVID KIRBY


DUE: 2 APRIL 2020

1. Problem P5, Chapter 3

The receiver cannot be certain that no bit errors have occurred because of how the checksum is calculated. Checksums add two 16-bit strings together. If, for example, there is a bit flip in each of these strings, then the sum could still match but the data would be incorrect.

2. Problem P27, Chapter 3

- (a) seq # = 207, source port = 302, destination port = 80
- (b) ACK # = 207, source port = 80, destination port = 302
- (c) ACK # = 127 because Host B indicates that it hasn't received 127 yet.
- (d) Timing Diagram



3. Problem 3

- (a) Congestion Window = 16KB, no packet loss (slow-start state)

	Initial	1RTT	2RTT	3RTT	4RTT
cwnd	1KB	2KB	4KB	8KB	16KB

$$4RTT = 4 \times 100ms = 400ms$$

(b) Timeout at 16KB, no packet loss (congestion-avoidance state**)

$$\text{ssthresh} = \frac{\text{cwnd}}{2} = \frac{16KB}{2} = 8KB \text{ and } \text{cwnd} = 1$$

	Initial	1RTT	2RTT	3RTT	4RTT	5RTT	6RTT	7RTT	8RTT	9RTT
cwnd	1KB	2KB	4KB	8KB**	9KB	10KB	11KB	12KB	13KB	14KB

$$9RTT = 9 \times 100ms = \boxed{900ms}$$

(c) Quadruple duplicate ACK event (fast-recovery state)

$$\text{ssthresh} = \frac{\text{cwnd}}{2} = \frac{14KB}{2} = 7KB \text{ and}$$

$$\text{cwnd} = \frac{\text{ssthresh}}{2} + \# \text{ Duplicates} = 3 + 4 = 7KB$$

	Initial	1RTT	2RTT
cwnd	7KB	8KB	9KB

$$2RTT = 2 \times 100ms = \boxed{200ms}$$