



ESEIAAT



Escola Superior d'Enginyeries Industrials,
Aeroespacial i Audiovisual de Terrassa

UNIVERSITAT POLITÈCNICA DE CATALUNYA

Cubesat Constellation Astrea

Report

Degree: Aerospace Engineering

Course: Engineering Projects

Group: G4 EA-T2016

Delivery date: 22-12-2016

Students:

Cebrián Galán, Joan

Foreman Campins, Lluís

Fuentes Muñoz, Óscar

Herrán Albelda, Fernando

Martínez Viol, Víctor

Pla Olea, Laura

Puig Ruiz, Josep

Tarroc Gil, Sergi

Urbano González, Eva María

Fontanes Molina, Pol

Fraixedas Lucea, Roger

González García, Sílvia

Kaloyanov Naydenov, Boyan

Morata Carranza, David

Pons Daza, Marina

Serra Moncunill, Josep Maria

Tió Malo, Xavier

Customer: Pérez Llera, Luís Manuel

Contents

List of Tables	iii
List of Figures	iv
1 Satellite design planning	1
2 Gantt of the section	2
3 Satellite design	4
3.1 Structure and mechanics	4
3.1.1 Structure	4
3.1.2 Deployments	5
3.1.3 Thermal protection	5
3.1.4 Study of the commercial available options	5
3.2 Electrical Power System	5
3.2.1 Solar arrays	6
3.2.2 Power management	6
3.2.3 Batteries	6
3.2.4 Study of the commercial available options	7
3.3 Payload	7
3.3.1 Antennas	7
3.3.1.1 Patch antenna	7
3.3.1.2 Turnstile antenna	8
3.3.2 Data Handling Systems	9
3.3.3 Study of the commercial available options	10
3.4 Propulsion Systems	10
3.4.1 Requirements	10
3.4.2 Orbit decay	10
3.4.3 Thrusters	11
3.5 Communication module	12
3.6 Attitude and Orbital Control Systems	12
3.6.1 Attitude Determination	12
3.6.2 Attitude Control	12
3.6.3 Orbital Control	13
3.6.4 Study of the commercial available options	13

CONTENTS

4 References

14

List of Tables

1.1	Prelations and Time	1
3.1	Options studied	5
3.2	Options studied	7
3.4	Main features of the turnstile antenna	9
3.5	Options studied	10
3.7	Options studied	13

List of Figures

3.1	Dimensions of a 1U CubeSat [?]	4
3.2	Basic schematics of the EPS [?]	6

1 Satellite design planning

Interdependency relationships among tasks, human resources and level of effort

ID	Work Package	Time (h)	Prelations
1. Preliminary design			
1.	Preliminary design	30	
2. Structure and mechanics			
2.1.	Structure	6	BF - 1
2.2.	Deployments	6	BF - 2.1.
2.3.	Thermal protection	9	BF - 2.2.
2.4.	Commercial availability	12	BF - 2.3.
2.5.	Choose option	6	BF - 2.4.
3. Electrical Power System			
3.1.	Solar arrays	9	BF - 1, BB - 5, 6
3.2.	Batteries	9	BF - 1, BB - 5, 6
3.3.	Power management	12	BF - 3.1, 3.2
3.4.	Commercial availability	15	BF - 3.3.
3.5.	Choose option	9	BF - 3.4.
4. Propulsion Systems			
4.1	Motivations	12	BF - 1, BB - 2
4.2	Commercial availability	15	BF - 5
4.3	Choose option	9	BF - 4.2.
5. Payloads			
5.1.1.	Data Handling Systems	15	BF - 1
5.1.2.	Antenna	12	BF - 1, FF - 5.1.1.
5.2.	Commercial availability	15	BF - 5.1.
5.3.	Choose option	15	BF - 5.2.
6. AOCS			
6.1.	Attitude determination	9	BF - 1, BB - 2
6.2.	Attitude control	9	BF - 1, BB - 2
6.3.	Orbital Control	12	BF - 1, BB - 4
6.4.	Commercial availability	20	BF - 5
6.5.	Choose option	4	BF - 6.4.

Table 1.1: Prelations and Time

2 Gantt of the section

3 Satellite design

3.1 Structure and mechanics

The design and operation of a CubeSat is a complex process that must be completed keeping in mind the different subsystems it has as well as their role within the satellite. Additionally, since these systems will operate in space, they have to be prepared to withstand the extreme conditions, and be certified to work properly under them.

The satellite used by Astrea must have high compatibility between all the systems to avoid potential problems during operation and has to be tested (either all the systems together or one by one) and ensure their correct functioning.




Figure 3.1: Dimensions of a 1U CubeSat [?]

3.1.1 Structure

The mission of the structure is to sustain and protect all the electronic devices carried by the satellite in order to fulfill the mission requirements. In order to ensure that all the electronic and mechanic systems can be mounted upon the structure, a high compatibility between these systems is required.

The structure used will be provided by Innovative Solutions In Space (ISIS). Among its features it is worth mentioning that it can withstand the high range of temperature it will face

3.1 Structure and mechanics

in the space (-40°C to 80°C) and it is highly compatible with almost every physical system that will be used. Additionally, it is a low mass structure (304.3g) and it can support different configurations within it.

Since the configuration within the CubeSat will not be as common as other configuration options within of current operational CubeSats because the mission of the project is to relay fast and reliable communication with the ground station and the other satellites, it is a really important point that the structure is highly flexible regarding the arrangement of the subsystems that it will carry.

3.1.2 Deployments

FALTA

3.1.3 Thermal protection

The thermal protection system protect the CubeSat from thermal shocks. The satellite must remain in a optimal range of temperatures, despite the external temperature. It consists of various insulating materials and thermal conductors in order to maintain it within acceptable temperatures.

Thermal protection system is needed to mantain the temperature of the CubeSat inside the range operational temperatures of the differents subsystems. In space, the CubeSat can suffer extreme temperatures, both below zero and above zero, and thermal protection must guarantee the correct operation of all devices. Furthermore, thermal protection remove heat caused by other systems.

Currently, the element most used as thermal protection in the aerospace industry is multilayer insulation (MLI). The MLI comply requirements previously explained and consists of multiple thin layers. The main objective of the MLI is to reduce the heat by radiation because the heat by convection or conduction don't affect so much.

After a market study, Dunmore Aerospace company has been chosen to provide us its MLI product. Specially, the product is the Dunmore Aerospace Satkit and it is made for small satellites for low earth orbit.

3.1.4 Study of the commercial available options

3.2 Electrical Power System

System	Brand and model	Price per unit (€)
3U Structure	ISIS	3900)
Thermal Protection 1	EMPTY	EMPTY

Table 3.1: Options studied

3.2 Electrical Power System

The Electric Power System of the satellite must provide and manage the energy generated efficiently in order to have all the systems operating under normal conditions. The Electrical Power System of a Cubesat is, probably, the most fundamental requirement of the satellite payload, since its failure would result in the mission failure. The functions of the EPS are to control and distribute power to the Cubesat, to supply a continuous source of electrical power for through the lifetime of the mission, to protect the satellite against bus failiures and to monitor and communicate the system status to the on-board computer. The role of the EPS is very diverse and the following subsystems have to be analyzed in detail.




Figure 3.2: Basic schematics of the EPS [?]

3.2.1 Solar arrays

The primary source of electrical power has to be photovoltaic cells, given the size of the CubeSat. The photovoltaic cells will collect and convert the energy of the sun into electrical energy. Since they are main power source, they have to be correctly selected to prevent failure. Among the characteristics we seek for our mission, we are looking specially wheter the solar cell has a decent amount of power collection, low mass, protective radiation shield, deployment system, great temperature range and compatibility with the other systems.

The selected option for the Astrea mission will be a set deployable solar panels provided by EXA (Agencia Espacial Civil Ecuatoriana). These panels are low mass (135g each), have a protective radiation shield (NEMEA Anti Radiation Shield protects the solar panels of EM,

3.2 Electrical Power System

High Gamma, X-Ray, Alfa, Beta and low neutron radiation), a very high temperature range (from -80 to 130°C), a gentle release and deployment with artificial muscles (developed by EXA) and provide a power of 16.8W each (19.2V@0.5A).

Every cubesat will have 4 deployable solar panels providing it with 67.2W of power to supply peak demands while it is operating. Additionally, it is worth mentioning that these solar arrays are compatible with the hardware used in each of the satellites.

3.2.2 Power management

The role of the power management systems is to distribute the power and supply the energy to the different systems used in the CubeSat.

3.2.3 Batteries

Batteries are essential for a proper mission operation. They will provide the spacecraft subsystems with the power needed when the solar arrays are working less efficiently or not properly. Astrea is looking for decent capacity batteries that provide a slightly high typical energy and power, since the subsystems will not usually operate under peak conditions. Through the lifetime of the mission, the solar arrays will face an important unfavorable condition; in the worst case scenario, the satellite will be in the dark during half of the time of the orbit. Thus, the batteries must store and supply the energy needed for this time.

Among all the commercial options, Astrea has chosen the *NanoPower BP4* batteries. The CubeSat will have two of these batteries, with a total capacity of 20800mAh or 77Wh. Each battery has a total of 4 cells, highly stackable and come with a temperature sensor and a heater that will automatically turn on if the temperature is worsening the whole operation of the system.

3.2.4 Study of the commercial available options

Several commercial options have to be studied. The table provided below organizes some information about the different options purchased.

System	Brand and model	Price per unit (€)
Solar arrays	EXA-Agencia Espacial Civil Ecuatoriana	17000
Batteries	Gomspace, Nanopower BP4	TO REQUEST!
Power Management	Gomspace, Nanopower	TO REQUEST!

Table 3.2: Options studied

3.3 Payload

3.3 Payload

3.3.1 Antennas

The antennas are an essential part of the communication subsystem and their principal role is to transmit and receive the data. In order to provide fast and reliable communication, several options have been studied and the solution is presented on the lines below.

3.3.1.1 Patch antenna

FALTA DESCRIPCIÓN

Patch antenna	
Features	Value
Bands	L,S,C,X
Frequency range	1-12 GHz
Bandwidth	20 MHz
Gain	6 dBi
Polarization	Circular
Maximum power consumption	10 W
Impedance	50 Ohms
Operational temperature range	-65°C to +100°C
Mass	<250 grams

3.3.1.2 Turnstile antenna

FALTA DESCRIPCIÓN

Nando, ¿esto se puede arreglar un poco?

The frequency range is one of the most important parameters, because it must take into account satellite-satellite and satellite-earth communication. The initial requirement of the antenna frequency range is that it should be between 1-10 GHz. This is due to limitations in satellite-ground communication due to atmospheric conditions. Finding an antenna that meets this stringent requirement is very complicated, and a margin must be given to find an optimal market option.

The bandwidth is the frequency range where the highest power of the signal is found. The higher this bandwidth the better performance we will have.

3.3 Payload

The gain of an antenna is the ratio between the power density radiated in one direction and the power density that would radiate an isotropic antenna. The best option is to have a high gain.

Polarization is the orientation of the electromagnetic waves when leaving the antenna. There are three types of polarization: linear, circular and elliptical. For better performance, an antenna that receives and an antenna that transmits must have the same polarization. In project case, the best option is circular polarization because it is able to keep the signal constant regardless of the appearance of different problems such as movement with respect to the ground station.

The weight of the antennas should be as small as possible because the total weight of the cubesat should not exceed 4 kg. Most of the antennas of the market have a similar weight and does not cause us an extra problem when choosing the antenna of the project.

The power consumption parameter is an important requirement because most of the power is consumed by the different subsystems. The stage of greater power consumption due to the antenna corresponds to its deployment, while once it is deployed, consumption is greatly reduced. In most cases, the power required for deployment ranges from 2-10 W.

The operational temperature range is important to the correct work of the antenna, because if the antenna was in a temperature outside this range, it would not be able to perform the communication of optimal form. An habitual temperature range use to be between XXXX

After a market study, the antennas chosen to perform the communication have been a Microstrip Patch Antenna developed by Antenna Development Corporation and a turnstile antenna ANT430. On the back and lower face of the cubesat will be implemented turnstile antennas, while on the lateral sides will be implemented the antennas patch.

On the lower face of the cubesat is necessary to use an antenna turnstile because a thruster must be incorporated.

The following table shows the main parameters of those antennas.

Turnstile antenna	
Features	Value
Frequency range	400-480 MHz
Bandwidth	5 MHz
Gain	1.5 dBi
Polarization	Circular

3.4 Propulsion Systems

Maximum power consumption	10 W
Impedance	50 Ohms
Operational temperature range	-40°C to +85°C
Mass	30 grams

Table 3.4: Main features of the turnstile antenna

3.3.2 Data Handling Systems

The communication system allows us to realize the reception and trasmission of data, voice signals, etc. It consists of a group of transponders, that are the combination of a transmitter and a receiver and whose functions are receiving, separating, amplify, process, reamplify and retransmit signals.

The telemetry subsystem analyses the information about the ground station and other sensors of the satellite in order to monitor conditions on board. It allows report to ground station about the conditions of the on board systems.

The command and control subsystem allows the ground station to control the satellite.

3.3.3 Study of the commercial available options

System	Brand and model	Price per unit (€)
Patch antenna	ADC, Microstrip	TO REQUEST!
Turnstile antenna 1	Gomspace, ANT430	TO REQUEST
TRANSCEIVER	EMPTY	TO REQUEST
DHS	EMPTY	20000

Table 3.5: Options studied

3.4 Propulsion Systems

3.4.1 Requirements

There is a big risk of a collision with space debris while a spacecraft is operating in Low Earth Orbits. The Inter-Agency Space Debris Coordination Committee recommended to the United Nations (section 5.3.2 ‘Objects Passing Through the LEO Region’): “Whenever possible space systems that are terminating their operational phases in orbits that pass through the LEO region, or have the potential to interfere with the LEO region, should be de-orbited (direct re-entry is preferred) or where appropriate manoeuvred into an orbit with a reduced lifetime.

3.4 Propulsion Systems

Retrieval is also a disposal option.” and “A space system should be left in an orbit in which, using an accepted nominal projection for solar activity, atmospheric drag will limit the orbital lifetime after completion of operations. A study on the effect of post- mission orbital lifetime limitation on collision rate and debris population growth has been performed by the IADC. This IADC and some other studies and a number of existing national guidelines have found 25 years to be a reasonable and appropriate lifetime limit.”

Thus, a proper propulsion system is needed both for maintaining the satellite’s orbit and for de-orbiting after the mission’s lifetime.

Given the size of the CubeSat, not many effective options are available and a committed solution has to be found in order to follow the recommendations by the IADC.

3.4.2 Orbit decay

Orbit decay prediction powered by the Bureau of Meteorology by the Australian Government.

To calculate the orbit decay the following parameters are used:

Solar Radio Flux at 10.7cm (F10.7). It is a clear indicator of solar activity and has proven very valuable in forecasting space weather. The extreme UV that impact the ionosphere also modify the upper atmosphere, thus F10.7 data is needed to account for these variations. The value used in this calculation is: 79.54. REF: <http://www.spaceweather.gc.ca/solarflux/sx-5-mavg-en.php>

Cubesat mass of up to 4kg.

The K-index, and by extension the Planetary K-index, are used to characterize the magnitude of geomagnetic storms. Kp is an excellent indicator of disturbances in the Earth’s magnetic field and is used by SWPC to decide whether geomagnetic alerts and warnings need to be issued for users who are affected by these disturbances.

The principal users affected by geomagnetic storms are the electrical power grid, spacecraft operations, users of radio signals that reflect off of or pass through the ionosphere, and observers of the aurora.

The geomagnetic index used in this calculation is: 12.

RE-ENTRY EVERY 106.25 DAYS!

Calculations based on day 100, with an altitude of 400Km. Already lost 100Km:

3.5 Communication module

3.4.3 Thrusters

Thruster is a main part of the structure because it is needed to allow the satellite to realise different maneuvers how incorporate it adequately to the orbit after the deployment of the rocket, can obtain the optimal orientation or to maintain the satellite in the orbital and avoid its fallen.

The main parameters that must consider are thrust, total specific impulse, power required, weight of the propulsion subsystem and its volume.

At the moment, the most used and more modern thrusters for satellites are: ionic, pulsed plasma, electrothermal and green monoprop thrusters. An important aspect to consider is that we are interested in is reducing the mass required although this will cause minor accelerations than conventional engines but it will be suitable for small satellites.

After a market study, an ionic thruster has been elected how the best option. The causes of this election are that the volume of the all propulsion subsystem and its weight are very small, specific impulse is very high, thrust is acceptable and power required can be supplied by the solar panels.

The following table shows the main parameters of this thruster.

BIT-1 ION THRUSTER	
PARAMETERS	VALUE
Total thruster power	10 W
Thrust	100 μ N
Specific impulse	2150 s
Thruster Mass	53 g
Propellant mass flow	4.9 μ g/s
Grid input voltage	2 kV
Ion beam current	1.5 mA
Propellant utilization	41 percent
Energy Efficiency	27 percent

3.5 Communication module

100kbps:

1mbps:

¿solo 9600bps?:

Links interesantes universidades:

3.6 Attitude and Orbital Control Systems

3.6 Attitude and Orbital Control Systems

Attitude and orbital control subsystem is needed to enable the satellite to keep a specific position within its orbit and to control the antennas in order to remain oriented to assigned area, because the satellite tends to change its orientation due to torque. The AOCS receives telecommands from the central computer and acquires measurements (satellite attitude and orbital position) from sensors. We will also refer to the attitude control as ADACS (Attitude Determination and Attitude control system).

3.6.1 Attitude Determination

EMPTY

3.6.2 Attitude Control

EMPTY

3.6.3 Orbital Control

Thrusters

3.6.4 Study of the commercial available options

Brand and model	Features and description	Money (€)
Solar Panels		
Fabricant 1	EMPTY	2000000
Chuscas 1	EMPTY	20000
Truñaas 1	EMPTY	20000
Cuescas 1	EMPTY	20000

Table 3.7: Options studied

4 References