# Poker hand simulation - two pairs probability

## **Global parameters**

```
In [1]: sample_size = 100
    simulation_size = 200
    poker_hand_size = 5
    confidence = 0.95
```

## Create class for deck cards

```
In [2]: from enum import Enum

class Suit(Enum):
    __order__ = 'CLUBS DIAMONDS HEARTS SPADES'
    CLUBS = 1
    DIAMONDS = 2
    HEARTS = 3
    SPADES = 4

class Card:
    def __init__(self, value, suit):
        self.value = value
        self.suit = suit
```

## **Create deck**

```
In [3]: deck = []
for v in range(13):
    for s in Suit:
        deck.append(Card(v, s))
```

## **Declare simulation function**

```
In [4]: import random
        def runSimulation():
            two_pairs = 0
            for n in range(simulation_size):
                #shuffle deck
                random.shuffle(deck)
                #counts
                pairs count = 0
                #init dic
                count = {}
                for i in range(13):
                     count[i] = 0
                 #count cards
                 for i in range(poker_hand_size):
                     card = deck[i].value
                     count[card] += 1
                #count pairs
                 for i in range(13):
                     if count[i] == 2:
                         pairs_count += 1
                #count two pairs
                if pairs count == 2:
                     two pairs += 1
            probability = two_pairs / simulation_size
            return probability
```

## **Run simulations**

```
In [5]: data = []
for i in range(sample_size):
    probability = runSimulation()
    data.append(probability)
```

### **Print statistics**

```
In [6]: import pandas as pd

df = pd.DataFrame(data)
   df.describe()
```

#### Out[6]:

```
        count
        100.000000

        mean
        0.046800

        std
        0.015595

        min
        0.015000

        25%
        0.038750

        50%
        0.045000

        75%
        0.055000

        max
        0.095000
```

0

```
In [7]: import numpy as np
import scipy.stats

a = 1.0 * np.array(data)
m, se = np.mean(a), scipy.stats.sem(a)
h = se * scipy.stats.t.ppf((1 + confidence) / 2., sample_size - 1)
print("confidence interval is: [" + str(m - h) + ", " + str(m + h) + "]
```

confidence interval is: [0.0437056906787055, 0.04989430932129452] at 95%

## **Print global parameters**

```
In [8]: print("confidence: " + str(confidence))
    print("sample_size: " + str(sample_size))
    print("simulation_size: " + str(simulation_size))
    print("poker_hand_size: " + str(poker_hand_size))

confidence: 0.95
    sample_size: 100
    simulation_size: 200
    poker hand size: 5
```